

## HARI PRASATH\_225229110

# Lab 10: Patients Physical Activities prediction using Boosting

## Step 1: Understand Data

```
In [6]: import pandas as pd
from sklearn.model_selection import train_test_split
import warnings
warnings.filterwarnings('ignore')
from sklearn.metrics import precision_score, recall_score, accuracy_score, roc_auc_score
from sklearn.ensemble import GradientBoostingClassifier, AdaBoostClassifier
from sklearn.model_selection import GridSearchCV
from sklearn.linear_model import LogisticRegressionCV
from sklearn.ensemble import RandomForestClassifier, VotingClassifier
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import cross_val_score
```


```
In [7]: df = pd.read_csv("Human_Activity_Data.csv")
```

```
In [8]: df.head()
```

```
Out[8]:
```

	tBodyAcc-mean()-X	tBodyAcc-mean()-Y	tBodyAcc-mean()-Z	tBodyAcc-std()-X	tBodyAcc-std()-Y	tBodyAcc-std()-Z	tBodyAcc-mad()-X	tBodyAcc-mad()-Y
0	0.288585	-0.020294	-0.132905	-0.995279	-0.983111	-0.913526	-0.995112	-0.983185
1	0.278419	-0.016411	-0.123520	-0.998245	-0.975300	-0.960322	-0.998807	-0.974914
2	0.279653	-0.019467	-0.113462	-0.995380	-0.967187	-0.978944	-0.996520	-0.963668
3	0.279174	-0.026201	-0.123283	-0.996091	-0.983403	-0.990675	-0.997099	-0.982750
4	0.276629	-0.016570	-0.115362	-0.998139	-0.980817	-0.990482	-0.998321	-0.979672

5 rows × 562 columns



```
In [9]: df.shape
```

```
Out[9]: (151, 562)
```

In [10]: `df.info()`

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 151 entries, 0 to 150
Columns: 562 entries, tBodyAcc-mean()-X to Activity
dtypes: float64(561), object(1)
memory usage: 663.1+ KB
```

In [11]: `df.columns`

```
Out[11]: Index(['tBodyAcc-mean()-X', 'tBodyAcc-mean()-Y', 'tBodyAcc-mean()-Z',
               'tBodyAcc-std()-X', 'tBodyAcc-std()-Y', 'tBodyAcc-std()-Z',
               'tBodyAcc-mad()-X', 'tBodyAcc-mad()-Y', 'tBodyAcc-mad()-Z',
               'tBodyAcc-max()-X',
               ...,
               'fBodyBodyGyroJerkMag-skewness()', 'fBodyBodyGyroJerkMag-kurtosis()',
               'angle(tBodyAccMean,gravity)', 'angle(tBodyAccJerkMean,gravityMea
n)',
               'angle(tBodyGyroMean,gravityMean)',
               'angle(tBodyGyroJerkMean,gravityMean)', 'angle(X,gravityMean)',
               'angle(Y,gravityMean)', 'angle(Z,gravityMean)', 'Activity'],
              dtype='object', length=562)
```

In [12]: `type(df)`

Out[12]: `pandas.core.frame.DataFrame`

In [13]: `df['Activity'].value_counts`

```
Out[13]: <bound method IndexOpsMixin.value_counts of 0          STANDING
1          STANDING
2          STANDING
3          STANDING
4          STANDING
...
146  WALKING_DOWNSTAIRS
147  WALKING_DOWNSTAIRS
148  WALKING_DOWNSTAIRS
149  WALKING_DOWNSTAIRS
150          NaN
Name: Activity, Length: 151, dtype: object>
```

## Step 2: Build a small dataset

```
In [14]: lay = df.loc[df['Activity'] == "LAYING"][:500]
sit = df.loc[df['Activity'] == "SITTING"][:500]
walk = df.loc[df['Activity'] == "WALKING"][:500]
frames = [lay, sit, walk]
df_new = pd.concat(frames)
```

```
In [15]: df_new.shape
```

```
Out[15]: (98, 562)
```

```
In [16]: df_new.to_csv("Human_Activity_sample.csv")
```


```
In [17]: df1=pd.read_csv('Human_Activity_sample.csv')
```

```
In [18]: df1.head()
```

```
Out[18]:
```

	Unnamed: 0	tBodyAcc-mean()-X	tBodyAcc-mean()-Y	tBodyAcc-mean()-Z	tBodyAcc-std()-X	tBodyAcc-std()-Y	tBodyAcc-std()-Z	tBodyAcc-mad()-X
0	51	0.403474	-0.015074	-0.118167	-0.914811	-0.895231	-0.891748	-0.917696
1	52	0.278373	-0.020561	-0.096825	-0.984883	-0.991118	-0.982112	-0.987985
2	53	0.276555	-0.017869	-0.107621	-0.994195	-0.996372	-0.995615	-0.994901
3	54	0.279575	-0.017276	-0.109481	-0.996135	-0.995812	-0.998689	-0.996393
4	55	0.276527	-0.016819	-0.107983	-0.996775	-0.997256	-0.995422	-0.997167

5 rows × 563 columns



```
In [19]: df1.shape
```

```
Out[19]: (98, 563)
```

```
In [20]: df1.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 98 entries, 0 to 97
Columns: 563 entries, Unnamed: 0 to Activity
dtypes: float64(561), int64(1), object(1)
memory usage: 431.2+ KB
```

In [21]: `df1.columns`

Out[21]: Index(['Unnamed: 0', 'tBodyAcc-mean()-X', 'tBodyAcc-mean()-Y', 'tBodyAcc-mean()-Z', 'tBodyAcc-std()-X', 'tBodyAcc-std()-Y', 'tBodyAcc-std()-Z', 'tBodyAcc-mad()-X', 'tBodyAcc-mad()-Y', 'tBodyAcc-mad()-Z', ..., 'fBodyBodyGyroJerkMag-skewness()', 'fBodyBodyGyroJerkMag-kurtosis()', 'angle(tBodyAccMean,gravity)', 'angle(tBodyAccJerkMean,gravityMean)', 'angle(tBodyGyroMean,gravityMean)', 'angle(tBodyGyroJerkMean,gravityMean)', 'angle(X,gravityMean)', 'angle(Y,gravityMean)', 'angle(Z,gravityMean)', 'Activity'], dtype='object', length=563)

In [22]: `type(df1)`

Out[22]: `pandas.core.frame.DataFrame`

In [23]: `df1["Activity"].value_counts()`

Out[23]:

WALKING	47
LAYING	27
SITTING	24

Name: Activity, dtype: int64

### Step 3: Build GradientBoostingClassifier

In [24]: `X=df1.drop('Activity',axis=1)`  
`y=df1.Activity`

In [25]: `X_train,X_test,y_train,y_test = train_test_split(X,y,test_size=0.3,random_state=42)`

In [26]: `model = GradientBoostingClassifier(n_estimators=100,learning_rate=1.0,max_depth=1)`  
`model.fit(X_train,y_train)`

Out[26]: `GradientBoostingClassifier(learning_rate=1.0, max_depth=1, random_state=42)`

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

In [27]: `y_pred=model.predict(X_test)`

```
In [28]: accuracy_score(y_test,y_pred)
```

```
Out[28]: 0.9666666666666667
```

```
In [29]: print(classification_report(y_test,y_pred))
```

	precision	recall	f1-score	support
LAYING	1.00	0.90	0.95	10
SITTING	0.89	1.00	0.94	8
WALKING	1.00	1.00	1.00	12
accuracy			0.97	30
macro avg	0.96	0.97	0.96	30
weighted avg	0.97	0.97	0.97	30

#### Step4. [Find Best no. of trees and Best Learning Rate using Grid Search and Cross Validation]

```
In [30]: classifier = GradientBoostingClassifier()
```

```
In [31]: all_scores = cross_val_score(estimator=classifier, X=X_train, y=y_train, cv=5)
```

```
In [32]: all_scores
```

```
Out[32]: array([1., 1., 1., 1., 1.])
```

**To find the average of all the accuracies, simple use the mean() method**

```
In [33]: all_scores.mean()
```

```
Out[33]: 1.0
```

```
In [34]: parameter = {'n_estimators': [50, 100, 200, 400], 'learning_rate': [0.1, 0.01]}
```

```
In [35]: model1 = GridSearchCV(estimator=classifier, param_grid=parameter, cv=5, n_jobs=
```

```
In [36]: model1.fit(X_train,y_train)
```

```
Out[36]: GridSearchCV(cv=5, estimator=GradientBoostingClassifier(), n_jobs=-1,
                  param_grid={'learning_rate': [0.1, 0.01],
                              'n_estimators': [50, 100, 200, 400]})
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

```
In [41]: y_pred2=model1.predict(X_test)
```

```
In [42]: accuracy_score(y_test,y_pred2)
```

```
Out[42]: 1.0
```

```
In [43]: print(classification_report(y_test,y_pred2))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

```
In [44]: print(model1.best_estimator_)
```

```
GradientBoostingClassifier(n_estimators=50)
```

## Step5. [Build AdaBoostClassifier]

```
In [45]: base = DecisionTreeClassifier()
```

```
In [46]: model2 = AdaBoostClassifier(base_estimator=base,random_state=0)
```

```
In [47]: param_grid = {'n_estimators': [100, 150, 200], 'learning_rate': [0.01, 0.001]}
```

```
In [48]: model3 = GridSearchCV(model2,param_grid,cv=5,n_jobs=-1)
```

```
In [49]: model3.fit(X_train,y_train)
```

```
Out[49]: GridSearchCV(cv=5,
                      estimator=AdaBoostClassifier(base_estimator=DecisionTreeClassifier(),
                                                    random_state=0),
                      n_jobs=-1,
                      param_grid={'learning_rate': [0.01, 0.001],
                                  'n_estimators': [100, 150, 200]})
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

```
In [50]: y_pred3=model3.predict(X_test)
```

```
In [51]: accuracy_score(y_test,y_pred3)
```

```
Out[51]: 1.0
```

```
In [52]: print(classification_report(y_test,y_pred3))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

```
In [53]: print(model3.best_estimator_)
```

```
AdaBoostClassifier(base_estimator=DecisionTreeClassifier(), learning_rate=0.01,
                   n_estimators=100, random_state=0)
```

## Step6. [Build LogisticRegressionCV classifier]

```
In [54]: model4 = LogisticRegressionCV(cv=4,Cs=5,penalty='l2')
```

```
In [55]: model4.fit(X_train,y_train)
```

```
Out[55]: LogisticRegressionCV(Cs=5, cv=4)
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

```
In [56]: y_pred4=model4.predict(X_test)
```

```
In [57]: accuracy_score(y_test,y_pred4)
```

```
Out[57]: 1.0
```

```
In [58]: print(classification_report(y_test,y_pred4))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

## Step 7 [ Build VotingClassifier]

```
In [59]: model5=VotingClassifier(estimators=[('lr',model4),('gbc',model1)], voting='ha
```



```
In [60]: model5.fit(X_train,y_train)
```

```
Out[60]: VotingClassifier(estimators=[('lr', LogisticRegressionCV(Cs=5, cv=4)),
                                      ('gbc',
                                       GridSearchCV(cv=5,
                                                    estimator=GradientBoostingClassif
ier(),
                                                    n_jobs=-1,
                                                    param_grid={'learning_rate': [0.
1,
                                                                0.0
1],
                                                                'n_estimators': [50,
100,
                                                                200,
                                                                40
0]}))])
```

In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.

On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.

```
In [63]: y_pred5=model5.predict(X_test)
```

```
In [64]: print(classification_report(y_test,y_pred5))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

## Step8. [ Interpret your results]

```
In [65]: print(model1.best_estimator_)
```

```
GradientBoostingClassifier(n_estimators=50)
```

```
In [66]: print(model3.best_estimator_)
```

```
AdaBoostClassifier(base_estimator=DecisionTreeClassifier(), learning_rate=0.01,
                   n_estimators=100, random_state=0)
```

## GradientBoostingClassifier

### GradientBoostingClassifier(n\_estimators=50)

```
In [67]: classifierF = GradientBoostingClassifier(n_estimators=50)
all_scoresF = cross_val_score(estimator=classifier, X=X_train, y=y_train, cv=
parameter = {'n_estimators': [50, 100, 200, 400], 'learning_rate': [0.1, 0.01
```

```
In [68]: modelGC = GridSearchCV(estimator=classifier, param_grid=parameter, cv=5, n_job
```

```
In [69]: modelGC.fit(X_train, y_train)
```

```
Out[69]: GridSearchCV(cv=5, estimator=GradientBoostingClassifier(), n_jobs=-1,
                    param_grid={'learning_rate': [0.1, 0.01],
                                'n_estimators': [50, 100, 200, 400]})
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

```
In [71]: y_predGC=model3.predict(X_test)
```

```
In [72]: accuracy_score(y_test, y_predGC)
```

```
Out[72]: 1.0
```

```
In [73]: print(classification_report(y_test, y_predGC))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

```
In [74]: ### AdaBoostClassifier
```

```
In [75]: #### AdaBoostClassifier(base_estimator=DecisionTreeClassifier(), Learning_rate
```

```
In [77]: modelABC = AdaBoostClassifier(base_estimator=DecisionTreeClassifier(), learni
```

```
In [78]: param_grid = {'n_estimators': [100, 150, 200], 'learning_rate': [0.01, 0.001]
```

```
In [79]: modelGSCV = GridSearchCV(modelABC,param_grid,cv=5,n_jobs=-1)
modelGSCV.fit(X_train,y_train)
```

```
Out[79]: GridSearchCV(cv=5,
                    estimator=AdaBoostClassifier(base_estimator=DecisionTreeClassif
                    ier(),
                                                    learning_rate=0.01),
                    n_jobs=-1,
                    param_grid={'learning_rate': [0.01, 0.001],
                                'n_estimators': [100, 150, 200]})
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.**

**On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.**

```
In [80]: y_predGSCV=model3.predict(X_test)
```

```
In [81]: accuracy_score(y_test,y_predGSCV)
```

```
Out[81]: 1.0
```

```
In [82]: print(classification_report(y_test,y_predGSCV))
```

	precision	recall	f1-score	support
LAYING	1.00	1.00	1.00	10
SITTING	1.00	1.00	1.00	8
WALKING	1.00	1.00	1.00	12
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

