

# Oxford Engineering Pre-course Revision Sheets

Harik Sodhi

# 1 Mathematics

## 1.1 Differentiation

1.  $\frac{d}{dx} 5x^2 = 10x$
2.  $\frac{d}{dx} 4e^x = 4e^x$
3.  $\frac{d}{dx} 4 \tan x = 4 \sec^2 x$
4.  $\frac{d}{dx} \sqrt{1+x} = \frac{1}{2\sqrt{1+x}}$
5.  $\frac{d}{dx} 6 \cos(x^2) = -12x \sin(x^2)$
6.  $\frac{d}{dx} e^{3x^4} = 12x^3 e^{3x^4}$
7.  $\frac{d}{dx} x^2 \sin x = 2x \sin x + x^2 \cos x$
8.  $\frac{d}{dx} \frac{\tan x}{x} = \frac{x \sec^2 x - \tan x}{x^2}$
9.  $a(t) = \dot{v}(t) = 40t + 400e^{-t} \implies a(2) = 80 + 400e^{-2} = 134 \text{ ms}^{-2}$ . Answer given to 3sf and SI units everywhere are assumed for the units.
10.  $\frac{dy}{dx} = 2xe^{-x} - x^2e^{-x} = 0 \implies x(x-2) = 0 \implies x = 0 \text{ or } x = 2$ . Consider that the function is everywhere non-negative, and at  $x = 0$ , it takes the value of 0, so this is a minima and the other stationary point is a maxima. Therefore, minima at  $(0, 0)$  and maxima at  $(2, 4e^{-2})$ .

## 1.2 Integration

11.  $\int_a^b 3x^2 dx = [x^3]_a^b = b^3 - a^3$
12.  $\int \sin x \cos^5 x dx = -\frac{1}{6} \cos^6 x + c$
13.  $\int x^4 + x^3 dx = \frac{1}{5} x^5 + \frac{1}{4} x^4 + c$
14.  $\int \frac{x}{\sqrt{1-x^2}} dx = -\sqrt{1-x^2} + c$
15.  $\int_0^{2\pi} \sin^2 x dx = \int_0^{2\pi} \frac{1}{2} - \frac{1}{2} \cos 2x dx = [\frac{1}{4}(2x - \sin 2x)]_0^{2\pi} = \pi$
16.  $\int \tan x dx = \int \frac{\sin x}{\cos x} dx = -\ln |\cos x| + c = \ln |\sec x| + c$

17. Using  $x = \sin \theta$ ,  $dx = \cos \theta$ , so  $\int \frac{1}{\sqrt{1-x^2}} dx = \int \frac{\cos \theta}{\sqrt{1-\sin^2 \theta}} \theta = \theta + c = \arcsin x + c$
18. Using  $x = a \sin \theta$ ,  $dx = a \cos \theta$ , so  $\int \frac{1}{\sqrt{a^2-x^2}} dx = \int \frac{a \cos \theta}{a \sqrt{1-\sin^2 \theta}} \theta = \theta + c = \arcsin \frac{x}{a} + c$
19.  $\int x \sin x = -x \cos x + \int \cos x = -x \cos x + \sin x + c$
20.  $y = 0 \implies x(8 - x^3) = 0 \implies x = 0$  or  $2$  so  $A = \int_0^2 8x - x^4 dx = [4x^2 - \frac{1}{5}x^5]_0^2 = 16 - \frac{32}{5} = \frac{48}{5}$  so the area is  $\frac{48}{5}$  units squared.
21.  $x(2) = x(0) + \int_0^2 v(t) dt = \int_0^2 (20t^2 - 400e^{-t}) dt = [\frac{20}{3}t^3 + 400e^{-t}]_0^2 = \frac{160}{3} - 400(1 - e^{-2}) = -293$  m. So, the particle is 293 metres from the origin (3sf, assuming SI everywhere).

### 1.3 Series

22.  $10.0 + 11.1 + 12.2 \dots + 19.9 = 10 \times \frac{10+19.9}{2} = 149.5$
23.  $S_{10} = \frac{x(1-(2x)^{10})}{1-2x}$
24.  $(a + 2x)^n = a^n + 2na^{n-1}x + 2n(n-1)a^{n-2}x^2 + \frac{4}{3}n(n-1)(n-2)a^{n-3}x^3$

### 1.4 Functions

25. The function is undefined when the denominator is 0, which means  $x = \pm 1$ . When approaching  $x = -1$  from below, the function goes to negative infinity. When approaching from above, it goes to positive infinity. When approaching  $x = 1$  from below, the limit is negative infinity and from above the limit is positive infinity.

## 1.5 Complex Algebra

26. (i)  $(1 + 2i) + (2 + 3i) = 3 + 5i$  (ii)  $(1 + 2i)(2 + 3i) = -4 + 7i$  (iii)  $(1 + 2i)^3 = 1 + 6i - 12 - 8i = -11 - 2i$ , (iv)  $\arg(1 + 2i) = \text{atan} 2$  and  $\arg(1 + 2i)^3 = 3 \text{atan} 2 - 2\pi$  where the last correction is because by convention,  $\theta \in [-\pi, \pi]$ .
27.  $z\bar{z} = (x + iy)(x - iy) = x^2 + y^2 + xyi - xyi = x^2 + y^2$ .
28.  $\frac{1+2i}{3+4i} = \frac{(1+2i)(3-4i)}{(3+4i)(3-4i)} = \frac{1}{25}(11 + 2i)$
29.  $z = \frac{-2 \pm \sqrt{4-8}}{2} = -1 \pm i$ . When the coefficients of a quadratic are real, the complex solutions are always conjugates
30.  $(\cos \theta + i \sin \theta)^2 = (\cos^2 \theta - \sin^2 \theta) + (2 \sin \theta \cos \theta)i = \cos 2\theta + i \sin 2\theta$

## 1.6 Vectors

31. This can be done by just dividing by the norm so  $\hat{v} = \frac{1}{\sqrt{6}}(\mathbf{i} - \mathbf{j} + 2\mathbf{k})$
32. This can be done by dividing by the norm and then multiplying by  $|\vec{OP}| =$   
 3. (i)  $\vec{OP} = \sqrt{3}(\mathbf{i} + \mathbf{j} + \mathbf{k})$ . (ii)  $\vec{OP} = \frac{3}{\sqrt{14}}(\mathbf{i} - 2\mathbf{j} + 3\mathbf{k})$ .
33. (i)  $\mathbf{r} = \lambda(\mathbf{i} + \mathbf{j} + \mathbf{k})$ . (ii)  $\mathbf{r} = (\mathbf{i} + \mathbf{j} + \mathbf{k}) + \lambda(\mathbf{i} - 2\mathbf{j} + \mathbf{k})$ .
34. Suppose the relevant point is  $\mathbf{r} = \lambda(\mathbf{i} + \mathbf{j} + \mathbf{k})$ . The vector from this point to the reference point is  $\mathbf{r}_1 = (\lambda - 3)\mathbf{i} + (\lambda - 4)\mathbf{j} + (\lambda - 5)\mathbf{k}$ . Because the distance is minimal, the dot product with the direction vector of the line is 0. So,  $3\lambda - 12 = 0$ . So, the point is  $(4, 4, 4)$ .
35.  $\cos \theta = \frac{10}{\sqrt{14} \times \sqrt{14}} = \frac{5}{7}$  so the angle between them is  $\theta = \arccos \frac{5}{7} = 44.4^\circ$ .
36. This is given by  $\mathbf{r}_1 + \frac{1}{3}(\mathbf{r}_2 - \mathbf{r}_1) = \frac{2}{3}\mathbf{r}_1 + \frac{1}{3}\mathbf{r}_2$ . So the point required is  $(\frac{2x_1+x_2}{3}, \frac{2y_1+y_2}{3}, \frac{2z_1+z_2}{3})$ .
37. The resultant force is given by  $\mathbf{f} = 3\mathbf{i} - \mathbf{j}$  and the acceleration takes the same value (adjusting for units) because the body is unit mass. So,  $\mathbf{r}(t) = (\frac{3}{2}t^2 + 1)\mathbf{i} + (-\frac{1}{2}t^2 + 2)\mathbf{j}$ . For  $t > 2$ , matching the initial velocities:  $\mathbf{r}(t) = (6(t-2) + 1)\mathbf{i} + (-\frac{1}{2}t^2 + 2)\mathbf{j} = (6t - 11)\mathbf{i} + (-\frac{1}{2}t^2 + 2)\mathbf{j}$

## 2 Electricity

### 2.1 Current as a flow of charge

$$I = Anev = \frac{\pi}{4}d^2nev, \text{ and } t = \frac{l}{v} = \frac{\pi d^2 nel}{4I} = 1800 \text{ s}$$

### 2.2 Resistance and Resistivity

Total length is given by  $L = N \times D_{\text{avg}} \times \pi$ , so the resistance is  $R = \frac{4\rho N D_{\text{avg}}}{d^2} = 3.4 \Omega$

Power is given by  $P = I^2 R = 120 \text{ W}$

### 2.3 More resistivity

Suppose you have  $\rho$  for Silver and  $x\rho$  for Tin where  $x = 7.2$ . Now consider the perpendicular resistivity. Suppose the specific dimensions are so that if the whole block was Silver, the Resistance would be  $R$ . Similarly, it would be  $xR$  if the block were Tin. Since  $2/3$  of the block is Tin, the resistance due to Tin is  $\frac{2xR}{3}$  and for Silver is  $\frac{R}{3}$ . Therefore,  $\rho_{\perp} = (\frac{2}{3}x + \frac{1}{3})\rho$ . Now for parallel, using  $r$  instead for the same concept as  $R$  before, the resistance of the Tin is  $\frac{3}{2}xr$  and silver is  $3r$  so the effective resistance is  $\frac{1}{\frac{3}{2} + \frac{2}{3x}}r$  so  $\rho_{\parallel} = \frac{1}{\frac{3}{2} + \frac{2}{3x}}\rho$  and so the final result is that  $\frac{\rho_{\perp}}{\rho_{\parallel}} = (\frac{2}{3}x + \frac{1}{3})(\frac{1}{3} + \frac{2}{3x}) = \frac{1771}{810} = 2.19$

### 2.4 Simplified models

Correction to Electricity Q4

e.  $R_{\text{wire}}$  not negligible, so

$$R_{\text{wire}} = \frac{\rho l}{\pi r^2} = 0.021 \Omega$$

f.  $I = \frac{V}{R_{\text{wire}} + R_0} = 230 \text{ A (2sf)}$

Wire heats up a lot

Figure 1: Correction to problem 4