

Exp-9 E-book management system


USECASE DIAGRAM:




CLASS DIAGRAM:




ACTIVITY DIAGRAM:




SEQUENCE DIAGRAM:




COLLABORATION DIAGRAM:






COMPONENT DIAGRAM:



DEPLOYMENT DIAGRAM:



PROGRAM CODING:

```
* Class E_BOOK_MANAGEMENT_CLASS3
public class E_BOOK_MANAGEMENT_CLASS3 {
 //
 // Fields
 private Integer Enter_ID;
 private String Verify_User;
 // Constructors
 public E_BOOK_MANAGEMENT_CLASS3 () { };
 // Methods
 //
 //
 // Accessor methods
 //
 /**
 * Set the value of Enter_ID
 * @param newVar the new value of Enter_ID
 private void setEnter_ID (Integer newVar) {
  Enter_ID = newVar;
 /**
 * Get the value of Enter_ID
 * @return the value of Enter_ID
 private Integer getEnter_ID () {
  return Enter_ID;
 ,
/**
 * Set the value of Verify_User
 * @param newVar the new value of Verify_User
 private void setVerify_User (String newVar) {
  Verify_User = newVar;
 * Get the value of Verify_User
 * @return the value of Verify_User
 private String getVerify_User () {
  return Verify_User;
 //
 // Other methods
 //
 /**
 */
 public void Check_Availability()
* Class INTERNET
public class INTERNET {
 //
 // Fields
 private Integer Enter_ID;
 private void Download;
private void Loging;
 private void Logout;
 // Constructors
 public INTERNET() { };
 // Methods
```

```
//
//
// Accessor methods
//
/**
* Set the value of Enter_ID
* @param newVar the new value of Enter_ID
private void setEnter_ID (Integer newVar) {
Enter_ID = newVar;
* Get the value of Enter_ID
* @return the value of Enter_ID
private Integer getEnter_ID () {
return Enter_ID;
* Set the value of Download
* @param newVar the new value of Download
private void setDownload (void newVar) {
 Download = newVar;
* Get the value of Download
* @return the value of Download
private void getDownload () {
 return Download;
* Set the value of Loging
* @param newVar the new value of Loging
private void setLoging (void newVar) {
Loging = newVar;
/**
* Get the value of Loging
* @return the value of Loging
private void getLoging () {
 return Loging;
/**
* Set the value of Logout
* @param newVar the new value of Logout
private void setLogout (void newVar) {
Logout = newVar;
/**
* Get the value of Logout
\ast @return the value of Logout
private void getLogout () {
return Logout;
// Other methods
//
/**
*/
public void Verify()
public void Status()
```

```
* Class USER
*/
public class USER
 //
 // Fields
 //
 private void Login;
 private void Logout;
 // Constructors
 //
 public USER () { };
 // Methods
 //
 //
 // Accessor methods
 //
 * Set the value of Login
 * @param newVar the new value of Login
 private void setLogin (void newVar) {
  Login = newVar;
 * Get the value of Login
 * @return the value of Login
 private void getLogin () {
  return Login;
 * Set the value of Logout
 * @param newVar the new value of Logout
 private void setLogout (void newVar) {
  Logout = newVar;
 }
/**
 * Get the value of Logout
  * @return the value of Logout
 private void getLogout () {
  return Logout;
 // Other methods
 //
 /**
 public void Surf_books()
```