

```

CREATE TABLE `Produced` (
  `business_event_instance_id` binary(16) NOT NULL,
  `date` datetime(3) NOT NULL DEFAULT CURRENT_TIMESTAMP(3),
  `client_id` varchar(100) NOT NULL,
  `business_event_id` binary(16) NOT NULL,
  `actor_id` varchar(100) NOT NULL,
  `trigger_type` enum('logiflow','data contract','sor') NOT NULL,
  `trigger_execution_id` json DEFAULT NULL,
  `trace_id` varchar(100) NOT NULL,
  `user_context` varchar(100) NOT NULL,
  `explicit_context` varchar(100) DEFAULT NULL,
  `mask` varchar(32) DEFAULT NULL,
  `identifierfield` json DEFAULT NULL,
  `identifiertype` varchar(32) DEFAULT NULL,
  PRIMARY KEY (`business_event_instance_id`),
  KEY `client_id` (`client_id`,`business_event_id`),
  KEY `client_id_2` (`client_id`,`actor_id`),
  KEY `client_id_3` (`client_id`,`date`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8;

```

```
drop table Produced;
```

```
truncate table
```

```
select * from Produced where JSON_CONTAINS(identifierfield, '222');
```

```

explain SELECT * from Produced WHERE client_id =
'10857fb9-3671-4d3f-8c50-d506e5fa59e8' and identifiertype = '2';

```

```
and JSON_SEARCH(identifierfield, 'one', '89') IS NOT NULL;
```

```
DROP INDEX identifiertype ON Produced;
```

```

explain SELECT business_event_id from Produced WHERE client_id = '002' and
identifiertype = '2';

```

```
and JSON_SEARCH(identifierfield, 'one', '89') IS NOT NULL;
```

SHOW INDEX FROM Produced;

SHOW INDEX FROM ClientBusinessEvents;

explain SELECT count(*) from Produced WHERE client_id = '002' and
identifiertype = '2' and JSON_SEARCH(identifierfield, 'one', '89') IS NOT NULL;

explain select count(*) from Produced where (client_id = '002' and
identifiertype = '2') and JSON_SEARCH(identifierfield, 'one', '89') IS NOT NULL;

explain SELECT * from Produced WHERE client_id = '002' and identifiertype =
'2';

explain select * from Produced WHERE client_id = '002' and date = '2021-10-30
19:02:43.903';

explain select * from Produced WHERE client_id = '002' and actor_id =
'0a365620-581a-578a-aa2d-915ee298c6d6';

SELECT * from Produced WHERE FIND_IN_SET("222", identifierfield)>0;

delete from Produced where client_id = '10857fb9-3671-4d3f-8c50-
d506e5fa59e8';

INSERT INTO Produced (identifierfield)
VALUES ('["111", "222"]') ;

9b7f635c-8b0c-4e85-b5c1-4e2bdce42520

update Produced set identifierfield = '["656", "89", "777", "2"]' where trace_id

```
= '26425053-2f98-44dc-9a8b-8f4c84fcacab';
```

```
ALTER TABLE Produced  
DROP COLUMN identifierfield;
```

```
ALTER TABLE Produced  
MODIFY identiertype varchar(32) NOT NULL;
```

```
ALTER TABLE Produced add KEY identiertype (identiertype);
```

```
ALTER TABLE Produced  
ADD INDEX (client_id, identiertype);
```

```
SHOW GRANTS FOR 'be_dashboard'@'%';
```

```
GRANT SELECT, INSERT, DELETE ON *.* TO 'be_dashboard'@'%';
```

```
show events;
```

```
INSERT INTO ScheduledBusinessEvents (scheduledBusinessEventKey, eventId,  
clientId, businessEventId, entityId, sorTriggerType, executionTime, dateCreated,  
lastModified) values('1234','12345','001','12345678','234','test','2021-11-08  
03:27:08','','');
```

```
ALTER EVENT jobs_polling_event_scheduler  
ON SCHEDULE EVERY 20 SECOND  
ENABLE;
```

```
select * from ScheduledBusinessEvents where scheduledBusinessEventKey  
='1234';
```

```
ALTER EVENT business_events.jobs_polling_event_scheduler  
ON SCHEDULE EVERY 20 SECOND  
DISABLE ON SLAVE;
```

```
ALTER EVENT business_events.jobs_polling_event_scheduler  
ON SCHEDULE EVERY 5 SECOND  
ENABLE;
```

```
SET GLOBAL event_scheduler = OFF;
```

```
SHOW EVENTS  
WHERE STATUS = 'SLAVESIDE_DISABLED';
```

```
show events;
```

```
SET GLOBAL event_scheduler = ON;  
SHOW EVENTS;  
ALTER EVENT bus_sre_test_c_59e8.jobs_polling_event_scheduler  
ON SCHEDULE EVERY 10 SECOND  
DISABLE ON SLAVE;
```

```
select JSON_EXTRACT(identifier_field, '$90069f02-b7b9-57eb-  
a343-5534523242') from Produced where client_id = '002' and identifier_type  
= 'associate' and JSON_SEARCH(identifier_field, 'one', '90069f02-b7b9-57eb-  
a343-5534523242') IS NOT NULL;
```

```
select @@version;
```