

PICO_DEVELOPMENT_BOARD

Available_Peripheral :

PERIPHERAL	USE_CAUSE	CONDITION
UART(0,1)	UART_READ_WRITE	Working
SPI(0,1)	3.5_TFT_DISPLAY	Working
I2C(0,1)	LCD_DISPLAY	Working
PIO	LED_TOOGLE	Working
USB	USB_READ_WRITE	Working
SD	SD_READ_WRITE	Working
EEPROM		WORKING
RTC		WORKING
LCD(1-16)		WORKING
DSUM-1		working

METHOD_OF_TEST:

- **UART**

Read and Write ,Pins UART0,1 (gpio 0 TX , gpio 1 RX AND gpio 8 TX ,gpio 9 RX)

- **SPI**

WOKED IN dedicated PIN GPIO 2,3,4,5,10,11

```
#define LCD_SPI spi0
```

```
#define PIN_SCK 2
```

```
#define PIN_MOSI 3
```

```
#define PIN_MISO 4
```

```
#define PIN_CS 5
```

```
#define PIN_DC 10
```

```
#define PIN_RST 11
```

1. SPI -LOOP_BACK

2. SPI_3.5_TFT

- **I2C**

WORKED IN ASSIGNED PINS SPI1 – SDA - 6 , SCK- 7 .also WORK IN GPIO14,15

1.20x4 LCD DISPLAY

- **PIO**

1.LED_BLINK

- **USB_READ_WRITE**

A .TXT File can be readable

- **SD CARD READ**

DATA.txt file can be read and write.

PROBLEM : XIP or QSPI

SOLUTION: Removed the RESISTOR (R6,R7,R8,,R9,R15,14) QSPI IS WORKING , PROGRAM
Download via flash memory,

PROBLEM : dedicated i2c (j4) is not work.

SOLUTION:

I2C - REMOVED 5V PULLUP(removed R4 ,R5) TO 3.3V AND 10k ohms ,also Removed (C40 , C41).

Suggestions –

ADD a button or (j pin) for RUN PIN TO USE RESET.