

# Rajalakshmi Engineering College

Name: Harini Nagarajan  
Email: 240701167@rajalakshmi.edu.in  
Roll no: 240701167  
Phone: 9363551582  
Branch: REC  
Department: I CSE AG  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

**Input Format**

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

### ***Output Format***

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
// You are using GCC
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));  
    newnode->item=item;  
    newnode->next=NULL;  
    if(*head==NULL){  
        newnode->prev=NULL;  
        *head=newnode;  
        return;  
    }  
}
```

```
    struct Node*temp=*head;
    while(temp->next!=NULL){
        temp=temp->next;
        temp->next=newnode;
        newnode->prev=temp;
    }
    void displayForward(struct Node* head) {
        struct Node*temp=head;
        while(temp != NULL){
            printf("%c ",temp->item);
            temp=temp->next;}
        printf("\n");
    }
```

```
    void displayBackward(struct Node* tail) {
        struct Node* temp=tail;
        while(temp != NULL){
            printf("%c ",temp->item);
            temp=temp->prev;}
        printf("\n");
    }
```

```
    void freePlaylist(struct Node* head) {
        struct Node*temp;
        while(head != NULL){
            temp=head;
            head=head->next;
            free(temp);
        }
    }
```

```
    int main() {
        struct Node* playlist = NULL;
        char item;

        while (1) {
            scanf(" %c", &item);
            if (item == '-') {
                break;
            }
            insertAtEnd(&playlist, item);
        }
```

```
    struct Node* tail = playlist;
    while (tail->next != NULL) {
        tail = tail->next;
    }

    printf("Forward Playlist: ");
    displayForward(playlist);

    printf("Backward Playlist: ");
    displayBackward(tail);

    freePlaylist(playlist);

    return 0;
}
```

**Status :** Correct

**Marks : 10/10**