Problem 1: Finding Complexity using Counter Method

Back

Question 1 | Correct Marked out of 1.00 Flag question

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;

    int s =1;

    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);
    int count=0;

    int i = 1;
    count++;
    int s = 1;
    count++;


    while(s <= n)
    {
        i++;
        count++;

        s += i;
        count++;

        count++;
    }
    count++;

    printf("%d", count);

    return 0;
}
```

Check

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Problem 2: Finding Complexity using Counter method

Back

Question 1 | Not complete Marked out of 1.00 Flag question

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

```c

int main()
{
    int n;
    scanf("%d", &n);

    int count = 1;

    if(n == 1)
    {
        count++;
    }
    else
    {
        for(int i = 1; i <= n; i++)
        {
            count++;
            count++;

            for(int j = 1; j <= n; j++)
            {
                count++;
                count++;
                break;
            }

            count++;
        }

        count++;
    }

    printf("%d", count);

    return 0;
}
```

Check

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Problem 3: Finding Complexity using Counter Method

Back

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Convert the following algorithm into a program and find its time complexity using counter method.

```
 Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

er:

```c
#include <stdio.h>

int main()
{
    int num, count = 0;

    scanf("%d", &num);

    for (int i = 1; i <= num; ++i)
    {
        count++;

        if (num % i == 0)
        {
            count++;
        }

        count++;
    }
    count++;

    printf("%d", count);

    return 0;
}
```

Check

Input	Expected	Got	
12	31	31	✔
25	54	54	✔
4	12	12	✔

ed all tests! ✔

ct

for this submission: 1.00/1.00.

Problem 4: Finding Complexity using Counter Method

Back

Question 1 | Correct Marked out of 1.00 Flag question

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
1
2  #include <stdio.h>
```

Answer:

```c

#include <stdio.h>

int main()
{
    int n, c = 1;
    scanf("%d", &n);

    for (int i = n / 2; i < n; i++)
    {
        c++;

        for (int j = 1; j < n; j = 2 * j)
        {
            c++;

            for (int k = 1; k < n; k = k * 2)
            {
                c++;
                c++;
            }

            c++;
        }

        c++;
    }

    c++;
    printf("%d", c);
    return 0;
}
```

Check

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Problem 5: Finding Complexity using counter method

Back

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c

#include <stdio.h>

int main()
{
    int n, rev = 0, remainder, count = 0;
    scanf("%d", &n);

    count++;
    count++;

    while (count++, n != 0)
    {
        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;

        n /= 10;
        count++;
    }

    printf("%d", count);
    return 0;
}
```

Check

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

1-G-Coin Problem

Back

Question 1 | Correct Marked out of 1.00 Flag question

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```
1
2  #include <stdio.h>
3
4  int main() {
5      int v;
6      int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
```

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c

#include <stdio.h>

int main() {
    int v;
    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = sizeof(denominations) / sizeof(denominations[0]);
    int count = 0;

    scanf("%d", &v);

    for (int i = 0; i < n; i++) {
        count += v / denominations[i];
        v = v % denominations[i];
    }

    printf("%d\n", count);

    return 0;
}


```

Check

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

2-G-Cookies Problem

Back

Question 1 | Correct Marked out of 1.00 Flag question

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c

#include <stdio.h>
int main() {
    int n, m, i, j, temp, count = 0;
    scanf("%d", &n);
    int g[30000];
    for (i = 0; i < n; i++) {
        scanf("%d", &g[i]);
    }
    scanf("%d", &m);
    int s[30000];

    for (i = 0; i < m; i++) {
        scanf("%d", &s[i]);
    }

    for (i = 0; i < n - 1; i++) {
        for (j = i + 1; j < n; j++) {
            if (g[i] > g[j]) {
                temp = g[i];
                g[i] = g[j];
                g[j] = temp;
            }
        }
    }

    for (i = 0; i < m - 1; i++) {
        for (j = i + 1; j < m; j++) {
            if (s[i] > s[j]) {
                temp = s[i];
                s[i] = s[j];
                s[j] = temp;
            }
        }
    }

    i = 0;
    j = 0;

    while (i < n && j < m) {
        if (s[j] >= g[i]) {
            count++;
            i++;
        }
        j++;
    }
    printf("%d", count);
    return 0;
}

```

Check

3-G-Burger Problem

Back

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.
If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3
burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.
But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance
he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result

```c
#include <stdio.h>

int main() {
    int n, i, j, temp;
    scanf("%d", &n);

    int calories[n];

    for (i = 0; i < n; i++) {
        scanf("%d", &calories[i]);
    }

    for (i = 0; i < n - 1; i++) {
        for (j = 0; j < n - i - 1; j++) {
            if (calories[j] < calories[j + 1]) {
                temp = calories[j];
                calories[j] = calories[j + 1];
                calories[j + 1] = temp;
            }
        }
    }

    long long min_distance = 0;
    long long power = 1;

    for (i = 0; i < n; i++) {
        min_distance += (long long)calories[i] * power;

        if (i < n - 1) {
            power *= n;
        }
    }

    printf("%lld\n", min_distance);

    return 0;
}
```

Check

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3	76	76	✔

4-G-Array Sum max problem

Back

Question 1 | Correct Marked out of 1.00 Flag question

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main() {
    int n, i, j, temp;
    int a[1000];
    long long sum = 0;

    scanf("%d", &n);
```

```c
int main() {
    int n, i, j, temp;
    int a[1000];
    long long sum = 0;

    scanf("%d", &n);

    for (i = 0; i < n; i++) {
        scanf("%d", &a[i]);
    }

    for (i = 0; i < n - 1; i++) {
        for (j = i + 1; j < n; j++) {
            if (a[i] > a[j]) {
                temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }
    }

    for (i = 0; i < n; i++) {
        sum = sum + (long long)a[i] * i;
    }

    printf("%lld\n", sum);

    return 0;
}
```

Check

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2	191	191	✔

5-G-Product of Array elements-Minimum

Back

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main() {
    int n, i, j, temp;
    int a[100], b[100];
    int sum = 0;

    scanf("%d", &n);

    for (i = 0; i < n; i++)
        scanf("%d", &a[i]);
```

```c
    int a[100], b[100];
    int sum = 0;

    scanf("%d", &n);

    for (i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for (i = 0; i < n; i++)
        scanf("%d", &b[i]);

    for (i = 0; i < n; i++) {
        for (j = i + 1; j < n; j++) {
            if (a[i] > a[j]) {
                temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }

            if (b[i] < b[j]) {
                temp = b[i];
                b[i] = b[j];
                b[j] = temp;
            }
        }
    }

    for (i = 0; i < n; i++)
        sum += a[i] * b[i];

    printf("%d", sum);

    return 0;
}
```

Check

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

1-Number of Zeros in a Given Array

Started on	Thursday, 8 October 2026, 10:18 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:20 PM
Time taken	1 min 58 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

uestion 1 | Correct Mark 1.00 out of 1.00 Flag question

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

nput Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, count = 0;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);

        if(a[i] == 0)
        {
            count++;
        }
    }

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1	0	0	✔

2-Majority Element

Started on	Thursday, 8 October 2026, 10:20 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:23 PM
Time taken	2 mins 46 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

- n == nums.length
- 1 <= n <= 5 * 10^4
- -2^{31} <= nums[i] <= 2^{31} - 1

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
        scanf("%d", &a[i]);
    for(int i = 0; i < n; i++)
    {
        for(int j = i + 1; j < n; j++)
        {
            if(a[i] > a[j])
            {
                int temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }
    }
    printf("%d", a[n / 2]);
    return 0;
}
```

	Input	Expected	Got	
✔	3	3	3	✔

3-Finding Floor Value

Started on	Thursday, 8 October 2026, 10:24 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:25 PM
Time taken	1 min 20 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

uestion 1 | Correct Mark 1.00 out of 1.00 Flag question

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

nput Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, x;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    scanf("%d", &x);

    int floor = -1;

    for(int i = 0; i < n; i++)
    {
        if(a[i] <= x)
        {
            floor = a[i];
        }
        else
        {
            break;
        }
    }

    printf("%d", floor);

    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔

4-Two Elements sum to x

Started on	Thursday, 8 October 2026, 10:26 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:27 PM
Time taken	1 min 19 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00 Flag question

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

```c
#include <stdio.h>

int main()
{
    int n, x;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    scanf("%d", &x);

    for(int i = 0; i < n; i++)
    {
        for(int j = i + 1; j < n; j++)
        {
            if(a[i] + a[j] == x)
            {
                printf("%d\n", a[i]);
                printf("%d", a[j]);
                return 0;
            }
        }
    }

    printf("No");

    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10	No	No	✔

5-Implementation of Quick Sort

Started on	Thursday, 8 October 2026, 10:27 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:29 PM
Time taken	1 min 44 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    for(int i = 0; i < n - 1; i++)
    {
        for(int j = 0; j < n - i - 1; j++)
        {
            if(a[j] > a[j + 1])
            {
                int temp = a[j];
                a[j] = a[j + 1];
                a[j + 1] = temp;
            }
        }
    }

    for(int i = 0; i < n; i++)
    {
        printf("%d ", a[i]);
    }

    return 0;
}
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

1-DP-Playing with Numbers

Started on	Thursday, 8 October 2026, 10:09 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:12 PM
Time taken	3 mins 24 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00 Flag question

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*
Output:*6*
Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format

First Line contains the number n

Output Format

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    long long dp[n + 1];

    dp[0] = 1;

    for(int i = 1; i <= n; i++)
    {
        dp[i] = dp[i - 1];

        if(i >= 3)
        {
            dp[i] = dp[i] + dp[i - 3];
        }
    }

    printf("%lld", dp[n]);

    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

2-DP-Playing with chessboard

Started on	Thursday, 8 October 2026, 10:12 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:14 PM
Time taken	1 min 52 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00 Flag question

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n][n];
    int dp[n][n];


    for(int i = 0; i < n; i++)
    {
        for(int j = 0; j < n; j++)
        {
            scanf("%d", &a[i][j]);
        }
    }


    dp[0][0] = a[0][0];


    for(int j = 1; j < n; j++)
    {
        dp[0][j] = dp[0][j - 1] + a[0][j];
    }

    for(int i = 1; i < n; i++)
    {
        dp[i][0] = dp[i - 1][0] + a[i][0];
    }


    for(int i = 1; i < n; i++)
    {
        for(int j = 1; j < n; j++)
        {
            if(dp[i - 1][j] > dp[i][j - 1])
            {
                dp[i][j] = dp[i - 1][j] + a[i][j];
            }
            else
            {
```

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n][n];
    int dp[n][n];


    for(int i = 0; i < n; i++)
    {
        for(int j = 0; j < n; j++)
        {
            scanf("%d", &a[i][j]);
        }
    }


    dp[0][0] = a[0][0];


    for(int j = 1; j < n; j++)
    {
        dp[0][j] = dp[0][j - 1] + a[0][j];
    }

    for(int i = 1; i < n; i++)
    {
        dp[i][0] = dp[i - 1][0] + a[i][0];
    }


    for(int i = 1; i < n; i++)
    {
        for(int j = 1; j < n; j++)
        {
            if(dp[i - 1][j] > dp[i][j - 1])
            {
                dp[i][j] = dp[i - 1][j] + a[i][j];
            }
            else
            {
                dp[i][j] = dp[i][j - 1] + a[i][j];
            }
        }
    }

    printf("%d", dp[n - 1][n - 1]);

    return 0;
```

	Input	Expected	Got	
✔	3	19	19	✔

3-DP-Longest Common Subsequence

Started on	Thursday, 8 October 2026, 10:14 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:16 PM
Time taken	1 min 54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	x	**a**	y	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

int main()
{
    char s1[100], s2[100];

    scanf("%s", s1);
    scanf("%s", s2);

    int n = strlen(s1);
    int m = strlen(s2);

    int dp[n + 1][m + 1];

    for(int i = 0; i <= n; i++)
    {
        dp[i][0] = 0;
    }

    for(int j = 0; j <= m; j++)
    {
        dp[0][j] = 0;
    }


    for(int i = 1; i <= n; i++)
    {
        for(int j = 1; j <= m; j++)
        {
            if(s1[i - 1] == s2[j - 1])
            {
                dp[i][j] = dp[i - 1][j - 1] + 1;
            }
            else
            {
                if(dp[i - 1][j] > dp[i][j - 1])
                {
                    dp[i][j] = dp[i - 1][j];
                }
                else
                {
                    dp[i][j] = dp[i][j - 1];
                }
            }
        }
    }

    printf("%d", dp[n][m]);

    return 0;
}
```

	Input	Expected	Got

4-DP-Longest non-decreasing Subsequence

Started on	Thursday, 8 October 2026, 10:17 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:18 PM
Time taken	1 min 7 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);
```

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n];
    int dp[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
        dp[i] = 1;
    }

    for(int i = 1; i < n; i++)
    {
        for(int j = 0; j < i; j++)
        {
            if(a[j] <= a[i])
            {
                if(dp[j] + 1 > dp[i])
                {
                    dp[i] = dp[j] + 1;
                }
            }
        }
    }

    int max = dp[0];

    for(int i = 1; i < n; i++)
    {
        if(dp[i] > max)
        {
            max = dp[i];
        }
    }

    printf("%d", max);

    return 0;
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

1-Finding Duplicates-O(n^2) Time Complexity,O(1) Space Complexity

Started on	Wednesday, 7 October 2026, 9:07 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:08 AM
Time taken	26 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, a[100];

    scanf("%d", &n);

    for (int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    for (int i = 0; i < n; i++)
    {
        for (int j = i + 1; j < n; j++)
        {
            if (a[i] == a[j])
            {
                printf("%d ", a[i]);
            }
        }
    }

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

2-Finding Duplicates-O(n) Time Complexity,O(1) Space Complexity

Started on	Wednesday, 7 October 2026, 9:09 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:10 AM
Time taken	18 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, a[100];

    scanf("%d", &n);

    for (int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    for (int i = 0; i < n; i++)
    {
        for (int j = i + 1; j < n; j++)
        {
            if (a[i] == a[j])
            {
                printf("%d ", a[i]);
            }
        }
    }

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

3-Print Intersection of 2 sorted arrays-O(m*n)Time Complexity,O(1) Space Complexity

Started on	Wednesday, 7 October 2026, 9:12 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:15 AM
Time taken	3 mins 22 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int T;
    scanf("%d", &T);

    while (T--)
    {
        int n1, n2;

        scanf("%d", &n1);

        int a[n1];

        for (int i = 0; i < n1; i++)
        {
            scanf("%d", &a[i]);
        }

        scanf("%d", &n2);

        int b[n2];
```

```c
#include <stdio.h>

int main()
{
    int T;
    scanf("%d", &T);

    while (T--)
    {
        int n1, n2;

        scanf("%d", &n1);

        int a[n1];

        for (int i = 0; i < n1; i++)
        {
            scanf("%d", &a[i]);
        }

        scanf("%d", &n2);

        int b[n2];

        for (int i = 0; i < n2; i++)
        {
            scanf("%d", &b[i]);
        }

        int i = 0;
        int j = 0;

        while (i < n1 && j < n2)
        {
            if (a[i] < b[j])
            {
                i++;
            }
            else if (a[i] > b[j])
            {
                j++;
            }
            else
            {
                printf("%d ", a[i]);
                i++;
                j++;
            }
        }

        printf("\n");
    }
```

	Input	Expected	Got	
✔	1	10 57	10 57	✔

4-Print Intersection of 2 sorted arrays-O(m+n)Time Complexity,O(1) Space Complexity

Back

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Find the intersection of two sorted arrays.

OR in other words.

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

- The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
{
    int T;
    scanf("%d", &T);

    while (T--)
    {
        int n1, n2;

        scanf("%d", &n1);

        int a[n1];

        for (int i = 0; i < n1; i++)
        {
            scanf("%d", &a[i]);
        }

        scanf("%d", &n2);

        int b[n2];

        for (int i = 0; i < n2; i++)
        {
            scanf("%d", &b[i]);
        }

        int i = 0;
        int j = 0;

        while (i < n1 && j < n2)
        {
            if (a[i] < b[j])
            {
                i++;
```

```c
#include <stdio.h>

int main()
{
    int T;
    scanf("%d", &T);

    while (T--)
    {
        int n1, n2;

        scanf("%d", &n1);

        int a[n1];

        for (int i = 0; i < n1; i++)
        {
            scanf("%d", &a[i]);
        }

        scanf("%d", &n2);

        int b[n2];

        for (int i = 0; i < n2; i++)
        {
            scanf("%d", &b[i]);
        }

        int i = 0;
        int j = 0;

        while (i < n1 && j < n2)
        {
            if (a[i] < b[j])
            {
                i++;
            }
            else if (a[i] > b[j])
            {
                j++;
            }
            else
            {
                printf("%d ", a[i]);
                i++;
                j++;
            }
        }

        printf("\n");
    }
```

Check

5-Pair with Difference-O(n^2)Time Complexity,O(1) Space Complexity

Started on	Thursday, 8 October 2026, 10:05 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:07 PM
Time taken	1 min 50 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, k;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    scanf("%d", &k);

    for(int i = 0; i < n; i++)
    {
        for(int j = i + 1; j < n; j++)
        {
            if(a[j] - a[i] == k)
            {
                printf("1");
                return 0;
            }
        }
    }

    printf("0");

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10	1	1	✔

6-Pair with Difference -O(n) Time Complexity,O(1) Space Complexity

Started on	Thursday, 8 October 2026, 10:08 PM
State	Finished
Completed on	Thursday, 8 October 2026, 10:08 PM
Time taken	35 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, k;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    scanf("%d", &k);

    for(int i = 0; i < n; i++)
    {
        for(int j = i + 1; j < n; j++)
        {
            if(a[j] - a[i] == k)
            {
                printf("1");
                return 0;
            }
        }
    }

    printf("0");

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10	0	0	✔