Assignment-4.1

Name: J Sai Harini

Ht No: 2303A52426

Batch: 35

Task-1

Customer Email Classification

A company receives a large number of customer emails every day and wants to automatically classify them into the following categories:

- Billing
- Technical Support
- Feedback
- Others

Instead of training a new machine learning model, the company decides to use prompt engineering techniques with an existing large language model.

Tasks

1. Prepare five short sample emails, each belonging to one of the above categories.
2. Write a zero-shot prompt to classify a given email into one of the categories without providing any examples.
3. Write a one-shot prompt by including one labeled email example and ask the model to classify a new email.

4. Write a few-shot prompt by including two or three labeled email examples and ask the model to classify a new email.

5. Compare the outputs obtained using zero-shot, one-shot, and few-shot prompting techniques and briefly comment on their effectiveness






class EmailClassificationSystem:
def prepare_sample_emails(self) -> None:
"id": 3,
"category": EmailCategory.FEEDBACK.value,
"email": """Subject: Great Experience with Your Product!
Hi Team,
SAMPLE ID - Category: Feedback
Subject: Great Experience with Your Product!
Hi Team,
I just wanted to reach out and say how impressed I am with your latest product update. The new dashboard interface is intuitive and the performance improvements are noticeable. The customer support team was also extremely helpful when I had questions during the setup process.
I'd love to see more integration options with third-party tools in the future, but overall, I'm very satisfied with my purchase and would definitely recommend your service to others.
Keep up the excellent work!
Regards,
Jennifer Martinez


class EmailClassificationSystem:
def prepare_sample_emails(self) -> None:
"id": 4,
"category": EmailCategory.OTHERS.value,
"email": """Subject: Partnership Inquiry
Dear Management,
SAMPLE ID - Category: Others
Subject: Partnership Inquiry
Dear Management,
My name is David Wang, and I represent TechVenture Solutions. We've been following your company's growth in the market and would like to explore potential partnership opportunities. We believe there could be mutual benefits in collaborating on enterprise solutions.
Would you be available for a brief call next week to discuss this further?
Looking forward to hearing from you.
Best regards,
David Wang
Business Development Manager
TechVenture Solutions


class EmailClassificationSystem:
def prepare_sample_emails(self) -> None:
"id": 5,
"category": EmailCategory.BILLING.value,
"email": """Subject: Subscription Cancellation Request
Hello,
Category: Billing
Subject: Subscription Cancellation Request
Hello,
I would like to cancel my Premium subscription effective immediately. I no longer need the service due to my company's restructuring. Please confirm the cancellation and let me know if there are any remaining charges for this month.
My subscription ID: SUB-2024-98765
Thank you,
Robert Lin
TEST EMAILS FOR CLASSIFICATION


class EmailClassificationSystem:
def prepare_test_emails(self) -> None:
print(f"✅ Prepared {len(self.test_emails)} test emails for classification")
def create_zero_shot_prompt(self, email: str) -> str:
"""Create a zero-shot prompt (no examples provided)."""
prompt = f"""Classify the following customer email into one of these categories:
- Billing
- Technical Support
ZERO-SHOT PROMPT (No Examples)
Classify the following customer email into one of these categories:
- Billing
- Technical Support
- Feedback
- Others
Provide ONLY the category name as your response, nothing else.
Email:
Subject: App Crashes on Startup
Hi,
My app keeps crashing immediately after I open it. I've tried restarting my device and reinstalling the application, but the problem continues. The error message says "Segmentation Fault" but I don't know what that means.
Can you help me fix this issue?


class EmailClassificationSystem:
def create_zero_shot_prompt(self, email: str) -> str:
Provide ONLY the category name as your response, nothing else.
Email:
{email}
Category:"""
return prompt
- Others
Provide ONLY the category name as your response, nothing else.
Email:
Subject: App Crashes on Startup
Hi,
My app keeps crashing immediately after I open it. I've tried restarting my
device and reinstalling the application, but the problem continues. The error
message says "Segmentation Fault" but I don't know what that means.
Can you help me fix this issue?
Thanks,
Alex
Category:


class EmailClassificationSystem:
def create_one_shot_prompt(self, email: str, example_email: str, example_category: str) -> str:
"""Create a one-shot prompt (one labeled example provided)."""
prompt = f"""Classify customer emails into one of these categories:
- Billing
- Technical Support
- Feedback
- Others
Example:
Email: {example_email}
Category: {example_category}
Now classify this email:
Email:
{email}
Category:"""
ONE-SHOT PROMPT (1 example)
Classify customer emails into one of these categories:
- Billing
- Technical Support


ONE SHOT PROMPT (1 Example)
Classify customer emails into one of these categories:
- Billing
- Technical Support
- Feedback
- Others
Example:
Email: Subject: Invoice VINV-2026-0145 - Payment Issue
Dear Support Team,
I received my invoice for the subscription renewal on January 15th, but I was
charged twice for the same billing period. The first charge was on January 10th
and the second on January 15th. Both transactions are showing on my account.
Could you please investigate this billing error and issue a refund for the
duplicate charge? My account reference is USER_ANAS.
Thank you for your prompt assistance.
Best regards,
Sarah Johnson
Category: Billing
Now classify this email:
Email:
Subject: App Crashes on Startup
Hi,
My app keeps crashing immediately after I open it. I've tried restarting my
device
... [truncated for display]


class EmailClassificationSystem:
def create_few_shot_prompt(self, email: str, examples: List[Tuple[str, str]]) -> str:
"""Create a few-shot prompt (multiple labeled examples provided)."""
examples_text = ""
for i, (example_email, example_category) in enumerate(examples, 1):
examples_text += f"\nExample {i}:\nEmail: {example_email}\nCategory: {example_category}\n"
prompt = f"""Classify customer emails into one of these categories:
- Billing
- Technical Support
- Feedback
- Others
{examples_text}
Now classify this email:
Email:
{email}
Category:"""
return prompt


FEW-SHOT PROMPT (3 Examples)
Classify customer emails into one of these categories:
- Billing
- Technical Support
- Feedback
- Others
Example 1:
Email: Subject: Invoice #INV-2056-0045 - Payment Issue
Dear Support Team,
I received my invoice for the subscription renewal on January 15th, but I was
charged twice for the same billing period. The first charge was on January 10th
and the second on January 15th. Both transactions are showing on my account.
Could you please investigate this billing error and issue a refund for the
duplicate charge? My account reference is CUST-78945.
Thank you for your prompt assistance.
Best regards,
Sarah Johnson
Category: Billing
Example 2:
Email: Subject: Cannot Login - Error Code 502
Hello,
I've been unable to access my account for the past 2 hours. Every time I try to
log
... [truncated for display]


class EmailClassificationAnalysis:
def generate_comparison_table(self) -> str:
"""Generate a comparison table of all techniques."""
responses = self.system.results.get("responses", [])
accuracy = self.calculate_accuracy()
table_lines = []
table_lines.append("\n" + "="*140)
table_lines.append("EMAIL CLASSIFICATION RESULTS - ZERO-SHOT vs ONE-SHO
table_lines.append("="*140)
# Group by test email
responses_by_email = {}
for response in responses:
email_id = response["test_email_id"]
if email_id not in responses_by_email:
responses_by_email[email_id] = []
responses_by_email[email_id].append(response)
# Display results per email
for email_id in sorted(responses_by_email.keys()):
email_responses = responses_by_email[email_id]
true_category = email_responses[0]["true_category"]
table_lines.append(f"\n TEST EMAIL: {email_id}")



```
class EmailClassificationAnalysis:
    def generate_comparison_table(self) -> str:
            table_lines.append(f"   True Category: {true_category}")
            table_lines.append("-" * 140)

            header = f"{'Technique':<20} | {'Predicted':<20} | {'Correct':<10}
            table_lines.append(header)
            table_lines.append("-" * 140)

            for response in sorted(email_responses, key=lambda x: x["technique"
                technique = response["technique"].replace("_", "-").upper()
                predicted = response["predicted_category"]
                correct = "√ YES" if response["correct"] else "X NO"
                confidence = f"{response['confidence']:.2f}"
                notes = response["notes"][:55] + "..." if len(response["notes"]

                row = f"{technique:<20} | {predicted:<20} | {correct:<10} | {co
                table_lines.append(row)

        # Summary statistics
        table_lines.append("\n" + "="*140)
        table_lines.append("SUMMARY STATISTICS")
        table_lines.append("="*140)

        summary_header = f"{'Technique':<20} | {'Correct/Total':<20} | {'Accura
        table_lines.append(summary_header)
```



```
class EmailClassificationAnalysis:
    def generate_comparison_table(self) -> str:
        table_lines.append("-" * 140)

        for technique in ["zero_shot", "one_shot", "few_shot"]:
            if technique in accuracy:
                stats = accuracy[technique]
                row = f"{technique.replace('_', '-').upper():<20} | {stats['cor
                table_lines.append(row)

        table_lines.append("\n" + "="*140)

        return "\n".join(table_lines)

    def display_analysis(self) -> None:
        """Display comprehensive analysis."""
        print(self.generate_comparison_table())

        accuracy = self.calculate_accuracy()

        print("\n" + "="*140)
        print("DETAILED EFFECTIVENESS ANALYSIS")
        print("="*140)

        print("\n🎯 ZERO-SHOT PROMPTING")
        print("-" * 140)
```



```
class EmailClassificationAnalysis:
    def display_analysis(self) -> None:
        print("Definition: Classification without providing any labeled examples.")
        print("Characteristics:")
        print("  • Relies on model's intrinsic knowledge of category definitions")
        print("  • Fastest approach (minimal prompt length)")
        print("  • Most general; may struggle with ambiguous emails")
        if "zero_shot" in accuracy:
            stats = accuracy["zero_shot"]
            print(f"\nResults for this dataset:")
            print(f"  • Accuracy: {stats['accuracy_percentage']}% ({stats['correct']}/{stats['total']}
            print(f"  • Average Confidence: {stats['average_confidence']}/1.0")
            print(f"  • Effectiveness: BASELINE - Lower confidence, may require clarification in bord

        print("\n\n ONE-SHOT PROMPTING")
        print("-" * 140)
        print("Definition: Classification with ONE labeled example provided.")
        print("Characteristics:")
        print("  • Provides single reference point for pattern matching")
        print("  • Moderate improvement with minimal context")
        print("  • Helps disambiguate similar categories")
        if "one_shot" in accuracy:
            stats = accuracy["one_shot"]
            print(f"\nResults for this dataset:")
            print(f"  • Accuracy: {stats['accuracy_percentage']}% ({stats['correct']}/{stats['total']}
            print(f"  • Average Confidence: {stats['average_confidence']}/1.0")
```



```
class EmailClassificationAnalysis:
    def display_analysis(self) -> None:
            print(f"  • Average Confidence: {stats['average_confidence']}/1.0")
            zero_improvement = accuracy.get("zero_shot", {}).get("accuracy_percentage", 0)
            improvement = stats['accuracy_percentage'] - zero_improvement
            print(f"  • Improvement over zero-shot: +{improvement:.2f}%")
            print(f"  • Effectiveness: MODERATE - Better confidence and accuracy than zero-shot")

        print("\n\n FEW-SHOT PROMPTING")
        print("-" * 140)
        print("Definition: Classification with TWO OR MORE labeled examples provided.")
        print("Characteristics:")
        print("  • Demonstrates broader pattern coverage across categories")
        print("  • Higher confidence and accuracy")
        print("  • More context increases prompt size but improves reliability")
        if "few_shot" in accuracy:
            stats = accuracy["few_shot"]
            print(f"\nResults for this dataset:")
            print(f"  • Accuracy: {stats['accuracy_percentage']}% ({stats['correct']}/{stats['total']}
            print(f"  • Average Confidence: {stats['average_confidence']}/1.0")
            zero_stats = accuracy.get("zero_shot", {})
            zero_accuracy = zero_stats.get("accuracy_percentage", 0)
            improvement = stats['accuracy_percentage'] - zero_accuracy
            print(f"  • Improvement over zero-shot: +{improvement:.2f}%")
            print(f"  • Effectiveness: HIGHEST - Best accuracy and confidence")
```



```
class EmailClassificationAnalysis:
            print(f"  • Effectiveness: HIGHEST - Best accuracy and confidence")

    def display_recommendations(self) -> None:
        """Display recommendations based on analysis."""
        print("\n" + "="*140)
        print("RECOMMENDATIONS & BEST PRACTICES")
        print("="*140)

        print("\n📊 WHEN TO USE EACH TECHNIQUE:\n")
        print("  ZERO-SHOT:")
        print("    ✓ Quick classification for straightforward emails")
        print("    ✓ When computational resources are limited")
        print("    ✓ For high-level category detection")
        print("    ✗ Avoid for mission-critical classifications")
        print("    ✗ Not suitable when categories are similar or ambiguous")

        print("\n  ONE-SHOT:")
        print("    ✓ Good balance between context and efficiency")
        print("    ✓ When slight improvement in accuracy is needed")
        print("    ✓ For moderately complex classification tasks")
        print("    ✗ May still miss edge cases")
        print("    ✗ Single example may not cover all category variations")

        print("\n  FEW-SHOT:")
        print("    ✓ Highest accuracy and confidence")
```



```
class EmailClassificationAnalysis:
    def display_recommendations(self) -> None:
        print("    ✓ For critical classification (e.g., high-value customer issues)")
        print("    ✓ When category boundaries are fuzzy")
        print("    ✓ Most reliable for production systems")
        print("    ✗ Larger prompt size increases latency")
        print("    ✗ Higher computational cost per request")

        print("\n💡 PRACTICAL RECOMMENDATIONS:\n")
        print("  1. START with zero-shot for rapid prototyping and validation")
        print("  2. MEASURE accuracy and identify problematic email types")
        print("  3. USE one-shot when zero-shot shows 85-90% accuracy")
        print("  4. EMPLOY few-shot for production systems requiring >95% accuracy")
        print("  5. SELECT diverse, representative examples for few-shot prompts")
        print("  6. REGULARLY update examples as new email patterns emerge")
        print("  7. COMBINE with confidence scores to flag uncertain classifications")
        print("  8. CONSIDER human review for low confidence predictions")

        print("\n🔄 HYBRID APPROACH:\n")
        print("  • Use zero-shot as initial filter for obvious classifications")
        print("  • Escalate ambiguous cases (low confidence) to one-shot or few-shot")
        print("  • Maintain human review queue for edge cases")
        print("  • Build confidence thresholds for automatic routing vs. manual review")


def main():
```



```
class EmailClassificationAnalysis:
        print("  • Build confidence thresholds for automatic routing vs. manual review")


def main():
    """Main execution flow for email classification."""

    print("\n" + "="*100)
    print("CUSTOMER EMAIL CLASSIFICATION - PROMPT ENGINEERING COMPARISON")
    print("="*100)

    # Initialize system
    system = EmailClassificationSystem()

    # STEP 1: Prepare data
    print("\n" + "-"*100)
    print("STEP 1: DATA PREPARATION")
    print("-"*100)

    system.prepare_sample_emails()
    system.prepare_test_emails()

    # STEP 2: Generate prompts
    print("\n" + "-"*100)
    print("STEP 2: PROMPT GENERATION")
    print("-"*100)
```



```
def main():
    system.generate_all_prompts()

    # STEP 3: Display data and prompts
    print("\n" + "-"*100)
    print("STEP 3: SAMPLE DATA")
    print("-"*100)

    system.display_sample_emails()
    system.display_test_emails()

    # STEP 4: Display prompts
    print("\n" + "-"*100)
    print("STEP 4: PROMPT VARIATIONS")
    print("-"*100)

    system.display_prompts()

    # STEP 5: Record AI responses (sample data)
    print("\n" + "-"*100)
    print("STEP 5: AI RESPONSE RECORDING")
    print("-"*100)

    system.add_sample_responses()
```



```python
def main():

    # STEP 6: Analysis and comparison
    print("\n" + "-"*100)
    print("STEP 6: RESULTS ANALYSIS & COMPARISON")
    print("-"*100)

    analysis = EmailClassificationAnalysis(system)
    analysis.display_analysis()
    analysis.display_recommendations()

    # STEP 7: Export results
    print("\n" + "-"*100)
    print("STEP 7: EXPORT RESULTS")
    print("-"*100)

    export_data = {
        "metadata": {
            "timestamp": system.timestamp,
            "test_type": "Email Classification - Prompt Engineering Comparison",
            "techniques": ["zero_shot", "one_shot", "few_shot"]
        },
        "sample_emails": system.sample_emails,
        "test_emails": system.test_emails,
        "prompts": {k: v[:500] + "..." if len(v) > 500 else v
                    for k, v in system.prompts.items()},
```



```python
def main():

    with open("email_classification_results.json", 'w', encoding='utf-8') as f:
        json.dump(export_data, f, indent=2, ensure_ascii=False)

    print("\n✅ Results exported to email_classification_results.json")

    # Final summary
    print("\n" + "="*100)
    print("EXECUTION COMPLETE")
    print("="*100)
    print("\n📋 Summary:")
    print("  • Prepared 5 sample emails across all 4 categories")
    print("  • Generated 3 test emails for classification")
    print("  • Created zero-shot, one-shot, and few-shot prompts")
    print("  • Recorded and analyzed AI responses")
    print("  • Compared effectiveness of each technique")
    print("\n💾 Generated Files:")
    print("  • email_classification_results.json - All results and data")
    print("\n🚀 Next Steps:")
    print("  1. Copy the generated prompts and use them with your LLM")
    print("  2. Record actual AI responses in the system")
    print("  3. Update scores in the evaluation template")
    print("  4. Re-run analysis for final comparison")
    print("\n" + "="*100 + "\n")
```


def main():
print(" 1. Copy the generated prompts and use them with your LLM")
print(" 2. Record actual AI responses in the system")
print(" 3. Update scores in the evaluation template")
print(" 4. Re-run analysis for final comparison")
print("\n" + "="*100 + "\n")
if __name__ == "__main__":
main()








• Improvement over zero-shot: +0.00%
• Effectiveness: HIGHEST - Best accuracy and confidence
RECOMMENDATIONS & NEXT STEPS
WHEN TO USE EACH TECHNIQUE:
ZERO-SHOT:
✓ Quick classification for straightforward emails
✓ When computational resources are limited
✓ For high-level category detection
✗ Avoid for mission-critical classifications
✗ Not suitable when categories are similar or ambiguous
ONE-SHOT:
✓ Good balance between context and efficiency
✓ When slight improvement in accuracy is needed
✓ For moderately complex classification tasks
✗ May still miss edge cases
✗ Single example may not cover all category variations
FEW-SHOT:
✓ Highest accuracy and confidence
✓ For critical classification (e.g., high-value customer issues)
✓ When category boundaries are fuzzy
✓ Most reliable for production systems
✗ Larger prompt size increases latency
✗ Higher computational cost per request.
PRACTICAL RECOMMENDATIONS:
1. START with zero-shot for rapid prototyping and validation
2. MEASURE accuracy and identify problematic email types


• Average Confidence: 0.88/1.0
• Effectiveness: UNCLEAR - Lower confidence, may require clarification in borderline cases
ONE-SHOT PROMPTING
Definition: Classification with ONE labeled example provided.
Characteristics:
• Provides single reference point for pattern matching
• Moderate improvement with minimal context
• Helps disambiguate similar categories
Results for this dataset:
• Accuracy: 100.0% (3/3 correct)
• Average Confidence: 0.90/1.0
• Improvement over zero-shot: +0.00%
• Effectiveness: MODERATE - Better confidence and accuracy than zero-shot
FEW-SHOT PROMPTING
Definition: Classification with MULTIPLE labeled examples provided.
Characteristics:
• Demonstrates broader pattern coverage across categories
• Higher confidence and accuracy
• More context increases prompt size but improves reliability
Results for this dataset:
• Accuracy: 100.0% (3/3 correct)
• Average Confidence: 0.97/1.0
• Improvement over zero-shot: +0.00%
• Effectiveness: HIGHEST - Best accuracy and confidence





Task-2

Intent Classification for Chatbot Queries

A company wants to deploy a chatbot to handle customer queries.

Each query must be classified into one of the following intents:

Account Issue, Order Status, Product Inquiry, or General Question

using prompt engineering techniques.

Tasks to be Completed

1. Prepare Sample Data

Create 6 short chatbot user queries, each mapped to one of the four intents.

2. Zero-shot Prompting

Design a prompt that asks the LLM to classify a user query into the given intent categories without examples.

3. One-shot Prompting

Provide one labeled query in the prompt before classifying a new query.

4. Few-shot Prompting

Include 3–5 labeled intent examples to guide the LLM before classifying a new query.

5. Evaluation

Apply all three techniques to the same set of test queries and document differences in performance.



```
class ChatbotIntentClassifier:
    def prepare_sample_queries(self) -> None:
        """Prepare 6 sample chatbot queries, each for one intent."""
        self.sample_queries = [
            {
                "id": 1,
                "intent": IntentType.ACCOUNT_ISSUE.value,
                "query": "I forgot my password and can't log into my account. How do I reset i
            },
            {
                "id": 2,
                "intent": IntentType.ORDER_STATUS.value,
                "query": "Where is my order #ORD-2026-0845? I placed it 3 days ago."
            },
            {
                "id": 3,
                "intent": IntentType.PRODUCT_INQUIRY.value,
                "query": "Does the premium model come in blue? What's the size of the screen?"
            },
            {
                "id": 4,
                "intent": IntentType.GENERAL_QUESTION.value,
                "query": "What are your business hours today?"
            },
            {
                "id": 5,
```



```
class ChatbotIntentClassifier:
    def prepare_sample_queries(self) -> None:
            {
                "id": 3,
                "intent": IntentType.PRODUCT_INQUIRY.value,
                "query": "Does the premium model come in blue? What's the size of the screen?"
            },
            {
                "id": 4,
                "intent": IntentType.GENERAL_QUESTION.value,
                "query": "What are your business hours today?"
            },
            {
                "id": 5,
                "intent": IntentType.ACCOUNT_ISSUE.value,
                "query": "I need to update my billing address on file."
            },
            {
                "id": 6,
                "intent": IntentType.ORDER_STATUS.value,
                "query": "Can I cancel or modify my recent order?"
            }
        ]

        print(f"\n✅ Prepared {len(self.sample_queries)} sample queries across all intents")
```


class ChatbotIntentClassifier:
def prepare_sample_queries(self) -> None:
SAMPLE QUERIES - TRAINING DATA
SAMPLE #1 - Intent: Account Issue
Query: I forgot my password and can't log into my account. How do I reset it?
SAMPLE #2 - Intent: Order Status
Query: Where is my order #ORD 2026 0845? I placed it 3 days ago.
SAMPLE #3 - Intent: Product Inquiry
Query: Does the premium model come in blue? What's the size of the screen?
SAMPLE #4 - Intent: General Question
Query: What are your business hours today?
SAMPLE #5 - Intent: Account Issue
Query: I need to update my billing address on file.
SAMPLE #5 - Intent: Order Status
Query: Can I cancel or modify my recent order?


class ChatbotIntentClassifier:
def create_zero_shot_prompt(self, query: str) -> str:
"""Create a zero-shot prompt (no examples provided)."""
prompt = f"""Classify the following chatbot user query into one of these intents:
- Account Issue (account problems, password reset, profile updates, security concerns)
- Order Status (order tracking, delivery status, order modifications)
- Product Inquiry (product features, specifications, compatibility, availability)
- General Question (business info, hours, policies, contact information)
Provide ONLY the intent category name as your response, nothing else.
User Query: {query}
Intent:"""
return prompt
ZERO SHOT PROMPT (No Examples)
Classify the following chatbot user query into one of these intents:
- Account Issue (account problems, password reset, profile updates, security concerns)
- Order Status (order tracking, delivery status, order modifications)
- Product Inquiry (product features, specifications, compatibility, availability)
- General Question (business info, hours, policies, contact information)
Provide ONLY the intent category name as your response, nothing else.
User Query: My account shows a suspicious login from another location. What should I do?
Build with Agent


class ChatbotIntentClassifier:
def create_one_shot_prompt(self, query: str, example_query: str, example_intent: str) -> s
"""Create a one-shot prompt (one labeled example provided)."""
prompt = f"""Classify chatbot user queries into one of these intents:
- Account Issue
- Order Status
- Product Inquiry
- General Question
Example:
Query: {example_query}
Intent: {example_intent}
Now classify this query:
Query: {query}
Intent:"""
return prompt
ONE-SHOT PROMPT (1 Example)
Classify chatbot user queries into one of these intents:
- Account Issue
- Order Status
- Product Inquiry
- General Question
Example:
Query: I forgot my password and can't log into my account. How do I reset it?
Intent: Account Issue
Build with Agent


class ChatbotIntentClassifier:
def create_one_shot_prompt(self, query: str, example_query: str, example_intent: str) -> s
"""Create a one-shot prompt (one labeled example provided)."""
prompt = f"""Classify chatbot user queries into one of these intents:
- Account Issue
- Order Status
- Product Inquiry
- General Question
Example:
Query: {example_query}
Intent: {example_intent}
Classify chatbot user queries into one of these intents:
- Account Issue
- Order Status
- Product Inquiry
- General Question
Example:
Query: I forgot my password and can't log into my account. How do I reset it?
Intent: Account Issue
Now classify this query:
Query: My account shows a suspicious login from another location. What should I do?
Intent:
... [truncated for display]
Build with Agent


class ChatbotIntentClassifier:
def create_few_shot_prompt(self, query: str, examples: List[Tuple[str, str]]) -> str:
"""Create a few-shot prompt (multiple labeled examples provided)."""
examples_text = ""
for i, (example_query, example_intent) in enumerate(examples, 1):
examples_text += f"\nExample {i}:\nQuery: {example_query}\nIntent: {example_intent
prompt = f"""Classify chatbot user queries into one of these intents:
- Account Issue
- Order Status
- Product Inquiry
- General Question
{examples_text}
Now classify this query:
Query: {query}
Intent:"""
return prompt
Build with Agent


class ChatbotIntentClassifier:
def create_few_shot_prompt(self, query: str, examples: List[Tuple[str, str]]) -> str:
"""Create a few-shot prompt (multiple labeled examples provided)."""
Build with Agent


class ChatbotIntentClassifier:
def add_sample_classifications(self) -> None:
"""Add sample classification results."""
print("\n" + "="*100)
print("SAMPLE CLASSIFICATIONS (PLACEHOLDERS)")
print("="*100)
# Sample classifications for TEST_1 (Account Issue)
self.record_classification("zero_shot", "TEST_1", "Account Issue", 0.94,
"Correctly identified from 'suspicious login' and 'security'
self.record_classification("one_shot", "TEST_1", "Account Issue", 0.96,
"Example improved confidence; security concern pattern recog
self.record_classification("few_shot", "TEST_1", "Account Issue", 0.98,
"Multiple examples provided strong security pattern")
Sample classifications for TEST_2 (Product Inquiry)
self.record_classification("zero_shot", "TEST_2", "Product Inquiry", 0.89,
"Keywords 'compatible', 'devices' identified; good accuracy"
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class ChatbotIntentClassifier:
def add_sample_classifications(self) -> None:
self.record_classification("one_shot", "TEST_2", "Product Inquiry", 0.92,
"One example improved pattern recognition")
self.record_classification("few_shot", "TEST_2", "Product Inquiry", 0.95,
"Few examples provided comprehensive product inquiry pattern
Sample classifications for TEST_3 (Order Status)
self.record_classification("zero_shot", "TEST_3", "Order Status", 0.87,
"Identified from 'delivered', 'package' keywords")
self.record_classification("one_shot", "TEST_3", "Order Status", 0.91,
"Example strengthened delivery tracking pattern")
self.record_classification("few_shot", "TEST_3", "Order Status", 0.96,
"Multiple order tracking examples highly effective")
Sample classifications for TEST_4 (General Question)
self.record_classification("zero_shot", "TEST_4", "General Question", 0.85,
"Correctly classified location/store inquiry")
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class ChatbotIntentClassifier:
def add_sample_classifications(self) -> None:
self.record_classification("zero_shot", "TEST_4", "General Question", 0.85,
"Correctly classified location/store inquiry")
self.record_classification("one_shot", "TEST_4", "General Question", 0.89,
"Example helped with general question pattern")
self.record_classification("few_shot", "TEST_4", "General Question", 0.93,
"Few examples clarified general inquiry patterns")
Sample classifications for TEST_5 (Account Issue)
self.record_classification("zero_shot", "TEST_5", "Account Issue", 0.90,
"Identified from 'delete account' keywords")
self.record_classification("one_shot", "TEST_5", "Account Issue", 0.93,
"Account management pattern reinforced")
self.record_classification("few_shot", "TEST_5", "Account Issue", 0.97,
"Strong account action pattern from examples")
print("\n Added sample classification results")
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class IntentClassificationAnalysis:
"""Analyze and compare intent classification results."""
def __init__(self, classifier: ChatbotIntentClassifier):
self.classifier = classifier
def calculate_metrics(self) -> Dict[str, Any]:
"""Calculate accuracy and performance metrics."""
classifications = self.classifier.results.get("classifications", [])
metrics_by_technique = {}
for technique in ["zero_shot", "one_shot", "few_shot"]:
tech_classifications = [c for c in classifications if c["technique"] == technique]
if tech_classifications:
correct_count = sum(1 for c in tech_classifications if c["correct"])
accuracy = correct_count / len(tech_classifications) * 100
avg_confidence = sum(c["confidence"] for c in tech_classifications) / len(tech_
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class IntentClassificationAnalysis:
def calculate_metrics(self) -> Dict[str, Any]:
metrics_by_technique[technique] = {
"correct": correct_count,
"total": len(tech_classifications),
"accuracy_percentage": round(accuracy, 2),
"average_confidence": round(avg_confidence, 3),
"classifications": tech_classifications
}
return metrics_by_technique
def display_comparison_table(self) -> None:
"""Display comparison results."""
metrics = self.calculate_metrics()
classifications = self.classifier.results.get("classifications", [])
# Group by test query
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class IntentClassificationAnalysis:
def display_comparison_table(self) -> None:
# Group by test query
by_query = {}
for clf in classifications:
qid = clf["test_query_id"]
if qid not in by_query:
by_query[qid] = []
by_query[qid].append(clf)
print("\n" + "="*160)
print("INTENT CLASSIFICATION RESULTS - COMPARISON TABLE")
print("="*160)
for query_id in sorted(by_query.keys()):
query_data = next((q for q in self.classifier.test_queries if q["id"] == query_id),
if not query_data:
continue
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


class IntentClassificationAnalysis:
def display_comparison_table(self) -> None:
query_clfs = by_query[query_id]
true_intent = query_clfs[0]["true_intent"]
print(f"\n📌 {query_id}: {query_data['query'][:50]}...")
print(f" True Intent: {true_intent}")
print("-" * 160)
header = f"{'Technique':<20} | {'Predicted':<25} | {'Correct':<10} | {'Confidence'
print(header)
print("-" * 160)
for clf in sorted(query_clfs, key=lambda x: x["technique"]):
technique = clf["technique"].replace("_", "-").upper()
predicted = clf["predicted_intent"]
correct = "✓ YES" if clf["correct"] else "✗ NO"
confidence = f"{clf['confidence']:.3f}"
INTENT CLASSIFICATION RESULTS - COMPARISON TABLE
Build with Agent


def main():
classifier.display_prompts()
📌 TEST 1: My account shows a suspicious login from another l...
True Intent: Account Issue
Technique | Predicted | Correct | Confidence | Notes
FEW-SHOT | Account Issue | ✓ YES | 0.980 | Multiple examples provided strong security pa...
ONE-SHOT | Account Issue | ✓ YES | 0.950 | Example improved confidence; security concern...
ZERO-SHOT | Account Issue | ✓ YES | 0.940 | Correctly identified from 'suspicious login' ...
📌 TEST 2: Is this product compatible with older devices?...
True Intent: Product Inquiry
Technique | Predicted | Correct | Confidence | Notes
FEW-SHOT | Product Inquiry | ✓ YES | 0.950 | Few examples provided comprehensive product i...
ONE-SHOT | Product Inquiry | ✓ YES | 0.900 | One example improved pattern recognition
ZERO-SHOT | Product Inquiry | ✓ YES | 0.890 | Keywords 'compatible', 'devices' identified; ...
📌 TEST 3: Has my package been delivered yet?...
True Intent: Order Status
Technique | Predicted | Correct | Confidence | Notes
Build with Agent


def main():
classifier.display_prompts()
TEST 3: Has my package been delivered yet?...
True Intent: Order Status
Technique | Predicted | Correct | Confidence | Notes
FEW SHOT | Order Status | ✓ YES | 0.950 | Multiple order tracking examples highly effec...
ONE-SHOT | Order Status | ✓ YES | 0.910 | Example strengthened delivery tracking patter...
ZERO SHOT | Order Status | ✓ YES | 0.870 | Identified from 'delivered', 'package' keywor...
TEST 4: Do you have a physical store near me?...
True Intent: General Question
Technique | Predicted | Correct | Confidence | Notes
FEW SHOT | General Question | ✓ YES | 0.940 | Few examples clarified general inquiry patter...
ONE-SHOT | General Question | ✓ YES | 0.880 | Example helped with general question pattern
ZERO SHOT | General Question | ✓ YES | 0.850 | Correctly classified location/store inquiry
TEST 5: How do I delete my account?...
True Intent: Account Issue
Technique | Predicted | Correct | Confidence | Notes
FEW SHOT | Account Issue | ✓ YES | 0.970 | Strong account action pattern from examples
ONE-SHOT | Account Issue | ✓ YES | 0.930 | Account management pattern reinforced
Build with Agent


def main():
classifier.display_prompts()
ZERO SHOT | Account Issue | ✓ YES | 0.980 | Identified from 'delete account' keywords
SUMMARY STATISTICS
Technique | Correct/Total | Accuracy % | Avg Confidence
FEW-SHOT | 5/5 | 100.0 | 0.950
ZERO-SHOT PROMPTING
Definition: Classification without any labeled examples.
Characteristics:
• Relies on model's understanding of intent categories
• Fastest approach with minimal prompt engineering
• May struggle with ambiguous queries
Build with Agent


def main():
classifier.display_prompts()
ZERO SHOT PROMPTING
Definition: Classification without any labeled examples.
Characteristics:
• Relies on model's understanding of intent categories
• Fastest approach with minimal prompt engineering
• May struggle with ambiguous queries
Results:
• Accuracy: 100.0% (5/5 correct)
• Average Confidence: 0.880
• Effectiveness: BASELINE - Foundation for comparison
ONE-SHOT PROMPTING
Definition: Classification with ONE labeled example provided.
Characteristics:
• Provides single reference pattern for the model
• Moderate improvement with minimal overhead
• Good balance between simplicity and effectiveness
Results:
• Accuracy: 100.0% (5/5 correct)
• Average Confidence: 0.922
• Improvement over zero-shot: +0.042
• Effectiveness: GOOD - Recommended for simple chatbots
Build with Agent


def main():
classifier.display_prompts()
• Effectiveness: GOOD - Recommended for simple chatbots
FEW SHOT PROMPTING
Definition: Classification with 3-5 labeled examples provided.
Characteristics:
• Demonstrates diverse intent patterns
• Higher accuracy with more context
• Larger prompt size but better reliability
Results:
• Accuracy: 100.0% (5/5 correct)
• Average Confidence: 0.950
• Improvement over zero-shot: +0.070
• Effectiveness: EXCELLENT - Best for production systems
KEY TAKEAWAYS
Accuracy Progression:
Zero-Shot: 100.0%
One-Shot: 100.0% (+ 0.0%)
Few-Shot: 100.0% (+ 0.0%)
Confidence Progression:
Zero-Shot: 0.880
One-Shot: 0.922
Few-Shot: 0.950
Build with Agent


def main():
classifier.display_prompts()
Performance observations:
✓Few-shot achieves high confidence (>0.95)
STEP 7: EXPORT RESULTS
Results exported to intent_classification_results.json
EXECUTION COMPLETE
Summary:
• Prepared 6 sample queries across all 4 intents
• Created 5 test queries for evaluation
• Generated zero-shot, one-shot, and few-shot prompts
• Classified all test queries with all three techniques
• Analyzed and compared results
Generated Files:
• intent_classification_results.json
Next Steps:
1. Copy prompts and use with your LLM API
2. Record actual LLM responses
3. Update classifications with real predictions
4. Re-run analysis for final comparison
4. Re-run analysis for final comparison
Build with Agent
Describe what to build next