

API Contracts & Integration Specification

ServiceGuard AI

1. External APIs

Endpoint	Method	Purpose
/api/auth/login	POST	Login
/api/customers	GET/POST	Customer management
/api/services	GET/POST	Service management
/api/services/{id}/telemetry	GET	Telemetry history
/api/telemetry	POST	Telemetry ingestion
/api/incidents	GET	Incident list
/api/incidents/{id}	GET	Incident detail
/api/incidents/{id}/analyze	POST	Start AI analysis
/api/incidents/{id}/actions	GET	Recommendations
/api/incidents/{id}/actions/{actionId}/approve	POST	Approve action
/api/ai/query	POST	Copilot query
/api/audit	GET	Audit history

2. Java → Python internal contracts

```
POST /internal/ai/analyze

{
  "requestId": "...",
  "incidentId": "...",
  "serviceId": "...",
  "question": "..."
}

{
  "risk": {"score": 0.93, "level": "CRITICAL"},
  "facts": [],
  "evidence": [],
  "recommendedActions": [],
  "requiresHumanApproval": true
}
```

3. Contract rules

- Version internal APIs.
- Use ISO-8601 timestamps.
- Propagate correlation/request IDs.
- Validate payloads on both sides.
- Never expose internal stack traces.
- Use explicit timeout and retry policy.
- Idempotency for analysis jobs where applicable.