| PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT PLEASE DO NOT SCALE THE DRAWING.   |   |
|--|---|
| THROUGH COOLANT  NOTES:-  1) DIMN. TOLERENCE ON FIX POCKETE ±0.05  2) THROUGH COOLENT IS PROVIDED.  3) BORING BAR WILL BE BALENCED AT 3000 RPM  WITHIN 2.5 mg.   | COMP,NAME-NORD HOUSING SK PART,NO-      |
| 5 6 6 C C C C C C C C C C C C C C C C C  | ;<br>!                                  |
| DESCRIPTION:-SPL COMB SEME FINISH BORDA  To cartende - Steck 12CA16  To cartende - Ste | ・ 中心・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・ |
| OMB SEME   |   |
| BT50(CASE H/CASE DEPTH (CASE D |   |
| ARDEN 58-62HRC 0.8-1.2 MM)  BAR DIA 99.5,GPL-1  G BAR DIA 99.5,GPL-1   | 2<br>1<br>NO MODIF                      |
| 50,BT-50  CUSTMER SHIPMENT &-BILL WISH BORING BAR VISH BORING BAR DATE DATE  | MODIFICATION                            |
| KASTURY,ASHT HARIOM AR DIA IAR DIA IAR DIA IAR DIA   | DATE                                    |
| 2024   | SIGN.                                   |