PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT PLEASE DO NOT SCALE THE DRAWING.	
THROUGH COOLANT NOTES:- 1) DIMN. TOLERENCE ON FIX POCKETE ±0.05 2) THROUGH COOLENT IS PROVIDED. 3) BORING BAR WILL BE BALENCED AT 3000 RPM WITHIN 2.5 mg.	COMP,NAME-NORD HOUSING SK PART,NO-
SR 1 2 3 4 6 6	
DESCRIPTION:-SPL CONTRIBUTE - STFCR 10CK16 COARTRIDGE - STFCR 10CK16 INSERT: TOMIT 167308 SR NOO HANOLIDESCRIPTION:-SPL CO	
BT50 CASE CASE O4	; i ;
DESCRIPTION:-SPL COMB SEME FINISH BORING BAR DIA 87.5X089.5,GPL-130,BT-50 DRG. NO. AK/DRG/09441 DRG. NO. AK/DRG/09441 DRG. NO. BESCRIPTION:-SPL COMB SEME FINISH BORING BAR DIA 87.5X089.5,GPL-130,BT-50 DRG. NO. AK/DRG/09441 DRG. NO. DRAWN M.K PO NO. CHD.BY. DATE II	
7.5XØ89.5,0 SEME FINE 83Y. M.K	MODIFICATION
SHIPMENT &-BILL WISH BORING I K PON	CATION
KASTURY,ASHT HARIOM R DIA 17/03/2024	DATE SIGN.