

Client-Side Functional & Performance Testing

Implement Client Script & UI Policy (Incident) for NM Project
Date: 03 October 2026 | Team ID: NM-TEAM-ID

Implementation Objective

Configure the ServiceNow Incident table so that state-specific fields become mandatory and priority is calculated from Impact and Urgency.

Client Script 1 – Calculate Priority (onChange)

Table: Incident [incident]

Type: onChange

Field: Impact (create one script) and duplicate logic for Urgency, or use an onChange script on each field calling the same function.

Suggested script:

```
function onChange(control, oldValue, newValue, isLoading, isTemplate) {  
    if (isLoading || newValue === '') return;  
    var impact = g_form.getValue('impact');  
    var urgency = g_form.getValue('urgency');  
    if (!impact || !urgency) return;  
    var priority = '';  
    if (impact == '1' && urgency == '1') priority = '1';  
    else if ((impact == '1' && urgency == '2') || (impact == '2' && urgency == '1')) priority = '2';  
    else if ((impact == '1' && urgency == '3') || (impact == '2' && urgency == '2') || (impact == '3' && urgency  
== '1')) priority = '3';  
    else if ((impact == '2' && urgency == '3') || (impact == '3' && urgency == '2')) priority = '4';  
    else if (impact == '3' && urgency == '3') priority = '5';  
    if (priority) g_form.setValue('priority', priority);  
}
```

Client Script 2 – Resolved Submit Validation

Table: Incident [incident]

Type: onSubmit

Suggested script:

```
function onSubmit() {  
    var state = g_form.getValue('state');  
    if (state == '6') { // Verify the Resolved choice value in the target instance.  
        var resolutionCode = g_form.getValue('close_code');  
        var resolutionNotes = g_form.getValue('close_notes');
```

```
    if (!resolutionCode || !resolutionNotes) {  
        g_form.addErrorMessage('Resolution Code and Resolution Notes are required before resolving the  
incident.');
```

```
        return false;  
    }  
}  
return true;  
}
```

Important: confirm the exact choice values/field names in the target ServiceNow instance before activation. Field labels can differ by configuration.

UI Policy 1 – Resolved State

Table: Incident. Condition: State is Resolved. Actions: Resolution Code = Mandatory, Resolution Notes = Mandatory. Optional: make relevant resolution fields visible.

UI Policy 2 – On Hold State

Table: Incident. Condition: State is On Hold. Action: On Hold Reason = Mandatory. Optional: make the field visible if hidden.

Implementation Checklist

Open System Definition → Client Scripts and create the scripts with the correct table and type.

Open System UI → UI Policies and create the two Incident policies.

Use descriptive names and descriptions.

Test in a non-production instance first.

Verify exact choice values and field names with the instance dictionary.

Use Update Sets or the approved application deployment process to move configuration.