

Exp No: 4**Create UDF in PIG****Step-by-step installation of Apache Pig on Hadoop cluster on Ubuntu****Pre-requisite:**

- Ubuntu 16.04 or higher version running (I have installed Ubuntu on Oracle VM (Virtual Machine) VirtualBox),
- Run Hadoop on ubuntu (I have installed Hadoop 3.2.1 on Ubuntu 16.04). You may refer to my blog “How to install Hadoop installation” click here for Hadoop installation).

Pig installation steps

Step 1: Login into Ubuntu

Step 2: Go to <https://pig.apache.org/releases.html> and copy the path of the latest version of pig that you want to install. Run the following command to download Apache Pig in Ubuntu:

```
$ wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz
```

Step 3: To untar pig-0.16.0.tar.gz file run the following command:

```
$ tar xvzf pig-0.16.0.tar.gz
```

Step 4: To create a pig folder and move pig-0.16.0 to the pig folder, execute the following command:

```
$ sudo mv /home/hadoop/pig-0.16.0 /home/hadoop/pig
```

Step 5: Now open the .bashrc file to edit the path and variables/settings for pig. Run the following command:

```
$ sudo nano .bashrc
```

Add the below given to .bashrc file at the end and save the file.

```
#PIG settingsexport PIG_HOME=/home/hadoop/pigexport
```

```
PATH=$PATH:$PIG_HOME/binexport
```

```
PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/export
```

```
PIG_CONF_DIR=$PIG_HOME/confexport JAVA_HOME=/usr/lib/jvm/java-8-openjdkamd64export
```

```
PIG_CLASSPATH=$PIG_CONF_DIR:$PATH#PIG setting ends
```

```
export PIG_HOME=/home/haresh/pig
export PATH=$PATH:$PIG_HOME/bin
export PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/
export PIG_CONF_DIR=$PIG_HOME/conf
export PIG_CLASSPATH=$PIG_CONF_DIR:$PATH
```

Step 6: Run the following command to make the changes effective in the .bashrc file:

```
$ source .bashrc
```

Step 7: To start all Hadoop daemons, navigate to the hadoop-3.2.1/sbin folder and run the following commands:

```
$ ./start-dfs.sh$ ./start-yarn$ jps
```

```
haresh@fedora:~$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as haresh in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [fedora]
Starting resourcemanager
Starting nodemanagers
haresh@fedora:~$
```

Now you can launch pig by executing the following command:

```
$ pig
```

```
haresh@fedora:~$ pig
2024-09-13 09:46:24,963 INFO pig.ExecTypeProvider: Trying ExecType : LOCAL
2024-09-13 09:46:24,964 INFO pig.ExecTypeProvider: Trying ExecType : MAPREDUCE
2024-09-13 09:46:24,964 INFO pig.ExecTypeProvider: Picked MAPREDUCE as the ExecT
ype
2024-09-13 09:46:25,012 [main] INFO org.apache.pig.Main - Apache Pig version 0.
16.0 (r1746530) compiled Jun 01 2016, 23:10:49
2024-09-13 09:46:25,012 [main] INFO org.apache.pig.Main - Logging error message
s to: /home/haresh/pig_1726200985006.log
2024-09-13 09:46:25,056 [main] INFO org.apache.pig.impl.util.Utls - Default bo
otup file /home/haresh/.pigbootup not found
2024-09-13 09:46:25,375 [main] INFO org.apache.hadoop.conf.Configuration.deprec
ation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.addr
ess
2024-09-13 09:46:25,375 [main] INFO org.apache.hadoop.conf.Configuration.deprec
ation - fs.default.name is deprecated. Instead, use fs.defaultFS
2024-09-13 09:46:25,375 [main] INFO org.apache.pig.backend.hadoop.executionengi
ne.HExecutionEngine - Connecting to hadoop file system at: hdfs://localhost:9000
2024-09-13 09:46:26,058 [main] INFO org.apache.hadoop.conf.Configuration.deprec
ation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.addr
```

Step 9: Now you are in pig and can perform your desired tasks on pig. You can come out of the pig by the quit command:

```
> quit
```