

First-Come,First-Serve CPU Scheduling Algorithm

Completed

Write a C program to implement the First-Come, First-Served (FCFS) CPU Scheduling Algorithm. The program should take the number of processes, their Arrival Times (AT), and Burst Times (BT) as input. Calculate and display the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process, along with the Average Turnaround Time and Average Waiting Time.

To evaluate the performance of the algorithm, we use the following formulas:

- **Completion Time (CT):** The time at which a process finishes execution.
- **Turnaround Time (TAT):** Total time taken from arrival to completion.
- $\$TAT = CT - AT$
- **Waiting Time (WT):** The time a process spends waiting in the ready queue.
- $\$WT = TAT - BT$

Input Format

1. The first input line contains an integer representing the

Select Language : C (GCC 9.2.0)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3
4 typedef struct {
5     int pid;
6     int at;
7     int bt;
8     int ct;
9     int tat;
10    int wt;
11 } Process;
12
13 int cmp_at(const void *a, const void *b) {
14     Process *p1 = (Process *)a;
15     Process *p2 = (Process *)b;
16     if (p1->at != p2->at) return p1->at - p2->at;
17     return p1->pid - p2->pid;
18 }

```

Test Cases

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Success ✓

Input :

Expected Output :

```

3
0 2
1 2
2 3

```

```

Enter number of
processes:
Enter Arrival Time and
Burst Time for P1:
Enter Arrival Time and
Burst Time for P2:
Enter Arrival Time and

```

Output :

```

Enter number of processes:
Enter Arrival Time and Burst Time for P1:
Enter Arrival Time and Burst Time for P2:
Enter Arrival Time and Burst Time for P3:

```