

```
31 *      return a;
32 * }
33 *
34 */
35 ▾ int* reverseArray(int arr_count, int *arr, int *result_count) {
36     int*result=(int*)malloc(arr_count*sizeof(int));
37 ▾     if(result==NULL){
38         return NULL;
39     }
40 ▾     for(int i=0;i<arr_count;i++){
41         result[i]=arr[arr_count-i-1];
42     }
43     *result_count=arr_count;
44     return result;
45 }
```

	Test	Expected	Got	
✓	<pre>int arr[] = {1, 3, 2, 4, 5}; int result_count; int* result = reverseArray(5, arr, &result_count); for (int i = 0; i < result_count; i++) printf("%d\n", *(result + i));</pre>	5 4 2 3 1	5 4 2 3 1	✓

Passed all tests! ✓

```
28 /
29 ▼ char* cutThemAll(int lengths_count, long *lengths, long minLength) {
30     long t=0,i=1;
31 ▼     for(int i=0;i<=lengths_count-1;i++){
32         t+=lengths[i];
33     }
34 ▼     do{
35 ▼         if(t-lengths[lengths_count-1]<minLength){
36             return "Impossible";
37         }i++;
38     }while(i<lengths_count-i);
39     return "Possible";
40
41 }
42
```

	Test	Expected	Got	
✓	long lengths[] = {3, 5, 4, 3}; printf("%s", cutThemAll(4, lengths, 9))	Possible	Possible	✓
✓	long lengths[] = {5, 6, 2}; printf("%s", cutThemAll(3, lengths, 12))	Impossible	Impossible	✓

Passed all tests! ✓