

✓ Exercise 1: Predict Taxi Fare from Trip Miles

Train a model to predict the fare of a taxi ride in Chicago based on trip distance.

```
#CH.SC.U4CSE24163 HARISH.R

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.metrics import mean_squared_error, r2_score
```

✓ Importing Dataset

```
df = pd.read_csv('../Data/chicago_taxi_trips.csv')
print(f"Shape: {df.shape}")
df.head()
```

Shape: (500, 2)

	trip_miles	fare
0	4.36	20.93
1	14.55	58.12
2	11.79	46.02
3	10.89	42.18
4	7.02	27.01

✓ Checking for any null values in dataset

```
df.isnull().sum()
```

```
trip_miles    0
fare          0
dtype: int64
```

✓ Assigning Dependent and Independent variables

```
x = df[['trip_miles']]  
y = df['fare']
```

✓ Splitting the dataset into Training and Testing Dataset

```
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2, random
```

```
print(f"Training set size: {x_train.shape[0]}")  
print(f"Testing set size: {x_test.shape[0]}")
```

```
Training set size: 400  
Testing set size: 100
```

✓ Fitting the Model (Linear Regression)

```
mdl = LinearRegression()  
mdl.fit(x_train, y_train)  
print(f"Intercept: {mdl.intercept_:.2f}")  
print(f"Coefficient: {mdl.coef_[0]:.2f}")
```

```
Intercept: 3.38  
Coefficient: 3.53
```

✓ Evaluation Metrics

```
y_pred = mdl.predict(x_test)  
mse = mean_squared_error(y_test, y_pred)  
r2 = r2_score(y_test, y_pred)  
print(f"MSE: {mse:.2f}")  
print(f"R2: {r2:.2f}")
```

```
MSE: 4.76  
R2: 0.98
```

✓ Plot

```
plt.figure(figsize=(8, 6))
plt.scatter(x_train, y_train, color='blue', label='Training data')
plt.scatter(x_test, y_test, color='green', label='Testing data')
plt.plot(x, mdl.predict(x), color='red', linewidth=2, label='Regression Line')
plt.title('Taxi Fare vs Trip Miles')
plt.xlabel('Trip Miles')
plt.ylabel('Fare ($)')
plt.legend()
plt.show()
```



