

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-20-1 Clocks****31-20-1-1 Pilot Clock**

Interval	Installed	Required	Procedure
A	1	0	NIL

May be inoperative provided:

- Reliable and functioning timepiece is readily available to all Flight Compartment crew members, and
- Repairs are made within three flight days.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative Clock on the glareshield.

Operating Procedures

None required.

Maintenance Procedures

- Placard inoperative Clock on the glareshield.
- Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-20-1. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-20-1 Clocks****31-20-1-2 Co-pilot Clock**

Interval	Installed	Required	Procedure
C	1	0	NIL

May be inoperative.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative Clock on the glareshield.

Operating Procedures

None required.

Maintenance Procedures

3. Placard inoperative Clock on the glareshield.
4. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-20-1. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-30-1 Flight Data Recorder**

Interval	Installed	Required	Procedure
A	1	0	(M)

May be inoperative provided:

- The Cockpit Voice Recorder is operative, and
- Repairs are made within three flight days.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative Flight Data Recorder in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

- Pull and clip the FDR circuit breaker, located on the avionics circuit breaker panel.
- Placard the Flight Data Recorder on the FLIGHT DATA RCDR/ELT Panel on the Overhead Console.
- Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-30-1. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-51-1 Caution and Warning Lights System****31-51-1-1 Dual Master Caution switchlight (Glareshield, light function only) (CR833CH00034)**

Interval	Installed	Required	Procedure
C	2	1	NIL

One may be inoperative.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative Master Caution/Warning switchlight in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

1. Placard the Master Caution switchlight on the glare shield panel.
2. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-51-1. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-51-1 Caution and Warning Lights System****31-51-1-2 Dual Master Warning Switchlight (Glareshield, light function only) (CR833CH00034)**

Interval	Installed	Required	Procedure
C	2	1	NIL

One may be inoperative.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative Master Caution/Warning switchlight in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

1. Placard the Master Warning switchlight on the glare shield panel.
2. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED –**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-51-1. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-1 ESID Control Panel****31-60-1-1 System Page Push Button Switches**

Interval	Installed	Required	Procedure
C	4	0	(O)

The ELEC SYS, ENG SYS, FUEL SYS, and DOORS SYS Switches may be inoperative provided the ALL Switch is operative.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Electronic Systems Integrated Display (ESID) Control Panel must be placarded in the flight compartment.

Operating Procedures

Sequence through all ESID Systems Synoptic pages as required by proviso and confirm relevant page is available.

Maintenance Procedures

1. Placard the ESID Control Panel with appropriate functions "XXX INOP".
2. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-1. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-1 ESID Control Panel****31-60-1-2 ALL Switch**

Interval	Installed	Required	Procedure
C	1	0	(O)

The ALL Switch may be inoperative provided the ELEC SYS, FUEL SYS, ENG SYS and DOORS SYS Switches are operative.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Electronic Systems Integrated Display (ESID) Control Panel must be placarded in the flight compartment.

Operating Procedures

Sequence through all ESID Systems Synoptic pages as required by proviso and confirm relevant page is available.

Maintenance Procedures

1. Placard the ESID Control Panel with appropriate functions "XXX INOP".
2. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00

APPROVED BY DAW DELHI, DATED -

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-1. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-1 ESID Control Panel****31-60-1-3 Engine Display Dimming Function**

Interval	Installed	Required	Procedure
C	1	0	NIL

Dimming may be inoperative provided the display intensity is adequate.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Electronic Systems Integrated Display (ESID) Control Panel must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

1. Placard the ESID Control Panel with appropriate functions "XXX INOP".
2. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DAT 00 -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-1. 3

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-2 MFD and PFD Engine Display Messages****31-60-2-1 PFD 1 / 2 LINK FAIL Engine Display message**

Interval	Installed	Required	Procedure
C	2	1	NIL

Message may be displayed.

Minimum Equipment List Procedures (MELP)**Placard**

MFD and PFD Engine Display Messages must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED –**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-2. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-2 MFD and PFD Engine Display Messages****31-60-2-2 MFD 1 / 2 LINK FAIL Engine Display message**

Interval	Installed	Required	Procedure
C	2	1	NIL

Message may be displayed.

Minimum Equipment List Procedures (MELP)**Placard**

MFD and PFD Engine Display Messages must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-2. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-3 Electronic Flight Instrument System Control Panels****31-60-3-1**

Interval	Installed	Required	Procedure
C	2	1	NIL

One panel may be inoperative provided:

- The pilot flying panel is fully operative, and
- Affected side must meet navigational requirements for route being flown.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Electronic Flight Instrument Systems (EFIS) Control Panel must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

- Placard the EFIS Control Panel with appropriate functions "XXX INOP".
- Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-3. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-3 Electronic Flight Instrument System Control Panels****31-60-3-2 Bright/Dim Controls**

Interval	Installed	Required	Procedure
C	6	0	NIL

Dimming may be inoperative provided the display intensity is adequate.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Electronic Flight Instrument Systems (EFIS) Control Panel must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

3. Placard the EFIS Control Panel with appropriate functions "XXX INOP".
4. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DAT 00 -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-3. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-4 FADEC 1 / DU or FADEC 2 / DU Engine
Display Message**

Interval	Installed	Required	Procedure
A	2	1	NIL

Message may be annunciated for three flight days.

Minimum Equipment List Procedures (MELP)**Placard**

FADEC DU Engine Display Message must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

(Due to possibility of this low level message being overwritten by a higher priority message, the FADEC X / DU message should be placarded below the Engine Display).

1. Placard below the Engine Display with "FADEC X / DU message illuminated".
2. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-4. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-5 EFIS/ESID Display Units**

Interval	Installed	Required	Procedure
A	5	4	(M)(O)

RH MFD (MFD2) may be inoperative provided:

- RNP AR approach is not being conducted,
- The left hand Electronic Flight Instrument System Control panel (EFCP) and the Engine and System Integrated Display Control Panel (ESCP) are fully functional,
- The MFD1 rotary selector and ELEC SYS, ENG SYS, FUEL SYS, DOOR SYS and ALL push button switches are operative, and
- Repairs are made within one flight day.

NOTE:

- The pilot occupying the left seat must conduct all departures and arrivals in Instrument Meteorological Conditions.
- RNAV1, RNAV2, RNAV5, RNP1, RNP APCH (LNAV or LNAV/VNAV or LPV) and CAT II operations not allowed.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Display Unit (MFD2) must be placarded in the flight compartment

Operating Procedures

- Select MFD1 rotary selector from SYS to NAV prior to takeoff.
- If necessary to view aircraft system page information during flight, select the MFD1 rotary selector to SYS or press the ESID ALL button.

Maintenance Procedures

- Pull circuit breakers of affected Display Units, as required (MFD1 AVIONICS LEFT ESS CB Panel; PFD1 – AVIONICS LEFT MAIN CB Panel; PFD2 – AVIONICS RIGHT MAIN CB Panel; ED – AVIONICS RIGHT MAIN and RIGHT ESS CB Panel) to re-arrange displays to provide operating Primary Flight Displays (PFD1 and PFD2), Engine Display and operating Multifunctional Display on pilot side (MFD1).

(...Continued)

ISS III R05**APPROVED BY DAW DELHI, DATED –**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-5. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****INDICATING AND RECORDING SYSTEMS******ATA 31*****31-60-5****EFIS/ESID Display Units**

2. Remove the avionics air cooling hoses and disconnect the connectors from affected display(s) and swap position of inoperative display, as required. (Refer to Aircraft Maintenance Manual PSM 1-84-2 Task 31-61-01-000-801 for more detailed information regarding Removal of the Display Units and Task 31-61-01-400-801 for Installation of the Display Unit).
3. Engage circuit breakers to operating Display Unit(s) and pull and clip MFD2 circuit breaker (AVIONICS RIGHT MAIN CB Panel).
4. Select the MFD1 rotary selector to PFD. Confirm MFD1 enters PFD display format and white "AVAIL" message is posted on PFD1 display unit.
5. Select the MFD1 rotary selector to NAV. Confirm MFD1 enters navigation display format.
6. Press the ALL button on the ESID panel to sequence through all system pages and confirm the relevant page is displayed on the ED.
7. Select the MFD1 rotary selector to SYS. Confirm MFD1 enters composite page display format as indicated by the presence of condensed FLAP, PFCS and digital hydraulic indications at the bottom of the display. Sequence through all systems pages using the ELEC SYS, ENG SYS, FUEL SYS, and DOOR SYS push buttons and confirm the relevant page is displayed on MFD1.
8. Select MFD1 rotary selector to ENG. Confirm MFD1 enters engine display mode and white "AVAIL" message is posted on the ED.
9. Placard Display Unit (MFD2) on copilot's side.
10. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

31-60-5. 2