

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-2 Warm Water Wash System (Not applicable to systems Deactivated as per Bombardier Modsum)****38-10-2-1**

Interval	Installed	Required	Procedure
C	1	0	(M)(O)

May be inoperative provided:

- System is drained and inspected to ensure no leakage, and
- Procedures are established and used to deactivate applicable system components to prevent its use or servicing, and
- System is placarded in the lavatory.

Minimum Equipment List Procedures (MELP)**Placard**

- Placard inoperative Warm Water Wash System in the flight compartment.
- Placard the Warm Water Wash System in a clear location visible to lavatory occupants that the sink, and subsequently the warm water wash system are inoperative and not for use.

Operating Procedures

- Alternate means should be established and used for provision of water for crew members.
- Procedures should be established to advise crew of system status during crew changes.
- Aviation Occupational Health Safety (AOH&S) requirements should be addressed.

Maintenance Procedures

- Ensure associated components are deactivated or isolated.
- Ensure associated system components are verified not to have leaks.
- Placard Warm Water Wash System in the lavatory and/or in the flight compartment.
- Make appropriate entry in the aircraft journey log.

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-2. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-2 Warm Water Wash System (Not applicable to systems Deactivated as per Bombardier Modsum)****38-10-2-2**

Interval	Installed	Required	Procedure
C	1	0	(M)(O)

Individual components may be inoperative provided:

- Associated components are deactivated or isolated, and
- Associated system components are verified not to have leaks.

NOTE: Any portion of the system which operates normally may be used.

Minimum Equipment List Procedures (MELP)**Placard**

Placard inoperative components of the Warm Water Wash System in the flight compartment and/or in the lavatory.

Operating Procedures

- Alternate means should be established and used for provision of water for crew members.
- Procedures should be established to advise crew of system status during crew changes.
- Aviation Occupational Health Safety (AOH&S) requirements should be addressed.

Maintenance Procedures

- Ensure associated components are deactivated or isolated.
- Ensure associated system components are verified not to have leaks.
- Placard Warm Water Wash System in the lavatory and/or in the flight compartment.
- Make appropriate entry in the aircraft journey log.

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-2. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-3 Drain Mast Heaters (Not applicable to systems deactivated as per Bombardier Modsum)****38-10-3-1 Galley/Lavatory Water Systems Installed****38-10-3-1A**

Interval	Installed	Required	Procedure
C	1	0	(M)(O)

May be inoperative provided:

- Flight and overnight storage is not carried out in freezing conditions,
- Procedures are established and used to verify drain mast and external fill ports' temperatures are acceptable prior to refilling or draining, and
- "DRAIN MAST HEATERS INOPERATIVE" is placarded on appropriate ground service doors.

Minimum Equipment List Procedures (MELP)**Placard**

- Placard in the flight compartment drain mast heaters that are inoperative.
- Placard at the appropriate ground service doors that drain mast heaters are inoperative.

Operating Procedures

- Prior to flight verify that flight plan does not encounter weather where extended periods of temperatures at or below freezing will be encountered. (If temperatures for extended periods of flight will be at or below freezing, then this relief cannot be applied).
- During on-ground servicing, inform ground crews to verify that fill ports and drain mast are not frozen prior to refilling/draining the system.

Maintenance Procedures

- Verify that the inoperative drain mast heater does not have a detrimental effect on other systems.

(...Continued)

ISS III R00**APPROVED BY DAW DELHI, DATE -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-3. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-3 Drain Mast Heaters (Not applicable to systems deactivated as per Bombardier Modsum)****38-10-3-1 Galley/Lavatory Water Systems Installed****38-10-3-1A**

- a) If multiple drain mast heaters on aircraft, verify the inoperative drain mast heater does not impact the other drain mast heaters' operation.
- b) If operation of other drain mast heaters is impacted, all impacted drain mast heaters must be considered inoperative.
- c) If required, open and collar drain mast circuit breaker "DRAIN MAST" on 115V AC RIGHT VARIABLE FREQUENCY AC BUS.
2. Placard in the flight compartment drain mast heaters that are inoperative.
3. Placard at the appropriate ground service doors (134BR and/or 142AR) that drain mast heaters are inoperative.
4. Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-3. 2

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-3 Drain Mast Heaters (Not applicable to systems deactivated as per Bombardier Modsum)****38-10-3-1 Galley/Lavatory Water Systems Installed****38-10-3-1B**

Interval	Installed	Required	Procedure
C	1	0	(M)

May be inoperative provided:

- Water systems are drained and considered inoperative, and
- "DRAIN MAST HEATERS INOPERATIVE" is placarded on appropriate ground service doors.

Minimum Equipment List Procedures (MELP)**Placard**

- Placard in the flight compartment drain mast heaters that are inoperative.
- Placard at the appropriate ground service doors that drain mast heaters are inoperative.

Operating Procedures

None required.

Maintenance Procedures

- Verify that the inoperative drain mast heater does not have a detrimental effect on other systems.
 - If multiple drain mast heaters on aircraft, verify the inoperative drain mast heater does not impact the other drain mast heaters' operation.
 - If operation of other drain mast heaters is impacted, all impacted drain mast heaters must be considered inoperative.
 - If required, open and collar drain mast circuit breaker "DRAIN MAST" on 115V AC RIGHT VARIABLE FREQUENCY AC BUS.

*(...Continued)***ISS III R00****APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49**38-10-3. 3**

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-3 Drain Mast Heaters (Not applicable to systems deactivated as per Bombardier Modsum)****38-10-3-1 Galley/Lavatory Water Systems Installed****38-10-3-1B**

2. For any galley or lavatory with installed water systems associated with an inoperative drain mast heaters, implement either, or both of the following:
 - a) Plug sink drain with an acceptable drain stop to prevent introduction of any form of liquid or waste into the water drainage system.
 - b) i) Within the lavatory, placard the water wash system in a clear location visible to occupants that the sink, and the subsequently the water wash system are inoperative and not for use.
ii) Placard the galley water system in a clear location visible anyone utilizing the galley, that the galley water system is inoperative and not for use.
3. Placard in the flight compartment drain mast heaters that are inoperative.
4. Placard at the appropriate ground service doors (134BR and/or 142AR) that drain mast heaters are inoperative.
5. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATE -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-3. 4

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-10-3 Drain Mast Heaters (Not applicable to systems deactivated as per Bombardier Modsum)****38-10-3-2 Galley/Lavatory Water Systems Deactivated or Not Installed**

Interval	Installed	Required	Procedure
D	1	0	NIL

May be inoperative.

Minimum Equipment List Procedures (MELP)**Placard**

1. Placard in the flight compartment drain mast heaters that are inoperative.
2. Placard at the appropriate ground service doors that drain mast heaters are inoperative.

Operating Procedures

None required.

Maintenance Procedures

1. Placard in the flight compartment drain mast heaters that are inoperative.
2. Placard at the appropriate ground service doors (134BR and/or 142AR) that drain mast heaters are inoperative.
3. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-10-3. 5

**DHC-8-402****MINIMUM EQUIPMENT LIST*****WATER/WASTE******ATA 38*****38-30-1 Lavatory Waste System****38-30-1-1**

Interval	Installed	Required	Procedure
C	1	0	(M)

Individual components may be inoperative provided:

- Associated components are deactivated or isolated, and
- Associated system components are verified not to have leaks.

NOTE: Any portion of system which operates normally may be used.

Minimum Equipment List Procedures (MELP)**Placard**

Placard the flight compartment that specific Lavatory Waste System component(s) are inoperative.

Operating Procedures

None required.

Maintenance Procedures

- Isolate and/or deactivate associated component (s) to inoperative component (s).
- Do a visual check of the lavatory waste system. If necessary, remove the center floor board next to the lavatory and check under lavatory for signs of leakage.
- If signs of leakage is found, drain and isolate and/or deactivate components suspected of leakage.
- Place placard in flight compartment indicating which Lavatory Waste Systems component (s) are inoperative.
- Make appropriate entry in the aircraft journey log.

■■■■

ISS III R00**APPROVED BY DAW DELHI, DATED -****Signature valid**

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

38-30-1. 1



38-30-1-2

May be inoperative provided:

- NOTE:** Aviation Occupational Health and Safety (AOH&S) requirements should be addressed.

Placard

- ## Operating Procedures

Maintenance Procedures

1. Drain Lavatory waste tank.
2. Place placard in flight compartment indicating that lavatory is inoperative.
3. Open and clip LAVATORY FLUSH circuit breaker on L SECONDARY bus.
4. Lock the lavatory door by placing a pen or other similar object in the hole in the latch and sliding it to the locked position.
5. Placard lavatory Door "INOPERATIVE - DO NOT ENTER".
6. Make appropriate entry in the aircraft journey log.