

**DHC-8-402****MINIMUM EQUIPMENT LIST*****ENGINE FUEL AND CONTROL******ATA 73*****73-20-1****Engine FADEC System: FADEC faults**

Interval	Installed	Required	Procedure
A	68	-	NIL

May be dispatched with FADEC faults provided repairs are made in accordance with times established in the Time Limited Dispatch section of Pratt & Whitney Canada Airworthiness Limitations Manual Part No.3043520.

NOTE:

1. MEL extensions are not permitted.
2. Time Limited Dispatch reporting system is maintained as per Pratt & Whitney Canada Airworthiness Limitations Manual Part No. 3043520.

Time Limited Dispatch (TLD) can be done under two scenarios. These scenarios along with risk factor calculation procedure are defined in Annexure-3.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative engine FADEC System must be placarded in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

1. Placard inoperative engine FADEC System in the flight compartment.
2. Make appropriate entry in the aircraft journey log.

— — — —

ISS III R00**APPROVED BY DAW DELHI, DATED -**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

73-20-1. 1

**DHC-8-402****MINIMUM EQUIPMENT LIST*****ENGINE FUEL AND CONTROL******ATA 73*****73-30-1 FF (Fuel Flow) Indications**

Interval	Installed	Required	Procedure
B	2	1	NIL

May be inoperative provided Fuel QTY indications are operative.

Minimum Equipment List Procedures (MELP)**Placard**

Inoperative Fuel Flow Indication(s) must be placarded on Engine Display in the flight compartment.

Operating Procedures

None required.

Maintenance Procedures

1. Placard Fuel Flow Indication(s) as "INOP" on Engine Display in the flight compartment.
2. Make appropriate entry in the aircraft journey log.

■ ■ ■ ■

ISS III R00**APPROVED BY DAW DELHI, DATED –**

Signature valid

Signed by: Manoj
Kumar Bajpai
Director
(Airworthiness)
Date: 07-Jun-
2024 13:52:49

73-30-1. 1