

Rajalakshmi Engineering College

Name: Harish V.H
Email: 240701175@rajalakshmi.edu.in
Roll no: 240701175
Phone: 9080255347
Branch: REC
Department: CSE - Section 2
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

Preethi is working on a project to automate sales tax calculations for items in a store. She wants to create a program that takes the price of an item and the sales tax rate as input and calculates the final price of the item after applying the sales tax.

Write a program using the class SalesTaxCalculator, which contains an overloaded method named calculateFinalPrice to handle both integer and double inputs. The program should also include a Main class that takes user input, calls the appropriate method from SalesTaxCalculator, and prints the final price of the item.

Formula Used: Final price = price + ((price * sales tax rate) / 100)

Input Format

The first line of input consists of an integer price (the price of the item for integer inputs).

The second line of input consists of an integer taxRate (the sales tax rate for integer inputs).

The third line of input consists of a double price (the price of the item for double inputs).

The fourth line of input consists of a double taxRate (the sales tax rate for double inputs).

Output Format

The first line of output prints an integer, representing the final price of the item after applying the sales tax for integer inputs (a and b).

The second line prints a double value, representing the final price of the item after applying the sales tax for double-value inputs (m and n), rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 100

10

100.0

5.0

Output: 110

105.00

Answer

```
import java.util.Scanner;
```

```
// You are using Java
```

```
import java.util.Scanner;
```

```
main class SalesTaxCalculator {
```

```
    public int calculateFinalPrice(int price, int taxRate) {
```

```

        return price + (price * taxRate / 100);
    }

    public double calculateFinalPrice(double price, double taxRate) {
        return price + ((price * taxRate) / 100);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int intPrice = sc.nextInt();
        int intTaxRate = sc.nextInt();

        double doublePrice = sc.nextDouble();
        double doubleTaxRate = sc.nextDouble();

        SalesTaxCalculator calculator = new SalesTaxCalculator();

        int finalIntPrice = calculator.calculateFinalPrice(intPrice, intTaxRate);
        double finalDoublePrice = calculator.calculateFinalPrice(doublePrice,
doubleTaxRate);

        System.out.println(finalIntPrice);
        System.out.printf("%.2f\n", finalDoublePrice);
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int intPrice = scanner.nextInt();
        int intTaxRate = scanner.nextInt();
        double doublePrice = scanner.nextDouble();
        double doubleTaxRate = scanner.nextDouble();

        int finalPriceInt = SalesTaxCalculator.calculateFinalPrice(intPrice,
intTaxRate);

```

```
double finalPriceDouble =  
SalesTaxCalculator.calculateFinalPrice(doublePrice, doubleTaxRate);  
  
    System.out.println(finalPriceInt);  
    System.out.format("%.2f", finalPriceDouble);  
}  
}
```

Status : Wrong

Marks : 0/10