


Sorting in linear time


Counting sort: No comparisons between elements.

- **Input:** $A[1 \dots n]$, where $A[j] \in \{1, 2, \dots, k\}$.
- **Output:** $B[1 \dots n]$, sorted.
- **Auxiliary storage:** $C[1 \dots k]$.







Counting sort

```
for  $i \leftarrow 1$  to  $k$ 
  do  $C[i] \leftarrow 0$ 
for  $j \leftarrow 1$  to  $n$ 
  do  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$ 
for  $i \leftarrow 2$  to  $k$ 
  do  $C[i] \leftarrow C[i] + C[i-1]$      $\triangleright C[i] = |\{\text{key} \leq i\}|$ 
for  $j \leftarrow n$  downto  $1$ 
  do  $B[C[A[j]]] \leftarrow A[j]$ 
     $C[A[j]] \leftarrow C[A[j]] - 1$ 
```



Counting-sort example





Loop 1

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3



	1	2	3	4
<i>C</i> :	0	0	0	0

<i>B</i> :					
------------	--	--	--	--	--

for $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$



Loop 2






for $j \leftarrow 1$ **to** n

do $C[A[j]] \leftarrow C[A[j]] + 1$ $\triangleright C[i] = |\{\text{key} = i\}|$





Loop 2



for $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$ $\triangleright C[i] = |\{\text{key} = i\}|$





Loop 2



for $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$ $\triangleright C[i] = |\{\text{key} = i\}|$





Loop 2



for $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$ $\triangleright C[i] = |\{\text{key} = i\}|$



Loop 2



for $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$ $\triangleright C[i] = |\{\text{key} = i\}|$



Loop 3

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

<i>B</i> :					
------------	--	--	--	--	--

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>C'</i> :	1	1	2	2
-------------	---	---	---	---

for $i \leftarrow 2$ **to** k

do $C[i] \leftarrow C[i] + C[i-1]$

$\triangleright C[i] = |\{\text{key} \leq i\}|$



Loop 3

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

<i>B</i> :					
------------	--	--	--	--	--

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>C'</i> :	1	1	3	2
-------------	---	---	---	---

for $i \leftarrow 2$ **to** k

do $C[i] \leftarrow C[i] + C[i-1]$ $\triangleright C[i] = |\{\text{key} \leq i\}|$



Loop 3

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

<i>B</i> :					
------------	--	--	--	--	--

	1	2	3	4
<i>C</i> :	1	0	2	2



<i>C'</i> :	1	1	3	5
-------------	---	---	---	---

for $i \leftarrow 2$ **to** k


do $C[i] \leftarrow C[i] + C[i-1]$ $\triangleright C[i] = |\{\text{key} \leq i\}|$





Loop 4



```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```





Loop 4



```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```





Loop 4



```
for  $j \leftarrow n$  downto 1
  do  $B[C[A[j]]] \leftarrow A[j]$ 
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```





Loop 4




```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```




Loop 4



```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```



Analysis

$\Theta(k)$ { **for** $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$

$\Theta(n)$ { **for** $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$

$\Theta(k)$ { **for** $i \leftarrow 2$ **to** k
 do $C[i] \leftarrow C[i] + C[i-1]$

$\Theta(n)$ { **for** $j \leftarrow n$ **downto** 1
 do $B[C[A[j]]] \leftarrow A[j]$
 $C[A[j]] \leftarrow C[A[j]] - 1$

$\Theta(n + k)$




Running time

If $k = O(n)$, then counting sort takes $\Theta(n)$ time.

- But, sorting takes $\Omega(n \lg n)$ time!
- Where's the fallacy?


Answer:

- *Comparison sorting* takes $\Omega(n \lg n)$ time.
- Counting sort is not a *comparison sort*.
- In fact, not a single comparison between elements occurs!



Stable sorting


Counting sort is a *stable* sort: it preserves the input order among equal elements.



Exercise: What other sorts have this property?




Radix sort

- *Origin*: Herman Hollerith's card-sorting machine for the 1890 U.S. Census. (See Appendix .)
- Digit-by-digit sort.
- Hollerith's original (bad) idea: sort on most-significant digit first.
- Good idea: Sort on *least-significant digit first* with auxiliary *stable* sort.



Operation of radix sort






Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t







Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t
 - Two numbers that differ in digit t are correctly sorted.







Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t
 - Two numbers that differ in digit t are correctly sorted.
 - Two numbers equal in digit t are put in the same order as the input \Rightarrow correct order.





Analysis of radix sort


- Assume counting sort is the auxiliary stable sort.
- Sort n computer words of b bits each.
- Each word can be viewed as having b/r base- 2^r digits.

Example: 32-bit word

--	--	--	--

$r = 8 \Rightarrow b/r = 4$ passes of counting sort on base- 2^8 digits; or $r = 16 \Rightarrow b/r = 2$ passes of counting sort on base- 2^{16} digits.

How many passes should we make?



Analysis (continued)


Recall: Counting sort takes $\Theta(n + k)$ time to sort n numbers in the range from 0 to $k - 1$.

If each b -bit word is broken into r -bit pieces, each pass of counting sort takes $\Theta(n + 2^r)$ time. Since there are b/r passes, we have

$$T(n, b) = \Theta\left(\frac{b}{r}(n + 2^r)\right).$$

Choose r to minimize $T(n, b)$:

- Increasing r means fewer passes, but as $r \gg \lg n$, the time grows exponentially.



Choosing r

$$T(n, b) = \Theta\left(\frac{b}{r} \left(n + 2^r\right)\right)$$

Minimize $T(n, b)$ by differentiating and setting to 0.

Or, just observe that we don't want $2^r \gg n$, and there's no harm asymptotically in choosing r as large as possible subject to this constraint.

Choosing $r = \lg n$ implies $T(n, b) = \Theta(bn/\lg n)$.

- For numbers in the range from 0 to $n^d - 1$, we have $b = d \lg n \Rightarrow$ radix sort runs in $\Theta(dn)$ time.



Conclusions

In practice, radix sort is fast for large inputs, as well as simple to code and maintain.

Example (32-bit numbers):

- At most 3 passes when sorting ≥ 2000 numbers.
- Merge sort and quicksort do at least $\lceil \lg 2000 \rceil = 11$ passes.

Downside: Unlike quicksort, radix sort displays little locality of reference, and thus a well-tuned quicksort fares better on modern processors, which feature steep memory hierarchies.