

Engineering Optics

Lecture 24

12/05/2023

Debolina Misra

Assistant Professor
Department of Physics
IIITDM Kancheepuram, Chennai, India


QWP and HWP

Wave plate → Retarder → alters the polarization state of a light wave travelling through it.

Two common types : Quarter wave plate (QWP) and half-wave plate (HWP)


QWP and HWP

What is the state of polarization of the out coming beam of light?




QWP and HWP

What is the state of polarization of the out coming beam of light?




QWP and HWP

What is the state of polarization of the out coming beam of light?




QWP and HWP



A linearly polarized beam making an angle 45° with the z axis gets converted to a LCP after propagating through a calcite QWP; further, a LCP gets converted to a RCP after propagating through a calcite HWP. The optic axis in the QWP and HWP is along the z direction as shown by lines parallel to the z axis.

Problem:1

A HWP is introduced between two crossed Polaroids P_1 and P_2 . The optic axis makes an angle of 15° with the pass axis of P_1 as shown in Figure. If an unpolarized beam of intensity I_0 is normally incident on P_1 and if I_1 , I_2 and I_3 are the intensities after P_1 , after HWP, and after P_2 , respectively, then calculate I_1 / I_0 , I_2 / I_0 , and I_3 / I_0



Problem-2

- ▶ A left circularly polarized beam ($\lambda_0 = 5893 \text{ \AA}$) is incident normally on a calcite crystal of thickness 0.005141 mm. What will be the state of polarization of the emergent beam?
- ▶ ($n_o = 1.65836$ and $n_e = 1.48641$)

Soltion-2

Solution: The electric field for the incident beam at $x = 0$ is

$$E_y = \frac{E_0}{\sqrt{2}} \sin \omega t \quad E_z = \frac{E_0}{\sqrt{2}} \cos \omega t \quad \leftarrow \text{Is it correct?}$$

Now

$$\begin{aligned} \theta &= \frac{(n_o - n_e)d \times 2\pi}{\lambda_0} \\ &= \frac{0.17195 \times 0.005141 \times 2\pi}{5893 \times 10^{-7}} \approx 3\pi \end{aligned}$$

Thus the emergent wave will be [cf. Eq. (49)]

$$\begin{aligned} E_y &= \frac{E_0}{\sqrt{2}} \sin(\omega t - 3\pi) \\ &= -\frac{E_0}{\sqrt{2}} \sin \omega t \quad E_z = \frac{E_0}{\sqrt{2}} \cos \omega t \end{aligned}$$

which represents a right circularly polarized beam.

Problem-3

- ▶ A left circularly polarized beam ($\lambda_0 = 5893 \text{ \AA}$) is incident on a quartz crystal of thickness 0.025 mm. Determine the state of polarization of the emergent beam. Assume n_o and n_e to be 1.54425 and 1.55336, respectively.

Solution-3

Solution: As in Example 22.1, the electric field for the incident beam at $x = 0$ is given by $E_y = \frac{E_0}{\sqrt{2}} \sin \omega t$ $E_z = \frac{E_0}{\sqrt{2}} \cos \omega t$

$$\theta' = (n_e - n_o) \frac{2\pi}{\lambda_0} d = 2\pi \frac{0.00911 \times 0.025}{5893 \times 10^{-7}} \approx 0.77\pi$$

Thus the emergent beam will be

$$E_y = \frac{E_0}{\sqrt{2}} \cos (\omega t + 0.77\pi) \quad E_z = \frac{E_0}{\sqrt{2}} \cos (\omega t)$$

which will represent a right elliptically polarized light beam.

Thank You