

CS 302.1 - Automata Theory

Lecture 02

Shantanav Chakraborty

Center for Quantum Science and Technology (CQST)


Center for Security, Theory and Algorithms (CSTAR)

IIIT Hyderabad



A quick recap


- Can a given problem be computed by a particular computational model?



A computational model solves a problem P if,

- (i) For all inputs belonging to the YES instance of P, the device outputs **YES**
- (ii) For all inputs belonging to the NO instance of P, the device outputs **NO**.


If (i) and (ii) hold, we say that the problem **P is computable** by this computational model.




Deterministic Finite Automata (DFA)

- Characteristics:
- (i) Single start State
 - (ii) Unique Transitions
 - (iii) Zero or more final states

A quick recap



Deterministic Finite Automata (DFA)



Run:

$Q0 \xrightarrow{0} Q1 \xrightarrow{1} Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q1 \xrightarrow{0} Q2 \xrightarrow{0} Q2 \xrightarrow{0} Q2$


The DFA “accepts” an input string, if it corresponds to a *run* that ends up in the final state Q2. **(Accepting Run)**

The DFA “rejects” an input string, if it corresponds to a *run* that ends up in any non-final state. **(Rejecting Run)**


$L(M) = \{\omega \mid \omega \text{ results in an accepting run}\}$

For the example above, $L(M) = \{\omega \mid \omega \text{ ends in “00”}\}$

Deterministic Finite Automata (DFA)



State transition diagram of the Finite State Machine




For any language L , we say **M decides L** or **M solves L** if


$\forall \omega \in L, M(\omega)$ accepts

$\forall \omega \notin L, M(\omega)$ rejects

Deterministic Finite Automata (DFA)



State transition diagram of the Finite State Machine



Characteristics of DFA : (i) Single start state (ii) Unique transitions (iii) Zero or more final states

Formally, a finite automaton M is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ where

- Q is a finite set called the **states**.
- Σ is a finite set called the **alphabet**.
- $\delta: Q \times \Sigma \mapsto Q$ is the **transition function** (unique).
- $q_0 \in Q$ is the **start state**.
- $F \subseteq Q$ are the **final/accepting states**.

$$Q = \{Q0, Q1, Q2\}$$

$$\Sigma = \{0,1\}$$

$$(Q0,0) \mapsto Q1; (Q0,1) \mapsto Q0, \dots, (Q2,1) \mapsto Q0$$

$$q_0 = Q0$$


$$F = Q2$$

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ has an even number of 0's}\}$


Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ has an even number of 0's}\}$




Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ has an even number of 0's}\}$




Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ has an even number of 0's}\}$



Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ has an even number of 0's}\}$



	0	1
Q0	Q1	Q0
Q1	Q0	Q1

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is divisible by } 3\}$

Any input string would leave three remainders: 0, 1 or 2.

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is divisible by } 3\}$

Any input string would leave three remainders: 0, 1 or 2.

Intuition: Let ω be any substring of the input string divisible by 3, i.e. $\omega = 0(mod\ 3)$

$$\omega 0 = 2 \times value(\omega) = 0(mod\ 3)$$

$$\omega 1 = 2 \times value(\omega) + 1 = 1(mod\ 3)$$

$$\omega 10 = 2 \times value(\omega 1) = 2(mod\ 3)$$


$$\omega 11 = 2 \times value(\omega 1) + 1 = 0(mod\ 3)$$

.... And so on

- The DFA will have three states, each corresponding to the remainder of $value(\omega)/3$.
- The final state = $0(mod\ 3)$ – the string ω is accepted if after reading it, the DFA ends in this state.

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is divisible by } 3\}$



Any input string would either leave remainders 0, 1 or 2.

Intuition: Let ω be any substring of the input string divisible by 3, i.e. $\omega = 0(\text{mod } 3)$

$$\omega 0 = 2 \times \text{value}(\omega) = 0(\text{mod } 3)$$

$$\omega 1 = 2 \times \text{value}(\omega) + 1 = 1(\text{mod } 3)$$


$$\omega 10 = 2 \times \text{value}(\omega 1) = 2(\text{mod } 3)$$

$$\omega 11 = 2 \times \text{value}(\omega 1) + 1 = 0(\text{mod } 3)$$

.... And so on

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is divisible by } 3\}$



	0	1
Q0	Q0	Q1
Q1	Q2	Q0
Q2	Q1	Q2

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is NOT divisible by } 3\}$

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is NOT divisible by } 3\}$

Intuition - Construct a **Toggled DFA**: Toggle the final states and the non-final states!

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is NOT divisible by } 3\}$

Intuition - Construct a **Toggled DFA**: Toggle the final states and the non-final states!


In fact if any DFA accepts L , the toggled DFA accepts \bar{L} , the complement of L

Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is NOT divisible by } 3\}$

Intuition - Construct a **Toggled DFA**: Toggle the final states and the non-final states!

In fact if any DFA accepts L , the toggled DFA accepts \bar{L} , the complement of L




Constructing DFA for a language

Examples: $\Sigma = \{0, 1\}$, $L(M) = \{\omega \mid \omega \text{ is NOT divisible by } 3\}$

Intuition - Construct a **Toggled DFA**: Toggle the final states and the non-final states!

In fact if any DFA accepts L , the toggled DFA accepts \bar{L} , the complement of L



Non-deterministic Finite Automata (NFA)

Characteristics of DFA : (i) Single start state (ii) Unique transitions (iii) Zero or more final states

Non-deterministic Finite Automata (NFA)


Characteristics of DFA : (i) Single start state (ii) Unique transitions (iii) Zero or more final states

Characteristics of NFA : (i) Single start state (ii) Zero or more final states



(iii) Multiple transitions are possible on the same input for a state

(iv) Some transitions might be missing

(v) ϵ - transitions



Non-deterministic Finite Automata (NFA)





Run 1: $Q_0 \xrightarrow{1} Q_0 \xrightarrow{0} Q_0 \xrightarrow{1} Q_0 \xrightarrow{1} Q_0 \xrightarrow{0} Q_0$ (REJECT)

Run 2: $Q_0 \xrightarrow{1} Q_0 \xrightarrow{0} Q_0 \xrightarrow{1} Q_1 \xrightarrow{1} Q_2 \xrightarrow{0} Q_3$ (ACCEPT)

Multiple **runs** per input is possible

Non-deterministic Finite Automata (NFA)



Run 1: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0$ (**REJECT**)



Run 2: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q1 \xrightarrow{1} Q2 \xrightarrow{0} Q3$ (**ACCEPT**)

Run 3: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q0 \xrightarrow{1} Q1 \xrightarrow{0}$ **CRASH**

Run 4: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q1 \xrightarrow{1} Q2 \xrightarrow{\epsilon} Q3 \xrightarrow{0}$ **CRASH**

CRASH is a Rejecting Run

Non-deterministic Finite Automata (NFA)



Run 1: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0$ (REJECT)

Run 2: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q1 \xrightarrow{1} Q2 \xrightarrow{0} Q3$ (ACCEPT)



Run 3: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q0 \xrightarrow{1} Q1 \xrightarrow{0}$ CRASH (REJECT)

Run 4: $Q0 \xrightarrow{1} Q0 \xrightarrow{0} Q0 \xrightarrow{1} Q1 \xrightarrow{1} Q2 \xrightarrow{\epsilon} Q3 \xrightarrow{0}$ CRASH (REJECT)

The NFA “accepts” an input string, if it at **least one run ends up in the final state. (Accepting Run)**



The NFA “rejects” an input string, if there are **no runs that end up in a final state. (Rejecting Run)**

Non-deterministic Finite Automata (NFA)



	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			

Non-deterministic Finite Automata (NFA)



Formally, a NFA M is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ where

- Q is a finite set called the **states**.
- Σ is a finite set called the **alphabet**.
- $\delta: Q \times \Sigma \mapsto P(Q)$ is the **transition function**. $P(Q)$ is the power set of Q
- $q_0 \in Q$ is the **start state**.
- $F \subseteq Q$ is the set of **final/accepting states**.

	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			

NFA vs DFA

- Are NFAs more powerful than DFAs?
- Intuitively, non-determinism seems to be adding more “power”.

NFA vs DFA

- Are NFAs more powerful than DFAs?
- Intuitively, non-determinism seems to be adding more “power”.
- Let L_1 be the language accepted by NFAs and L_2 be the language accepted by DFAs
- Is $L_2 \subseteq L_1$?

NFA vs DFA

- Are NFAs more powerful than DFAs?
- Intuitively, non-determinism seems to be adding more “power”.
- Let L_1 be the language accepted by NFAs and L_2 be the language accepted by DFAs
- Is $L_2 \subseteq L_1$? Clearly true, because a DFA is just a special case of an NFA.

NFA vs DFA

- Are NFAs more powerful than DFAs?
- Intuitively, non-determinism seems to be adding more “power”.
- Let L_1 be the language accepted by NFAs and L_2 be the language accepted by DFAs
- Is $L_2 \subseteq L_1$? Clearly true, because a DFA is just a special case of an NFA.
- Surprisingly, what we will show next is that $L_1 \subseteq L_2$!
- That is, **given an NFA, we can convert it to a DFA that accepts the same language.**
- Such a DFA is called a “**Remembering DFA**”.

Thus, DFAs and NFAs are completely equivalent and $L_1 = L_2$!

Converting an NFA to a DFA

Intuitive idea for the construction of a Remembering DFA from an NFA:

- Let R be the Remembering DFA corresponding to an NFA N .
- R on an input enters a state that is labelled by all possible states that N can enter on that input.
- Note that this “trims away” the non-determinism of the NFA N without “losing” the language it accepts.
- Also note that if N has k states, then R has at most 2^k states. Why?


Converting an NFA to a DFA

Intuitive idea for the construction of a Remembering DFA from an NFA:

- Let R be the Remembering DFA corresponding to an NFA N .
- R on an input enters a state that is labelled by all possible states that N can enter on that input.
- Note that this “trims away” the non-determinism of the NFA N without “losing” the language it accepts.
- Also note that if N has k states, then R has at most 2^k states. Why?
- Any label in the Remembering DFA is a subset of $\{Q_0, Q_1, Q_2, \dots, Q_{k-1}\}$, where Q_i = State of the NFA.
- There are at most 2^k labels for the DFA.

Converting an NFA to a DFA


- R on an input enters a state that is labelled by all possible states that N can enter on that input.




	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			

Converting an NFA to a DFA

- R on an input enters a state that is labelled by all possible states that N can enter on that input.




	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			




Remembering DFA R

Converting an NFA to a DFA

- R on an input enters a state that is labelled by all possible states that N can enter on that input.



	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			




Remembering DFA R


Any state of R that contains in its label, an accepting state of N is an accepting state of R .

Converting an NFA to a DFA

- R on an input enters a state that is labelled by all possible states that N can enter on that input.



	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			




Remembering DFA R


Any state of R that contains in its label, an accepting state of N is an accepting state of R .

Converting an NFA to a DFA

- M_2 on an input enters a state that is labelled by all possible states that M_1 can enter on that input.



	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			




Remembering DFA R


Any state of R that contains in its label, an accepting state of N is an accepting state of R .

Converting an NFA to a DFA

- M_2 on an input enters a state that is labelled by all possible states that M_1 can enter on that input.



	0	1	ϵ
Q0	Q0	Q0, Q1	
Q1		Q2	
Q2	Q3		Q3
Q3			




Remembering DFA R


Any state of R that contains in its label, an accepting state of N is an accepting state of R .

Converting an NFA to a DFA

- M_2 on an input enters a state that is labelled by all possible states that M_1 can enter on that input.




	0	1	ϵ
A	A, B	A	
B	C		D
C			
D	C	C	




Remembering DFA R

Converting an NFA to a DFA

- M_2 on an input enters a state that is labelled by all possible states that M_1 can enter on that input.




	0	1	ϵ
A	A, B	A	
B	C		D
C			
D	C	C	




Remembering DFA R

Converting an NFA to a DFA

- M_2 on an input enters a state that is labelled by all possible states that M_1 can enter on that input.



	0	1	ϵ
A	A, B	A	
B	C		D
C			
D	C	C	



Remembering DFA R

Thank You!