
SIM900 GSM/GPRS Module





The SIM900 is a complete Quad-band GSM/GPRS solution in a SMT module which can be embedded in the customer applications.

Featuring an industry-standard interface, the SIM900 delivers GSM/GPRS 850/900/1800/1900MHz performance for voice, SMS, Data, and Fax in a small form factor and with low power consumption. With a tiny configuration of 24mm x 24mm x 3 mm, SIM900 can fit almost all the space requirements in your M2M application, especially for slim and compact demand of design.

- SIM900 is designed with a very powerful single-chip processor integrating AMR926EJ-S core
- Quad band GSM/GPRS module with a size of 24mmx24mmx3mm
- SMT type suit for customer application
- An embedded Powerful TCP/IP protocol stack
- Based upon mature and field-proven platform, backed up by our support service, from definition to design and production

General featrues

- Quad-Band 850/ 900/ 1800/ 1900 MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
 - Class 4 (2 W @850/ 900 MHz)
 - Class 1 (1 W @ 1800/1900MHz)
- Dimensions: 24* 24 * 3 mm
- Weight: 3.4g
- Control via AT commands (GSM 07.07,07.05 and SIMCOM enhanced AT ● Commands)
- SIM application toolkit
- Supply voltage range 3.4 ... 4.5 V
- Low power consumption
- Operation temperature:
 - -30 °C to +80 °C

Specifications for fax

Group 3, class 1

Specifications for data

- GPRS class 10: max. 85.6 kbps (downlink)
- PBCCH support
- Coding schemes CS 1, 2, 3, 4
- CSD up to 14.4 kbps
- USSD
- Non transparent mode
- PPP-stack

- Hands-free operation (Echo suppression)
- **AMR** Half Rate(HR) Full Rate(FR)

Interfaces

- Interface to external SIM 3V/ 1.8V
- analog audio interface
- RTC backup
- SPI interface
- Serial interface
- Antenna pad
- I2C
- **GPIO**
- **PWM**
- **ADC**

Compatibility

AT cellular command interface

Approvals (in planning)

- CE
- **FCC**
- **ROHS**
- **PTCRB**
- **GCF**
- AT&T
- IC
- TΑ

Specifications for SMS via GSMPin Assignment

/ GPRS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Drivers

MUX Driver

Specifications for voice

- Tricodec
 - Half rate (HR)
 - Full rate (FR)
 - Enhanced Full rate (EFR)

Fax:+86 21 32523301 Email:simcom@sim.com