
Week-8: Code-along

Hariz Emran

2023-10-09

Image



Code

```
library(shiny)
library(datasets)

# Data pre-processing ----
# Tweak the "am" variable to have nicer factor labels -- since this
# doesn't rely on any user inputs, we can do this once at startup
# and then use the value throughout the lifetime of the app
mpgData <- mtcars
mpgData$am <- factor(mpgData$am, labels = c("Automatic", "Manual"))</pre>
```

```
# Define UI for miles per gallon app ----
ui <- fluidPage(</pre>
  # App title ----
 titlePanel("Challenge 8: Fuel Economy"),
  # Sidebar layout with input and output definitions ----
  sidebarLayout(
    # Sidebar panel for inputs ----
    sidebarPanel(
      # Input: Selector for variable to plot against mpg ----
      selectInput("variable", "Variable:",
                  c("Cylinders" = "cyl",
                    "Transmission" = "am",
                    "Gears" = "gear",
                    "Horsepower" = "hp",
                    "Displacement Size per Cylinder" = "disp")),
      # Input: Checkbox for whether outliers should be included ----
      checkboxInput("outliers", "Show outliers", TRUE)
   ),
    # Main panel for displaying outputs ----
    mainPanel(
      # Output: Formatted text for caption ----
      h3(textOutput("caption")),
      # Output: Plot of the requested variable against mpg ----
      plotOutput("mpgPlot"),
      h3("BMW M3 & Honda Civic"),
      img(src = "car.jpeg", height = 60, width = 100),
      img(src = "car2.jpeg", height = 60, width = 100),
      h3("Conclusion of Findings"),
      p("As the findings above demonstrate, fuel economy often referred to as miles per gallon (mpg) ar
        a(span("website", style = "color:blue"), href = "https://mobil.com/en/sap/personal-vehicles/car
        "provides tips on how to improve your car's fuel economy when driving."),
   )
 )
# Define server logic to plot various variables against mpg ----
server <- function(input, output) {</pre>
  # Compute the formula text ----
  # This is in a reactive expression since it is shared by the
  # output$caption and output$mpgPlot functions
```

```
formulaText <- reactive({</pre>
   paste("mpg ~", input$variable)
  # Return the formula text for printing as a caption ----
  output$caption <- renderText({</pre>
    formulaText()
  })
  # Generate a plot of the requested variable against mpg ----
  # and only exclude outliers if requested
  output$mpgPlot <- renderPlot({</pre>
    boxplot(as.formula(formulaText()),
            data = mpgData,
            outline = input$outliers,
            col = "#75AADB", pch = 19)
 })
}
# Create Shiny app ----
shinyApp(ui, server)
```