



# Project Report Dijkstra's Algorithm

**Subject Name** – Design and Analysis of Algorithms

**Subject Code** – 23CSH-301

**Submitted To:**

**Er. Mohammad Shaqlain**

**(E17211)**

**Submitted By:**

**Name:** Harjit Singh

**UID:** 23BCS10849

**Section:** KRG\_2-B

*An implementation of Dijkstra's Algorithm to find the Shortest route*

**1. Aim:** To develop and analyse the complexity of a program to find the shortest route using Dijkstra's Algorithm.

**2. Objective:** The objective is to implement a Dijkstra's Algorithm that finds the shortest path in a Weighted Graph :

- Each edge shows a path and weight of each path gives the distance of that path.
- The program efficiently finds the shortest route

**3. Input / Software Used:**

- **Programming Language:** C++
- **IDE used:** Clion ide
- **Input:** Weighted Graph

**4. Algorithm:**

1. Start
2. Set  $\text{dist}[\text{source}] = 0$  and all other distances as infinity
3. Push the source node into the min heap as a pair  $\langle \text{distance}, \text{node} \rangle \rightarrow$  i.e.,  $\langle 0, \text{source} \rangle$
4. Pop the top element (node with the smallest distance) from the min heap
  - For each adjacent neighbor of the current node:
  - Calculate the distance using the formula:
    - i.  $\text{dist}[v] = \text{dist}[u] + \text{weight}[u][v]$
    - ii. If this new distance is shorter than the current  $\text{dist}[v]$ , update it.
    - iii. Push the updated pair  $\langle \text{dist}[v], v \rangle$  into the min heap
5. Repeat step 3 until the min heap is empty.
6. Return the distance array, which holds the shortest distance from the source to all nodes.
7. Stop

**5. C++ Program:**

```
#include <iostream>

#include <vector>

#include <queue>

#include <climits>

using namespace std;
```

```
// Function to construct adjacency
vector<vector<vector<int>>> constructAdj(vector<vector<int>>
    &edges, int V) {

    // adj[u] = list of {v, wt}
    vector<vector<vector<int>>> adj(V);

    for (const auto &edge : edges) {
        int u = edge[0];
        int v = edge[1];
        int wt = edge[2];
        adj[u].push_back({v, wt});
        adj[v].push_back({u, wt});
    }

    return adj;
}

//Driver Code Ends
// Returns shortest distances from src to all other vertices
vector<int> dijkstra(int V, vector<vector<int>> &edges, int src){

    // Create adjacency list
    vector<vector<vector<int>>> adj = constructAdj(edges, V);

    // Create a priority queue to store vertices that
    // are being preprocessed.
    priority_queue<vector<int>, vector<vector<int>>,
        greater<vector<int>>> pq;
```

```
// Create a vector for distances and initialize all
// distances as infinite
vector<int> dist(V, INT_MAX);

// Insert source itself in priority queue and initialize
// its distance as 0.
pq.push({0, src});
dist[src] = 0;

// Looping till priority queue becomes empty (or all
// distances are not finalized)
while (!pq.empty()){

    // The first vertex in pair is the minimum distance
    // vertex, extract it from priority queue.
    int u = pq.top()[1];
    pq.pop();

    // Get all adjacent of u.
    for (auto x : adj[u]){

        // Get vertex label and weight of current
        // adjacent of u.
        int v = x[0];
        int weight = x[1];

        // If there is shorter path to v through u.
        if (dist[v] > dist[u] + weight)
        {
```

```

        // Updating distance of v
        dist[v] = dist[u] + weight;
        pq.push({dist[v], v});
    }
}

return dist;
}

int main(){
    int V = 5;
    int src = 0;

    // edge list format: {u, v, weight}
    vector<vector<int>> edges = {{0, 1, 4}, {0, 2, 8}, {1, 4, 6},
                                {2, 3, 2}, {3, 4, 10}};

    vector<int> result = dijkstra(V, edges, src);

    // Print shortest distances in one line
    for (int dist : result)
        cout << dist << " ";

    return 0;
}

```

**OUTPUT:** 0 4 8 10 10

## 6. Complexity Analyses:

- i. **Time Complexity:**  $O(E \cdot \log V)$ , Where  $E$  is the number of edges and  $V$  is the number of vertices.
- ii. **Auxiliary Space:**  $O(V)$ , Where  $V$  is the number of vertices, We do not count the adjacency list in auxiliary space as it is necessary for representing the input graph.

**7. Result:** The program finds find the Shortest route successfully and satisfies all the constraints.