

## mod

### Specifying Loading Options for Each Matlab Matrix

The /Z flag instructs MLoadWave to load each Matlab object (matrix, vector, variable, string) step by step. MLoadWave presents a dialog for each Matlab object in the file. You can choose to load or skip the object. If you omit the /Z flag, MLoadWave will load all objects in the file without presenting any dialogs.

### Output Variables

MLoadWave sets the following output variables:

S_path	File system path to the folder containing the file.  This is a system file path (e.g., "hd:FolderA:FolderB:"), not an Igor symbolic path. The path uses Macintosh path syntax, even on Windows, and has a trailing colon.
S_fileName	Name of the loaded file.
V_flag	Number of waves created.
V_flag1	Number of Matlab data sets (2D, 3D, or 4D) loaded.
V_flag2	Number of waves created.
V_flag3	Number of numeric variables created.
V_flag4	Number of string variables created.
S_waveNames	Semicolon-separated list of the names of loaded waves.

Prior to MLoadWave 5.50, the variables V\_Flag1, V\_Flag2, V\_Flag3 and V\_Flag4 were named V1\_Flag, V2\_Flag, V3\_Flag and V4\_Flag.

### See Also

**Symbolic Paths** on page II-22

See **Loading Matlab MAT Files** on page II-163 for background information, including configuration instructions.

## mod

### **mod(num, div)**

The mod function returns the remainder when *num* is divided by *div*.

The mod function may give unexpected results when *num* or *div* is fractional because most fractional numbers can not be precisely represented by a finite-precision floating point value.

### See Also

**trunc, gcd**

## ModDate

### **ModDate(waveName)**

The ModDate function returns the modification date/time of the wave.

### Details

The returned value is a double precision Igor date/time value, which is the number of seconds from 1/1/1904. It returns zero for waves created by versions of Igor prior to 1.2, for which no modification date/time is available.

### See Also

**WaveModCount, Secs2Date, Secs2Time**