

*kwListStr* is treated as if it ends with a *listSepStr* even if it doesn't.

Searches for *keySepStr* and *listSepStr* are always case-sensitive. Searches for *keyStr* in *kwListStr* are usually case-insensitive. Setting the optional *matchCase* parameter to 1 makes the comparisons case sensitive.

In Igor6, only the first byte of *keySepStr* and *listSepStr* was used. In Igor7 and later, all bytes are used.

If *listSepStr* is specified, then *keySepStr* must also be specified. If *matchCase* is specified, *keySepStr* and *listSepStr* must be specified.

### Examples

```
Print RemoveByKey("AKEY", "AKEY:123;BKEY:val") // prints "BKEY:val"
Print RemoveByKey("AKEY", "akey=1;BK=b;", "=") // prints "BK=b;"
Print RemoveByKey("AKEY", "AKEY=1,BK=b,", "=", ",") // prints "BK=b,"
Print RemoveByKey("ckey", "CKEY:1;BKEY:2") // prints "BKEY:2"
Print RemoveByKey("ckey", "CKEY:1;BKEY:2", ":", ";", 1) // prints "CKEY:1;BKEY:2"
```

### See Also

The **NumberByKey**, **StringByKey**, **ReplaceNumberByKey**, **ReplaceStringByKey**, **ItemsInList**, **AxisInfo**, **IgorInfo**, **SetWindow**, and **TraceInfo** functions.

## RemoveContour

**RemoveContour** [/W=*winName*] *contourInstanceName* [, *contourInstanceName*]...

The RemoveContour operation removes the traces, and releases memory associated with the contour plot of *contourInstanceName* in the target or named graph.

### Parameters

*contourInstanceName* is usually simply the name of a wave. More precisely, *contourInstanceName* is a wave name, optionally followed by the # character and an instance number to identify which contour plot of a given wave is to be removed.

### Flags

/ALL	Removes all contour plots from the graph. Any contour name parameters listed are ignored. /ALL was added in Igor Pro 9.00.
/W= <i>winName</i>	Removes contours from the named graph window or subwindow. When omitted, action will affect the active window or subwindow. This must be the first flag specified when used in a Proc or Macro or on the command line.  When identifying a subwindow with <i>winName</i> , see <b>Subwindow Syntax</b> on page III-92 for details on forming the window hierarchy.

### Details

If the axes used by the contour plot are no longer in use, they will also be removed.

A contour instance name in a string can be used with the \$ operator to specify *contourInstance*.

### Examples

```
Display;AppendMatrixContour zw //new graph, contour of zw matrix
AppendMatrixContour zw //two contours of zw
RemoveContour zw#1 //remove the second contour
```

### See Also

The **AppendMatrixContour** and **AppendXYZContour** operations.