

MatrixLinearSolve

Flags

- /D Creates the wave W_W that contains eigenvalues of the singular value decomposition (SVD) for the pseudo-inverse calculation. If one or more of the eigenvalues are small, the matrix may be close to singular.
- /G Calculates only the direct inverse; does not affect calculation of pseudo-inverse. By default, it calculates the inverse of the matrix using LU decomposition. The inverse is calculated using Gauss-Jordan method. The only advantage in using Gauss-Jordan is that it is more likely to flag singular matrices than the LU method.
- /O Overwrites the source with the result.
- /P Calculates the pseudo-inverse of a matrix using the SVD algorithm. The calculated pseudo-inverse is a unique minimal solution to the problem:

$$\min_{\mathbf{X} \in \mathbb{R}^{n \times m}} \|\mathbf{AX} - \mathbf{I}_m\|.$$

Examples

```
Make/O/N=(2,2) mat0 = {{2,3},{1,7}}
MatrixInverse mat0 // Creates wave M_inverse
MatrixOp/O/T=1 mat1 = M_inverse x mat0 // Check result

Make/O/D/N=(4,6) mat1 = enoise(4)
MatrixInverse/P mat1
MatrixOP/O/T=1 aa = mat1 x M_Inverse
MatrixOP/O/P=1 avgAbsErr = sum(abs(mat1 x M_Inverse - identity(4)))/12
```

See Also

The **MatrixOp** operation for more efficient matrix operations.

Matrix Math Operations on page III-138 for more about Igor's matrix routines.

References

See sec. 5.5.4 of:

Golub, G.H., and C.F. Van Loan, *Matrix Computations*, 2nd ed., Johns Hopkins University Press, 1986.

MatrixLinearSolve

MatrixLinearSolve [*flags*] *matrixA matrixB*

The **MatrixLinearSolve** operation solves the linear system $\text{matrixA} * \mathbf{X} = \text{matrixB}$ where *matrixA* is an N-by-N matrix and *matrixB* is an N-by-NRHS matrix of the same data type.