

You set user data on a window or subwindow using the `userData` keyword of the `SetWindow` operation. You set it on a graph trace using the `userData` keyword of the `ModifyGraph` operation. You set it on a control using the `userData` keyword of the various control operations.

#### Parameters

*winName* may specify a window or subwindow name. Use "" for the top window.

When identifying a subwindow with *winName*, see **Subwindow Syntax** on page III-92 for details on forming the window hierarchy.

*objID* is a string specifying the name of a control or graph trace. Use "" for a window or subwindow.

*userdataName* is the name of the user data or "" for the default unnamed user data.

#### See Also

The **ControlInfo**, **GetWindow**, and **SetWindow** operations.

## GetWavesDataFolder

### GetWavesDataFolder(*waveName*, *kind*)

The `GetWavesDataFolder` function returns a string containing the name of a data folder containing the wave named by *waveName*. Variations on the theme are selected by *kind*.

The most common use for this is in a procedure, when you want to create a wave or a global variable in the data folder containing a wave passed as a parameter.

`GetWavesDataFolderDFR` is preferred.

#### Details

<i>kind</i>	GetWavesDataFolder Returns
0	Only the name of the data folder containing <i>waveName</i> .
1	Full path of data folder containing <i>waveName</i> , without wave name.
2	Full path of data folder containing <i>waveName</i> , including possibly quoted wave name.
3	Partial path from current data folder to the data folder containing <i>waveName</i> .
4	Partial path including possibly quoted wave name.

Kinds 2 and 4 are especially useful in creating command strings to be passed to **Execute**.

#### Examples

```
Function DuplicateWaveInDataFolder(w)
    Wave w
    DFREF dfSav = GetDataFolderDFR()
    SetDataFolder GetWavesDataFolder(w,1)
    Duplicate/O w, $(NameOfWave(w) + "_2")
    SetDataFolder dfSav
End
```

#### See Also

Chapter II-8, **Data Folders**.

## GetWavesDataFolderDFR

### GetWavesDataFolderDFR(*waveName*)

The `GetWavesDataFolderDFR` function returns a data folder reference for the data folder containing the specified wave.

`GetWavesDataFolderDFR` is the same as `GetWavesDataFolder` except that it returns a data folder reference instead of a string containing a path.

#### See Also

**Data Folders** on page II-107, **Data Folder References** on page IV-78, **Built-in DFREF Functions** on page IV-81.