

```
SVAR SJC_YUNITS
Printf "Y Units: %s\r", SJC_YUNITS

return 0
End
```

The code above assumes that the header contains the `##NPOINTS` label from which the variables `VJC_NPOINTS` and `SJC_YUNITS` are created. If you can't guarantee that the file contains such a label, then you must use `NVAR/Z` and `NVAR_Exists` to test for the existence of the variable before using it.

If you need to determine which variables were created at runtime, use the `GetIndexedObjName` function and test each name for the `SJC_` or `VJC_` prefix.

Another problem with header variables in functions is that they leave a lot of clutter around. You can clean up like this:

```
KillVariables/Z VJC_NPOINTS
KillStrings/Z SJC_YUNITS
```

Loading Sound Files

The `SoundLoadWave` operation, which was added in Igor Pro 7, loads data from various sound file formats. See **Sound** on page IV-245 for general information on Igor's sound-related features.

Loading Waves Using Igor Procedures

One of Igor's strong points is that it you can write procedures to automatically load, process and graph data. This is useful if you have accumulated a large number of data files with identical or similar structures or if your work generates such files on a regular basis.

The input to the procedures is one or more data files. The output might be a printout of a graph or page layout or a text file of computed results.

Each person will need procedures customized to his or her situation. In this section, we present some examples that might serve as a starting point.

Variables Set by File Loaders

The `LoadWave` operation creates the numeric variable `V_flag` and the string variables `S_fileName`, `S_path`, and `S_waveNames` to provide information that is useful for procedures that automatically load waves. When used in a function, the `LoadWave` operation creates these as local variables.

Most other file loaders create the same or similar output variables.

`LoadWave` sets the string variable `S_fileName` to the name of the file being loaded. This is useful for annotating graphs or page layouts.

`LoadWave` sets the string variable `S_path` to the full path to the folder containing the file that was loaded. This is useful if you need to load a second file from the same folder as the first.

`LoadWave` sets the variable `V_flag` to the number of waves loaded. This allows a procedure to process the waves without knowing in advance how many waves are in a file.

`LoadWave` also sets the string variable `S_waveNames` to a semicolon-separated list of the names of the loaded waves. From a procedure, you can use the names in this list for subsequent processing.