

$$Ci(z) = \gamma + \ln(z) + \int_0^z \frac{\cos(t) - 1}{t} dt, \quad (|\arg(z)| < \pi)$$

where γ is the Euler-Mascheroni constant 0.5772156649015328606065.

IGOR computes the CosIntegral using the expression:

$$Ci(z) = -\frac{Z^2}{4} {}_2F_3\left(1, 1; 2, 2, \frac{3}{2}; -\frac{z^2}{4}\right) + \ln(z) + \gamma,$$

References

Abramowitz, M., and I.A. Stegun, "Handbook of Mathematical Functions", Dover, New York, 1972. Chapter 5.

See Also

SinIntegral, **ExpIntegralE1**, **hyperGPFQ**

cot

cot(*angle*)

The cot function returns the cotangent of *angle* which is in radians.

In complex expressions, *angle* is complex, and cot(*angle*) returns a complex value.

See Also

sin, **cos**, **tan**, **sec**, **csc**

coth

coth(*num*)

The coth function returns the hyperbolic cotangent of *num*:

$$\coth(x) = \frac{e^x + e^{-x}}{e^x - e^{-x}}.$$

In complex expressions, *num* is complex, and coth(*num*) returns a complex value.

See Also

sinh, **cosh**, **tanh**

CountObjects

CountObjects(*sourceFolderStr*, *objectType*)

The CountObjects function returns the number of objects of the specified type in the data folder specified by the string expression.

CountObjectsDFR is preferred.

Parameters

sourceFolderStr can be either ":" or "" to specify the current data folder. You can also use a full or partial data folder path. *objectType* should be one of the following values:

- 1 Waves
- 2 Numeric variables
- 3 String variables
- 4 Data folders