

Opus
0.9.8

Generated by Doxygen 1.7.4

Mon Oct 31 2011 23:49:19

Contents

1	Opus	1
2	Module Index	3
2.1	Modules	3
3	File Index	5
3.1	File List	5
4	Module Documentation	7
4.1	Opus Encoder	7
4.1.1	Detailed Description	8
4.1.2	Typedef Documentation	9
4.1.2.1	OpusEncoder	9
4.1.3	Function Documentation	9
4.1.3.1	opus_encode	9
4.1.3.2	opus_encode_float	10
4.1.3.3	opus_encoder_create	10
4.1.3.4	opus_encoder_ctl	11
4.1.3.5	opus_encoder_destroy	11
4.1.3.6	opus_encoder_get_size	11
4.1.3.7	opus_encoder_init	12
4.2	Opus Decoder	12
4.2.1	Detailed Description	13
4.2.2	Typedef Documentation	14
4.2.2.1	OpusDecoder	14
4.2.3	Function Documentation	14

4.2.3.1	opus_decode	14
4.2.3.2	opus_decode_float	15
4.2.3.3	opus_decoder_create	15
4.2.3.4	opus_decoder_ctl	16
4.2.3.5	opus_decoder_destroy	16
4.2.3.6	opus_decoder_get_nb_samples	16
4.2.3.7	opus_decoder_get_size	16
4.2.3.8	opus_decoder_init	17
4.2.3.9	opus_packet_get_bandwidth	17
4.2.3.10	opus_packet_get_nb_channels	18
4.2.3.11	opus_packet_get_nb_frames	18
4.2.3.12	opus_packet_get_samples_per_frame	19
4.2.3.13	opus_packet_parse	19
4.3	Repackitizer	19
4.3.1	Detailed Description	20
4.3.2	Typedef Documentation	20
4.3.2.1	OpusRepackitizer	20
4.3.3	Function Documentation	20
4.3.3.1	opus_repackitizer_cat	20
4.3.3.2	opus_repackitizer_create	20
4.3.3.3	opus_repackitizer_destroy	20
4.3.3.4	opus_repackitizer_get_nb_frames	20
4.3.3.5	opus_repackitizer_get_size	20
4.3.3.6	opus_repackitizer_init	20
4.3.3.7	opus_repackitizer_out	20
4.3.3.8	opus_repackitizer_out_range	21
4.4	Error codes	21
4.4.1	Define Documentation	21
4.4.1.1	OPUS_ALLOC_FAIL	21
4.4.1.2	OPUS_BAD_ARG	21
4.4.1.3	OPUS_BUFFER_TOO_SMALL	21
4.4.1.4	OPUS_INTERNAL_ERROR	21
4.4.1.5	OPUS_INVALID_PACKET	22
4.4.1.6	OPUS_INVALID_STATE	22

4.4.1.7	OPUS_OK	22
4.4.1.8	OPUS_UNIMPLEMENTED	22
4.5	Pre-defined values for CTL interface	22
4.5.1	Detailed Description	23
4.5.2	Define Documentation	23
4.5.2.1	OPUS_APPLICATION_AUDIO	23
4.5.2.2	OPUS_APPLICATION_RESTRICTED_LOWDELAY	23
4.5.2.3	OPUS_APPLICATION_VOIP	23
4.5.2.4	OPUS_AUTO	23
4.5.2.5	OPUS_BANDWIDTH_FULLBAND	23
4.5.2.6	OPUS_BANDWIDTH_MEDIUMBAND	23
4.5.2.7	OPUS_BANDWIDTH_NARROWBAND	23
4.5.2.8	OPUS_BANDWIDTH_SUPERWIDEBAND	24
4.5.2.9	OPUS_BANDWIDTH_WIDEBAND	24
4.5.2.10	OPUS_BITRATE_MAX	24
4.5.2.11	OPUS_SIGNAL_MUSIC	24
4.5.2.12	OPUS_SIGNAL_VOICE	24
4.6	Encoder related CTLs	24
4.6.1	Detailed Description	25
4.6.2	Define Documentation	25
4.6.2.1	OPUS_GET_APPLICATION	25
4.6.2.2	OPUS_GET_BITRATE	26
4.6.2.3	OPUS_GET_COMPLEXITY	26
4.6.2.4	OPUS_GET_DTX	26
4.6.2.5	OPUS_GET_FORCE_CHANNELS	26
4.6.2.6	OPUS_GET_INBAND_FEC	27
4.6.2.7	OPUS_GET_LOOKAHEAD	27
4.6.2.8	OPUS_GET_MAX_BANDWIDTH	27
4.6.2.9	OPUS_GET_PACKET_LOSS_PERC	28
4.6.2.10	OPUS_GET_SIGNAL	28
4.6.2.11	OPUS_GET_VBR	28
4.6.2.12	OPUS_GET_VBR_CONSTRAINT	28
4.6.2.13	OPUS_SET_APPLICATION	29
4.6.2.14	OPUS_SET_BANDWIDTH	29

4.6.2.15	OPUS_SET_BITRATE	29
4.6.2.16	OPUS_SET_COMPLEXITY	30
4.6.2.17	OPUS_SET_DTX	30
4.6.2.18	OPUS_SET_FORCE_CHANNELS	30
4.6.2.19	OPUS_SET_INBAND_FEC	30
4.6.2.20	OPUS_SET_MAX_BANDWIDTH	31
4.6.2.21	OPUS_SET_PACKET_LOSS_PERC	31
4.6.2.22	OPUS_SET_SIGNAL	31
4.6.2.23	OPUS_SET_VBR	31
4.6.2.24	OPUS_SET_VBR_CONSTRAINT	32
4.7	Generic CTLs	32
4.7.1	Detailed Description	33
4.7.2	Define Documentation	33
4.7.2.1	OPUS_GET_BANDWIDTH	33
4.7.2.2	OPUS_GET_FINAL_RANGE	33
4.7.2.3	OPUS_GET_PITCH	33
4.7.2.4	OPUS_RESET_STATE	33
4.8	Opus library information functions	34
4.8.1	Function Documentation	34
4.8.1.1	opus_get_version_string	34
4.8.1.2	opus_strerror	34
5	File Documentation	35
5.1	opus.h File Reference	35
5.1.1	Detailed Description	37
5.2	opus_defines.h File Reference	37
5.2.1	Detailed Description	39
5.3	opus_multistream.h File Reference	39
5.3.1	Detailed Description	41
5.3.2	Define Documentation	41
5.3.2.1	__opus_check_decstate_ptr	41
5.3.2.2	__opus_check_encstate_ptr	41
5.3.2.3	OPUS_MULTISTREAM_GET_DECODER_STATE	41
5.3.2.4	OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST	41

5.3.2.5	OPUS_MULTISTREAM_GET_ENCODER_STATE . . .	41
5.3.2.6	OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST	41
5.3.3	Typedef Documentation	41
5.3.3.1	OpusMSDecoder	41
5.3.3.2	OpusMSEncoder	41
5.3.4	Function Documentation	41
5.3.4.1	opus_multistream_decode	42
5.3.4.2	opus_multistream_decode_float	42
5.3.4.3	opus_multistream_decoder_create	42
5.3.4.4	opus_multistream_decoder_ctl	43
5.3.4.5	opus_multistream_decoder_destroy	43
5.3.4.6	opus_multistream_decoder_get_size	43
5.3.4.7	opus_multistream_decoder_init	43
5.3.4.8	opus_multistream_encode	43
5.3.4.9	opus_multistream_encode_float	44
5.3.4.10	opus_multistream_encoder_create	44
5.3.4.11	opus_multistream_encoder_ctl	44
5.3.4.12	opus_multistream_encoder_destroy	45
5.3.4.13	opus_multistream_encoder_get_size	45
5.3.4.14	opus_multistream_encoder_init	45
5.4	opus_types.h File Reference	45
5.4.1	Detailed Description	46
5.4.2	Define Documentation	46
5.4.2.1	opus_int	46
5.4.2.2	opus_int64	46
5.4.2.3	opus_int8	46
5.4.2.4	opus_uint	46
5.4.2.5	opus_uint64	46
5.4.2.6	opus_uint8	46
5.4.3	Typedef Documentation	46
5.4.3.1	opus_int16	46
5.4.3.2	opus_int32	46
5.4.3.3	opus_uint16	46
5.4.3.4	opus_uint32	46

Chapter 1

Opus

The Opus codec is designed for interactive speech and audio transmission over the Internet. It is designed by the IETF Codec Working Group and incorporates technology from Skype's SILK codec and Xiph.Org's CELT codec.

The Opus codec is designed to handle a wide range of interactive audio applications, including Voice over IP, videoconferencing, in-game chat, and even remote live music performances. It can scale from low bit-rate narrowband speech to very high quality stereo music. Its main features are:

- Sampling rates from 8 to 48 kHz
- Bit-rates from 6 kb/s 510 kb/s
- Support for both constant bit-rate (CBR) and variable bit-rate (VBR)
- Audio bandwidth from narrowband to full-band
- Support for speech and music
- Support for mono and stereo
- Frame sizes from 2.5 ms to 60 ms
- Good loss robustness and packet loss concealment (PLC)
- Floating point and fixed-point implementation

Documentation sections:

- [Opus Encoder](#)
- [Opus Decoder](#)
- [Repacketizer](#)
- [Opus library information functions](#)

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Opus Encoder	7
Opus Decoder	12
Repacketizer	19
Error codes	21
Pre-defined values for CTL interface	22
Encoder related CTLs	24
Generic CTLs	32
Opus library information functions	34

Chapter 3

File Index

3.1 File List

Here is a list of all files with brief descriptions:

opus.h (Opus reference implementation API)	35
opus_defines.h (Opus reference implementation constants)	37
opus_multistream.h (Opus reference implementation multistream API)	39
opus_types.h (Opus reference implementation types)	45

Chapter 4

Module Documentation

4.1 Opus Encoder

Since Opus is a stateful codec, the encoding process starts with creating an encoder state.

Typedefs

- typedef struct [OpusEncoder](#) [OpusEncoder](#)
Opus encoder state.

Functions

- int [opus_encoder_get_size](#) (int channels)
- [OpusEncoder](#) * [opus_encoder_create](#) ([opus_int32](#) Fs, int channels, int application, int *error)
Allocates and initializes an encoder state.
- int [opus_encoder_init](#) ([OpusEncoder](#) *st, [opus_int32](#) Fs, int channels, int application)
Initializes a previously allocated encoder state. The memory pointed to by st must be the size returned by opus_encoder_get_size.
- int [opus_encode](#) ([OpusEncoder](#) *st, const [opus_int16](#) *pcm, int frame_size, unsigned char *data, int max_data_bytes)
Encodes an Opus frame.
- int [opus_encode_float](#) ([OpusEncoder](#) *st, const float *pcm, int frame_size, unsigned char *data, int max_data_bytes)
Encodes an Opus frame from floating point input.
- void [opus_encoder_destroy](#) ([OpusEncoder](#) *st)
Frees an OpusEncoder allocated by opus_encoder_create.
- int [opus_encoder_ctl](#) ([OpusEncoder](#) *st, int request,...)
Perform a CTL function on an Opus encoder.

4.1.1 Detailed Description

Since Opus is a stateful codec, the encoding process starts with creating an encoder state. This can be done with:

```
int          error;
OpusEncoder *enc;
enc = opus_encoder_create(Fs, channels, application, &error);
```

From this point, `enc` can be used for encoding an audio stream. An encoder state **must not** be used for more than one stream at the same time. Similarly, the encoder state **must not** be re-initialized for each frame.

While [opus_encoder_create\(\)](#) allocates memory for the state, it's also possible to initialize pre-allocated memory:

```
int          size;
int          error;
OpusEncoder *enc;
size = opus_encoder_get_size(channels);
enc = malloc(size);
error = opus_encoder_init(enc, Fs, channels, application);
```

where [opus_encoder_get_size\(\)](#) returns the required size for the encoder state. Note that future versions of this code may change the size, so no assumptions should be made about it.

The encoder state is always continuous in memory and only a shallow copy is sufficient to copy it (e.g. `memcpy()`)

It is possible to change some of the encoder's settings using the [opus_encoder_ctl\(\)](#) interface. All these settings already default to the recommended value, so they should only be changed when necessary. The most common settings one may want to change are:

```
opus_encoder_ctl(enc, OPUS_SET_BITRATE(bitrate));
opus_encoder_ctl(enc, OPUS_SET_COMPLEXITY(complexity));
opus_encoder_ctl(enc, OPUS_SET_SIGNAL(signal_type));
```

where

- `bitrate` is in bits per second (b/s)
- `complexity` is a value from 1 to 10, where 1 is the lowest complexity and 10 is the highest
- `signal_type` is either `OPUS_AUTO` (default), `OPUS_SIGNAL_VOICE`, or `OPUS_SIGNAL_MUSIC`

See [Encoder related CTLs](#) and [Generic CTLs](#) for a complete list of parameters that can be set or queried. Most parameters can be set or changed at any time during a stream.

To encode a frame, [opus_encode\(\)](#) or [opus_encode_float\(\)](#) must be called with exactly one frame (2.5, 5, 10, 20, 40 or 60 ms) of audio data:


```
len = opus_encode(enc, audio_frame, frame_size, packet, max_packet);
```

where

- `audio_frame` is the audio data in `opus_int16` (or float for [opus_encode_float\(\)](#))
- `frame_size` is the duration of the frame in samples (per channel)
- `packet` is the byte array to which the compressed data is written
- `max_packet` is the maximum number of bytes that can be written in the packet (1276 bytes is recommended)

[opus_encode\(\)](#) and `opus_encode_frame()` return the number of bytes actually written to the packet. The return value **can be negative**, which indicates that an error has occurred. If the return value is 1 byte, then the packet does not need to be transmitted (DTX).

Once the encoder state is no longer needed, it can be destroyed with

```
opus_encoder_destroy(enc);
```

If the encoder was created with [opus_encoder_init\(\)](#) rather than [opus_encoder_create\(\)](#), then no action is required aside from potentially freeing the memory that was manually allocated for it (calling `free(enc)` for the example above)

4.1.2 Typedef Documentation

4.1.2.1 typedef struct OpusEncoder OpusEncoder

Opus encoder state.

This contains the complete state of an Opus encoder. It is position independent and can be freely copied.

See also

[opus_encoder_create](#), [opus_encoder_init](#)

4.1.3 Function Documentation

4.1.3.1 `int opus_encode (OpusEncoder * st, const opus_int16 * pcm, int frame_size, unsigned char * data, int max_data_bytes)`

Encodes an Opus frame.

The passed `frame_size` must be an opus frame size for the encoder's sampling rate. For example, at 48kHz the permitted values are 120, 240, 480, or 960. Passing in a duration of less than 10ms (480 samples at 48kHz) will prevent the encoder from using the LPC or hybrid modes.

Parameters

in	<i>st</i>	OpusEncoder*: Encoder state
in	<i>pcm</i>	opus_int16*: Input signal (interleaved if 2 channels). length is frame_size*channels*sizeof(opus_int16)
in	<i>frame_size</i>	int: Number of samples per frame of input signal
out	<i>data</i>	char*: Output payload (at least max_data_bytes long)
in	<i>max_data_bytes</i>	int: Allocated memory for payload; don't use for controlling bi-rate

Returns

length of the data payload (in bytes) or [Error codes](#)

4.1.3.2 `int opus_encode_float (OpusEncoder * st, const float * pcm, int frame_size, unsigned char * data, int max_data_bytes)`

Encodes an Opus frame from floating point input.

The passed frame_size must an opus frame size for the encoder's sampling rate. For example, at 48kHz the permitted values are 120, 240, 480, or 960. Passing in a duration of less than 10ms (480 samples at 48kHz) will prevent the encoder from using the LPC or hybrid modes.

Parameters

in	<i>st</i>	OpusEncoder*: Encoder state
in	<i>pcm</i>	float*: Input signal (interleaved if 2 channels). length is frame_size*channels*sizeof(float)
in	<i>frame_size</i>	int: Number of samples per frame of input signal
out	<i>data</i>	char*: Output payload (at least max_data_bytes long)
in	<i>max_data_bytes</i>	int: Allocated memory for payload; don't use for controlling bi-rate

Returns

length of the data payload (in bytes) or [Error codes](#)

4.1.3.3 `OpusEncoder* opus_encoder_create (opus_int32 Fs, int channels, int application, int * error)`

Allocates and initializes an encoder state.

There are three coding modes:

[OPUS_APPLICATION_VOIP](#) gives best quality at a given bitrate for voice signals. It enhances the input signal by high-pass filtering and emphasizing formants and harmonics. Optionally it includes in-band forward error correction to protect against packet loss. Use this mode for typical VoIP applications. Because of the enhancement, even at high bitrates the output may sound different from the input.

[OPUS_APPLICATION_AUDIO](#) gives best quality at a given bitrate for most non-voice signals like music. Use this mode for music and mixed (music/voice) content, broadcast, and applications requiring less than 15 ms of coding delay.

[OPUS_APPLICATION_RESTRICTED_LOWDELAY](#) configures low-delay mode that disables the speech-optimized mode in exchange for slightly reduced delay.

This is useful when the caller knows that the speech-optimized modes will not be needed (use with caution).

Parameters

in	<i>Fs</i>	opus_int32: Sampling rate of input signal (Hz)
in	<i>channels</i>	int: Number of channels (1/2) in input signal
in	<i>application</i>	int: Coding mode (OPUS_APPLICATION_VOIP / OPUS_APPLICATION_AUDIO / OPUS_APPLICATION_RESTRICTED_LOWDELAY)
out	<i>error</i>	int*: Error codes

Note

Regardless of the sampling rate and number channels selected, the Opus encoder can switch to a lower audio audio bandwidth or number of channels if the bitrate selected is too low. This also means that it is safe to always use 48 kHz stereo input and let the encoder optimize the encoding.

4.1.3.4 int opus_encoder_ctl (OpusEncoder * st, int request, ...)

Perform a CTL function on an Opus encoder.

See also

[Encoder related CTLs](#)

4.1.3.5 void opus_encoder_destroy (OpusEncoder * st)

Frees an OpusEncoder allocated by opus_encoder_create.

Parameters

in	<i>st</i>	OpusEncoder*: State to be freed.
----	-----------	----------------------------------

4.1.3.6 int opus_encoder_get_size (int channels)

4.1.3.7 `int opus_encoder_init (OpusEncoder * st, opus_int32 Fs, int channels, int application)`

Initializes a previously allocated encoder state. The memory pointed to by `st` must be the size returned by `opus_encoder_get_size`.

This is intended for applications which use their own allocator instead of `malloc`.

See also

[opus_encoder_create\(\)](#), [opus_encoder_get_size\(\)](#) To reset a previously initialized state use the [OPUS_RESET_STATE](#) CTL.

Parameters

in	<i>st</i>	OpusEncoder*: Encoder state
in	<i>Fs</i>	opus_int32: Sampling rate of input signal (Hz)
in	<i>channels</i>	int: Number of channels (1/2) in input signal
in	<i>application</i>	int: Coding mode (OPUS_APPLICATION_VOIP/OPUS_APPLICATION_AUDIO/OPUS_APPLICATION_RESTRICTED_LOWDELAY)

Return values

<i>OPUS_OK</i>	Success or Error codes
----------------	--

4.2 Opus Decoder

The decoding process also starts with creating a decoder state.

Typedefs

- typedef struct [OpusDecoder](#) [OpusDecoder](#)
Opus decoder state.

Functions

- int [opus_decoder_get_size](#) (int channels)
Gets the size of an OpusDecoder structure.
- [OpusDecoder *](#) [opus_decoder_create](#) ([opus_int32](#) Fs, int channels, int *error)
Allocates and initializes a decoder state.
- int [opus_decoder_init](#) ([OpusDecoder *](#)st, [opus_int32](#) Fs, int channels)
Initializes a previously allocated decoder state.
- int [opus_decode](#) ([OpusDecoder *](#)st, const unsigned char *data, int len, [opus_int16 *](#)pcm, int frame_size, int decode_fec)
Decode an Opus frame.

- int [opus_decode_float](#) ([OpusDecoder](#) *st, const unsigned char *data, int len, float *pcm, int frame_size, int decode_fec)
Decode an opus frame with floating point output.
- int [opus_decoder_ctl](#) ([OpusDecoder](#) *st, int request,...)
Perform a CTL function on an Opus decoder.
- void [opus_decoder_destroy](#) ([OpusDecoder](#) *st)
Frees an OpusDecoder allocated by opus_decoder_create.
- int [opus_packet_parse](#) (const unsigned char *data, int len, unsigned char *out_toc, const unsigned char *frames[48], short size[48], int *payload_offset)
Parse an opus packet into one or more frames.
- int [opus_packet_get_bandwidth](#) (const unsigned char *data)
Gets the bandwidth of an Opus packet.
- int [opus_packet_get_samples_per_frame](#) (const unsigned char *data, [opus_int32](#) Fs)
Gets the number of samples per frame from an Opus packet.
- int [opus_packet_get_nb_channels](#) (const unsigned char *data)
Gets the number of channels from an Opus packet.
- int [opus_packet_get_nb_frames](#) (const unsigned char packet[], int len)
Gets the number of frame in an Opus packet.
- int [opus_decoder_get_nb_samples](#) (const [OpusDecoder](#) *dec, const unsigned char packet[], int len)
Gets the number of samples of an Opus packet.

4.2.1 Detailed Description

The decoding process also starts with creating a decoder state. This can be done with:

```
int          error;
OpusDecoder *dec;
dec = opus_decoder_create(Fs, channels, &error);
```

where

- Fs is the sampling rate and must be 8000, 12000, 16000, 24000, or 48000
- channels is the number of channels (1 or 2)
- error will hold the error code in case of failure (or OPUS_OK on success)
- the return value is a newly created decoder state to be used for decoding

While [opus_decoder_create\(\)](#) allocates memory for the state, it's also possible to initialize pre-allocated memory:

```
int          size;
int          error;
OpusDecoder *dec;
size = opus_decoder_get_size(channels);
dec = malloc(size);
error = opus_decoder_init(dec, Fs, channels);
```

where [opus_decoder_get_size\(\)](#) returns the required size for the decoder state. Note that future versions of this code may change the size, so no assumptions should be made about it.

The decoder state is always continuous in memory and only a shallow copy is sufficient to copy it (e.g. `memcpy()`)

To decode a frame, [opus_decode\(\)](#) or [opus_decode_float\(\)](#) must be called with a packet of compressed audio data:

```
frame_size = opus_decode(enc, packet, len, decoded, max_size);
```

where

- `packet` is the byte array containing the compressed data
- `len` is the exact number of bytes contained in the packet
- `decoded` is the decoded audio data in `opus_int16` (or float for [opus_decode_float\(\)](#))
- `max_size` is the max duration of the frame in samples (per channel) that can fit into the `decoded_frame` array

[opus_decode\(\)](#) and [opus_decode_frame\(\)](#) return the number of samples (per channel) decoded from the packet. If that value is negative, then an error has occurred. This can occur if the packet is corrupted or if the audio buffer is too small to hold the decoded audio.

4.2.2 Typedef Documentation

4.2.2.1 typedef struct `OpusDecoder` `OpusDecoder`

Opus decoder state.

This contains the complete state of an Opus decoder. It is position independent and can be freely copied.

See also

[opus_decoder_create](#), [opus_decoder_init](#)

4.2.3 Function Documentation

4.2.3.1 `int opus_decode (OpusDecoder * st, const unsigned char * data, int len, opus_int16 * pcm, int frame_size, int decode_fec)`

Decode an Opus frame.

Parameters

in	<i>st</i>	OpusDecoder*: Decoder state
in	<i>data</i>	char*: Input payload. Use a NULL pointer to indicate packet loss
in	<i>len</i>	int: Number of bytes in payload*
out	<i>pcm</i>	opus_int16*: Output signal (interleaved if 2 channels). length is frame_size*channels*sizeof(opus_int16)
in	<i>frame_size</i>	Number of samples per channel of available space in *pcm, if less than the maximum frame size (120ms) some frames can not be decoded
in	<i>decode_fec</i>	int: Flag (0/1) to request that any in-band forward error correction data be decoded. If no such data is available the frame is decoded as if it were lost.

Returns

Number of decoded samples or [Error codes](#)

4.2.3.2 `int opus_decode_float (OpusDecoder * st, const unsigned char * data, int len, float * pcm, int frame_size, int decode_fec)`

Decode an opus frame with floating point output.

Parameters

in	<i>st</i>	OpusDecoder*: Decoder state
in	<i>data</i>	char*: Input payload. Use a NULL pointer to indicate packet loss
in	<i>len</i>	int: Number of bytes in payload
out	<i>pcm</i>	float*: Output signal (interleaved if 2 channels). length is frame_size*channels*sizeof(float)
in	<i>frame_size</i>	Number of samples per channel of available space in *pcm, if less than the maximum frame size (120ms) some frames can not be decoded
in	<i>decode_fec</i>	int: Flag (0/1) to request that any in-band forward error correction data be decoded. If no such data is available the frame is decoded as if it were lost.

Returns

Number of decoded samples or [Error codes](#)

4.2.3.3 `OpusDecoder* opus_decoder_create (opus_int32 Fs, int channels, int * error)`

Allocates and initializes a decoder state.

Parameters

in	<i>Fs</i>	opus_int32: Sampling rate of input signal (Hz)
----	-----------	--

in	<i>channels</i>	int: Number of channels (1/2) in input signal
out	<i>error</i>	int*: OPUS_OK Success or Error codes

4.2.3.4 int opus_decoder_ctl (OpusDecoder * *st*, int *request*, ...)

Perform a CTL function on an Opus decoder.

See also

decoderctls

4.2.3.5 void opus_decoder_destroy (OpusDecoder * *st*)

Frees an OpusDecoder allocated by opus_decoder_create.

Parameters

in	<i>st</i>	OpusDecoder*: State to be freed.
----	-----------	----------------------------------

4.2.3.6 int opus_decoder_get_nb_samples (const OpusDecoder * *dec*, const unsigned char *packet*[], int *len*)

Gets the number of samples of an Opus packet.

Parameters

in	<i>dec</i>	OpusDecoder*: Decoder state
in	<i>packet</i>	char*: Opus packet
in	<i>len</i>	int: Length of packet

Returns

Number of samples

Return values

<i>OPUS_INVALID_PACKET</i>	The compressed data passed is corrupted or of an unsupported type
----------------------------	---

4.2.3.7 int opus_decoder_get_size (int *channels*)

Gets the size of an OpusDecoder structure.

Parameters

in	<i>channels</i>	int: Number of channels
----	-----------------	-------------------------

Returns

size

4.2.3.8 int opus_decoder_init (OpusDecoder * *st*, opus_int32 *Fs*, int *channels*)

Initializes a previously allocated decoder state.

The state must be the size returned by opus_decoder_get_size. This is intended for applications which use their own allocator instead of malloc.

See also

[opus_decoder_create](#), [opus_decoder_get_size](#) To reset a previously initialized state use the [OPUS_RESET_STATE](#) CTL.

Parameters

in	<i>st</i>	OpusDecoder*: Decoder state.
in	<i>Fs</i>	opus_int32: Sampling rate of input signal (Hz)
in	<i>channels</i>	int: Number of channels (1/2) in input signal

Return values

<i>OPUS_OK</i>	Success or Error codes
----------------	--

4.2.3.9 int opus_packet_get_bandwidth (const unsigned char * *data*)

Gets the bandwidth of an Opus packet.

Parameters

in	<i>data</i>	char*: Opus packet
----	-------------	--------------------

Return values

<i>OPUS_BANDWIDTH_NARROWBAND</i>	Narrowband (4kHz bandpass)
<i>OPUS_BANDWIDTH_MEDIUMBAND</i>	Mediumband (6kHz bandpass)
<i>OPUS_BANDWIDTH_WIDEBAND</i>	Wideband (8kHz bandpass)

<i>OPUS_ - BANDWIDTH_ - SUPERWIDEBAND</i>	Superwideband (12kHz bandpass)
<i>OPUS_ - BANDWIDTH_ - FULLBAND</i>	Fullband (20kHz bandpass)
<i>OPUS_INVALID_ - PACKET</i>	The compressed data passed is corrupted or of an unsupported type

4.2.3.10 int opus_packet_get_nb_channels (const unsigned char * *data*)

Gets the number of channels from an Opus packet.

Parameters

in	<i>data</i>	char*: Opus packet
----	-------------	--------------------

Returns

Number of channels

Return values

<i>OPUS_INVALID_ - PACKET</i>	The compressed data passed is corrupted or of an unsupported type
-----------------------------------	---

4.2.3.11 int opus_packet_get_nb_frames (const unsigned char *packet*[], int *len*)

Gets the number of frame in an Opus packet.

Parameters

in	<i>packet</i>	char*: Opus packet
in	<i>len</i>	int: Length of packet

Returns

Number of frames

Return values

<i>OPUS_INVALID_ - PACKET</i>	The compressed data passed is corrupted or of an unsupported type
-----------------------------------	---

4.2.3.12 `int opus_packet_get_samples_per_frame (const unsigned char * data, opus_int32 Fs)`

Gets the number of samples per frame from an Opus packet.

Parameters

in	<i>data</i>	char*: Opus packet
in	<i>Fs</i>	opus_int32: Sampling rate in Hz

Returns

Number of samples per frame

Return values

<i>OPUS_INVALID_PACKET</i>	The compressed data passed is corrupted or of an unsupported type
----------------------------	---

4.2.3.13 `int opus_packet_parse (const unsigned char * data, int len, unsigned char * out_toc, const unsigned char * frames[48], short size[48], int * payload_offset)`

Parse an opus packet into one or more frames.

Opus_decode will perform this operation internally so most applications do not need to use this function. This function does not copy the frames, the returned pointers are pointers into the input packet.

Parameters

in	<i>data</i>	char*: Opus packet to be parsed
in	<i>len</i>	int: size of data
out	<i>out_toc</i>	char*: TOC pointer
out	<i>frames</i>	char*[48] encapsulated frames
out	<i>size</i>	short[48] sizes of the encapsulated frames
out	<i>payload_offset</i>	int*: returns the position of the payload within the packet (in bytes)

Returns

number of frames

4.3 Repackitizer

The repackitizer can be used to merge multiple Opus packets into a single packet or alternatively to split Opus packets that have previously been merged.

Typedefs

- typedef struct [OpusRepacketizer](#) [OpusRepacketizer](#)

Functions

- int [opus_repacketizer_get_size](#) (void)
- [OpusRepacketizer](#) * [opus_repacketizer_init](#) ([OpusRepacketizer](#) *rp)
- [OpusRepacketizer](#) * [opus_repacketizer_create](#) (void)
- void [opus_repacketizer_destroy](#) ([OpusRepacketizer](#) *rp)
- int [opus_repacketizer_cat](#) ([OpusRepacketizer](#) *rp, const unsigned char *data, int len)
- [opus_int32](#) [opus_repacketizer_out_range](#) ([OpusRepacketizer](#) *rp, int begin, int end, unsigned char *data, int maxlen)
- int [opus_repacketizer_get_nb_frames](#) ([OpusRepacketizer](#) *rp)
- [opus_int32](#) [opus_repacketizer_out](#) ([OpusRepacketizer](#) *rp, unsigned char *data, int maxlen)

4.3.1 Detailed Description

The repacketizer can be used to merge multiple Opus packets into a single packet or alternatively to split Opus packets that have previously been merged.

4.3.2 Typedef Documentation

4.3.2.1 typedef struct [OpusRepacketizer](#) [OpusRepacketizer](#)

4.3.3 Function Documentation

4.3.3.1 int [opus_repacketizer_cat](#) ([OpusRepacketizer](#) * *rp*, const unsigned char * *data*, int *len*)

4.3.3.2 [OpusRepacketizer](#)* [opus_repacketizer_create](#) (void)

4.3.3.3 void [opus_repacketizer_destroy](#) ([OpusRepacketizer](#) * *rp*)

4.3.3.4 int [opus_repacketizer_get_nb_frames](#) ([OpusRepacketizer](#) * *rp*)

4.3.3.5 int [opus_repacketizer_get_size](#) (void)

4.3.3.6 [OpusRepacketizer](#)* [opus_repacketizer_init](#) ([OpusRepacketizer](#) * *rp*)

4.3.3.7 [opus_int32](#) [opus_repacketizer_out](#) ([OpusRepacketizer](#) * *rp*, unsigned char * *data*, int *maxlen*)

4.3.3.8 `opus_int32 opus_repacketizer_out_range (OpusRepacketizer * rp, int begin, int end, unsigned char * data, int maxlen)`

4.4 Error codes

Defines

- `#define OPUS_OK`
No error.
- `#define OPUS_BAD_ARG`
One or more invalid/out of range arguments.
- `#define OPUS_BUFFER_TOO_SMALL`
The mode struct passed is invalid.
- `#define OPUS_INTERNAL_ERROR`
An internal error was detected.
- `#define OPUS_INVALID_PACKET`
The compressed data passed is corrupted.
- `#define OPUS_UNIMPLEMENTED`
Invalid/unsupported request number.
- `#define OPUS_INVALID_STATE`
An encoder or decoder structure is invalid or already freed.
- `#define OPUS_ALLOC_FAIL`
Memory allocation has failed.

4.4.1 Define Documentation

4.4.1.1 `#define OPUS_ALLOC_FAIL`

Memory allocation has failed.

4.4.1.2 `#define OPUS_BAD_ARG`

One or more invalid/out of range arguments.

4.4.1.3 `#define OPUS_BUFFER_TOO_SMALL`

The mode struct passed is invalid.

4.4.1.4 `#define OPUS_INTERNAL_ERROR`

An internal error was detected.

4.4.1.5 #define OPUS_INVALID_PACKET

The compressed data passed is corrupted.

4.4.1.6 #define OPUS_INVALID_STATE

An encoder or decoder structure is invalid or already freed.

4.4.1.7 #define OPUS_OK

No error.

4.4.1.8 #define OPUS_UNIMPLEMENTED

Invalid/unsupported request number.

4.5 Pre-defined values for CTL interface

Defines

- #define [OPUS_AUTO](#)
Auto/default setting.
- #define [OPUS_BITRATE_MAX](#)
Maximum bitrate.
- #define [OPUS_APPLICATION_VOIP](#)
Best for "standard" VoIP/videoconference applications where listening quality and intelligibility matter most.
- #define [OPUS_APPLICATION_AUDIO](#)
Best for broadcast/high-fidelity application where the decoded audio should be as close as possible to the input.
- #define [OPUS_APPLICATION_RESTRICTED_LOWDELAY](#)
Only use when lowest-achievable latency is what matters most.
- #define [OPUS_SIGNAL_VOICE](#) 3001
Signal being encoded is voice.
- #define [OPUS_SIGNAL_MUSIC](#) 3002
Signal being encoded is music.
- #define [OPUS_BANDWIDTH_NARROWBAND](#)
4kHz bandpass
- #define [OPUS_BANDWIDTH_MEDIUMBAND](#)
6kHz bandpass
- #define [OPUS_BANDWIDTH_WIDEBAND](#)
8kHz bandpass

- #define [OPUS_BANDWIDTH_SUPERWIDEBAND](#)
12kHz bandpass
- #define [OPUS_BANDWIDTH_FULLBAND](#)
20kHz bandpass

4.5.1 Detailed Description

See also

[Generic CTLs,Encoder related CTLs](#)

4.5.2 Define Documentation

4.5.2.1 #define OPUS_APPLICATION_AUDIO

Best for broadcast/high-fidelity application where the decoded audio should be as close as possible to the input.

4.5.2.2 #define OPUS_APPLICATION_RESTRICTED_LOWDELAY

Only use when lowest-achievable latency is what matters most.

Voice-optimized modes cannot be used.

4.5.2.3 #define OPUS_APPLICATION_VOIP

Best for "standard" VoIP/videoconference applications where listening quality and intelligibility matter most.

4.5.2.4 #define OPUS_AUTO

Auto/default setting.

4.5.2.5 #define OPUS_BANDWIDTH_FULLBAND

20kHz bandpass

4.5.2.6 #define OPUS_BANDWIDTH_MEDIUMBAND

6kHz bandpass

4.5.2.7 #define OPUS_BANDWIDTH_NARROWBAND

4kHz bandpass

4.5.2.8 `#define OPUS_BANDWIDTH_SUPERWIDEBAND`

12kHz bandpass

4.5.2.9 `#define OPUS_BANDWIDTH_WIDEBAND`

8kHz bandpass

4.5.2.10 `#define OPUS_BITRATE_MAX`

Maximum bitrate.

4.5.2.11 `#define OPUS_SIGNAL_MUSIC 3002`

Signal being encoded is music.

4.5.2.12 `#define OPUS_SIGNAL_VOICE 3001`

Signal being encoded is voice.

4.6 Encoder related CTLs

Defines

- `#define OPUS_SET_COMPLEXITY(x)`
Configures the encoder's computational complexity.
- `#define OPUS_GET_COMPLEXITY(x)`
Gets the encoder's complexity configuration,.
- `#define OPUS_SET_BITRATE(x)`
Configures the bitrate in the encoder.
- `#define OPUS_GET_BITRATE(x)`
Gets the encoder's bitrate configuration,.
- `#define OPUS_SET_VBR(x)`
Configures VBR in the encoder.
- `#define OPUS_GET_VBR(x)`
Gets the encoder's VBR configuration,.
- `#define OPUS_SET_VBR_CONSTRAINT(x)`
Configures constrained VBR in the encoder.
- `#define OPUS_GET_VBR_CONSTRAINT(x)`
Gets the encoder's constrained VBR configuration.
- `#define OPUS_SET_FORCE_CHANNELS(x)`
Configures mono/stereo forcing in the encoder.

- #define [OPUS_GET_FORCE_CHANNELS\(x\)](#)
Gets the encoder's forced channel configuration,.
- #define [OPUS_SET_MAX_BANDWIDTH\(x\)](#)
Configures the encoder's maximum bandpass allowed,.
- #define [OPUS_GET_MAX_BANDWIDTH\(x\)](#)
Gets the encoder's configured maximum bandpass allowed,.
- #define [OPUS_SET_BANDWIDTH\(x\)](#)
Configures the encoder's bandpass,.
- #define [OPUS_SET_SIGNAL\(x\)](#)
Configures the type of signal being encoded.
- #define [OPUS_GET_SIGNAL\(x\)](#)
Gets the encoder's configured signal type,.
- #define [OPUS_SET_APPLICATION\(x\)](#)
Configures the encoder's intended application.
- #define [OPUS_GET_APPLICATION\(x\)](#)
Gets the encoder's configured application,.
- #define [OPUS_GET_LOOKAHEAD\(x\)](#)
Gets the total samples of delay added by the entire codec.
- #define [OPUS_SET_INBAND_FEC\(x\)](#)
Configures the encoder's use of inband forward error correction.
- #define [OPUS_GET_INBAND_FEC\(x\)](#)
Gets encoder's configured use of inband forward error correction,.
- #define [OPUS_SET_PACKET_LOSS_PERC\(x\)](#)
Configures the encoder's expected packet loss percentage.
- #define [OPUS_GET_PACKET_LOSS_PERC\(x\)](#)
Gets the encoder's configured packet loss percentage,.
- #define [OPUS_SET_DTX\(x\)](#)
Configures the encoder's use of discontinuous transmission.
- #define [OPUS_GET_DTX\(x\)](#)
Gets encoder's configured use of discontinuous transmission,.

4.6.1 Detailed Description

See also

[Generic CTLs](#), [Opus Encoder](#)

4.6.2 Define Documentation

4.6.2.1 #define OPUS_GET_APPLICATION(x)

Gets the encoder's configured application,.

See also[OPUS_SET_APPLICATION](#)**Parameters**

out	x	int*: Application value
-----	---	-------------------------

4.6.2.2 #define OPUS_GET_BITRATE(x)

Gets the encoder's bitrate configuration,.

See also[OPUS_SET_BITRATE](#)**Parameters**

out	x	opus_int32*: bitrate in bits per second.
-----	---	--

4.6.2.3 #define OPUS_GET_COMPLEXITY(x)

Gets the encoder's complexity configuration,.

See also[OPUS_SET_COMPLEXITY](#)**Parameters**

out	x	int*: 0-10, inclusive
-----	---	-----------------------

4.6.2.4 #define OPUS_GET_DTX(x)

Gets encoder's configured use of discontinuous transmission,.

See also[OPUS_SET_DTX](#)**Parameters**

out	x	int*: DTX flag
-----	---	----------------

4.6.2.5 #define OPUS_GET_FORCE_CHANNELS(x)

Gets the encoder's forced channel configuration,.

See also[OPUS_SET_FORCE_CHANNELS](#)**Parameters**

out	x	int*: OPUS_AUTO; 0; 1
-----	---	-----------------------

4.6.2.6 #define OPUS_GET_INBAND_FEC(x)

Gets encoder's configured use of inband forward error correction,.

See also[OPUS_SET_INBAND_FEC](#)**Parameters**

out	x	int*: FEC flag
-----	---	----------------

4.6.2.7 #define OPUS_GET_LOOKAHEAD(x)

Gets the total samples of delay added by the entire codec.

This can be queried by the encoder and then the provided number of samples can be skipped on from the start of the decoder's output to provide time aligned input and output. From the perspective of a decoding application the real data begins this many samples late.

The decoder contribution to this delay is identical for all decoders, but the encoder portion of the delay may vary from implementation to implementation, version to version, or even depend on the encoder's initial configuration. Applications needing delay compensation should call this CTL rather than hard-coding a value.

Parameters

out	x	int*: Number of lookahead samples
-----	---	-----------------------------------

4.6.2.8 #define OPUS_GET_MAX_BANDWIDTH(x)

Gets the encoder's configured maximum bandpass allowed,.

See also[OPUS_SET_MAX_BANDWIDTH](#)**Parameters**

out	x	int*: Bandwidth value
-----	---	-----------------------

4.6.2.9 #define OPUS_GET_PACKET_LOSS_PERC(x)

Gets the encoder's configured packet loss percentage,.

See also

[OPUS_SET_PACKET_LOSS_PERC](#)

Parameters

out	x	int*: Loss percentage in the range 0-100, inclusive.
-----	---	--

4.6.2.10 #define OPUS_GET_SIGNAL(x)

Gets the encoder's configured signal type,.

See also

[OPUS_SET_SIGNAL](#)

Parameters

out	x	int*: Signal type
-----	---	-------------------

4.6.2.11 #define OPUS_GET_VBR(x)

Gets the encoder's VBR configuration,.

See also

[OPUS_SET_VBR](#)

Parameters

out	x	int*: 0; 1
-----	---	------------

4.6.2.12 #define OPUS_GET_VBR_CONSTRAINT(x)

Gets the encoder's constrained VBR configuration.

See also

[OPUS_SET_VBR_CONSTRAINT](#)

Parameters

out	x	int*: 0; 1
-----	---	------------

4.6.2.13 #define OPUS_SET_APPLICATION(x)

Configures the encoder's intended application.

The initial value is a mandatory argument to the `encoder_create` function. The supported values are:

- `OPUS_APPLICATION_VOIP` Process signal for improved speech intelligibility
- `OPUS_APPLICATION_AUDIO` Favor faithfulness to the original input

Parameters

in	x	int: Application value
----	---	------------------------

4.6.2.14 #define OPUS_SET_BANDWIDTH(x)

Configures the encoder's bandpass,.

See also

[OPUS_GET_BANDWIDTH](#) The supported values are:

- `OPUS_AUTO` (default)
- `OPUS_BANDWIDTH_NARROWBAND` 4kHz passband
- `OPUS_BANDWIDTH_MEDIUMBAND` 6kHz passband
- `OPUS_BANDWIDTH_WIDEBAND` 8kHz passband
- `OPUS_BANDWIDTH_SUPERWIDEBAND` 12kHz passband
- `OPUS_BANDWIDTH_FULLBAND` 20kHz passband

Parameters

in	x	int: Bandwidth value
----	---	----------------------

4.6.2.15 #define OPUS_SET_BITRATE(x)

Configures the bitrate in the encoder.

Rates from 500 to 512000 bits per second are meaningful as well as the special values `OPUS_BITRATE_AUTO` and `OPUS_BITRATE_MAX`. The value `OPUS_BITRATE_MAX` can be used to cause the codec to use as much rate as it can, which is useful for controlling the rate by adjusting the output buffer size.

Parameters

in	x	opus_int32: bitrate in bits per second.
----	---	---

4.6.2.16 #define OPUS_SET_COMPLEXITY(*x*)

Configures the encoder's computational complexity.

The supported range is 0-10 inclusive with 10 representing the highest complexity. The default value is 10.

Parameters

<i>in</i>	<i>x</i>	int: 0-10, inclusive
-----------	----------	----------------------

4.6.2.17 #define OPUS_SET_DTX(*x*)

Configures the encoder's use of discontinuous transmission.

Note

This is only applicable to the LPC layer

Parameters

<i>in</i>	<i>x</i>	int: DTX flag, 0 (disabled) is default
-----------	----------	--

4.6.2.18 #define OPUS_SET_FORCE_CHANNELS(*x*)

Configures mono/stereo forcing in the encoder.

This is useful when the caller knows that the input signal is currently a mono source embedded in a stereo stream.

Parameters

<i>in</i>	<i>x</i>	int: OPUS_AUTO (default); 1 (forced mono); 2 (forced stereo)
-----------	----------	--

4.6.2.19 #define OPUS_SET_INBAND_FEC(*x*)

Configures the encoder's use of inband forward error correction.

Note

This is only applicable to the LPC layer

Parameters

<i>in</i>	<i>x</i>	int: FEC flag, 0 (disabled) is default
-----------	----------	--

4.6.2.20 #define OPUS_SET_MAX_BANDWIDTH(x)

Configures the encoder's maximum bandpass allowed,.

See also

[OPUS_GET_MAX_BANDWIDTH](#) The supported values are:

- [OPUS_BANDWIDTH_NARROWBAND](#) 4kHz passband
- [OPUS_BANDWIDTH_MEDIUMBAND](#) 6kHz passband
- [OPUS_BANDWIDTH_WIDEBAND](#) 8kHz passband
- [OPUS_BANDWIDTH_SUPERWIDEBAND](#) 12kHz passband
- [OPUS_BANDWIDTH_FULLBAND](#) 20kHz passband (default)

Parameters

in	x	int: Bandwidth value
----	---	----------------------

4.6.2.21 #define OPUS_SET_PACKET_LOSS_PERC(x)

Configures the encoder's expected packet loss percentage.

Higher values with trigger progressively more loss resistant behavior in the encoder at the expense of quality at a given bitrate in the lossless case, but greater quality under loss.

Parameters

in	x	int: Loss percentage in the range 0-100, inclusive.
----	---	---

4.6.2.22 #define OPUS_SET_SIGNAL(x)

Configures the type of signal being encoded.

This is a hint which helps the encoder's mode selection. The supported values are:

- [OPUS_SIGNAL_AUTO](#) (default)
- [OPUS_SIGNAL_VOICE](#)
- [OPUS_SIGNAL_MUSIC](#)

Parameters

in	x	int: Signal type
----	---	------------------

4.6.2.23 #define OPUS_SET_VBR(x)

Configures VBR in the encoder.

The following values are currently supported:

- 0 CBR
- 1 VBR (default) The configured bitrate may not be met exactly because frames must be an integer number of bytes in length.

Warning

Only the MDCT mode of Opus can provide hard CBR behavior.

Parameters

in	x	int: 0; 1 (default)
----	---	---------------------

4.6.2.24 #define OPUS_SET_VBR_CONSTRAINT(x)

Configures constrained VBR in the encoder.

The following values are currently supported:

- 0 Unconstrained VBR (default)
- 1 Maximum one frame buffering delay assuming transport with a serialization speed of the nominal bitrate This setting is irrelevant when the encoder is in CBR mode.

Warning

Only the MDCT mode of Opus currently heeds the constraint. Speech mode ignores it completely, hybrid mode may fail to obey it if the LPC layer uses more bitrate than the constraint would have permitted.

Parameters

in	x	int: 0 (default); 1
----	---	---------------------

4.7 Generic CTLs

Defines

- #define [OPUS_RESET_STATE](#)
Resets the codec state to be equivalent to a freshly initialized state.
- #define [OPUS_GET_FINAL_RANGE](#)(x)
Gets the final state of the codec's entropy coder.
- #define [OPUS_GET_PITCH](#)(x)
Gets the pitch of the last decoded frame, if available.
- #define [OPUS_GET_BANDWIDTH](#)(x)
Gets the encoder's configured bandpass or the decoder's last bandpass.

4.7.1 Detailed Description

See also

[opus_encoder_ctl](#), [Opus Encoder](#), [Opus Decoder](#)

4.7.2 Define Documentation

4.7.2.1 `#define OPUS_GET_BANDWIDTH(x)`

Gets the encoder's configured bandpass or the decoder's last bandpass,.

See also

[OPUS_SET_BANDWIDTH](#)

Parameters

out	x	int*: Bandwidth value
-----	---	-----------------------

4.7.2.2 `#define OPUS_GET_FINAL_RANGE(x)`

Gets the final state of the codec's entropy coder.

This is used for testing purposes, The encoder and decoder state should be identical after coding a payload (assuming no data corruption or software bugs)

Parameters

out	x	opus_uint32*: Entropy coder state
-----	---	-----------------------------------

4.7.2.3 `#define OPUS_GET_PITCH(x)`

Gets the pitch of the last decoded frame, if available.

This can be used for any post-processing algorithm requiring the use of pitch, e.g. time stretching/shortening. If the last frame was not voiced, or if the pitch was not coded in the frame, then zero is returned.

Parameters

out	x	opus_int32*: pitch period at 48 kHz (or 0 if not available)
-----	---	---

4.7.2.4 `#define OPUS_RESET_STATE`

Resets the codec state to be equivalent to a freshly initialized state.

This should be called when switching streams in order to prevent the back to back

decoding from giving different results from one at a time decoding.

4.8 Opus library information functions

Functions

- const char * [opus_strerror](#) (int error)
Converts an opus error code into a human readable string.
- const char * [opus_get_version_string](#) (void)
Gets the libopus version string.

4.8.1 Function Documentation

4.8.1.1 const char* opus_get_version_string (void)

Gets the libopus version string.

Returns

Version string

4.8.1.2 const char* opus_strerror (int error)

Converts an opus error code into a human readable string.

Parameters

in	<i>error</i>	int: Error number
----	--------------	-------------------

Returns

Error string

Chapter 5

File Documentation

5.1 opus.h File Reference

Opus reference implementation API.

```
#include "opus_types.h"
#include "opus_defines.h"
```

Typedefs

- typedef struct [OpusEncoder](#) [OpusEncoder](#)
Opus encoder state.
- typedef struct [OpusDecoder](#) [OpusDecoder](#)
Opus decoder state.
- typedef struct [OpusRepacketizer](#) [OpusRepacketizer](#)

Functions

- int [opus_encoder_get_size](#) (int channels)
- [OpusEncoder](#) * [opus_encoder_create](#) ([opus_int32](#) Fs, int channels, int application, int *error)
Allocates and initializes an encoder state.
- int [opus_encoder_init](#) ([OpusEncoder](#) *st, [opus_int32](#) Fs, int channels, int application)
Initializes a previously allocated encoder state The memory pointed to by st must be the size returned by opus_encoder_get_size.
- int [opus_encode](#) ([OpusEncoder](#) *st, const [opus_int16](#) *pcm, int frame_size, unsigned char *data, int max_data_bytes)
Encodes an Opus frame.
- int [opus_encode_float](#) ([OpusEncoder](#) *st, const float *pcm, int frame_size, unsigned char *data, int max_data_bytes)

- Encodes an Opus frame from floating point input.*

 - void `opus_encoder_destroy` (`OpusEncoder` *st)

Frees an OpusEncoder allocated by opus_encoder_create.
- int `opus_encoder_ctl` (`OpusEncoder` *st, int request,...)

Perform a CTL function on an Opus encoder.
- int `opus_decoder_get_size` (int channels)

Gets the size of an OpusDecoder structure.
- `OpusDecoder` * `opus_decoder_create` (`opus_int32` Fs, int channels, int *error)

Allocates and initializes a decoder state.
- int `opus_decoder_init` (`OpusDecoder` *st, `opus_int32` Fs, int channels)

Initializes a previously allocated decoder state.
- int `opus_decode` (`OpusDecoder` *st, const unsigned char *data, int len, `opus_int16` *pcm, int frame_size, int decode_fec)

Decode an Opus frame.
- int `opus_decode_float` (`OpusDecoder` *st, const unsigned char *data, int len, float *pcm, int frame_size, int decode_fec)

Decode an opus frame with floating point output.
- int `opus_decoder_ctl` (`OpusDecoder` *st, int request,...)

Perform a CTL function on an Opus decoder.
- void `opus_decoder_destroy` (`OpusDecoder` *st)

Frees an OpusDecoder allocated by opus_decoder_create.
- int `opus_packet_parse` (const unsigned char *data, int len, unsigned char *out_toc, const unsigned char *frames[48], short size[48], int *payload_offset)

Parse an opus packet into one or more frames.
- int `opus_packet_get_bandwidth` (const unsigned char *data)

Gets the bandwidth of an Opus packet.
- int `opus_packet_get_samples_per_frame` (const unsigned char *data, `opus_int32` Fs)

Gets the number of samples per frame from an Opus packet.
- int `opus_packet_get_nb_channels` (const unsigned char *data)

Gets the number of channels from an Opus packet.
- int `opus_packet_get_nb_frames` (const unsigned char packet[], int len)

Gets the number of frame in an Opus packet.
- int `opus_decoder_get_nb_samples` (const `OpusDecoder` *dec, const unsigned char packet[], int len)

Gets the number of samples of an Opus packet.
- int `opus_repacketizer_get_size` (void)
- `OpusRepacketizer` * `opus_repacketizer_init` (`OpusRepacketizer` *rp)
- `OpusRepacketizer` * `opus_repacketizer_create` (void)
- void `opus_repacketizer_destroy` (`OpusRepacketizer` *rp)
- int `opus_repacketizer_cat` (`OpusRepacketizer` *rp, const unsigned char *data, int len)
- `opus_int32` `opus_repacketizer_out_range` (`OpusRepacketizer` *rp, int begin, int end, unsigned char *data, int maxlen)
- int `opus_repacketizer_get_nb_frames` (`OpusRepacketizer` *rp)
- `opus_int32` `opus_repacketizer_out` (`OpusRepacketizer` *rp, unsigned char *data, int maxlen)

5.1.1 Detailed Description

Opus reference implementation API.

5.2 opus_defines.h File Reference

Opus reference implementation constants.

```
#include "opus_types.h"
```

Defines

- `#define OPUS_OK`
No error.
- `#define OPUS_BAD_ARG`
One or more invalid/out of range arguments.
- `#define OPUS_BUFFER_TOO_SMALL`
The mode struct passed is invalid.
- `#define OPUS_INTERNAL_ERROR`
An internal error was detected.
- `#define OPUS_INVALID_PACKET`
The compressed data passed is corrupted.
- `#define OPUS_UNIMPLEMENTED`
Invalid/unsupported request number.
- `#define OPUS_INVALID_STATE`
An encoder or decoder structure is invalid or already freed.
- `#define OPUS_ALLOC_FAIL`
Memory allocation has failed.
- `#define OPUS_AUTO`
Auto/default setting.
- `#define OPUS_BITRATE_MAX`
Maximum bitrate.
- `#define OPUS_APPLICATION_VOIP`
Best for "standard" VoIP/videoconference applications where listening quality and intelligibility matter most.
- `#define OPUS_APPLICATION_AUDIO`
Best for broadcast/high-fidelity application where the decoded audio should be as close as possible to the input.
- `#define OPUS_APPLICATION_RESTRICTED_LOWDELAY`
Only use when lowest-achievable latency is what matters most.
- `#define OPUS_SIGNAL_VOICE 3001`
Signal being encoded is voice.
- `#define OPUS_SIGNAL_MUSIC 3002`

Signal being encoded is music.

- #define [OPUS_BANDWIDTH_NARROWBAND](#)
4kHz bandpass
- #define [OPUS_BANDWIDTH_MEDIUMBAND](#)
6kHz bandpass
- #define [OPUS_BANDWIDTH_WIDEBAND](#)
8kHz bandpass
- #define [OPUS_BANDWIDTH_SUPERWIDEBAND](#)
12kHz bandpass
- #define [OPUS_BANDWIDTH_FULLBAND](#)
20kHz bandpass
- #define [OPUS_SET_COMPLEXITY\(x\)](#)
Configures the encoder's computational complexity.
- #define [OPUS_GET_COMPLEXITY\(x\)](#)
Gets the encoder's complexity configuration,.
- #define [OPUS_SET_BITRATE\(x\)](#)
Configures the bitrate in the encoder.
- #define [OPUS_GET_BITRATE\(x\)](#)
Gets the encoder's bitrate configuration,.
- #define [OPUS_SET_VBR\(x\)](#)
Configures VBR in the encoder.
- #define [OPUS_GET_VBR\(x\)](#)
Gets the encoder's VBR configuration,.
- #define [OPUS_SET_VBR_CONSTRAINT\(x\)](#)
Configures constrained VBR in the encoder.
- #define [OPUS_GET_VBR_CONSTRAINT\(x\)](#)
Gets the encoder's constrained VBR configuration.
- #define [OPUS_SET_FORCE_CHANNELS\(x\)](#)
Configures mono/stereo forcing in the encoder.
- #define [OPUS_GET_FORCE_CHANNELS\(x\)](#)
Gets the encoder's forced channel configuration,.
- #define [OPUS_SET_MAX_BANDWIDTH\(x\)](#)
Configures the encoder's maximum bandpass allowed,.
- #define [OPUS_GET_MAX_BANDWIDTH\(x\)](#)
Gets the encoder's configured maximum bandpass allowed,.
- #define [OPUS_SET_BANDWIDTH\(x\)](#)
Configures the encoder's bandpass,.
- #define [OPUS_SET_SIGNAL\(x\)](#)
Configures the type of signal being encoded.
- #define [OPUS_GET_SIGNAL\(x\)](#)
Gets the encoder's configured signal type,.
- #define [OPUS_SET_APPLICATION\(x\)](#)
Configures the encoder's intended application.

- #define [OPUS_GET_APPLICATION\(x\)](#)
Gets the encoder's configured application,.
- #define [OPUS_GET_LOOKAHEAD\(x\)](#)
Gets the total samples of delay added by the entire codec.
- #define [OPUS_SET_INBAND_FEC\(x\)](#)
Configures the encoder's use of inband forward error correction.
- #define [OPUS_GET_INBAND_FEC\(x\)](#)
Gets encoder's configured use of inband forward error correction,.
- #define [OPUS_SET_PACKET_LOSS_PERC\(x\)](#)
Configures the encoder's expected packet loss percentage.
- #define [OPUS_GET_PACKET_LOSS_PERC\(x\)](#)
Gets the encoder's configured packet loss percentage,.
- #define [OPUS_SET_DTX\(x\)](#)
Configures the encoder's use of discontinuous transmission.
- #define [OPUS_GET_DTX\(x\)](#)
Gets encoder's configured use of discontinuous transmission,.
- #define [OPUS_RESET_STATE](#)
Resets the codec state to be equivalent to a freshly initialized state.
- #define [OPUS_GET_FINAL_RANGE\(x\)](#)
Gets the final state of the codec's entropy coder.
- #define [OPUS_GET_PITCH\(x\)](#)
Gets the pitch of the last decoded frame, if available.
- #define [OPUS_GET_BANDWIDTH\(x\)](#)
Gets the encoder's configured bandpass or the decoder's last bandpass,.

Functions

- const char * [opus_strerror](#) (int error)
Converts an opus error code into a human readable string.
- const char * [opus_get_version_string](#) (void)
Gets the libopus version string.

5.2.1 Detailed Description

Opus reference implementation constants.

5.3 opus_multistream.h File Reference

Opus reference implementation multistream API.

```
#include "opus.h"
```

Defines

- `#define __opus_check_encstate_ptr(ptr) ((ptr) + ((ptr) - (OpusEncoder**)(ptr)))`
- `#define __opus_check_decstate_ptr(ptr) ((ptr) + ((ptr) - (OpusDecoder**)(ptr)))`
- `#define OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST 5120`
- `#define OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST 5122`
- `#define OPUS_MULTISTREAM_GET_ENCODER_STATE(x, y) OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST, __opus_check_int(x), __opus_check_encstate_ptr(y)`
- `#define OPUS_MULTISTREAM_GET_DECODER_STATE(x, y) OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST, __opus_check_int(x), __opus_check_decstate_ptr(y)`

Typedefs

- `typedef struct OpusMSEncoder OpusMSEncoder`
- `typedef struct OpusMSDecoder OpusMSDecoder`

Functions

- `OpusMSEncoder * opus_multistream_encoder_create (opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char *mapping, int application, int *error)`
Allocate and initialize a multistream encoder state object.
- `int opus_multistream_encoder_init (OpusMSEncoder *st, opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char *mapping, int application)`
Initialize an already allocated multistream encoder state.
- `int opus_multistream_encode (OpusMSEncoder *st, const opus_int16 *pcm, int frame_size, unsigned char *data, int max_data_bytes)`
Returns length of the data payload (in bytes) or a negative error code.
- `int opus_multistream_encode_float (OpusMSEncoder *st, const float *pcm, int frame_size, unsigned char *data, int max_data_bytes)`
Returns length of the data payload (in bytes) or a negative error code.
- `opus_int32 opus_multistream_encoder_get_size (int streams, int coupled_streams)`
Gets the size of an OpusMSEncoder structure.
- `void opus_multistream_encoder_destroy (OpusMSEncoder *st)`
Deallocate a multistream encoder state.
- `int opus_multistream_encoder_ctl (OpusMSEncoder *st, int request,...)`
Get or set options on a multistream encoder state.
- `OpusMSDecoder * opus_multistream_decoder_create (opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char *mapping, int *error)`
Allocate and initialize a multistream decoder state object.
- `int opus_multistream_decoder_init (OpusMSDecoder *st, opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char *mapping)`

Initialize a previously allocated decoder state object.

- int [opus_multistream_decode](#) ([OpusMSDecoder](#) *st, const unsigned char *data, int len, [opus_int16](#) *pcm, int frame_size, int decode_fec)

Returns the number of samples decoded or a negative error code.

- int [opus_multistream_decode_float](#) ([OpusMSDecoder](#) *st, const unsigned char *data, int len, float *pcm, int frame_size, int decode_fec)

Returns the number of samples decoded or a negative error code.

- [opus_int32 opus_multistream_decoder_get_size](#) (int streams, int coupled_streams)

Gets the size of an OpusMSDecoder structure.

- int [opus_multistream_decoder_ctl](#) ([OpusMSDecoder](#) *st, int request,...)

Get or set options on a multistream decoder state.

- void [opus_multistream_decoder_destroy](#) ([OpusMSDecoder](#) *st)

Deallocate a multistream decoder state object.

5.3.1 Detailed Description

Opus reference implementation multistream API.

5.3.2 Define Documentation

5.3.2.1 `#define __opus_check_decstate_ptr(ptr) ((ptr) + ((ptr) - (OpusDecoder**)(ptr)))`

5.3.2.2 `#define __opus_check_encstate_ptr(ptr) ((ptr) + ((ptr) - (OpusEncoder**)(ptr)))`

5.3.2.3 `#define OPUS_MULTISTREAM_GET_DECODER_STATE(x, y
) OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST, __opus_check_int(x),
 __opus_check_decstate_ptr(y)`

5.3.2.4 `#define OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST 5122`

5.3.2.5 `#define OPUS_MULTISTREAM_GET_ENCODER_STATE(x, y
) OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST, __opus_check_int(x),
 __opus_check_encstate_ptr(y)`

5.3.2.6 `#define OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST 5120`

5.3.3 Typedef Documentation

5.3.3.1 `typedef struct OpusMSDecoder OpusMSDecoder`

5.3.3.2 `typedef struct OpusMSEncoder OpusMSEncoder`

5.3.4 Function Documentation

5.3.4.1 `int opus_multistream_decode (OpusMSDecoder * st, const unsigned char * data, int len, opus_int16 * pcm, int frame_size, int decode_fec)`

Returns the number of samples decoded or a negative error code.

Parameters

<i>st</i>	Decoder state
<i>data</i>	Input payload. Use a NULL pointer to indicate packet loss
<i>len</i>	Number of bytes in payload
<i>pcm</i>	Output signal, samples interleaved in channel order . length is <i>frame_size</i> *channels
<i>frame_size</i>	Number of samples per frame of input signal
<i>decode_fec</i>	Flag (0/1) to request that any in-band forward error correction data be decoded. If no such data is available the frame is decoded as if it were lost.

5.3.4.2 `int opus_multistream_decode_float (OpusMSDecoder * st, const unsigned char * data, int len, float * pcm, int frame_size, int decode_fec)`

Returns the number of samples decoded or a negative error code.

Parameters

<i>st</i>	Decoder state
<i>data</i>	Input payload buffer. Use a NULL pointer to indicate packet loss
<i>len</i>	Number of payload bytes in data
<i>pcm</i>	Buffer for the output signal (interleaved in channel order). length is <i>frame_size</i> *channels
<i>frame_size</i>	Number of samples per frame of input signal
<i>decode_fec</i>	Flag (0/1) to request that any in-band forward error correction data be decoded. If no such data is available the frame is decoded as if it were lost.

5.3.4.3 `OpusMSDecoder* opus_multistream_decoder_create (opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char * mapping, int * error)`

Allocate and initialize a multistream decoder state object.

Call [opus_multistream_decoder_destroy\(\)](#) to release this object when finished.

Parameters

<i>Fs</i>	Sampling rate to decode at (Hz)
<i>channels</i>	Number of channels to decode
<i>streams</i>	Total number of coded streams in the multistream
<i>coupled_streams</i>	Number of coupled (stereo) streams in the multistream
<i>mapping</i>	Stream to channel mapping table
<i>error</i>	Error code

5.3.4.4 `int opus_multistream_decoder_ctl (OpusMSDecoder * st, int request, ...)`

Get or set options on a multistream decoder state.

5.3.4.5 `void opus_multistream_decoder_destroy (OpusMSDecoder * st)`

Deallocate a multistream decoder state object.

5.3.4.6 `opus_int32 opus_multistream_decoder_get_size (int streams, int coupled_streams)`

Gets the size of an OpusMSDecoder structure.

Returns

size

Parameters

<i>streams</i>	Total number of coded streams
<i>coupled_ - streams</i>	Number of coupled (stereo) streams

5.3.4.7 `int opus_multistream_decoder_init (OpusMSDecoder * st, opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char * mapping)`

Initialize a previously allocated decoder state object.

Parameters

<i>st</i>	Encoder state
<i>Fs</i>	Sample rate of input signal (Hz)
<i>channels</i>	Number of channels in the input signal
<i>streams</i>	Total number of coded streams
<i>coupled_ - streams</i>	Number of coupled (stereo) streams
<i>mapping</i>	Stream to channel mapping table

5.3.4.8 `int opus_multistream_encode (OpusMSEncoder * st, const opus_int16 * pcm, int frame_size, unsigned char * data, int max_data_bytes)`

Returns length of the data payload (in bytes) or a negative error code.

Parameters

<i>st</i>	Encoder state
<i>pcm</i>	Input signal as interleaved samples. Length is <i>frame_size</i> * <i>channels</i>
<i>frame_size</i>	Number of samples per frame of input signal

<i>data</i>	Output buffer for the compressed payload (no more than <i>max_data_bytes</i> long)
<i>max_data_bytes</i>	Allocated memory for payload; don't use for controlling bitrate

5.3.4.9 `int opus_multistream_encode_float (OpusMSEncoder * st, const float * pcm, int frame_size, unsigned char * data, int max_data_bytes)`

Returns length of the data payload (in bytes) or a negative error code.

Parameters

<i>st</i>	Encoder state
<i>pcm</i>	Input signal interleaved in channel order. length is <i>frame_size</i> *channels
<i>frame_size</i>	Number of samples per frame of input signal
<i>data</i>	Output buffer for the compressed payload (no more than <i>max_data_bytes</i> long)
<i>max_data_bytes</i>	Allocated memory for payload; don't use for controlling bitrate

5.3.4.10 `OpusMSEncoder* opus_multistream_encoder_create (opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char * mapping, int application, int * error)`

Allocate and initialize a multistream encoder state object.

Call [opus_multistream_encoder_destroy\(\)](#) to release this object when finished.

Parameters

<i>Fs</i>	Sampling rate of input signal (Hz)
<i>channels</i>	Number of channels in the input signal
<i>streams</i>	Total number of streams to encode from the input
<i>coupled_streams</i>	Number of coupled (stereo) streams to encode
<i>mapping</i>	Encoded mapping between channels and streams
<i>application</i>	Coding mode (OPUS_APPLICATION_VOIP/OPUS_APPLICATION_AUDIO)
<i>error</i>	Error code

5.3.4.11 `int opus_multistream_encoder_ctl (OpusMSEncoder * st, int request, ...)`

Get or set options on a multistream encoder state.

5.3.4.12 `void opus_multistream_encoder_destroy (OpusMSEncoder * st)`

Deallocate a multistream encoder state.

5.3.4.13 `opus_int32 opus_multistream_encoder_get_size (int streams, int coupled_streams)`

Gets the size of an OpusMSEncoder structure.

Returns

size

Parameters

<i>streams</i>	Total number of coded streams
<i>coupled_ - streams</i>	Number of coupled (stereo) streams

5.3.4.14 `int opus_multistream_encoder_init (OpusMSEncoder * st, opus_int32 Fs, int channels, int streams, int coupled_streams, unsigned char * mapping, int application)`

Initialize an already allocated multistream encoder state.

Parameters

<i>st</i>	Encoder state
<i>Fs</i>	Sampling rate of input signal (Hz)
<i>channels</i>	Number of channels in the input signal
<i>streams</i>	Total number of streams to encode from the input
<i>coupled_ - streams</i>	Number of coupled (stereo) streams to encode
<i>mapping</i>	Encoded mapping between channels and streams
<i>application</i>	Coding mode (OPUS_APPLICATION_VOIP/OPUS_APPLICATION_AUDIO)

5.4 opus_types.h File Reference

Opus reference implementation types.

Defines

- `#define opus_int int`
- `#define opus_int64 long long`
- `#define opus_int8 signed char`
- `#define opus_uint unsigned int`

- #define `opus_uint64` unsigned long long
- #define `opus_uint8` unsigned char

Typedefs

- typedef short `opus_int16`
- typedef unsigned short `opus_uint16`
- typedef int `opus_int32`
- typedef unsigned int `opus_uint32`

5.4.1 Detailed Description

Opus reference implementation types.

5.4.2 Define Documentation

5.4.2.1 #define `opus_int` int

5.4.2.2 #define `opus_int64` long long

5.4.2.3 #define `opus_int8` signed char

5.4.2.4 #define `opus_uint` unsigned int

5.4.2.5 #define `opus_uint64` unsigned long long

5.4.2.6 #define `opus_uint8` unsigned char

5.4.3 Typedef Documentation

5.4.3.1 typedef short `opus_int16`

5.4.3.2 typedef int `opus_int32`

5.4.3.3 typedef unsigned short `opus_uint16`

5.4.3.4 typedef unsigned int `opus_uint32`

Index

- [__opus_check_decstate_ptr](#)
 - [opus_multistream.h, 41](#)
- [__opus_check_encstate_ptr](#)
 - [opus_multistream.h, 41](#)
- Encoder related CTLs, [24](#)
 - [OPUS_GET_APPLICATION, 25](#)
 - [OPUS_GET_BITRATE, 26](#)
 - [OPUS_GET_COMPLEXITY, 26](#)
 - [OPUS_GET_DTX, 26](#)
 - [OPUS_GET_FORCE_CHANNELS, 26](#)
 - [OPUS_GET_INBAND_FEC, 27](#)
 - [OPUS_GET_LOOKAHEAD, 27](#)
 - [OPUS_GET_MAX_BANDWIDTH, 27](#)
 - [OPUS_GET_PACKET_LOSS_PERC, 27](#)
 - [OPUS_GET_SIGNAL, 28](#)
 - [OPUS_GET_VBR, 28](#)
 - [OPUS_GET_VBR_CONSTRAINT, 28](#)
 - [OPUS_SET_APPLICATION, 28](#)
 - [OPUS_SET_BANDWIDTH, 29](#)
 - [OPUS_SET_BITRATE, 29](#)
 - [OPUS_SET_COMPLEXITY, 29](#)
 - [OPUS_SET_DTX, 30](#)
 - [OPUS_SET_FORCE_CHANNELS, 30](#)
 - [OPUS_SET_INBAND_FEC, 30](#)
 - [OPUS_SET_MAX_BANDWIDTH, 30](#)
 - [OPUS_SET_PACKET_LOSS_PERC, 31](#)
 - [OPUS_SET_SIGNAL, 31](#)
 - [OPUS_SET_VBR, 31](#)
 - [OPUS_SET_VBR_CONSTRAINT, 32](#)
- Error codes, [21](#)
 - [OPUS_ALLOC_FAIL, 21](#)
 - [OPUS_BAD_ARG, 21](#)
 - [OPUS_BUFFER_TOO_SMALL, 21](#)
 - [OPUS_INTERNAL_ERROR, 21](#)
 - [OPUS_INVALID_PACKET, 21](#)
 - [OPUS_INVALID_STATE, 22](#)
 - [OPUS_OK, 22](#)
 - [OPUS_UNIMPLEMENTED, 22](#)
- Generic CTLs, [32](#)
 - [OPUS_GET_BANDWIDTH, 33](#)
 - [OPUS_GET_FINAL_RANGE, 33](#)
 - [OPUS_GET_PITCH, 33](#)
 - [OPUS_RESET_STATE, 33](#)
- Opus Decoder, [12](#)
 - [opus_decode, 14](#)
 - [opus_decode_float, 15](#)
 - [opus_decoder_create, 15](#)
 - [opus_decoder_ctl, 16](#)
 - [opus_decoder_destroy, 16](#)
 - [opus_decoder_get_nb_samples, 16](#)
 - [opus_decoder_get_size, 16](#)
 - [opus_decoder_init, 17](#)
 - [opus_packet_get_bandwidth, 17](#)
 - [opus_packet_get_nb_channels, 18](#)
 - [opus_packet_get_nb_frames, 18](#)
 - [opus_packet_get_samples_per_frame, 18](#)
 - [opus_packet_parse, 19](#)
 - [OpusDecoder, 14](#)
- Opus Encoder, [7](#)
 - [opus_encode, 9](#)
 - [opus_encode_float, 10](#)
 - [opus_encoder_create, 10](#)
 - [opus_encoder_ctl, 11](#)
 - [opus_encoder_destroy, 11](#)
 - [opus_encoder_get_size, 11](#)
 - [opus_encoder_init, 11](#)
 - [OpusEncoder, 9](#)
- Opus library information functions, [34](#)
 - [opus_get_version_string, 34](#)
 - [opus_strerror, 34](#)
- [opus.h, 35](#)
- [OPUS_ALLOC_FAIL](#)
 - Error codes, [21](#)
- [OPUS_APPLICATION_AUDIO](#)
 - Pre-defined values for CTL interface, [23](#)
- [OPUS_APPLICATION_RESTRICTED_LOWDELAY](#)

- Pre-defined values for CTL interface, [23](#)
- OPUS_APPLICATION_VOIP
 - Pre-defined values for CTL interface, [23](#)
- OPUS_AUTO
 - Pre-defined values for CTL interface, [23](#)
- OPUS_BAD_ARG
 - Error codes, [21](#)
- OPUS_BANDWIDTH_FULLBAND
 - Pre-defined values for CTL interface, [23](#)
- OPUS_BANDWIDTH_MEDIUMBAND
 - Pre-defined values for CTL interface, [23](#)
- OPUS_BANDWIDTH_NARROWBAND
 - Pre-defined values for CTL interface, [23](#)
- OPUS_BANDWIDTH_SUPERWIDEBAND
 - Pre-defined values for CTL interface, [23](#)
- OPUS_BANDWIDTH_WIDEBAND
 - Pre-defined values for CTL interface, [24](#)
- OPUS_BITRATE_MAX
 - Pre-defined values for CTL interface, [24](#)
- OPUS_BUFFER_TOO_SMALL
 - Error codes, [21](#)
- opus_decode
 - Opus Decoder, [14](#)
- opus_decode_float
 - Opus Decoder, [15](#)
- opus_decoder_create
 - Opus Decoder, [15](#)
- opus_decoder_ctl
 - Opus Decoder, [16](#)
- opus_decoder_destroy
 - Opus Decoder, [16](#)
- opus_decoder_get_nb_samples
 - Opus Decoder, [16](#)
- opus_decoder_get_size
 - Opus Decoder, [16](#)
- opus_decoder_init
 - Opus Decoder, [17](#)
- opus_defines.h, [37](#)
- opus_encode
 - Opus Encoder, [9](#)
- opus_encode_float
 - Opus Encoder, [10](#)
- opus_encoder_create
 - Opus Encoder, [10](#)
- opus_encoder_ctl
 - Opus Encoder, [11](#)
- opus_encoder_destroy
 - Opus Encoder, [11](#)
- opus_encoder_get_size
 - Opus Encoder, [11](#)
- opus_encoder_init
 - Opus Encoder, [11](#)
- OPUS_GET_APPLICATION
 - Encoder related CTLs, [25](#)
- OPUS_GET_BANDWIDTH
 - Generic CTLs, [33](#)
- OPUS_GET_BITRATE
 - Encoder related CTLs, [26](#)
- OPUS_GET_COMPLEXITY
 - Encoder related CTLs, [26](#)
- OPUS_GET_DTX
 - Encoder related CTLs, [26](#)
- OPUS_GET_FINAL_RANGE
 - Generic CTLs, [33](#)
- OPUS_GET_FORCE_CHANNELS
 - Encoder related CTLs, [26](#)
- OPUS_GET_INBAND_FEC
 - Encoder related CTLs, [27](#)
- OPUS_GET_LOOKAHEAD
 - Encoder related CTLs, [27](#)
- OPUS_GET_MAX_BANDWIDTH
 - Encoder related CTLs, [27](#)
- OPUS_GET_PACKET_LOSS_PERC
 - Encoder related CTLs, [27](#)
- OPUS_GET_PITCH
 - Generic CTLs, [33](#)
- OPUS_GET_SIGNAL
 - Encoder related CTLs, [28](#)
- OPUS_GET_VBR
 - Encoder related CTLs, [28](#)
- OPUS_GET_VBR_CONSTRAINT
 - Encoder related CTLs, [28](#)
- opus_get_version_string
 - Opus library information functions, [34](#)
- opus_int
 - opus_types.h, [46](#)
- opus_int16
 - opus_types.h, [46](#)
- opus_int32
 - opus_types.h, [46](#)
- opus_int64

- opus_types.h, 46
- opus_int8
 - opus_types.h, 46
- OPUS_INTERNAL_ERROR
 - Error codes, 21
- OPUS_INVALID_PACKET
 - Error codes, 21
- OPUS_INVALID_STATE
 - Error codes, 22
- opus_multistream.h, 39
 - __opus_check_decstate_ptr, 41
 - __opus_check_encstate_ptr, 41
 - opus_multistream_decode, 41
 - opus_multistream_decode_float, 42
 - opus_multistream_decoder_create, 42
 - opus_multistream_decoder_ctl, 43
 - opus_multistream_decoder_destroy, 43
 - opus_multistream_decoder_get_size, 43
 - opus_multistream_decoder_init, 43
 - opus_multistream_encode, 43
 - opus_multistream_encode_float, 44
 - opus_multistream_encoder_create, 44
 - opus_multistream_encoder_ctl, 44
 - opus_multistream_encoder_destroy, 44
 - opus_multistream_encoder_get_size, 45
 - opus_multistream_encoder_init, 45
- OPUS_MULTISTREAM_GET_DECODER_STATE, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_ENCODER_STATE, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST, 41
 - opus_multistream.h, 41
- OpusMSDecoder, 41
- OpusMSEncoder, 41
- opus_multistream_decode
 - opus_multistream.h, 41
- opus_multistream_decode_float
 - opus_multistream.h, 42
- opus_multistream_decoder_create
 - opus_multistream.h, 42
- opus_multistream_decoder_ctl
 - opus_multistream.h, 43
- opus_multistream_decoder_destroy
 - opus_multistream.h, 43
- opus_multistream_decoder_get_size
 - opus_multistream.h, 43
- opus_multistream_decoder_init
 - opus_multistream.h, 43
- opus_multistream_encode
 - opus_multistream.h, 43
- opus_multistream_encode_float
 - opus_multistream.h, 44
- opus_multistream_encoder_create
 - opus_multistream.h, 44
- opus_multistream_encoder_ctl
 - opus_multistream.h, 44
- opus_multistream_encoder_destroy
 - opus_multistream.h, 44
- opus_multistream_encoder_get_size
 - opus_multistream.h, 45
- opus_multistream_encoder_init
 - opus_multistream.h, 45
- OPUS_MULTISTREAM_GET_DECODER_STATE, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_DECODER_STATE_REQUEST, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_ENCODER_STATE, 41
 - opus_multistream.h, 41
- OPUS_MULTISTREAM_GET_ENCODER_STATE_REQUEST, 41
 - opus_multistream.h, 41
- OPUS_OK
 - Error codes, 22
- opus_packet_get_bandwidth
 - Opus Decoder, 17
- opus_packet_get_nb_channels
 - Opus Decoder, 18
- opus_packet_get_nb_frames
 - Opus Decoder, 18
- opus_packet_get_samples_per_frame
 - Opus Decoder, 18
- opus_packet_parse
 - Opus Decoder, 19
- opus_repacketizer_cat
 - Repacketizer, 20
- opus_repacketizer_create
 - Repacketizer, 20
- opus_repacketizer_destroy
 - Repacketizer, 20
- opus_repacketizer_get_nb_frames
 - Repacketizer, 20
- opus_repacketizer_get_size
 - Repacketizer, 20

- opus_repacketizer_init
 - Repacketizer, [20](#)
- opus_repacketizer_out
 - Repacketizer, [20](#)
- opus_repacketizer_out_range
 - Repacketizer, [20](#)
- OPUS_RESET_STATE
 - Generic CTLs, [33](#)
- OPUS_SET_APPLICATION
 - Encoder related CTLs, [28](#)
- OPUS_SET_BANDWIDTH
 - Encoder related CTLs, [29](#)
- OPUS_SET_BITRATE
 - Encoder related CTLs, [29](#)
- OPUS_SET_COMPLEXITY
 - Encoder related CTLs, [29](#)
- OPUS_SET_DTX
 - Encoder related CTLs, [30](#)
- OPUS_SET_FORCE_CHANNELS
 - Encoder related CTLs, [30](#)
- OPUS_SET_INBAND_FEC
 - Encoder related CTLs, [30](#)
- OPUS_SET_MAX_BANDWIDTH
 - Encoder related CTLs, [30](#)
- OPUS_SET_PACKET_LOSS_PERC
 - Encoder related CTLs, [31](#)
- OPUS_SET_SIGNAL
 - Encoder related CTLs, [31](#)
- OPUS_SET_VBR
 - Encoder related CTLs, [31](#)
- OPUS_SET_VBR_CONSTRAINT
 - Encoder related CTLs, [32](#)
- OPUS_SIGNAL_MUSIC
 - Pre-defined values for CTL interface, [24](#)
- OPUS_SIGNAL_VOICE
 - Pre-defined values for CTL interface, [24](#)
- opus_strerror
 - Opus library information functions, [34](#)
- opus_types.h, [45](#)
 - opus_int, [46](#)
 - opus_int16, [46](#)
 - opus_int32, [46](#)
 - opus_int64, [46](#)
 - opus_int8, [46](#)
 - opus_uint, [46](#)
 - opus_uint16, [46](#)
 - opus_uint32, [46](#)
 - opus_uint64, [46](#)
 - opus_uint8, [46](#)
- opus_uint
 - opus_types.h, [46](#)
- opus_uint16
 - opus_types.h, [46](#)
- opus_uint32
 - opus_types.h, [46](#)
- opus_uint64
 - opus_types.h, [46](#)
- opus_uint8
 - opus_types.h, [46](#)
- OPUS_UNIMPLEMENTED
 - Error codes, [22](#)
- OpusDecoder
 - Opus Decoder, [14](#)
- OpusEncoder
 - Opus Encoder, [9](#)
- OpusMSDecoder
 - opus_multistream.h, [41](#)
- OpusMSEncoder
 - opus_multistream.h, [41](#)
- OpusRepacketizer
 - Repacketizer, [20](#)
- Pre-defined values for CTL interface, [22](#)
 - OPUS_APPLICATION_AUDIO, [23](#)
 - OPUS_APPLICATION_RESTRICTED_ -
LOWDELAY, [23](#)
 - OPUS_APPLICATION_VOIP, [23](#)
 - OPUS_AUTO, [23](#)
 - OPUS_BANDWIDTH_FULLBAND, [23](#)
 - OPUS_BANDWIDTH_MEDIUMBAND, [23](#)
 - OPUS_BANDWIDTH_NARROWBAND, [23](#)
 - OPUS_BANDWIDTH_SUPERWIDEBAND, [23](#)
 - OPUS_BANDWIDTH_WIDEBAND, [24](#)
 - OPUS_BITRATE_MAX, [24](#)
 - OPUS_SIGNAL_MUSIC, [24](#)
 - OPUS_SIGNAL_VOICE, [24](#)
- Repacketizer, [19](#)
 - opus_repacketizer_cat, [20](#)
 - opus_repacketizer_create, [20](#)
 - opus_repacketizer_destroy, [20](#)
 - opus_repacketizer_get_nb_frames, [20](#)
 - opus_repacketizer_get_size, [20](#)
 - opus_repacketizer_init, [20](#)
 - opus_repacketizer_out, [20](#)

opus_repacketizer_out_range, [20](#)
OpusRepackitizer, [20](#)