

GameOutcome
<<enumeration>>
IN_PROGRESS
VICTORY
DEFEAT

Change of price type
We are changing the price types from double to int as per section "2.2 General Rules". See the highlighted texts

GameConfig
<<Entity>>
-maxTurns: int = 18
-tableCount: int = 2
-victoryRevenueCents: int = 4500
-victoryPaidCustomers: int = 4
-victorySatisfaction: double = 60
-FIRST_ARRIVAL_TURN: int = 1
-ARRIVAL_INTERVAL: int = 3
-TOTAL_ARRIVALS: int = 6
+getMaxTurns(): int
+getTableCount(): int
+getVictoryRevenue(): int
+getVictoryPaidCustomers(): int
+getVictorySatisfaction(): double
+isArrivalTurn(turn: int): boolean

GameResult
<<Entity>>
-revenueCents: int
-paidCount: int
-satisfactionTotal: int
-outcome: GameOutcome
-servedCount: int
-abandonedCount: int
+recordPayment(priceCents: int, satisfaction: int): void
+recordServed(): void
+recordAbandonment(): void
+calculateAverageSatisfaction(): double
+evaluate(cfg: GameConfig): GameOutcome
+isVictory(): boolean
+getRevenue(): int
+getPaidCount(): int
+getSatisfactionTotal(): int
+getOutcome(): GameOutcome
+getServedCount(): int
+getAbandonedCount(): int

UserInterface
<<Boundary>>
-in: Scanner
-inputEnded: boolean
+UserInterface()
+UserInterface(in: Scanner)
+displayState(turn: int, maxTurns: int, restaurant: Restaurant, result: GameResult): void
+promptDecision(options: List<Decision>): Decision
+displayError(message: String): void
+displayMessage(message: String): void
+displayResult(result: GameResult, cfg: GameConfig, turnsUsed: int): void
+waitOption(options: List<Decision>): Decision
+averageText(result: GameResult): String
+money(cents: int): String
+displayHappyHour(remainingTurns: int, activatedBefore: boolean, isActive: boolean): void
+promptHappyHourActivation(): boolean

Decision
<<Entity>>
-type: Decision.Type
-customer: Customer
-table: Table
-order: Order
-description: String
-Decision(type: Type, customer: Customer, table: Table, order: Order, description: String)
+seat(c: Customer, t: Table): Decision
+takeOrder(c: Customer, t: Table): Decision
+pay(c: Order, t: Table): Decision
+prepare(o: Order, t: Table): Decision
+doNothing(msg: String): Decision
+getType(): Decision.Type
+getCustomer(): Customer
+getTable(): Table
+getOrder(): Order
+getDescription(): String
+toString(): String

Dev Note
while HappyHour has not been activated promptHappyHourActivation() will prompt user each turn if they want to activate happy hour. The result will then be used to activate HappyHour via TurnController.

Decision.Type
<<enumeration>>
SEAT
TAKE_ORDER
SERVE
PREPARE
WAIT

GameController
<<Control>>
-currentTurn: int
-config: GameConfig
-ui: UserInterface
-result: GameResult
-turnController: TurnController
+GameController(config: GameConfig, ui: UserInterface)
+startGame(): void
+runGame(): void
+getResult(): GameResult

Idea is for **GameController** to manage the 18 round logic and for **TurnController** to manage execution of each individual turn

TurnController
<<Control>>
-config: GameConfig
-restaurant: Restaurant
-result: GameResult
-ui: UserInterface
-waiter: Waiter
-chef: Chef
-cashier: Cashier
-customerFactory: CustomerFactory
-nextCustomerId: int
-host: Host
-happyHour: HappyHour
+TurnController(config: GameConfig, restaurant: Restaurant, result: GameResult, ui: UserInterface)
+executeTurn(turn: int): void
-processArrivals(turn: int): void
-processWaiterAction(d: Decision, turn: int): void
-processChefAction(d: Decision, turn: int): void
-processEating(turn: int): void
-processPayment(): void
-processAbandonment(): void
-buildWaiterOptions(): List<Decision>
-buildChefOptions(): List<Decision>
-abandon(c: Customer): void
-money(cents: int): String
-processHostAction(d: Decision, turn: int): void
-processHappyHourActivation(turn: int): void
-applyHappyHourRecovery(turn: int): void
-buildHostOptions(): List<Decision>

processWaiterAction and **processChefAction** are dependent on the decisions from the manager (i.e the player). Each decision is one of the options built by **buildWaiterOptions** / **buildChefOptions**.

Order of steps inside **executeTurn**: arrivals, display, Happy hour activation & recovery, Host decision, Waiter decision, Chef decision, processPayment, processEating, processAbandonment. Payment runs before eating so a customer who becomes READY_TO_PAY pays on the next turn.

Game flow decision
Since waiter and host can both seat customers but waiter can do more than just seat customers, we will offer the manager the choice to decide what the host does before the waiter.
Since is is not specified we will allow the waiter to take the order of a customer who was seated by the host on the same turn they have been seated.

Composition
Restaurant creates and owns its 2 Tables and its WaitingQueue. They have no life outside the Restaurant.

Restaurant
<<Entity>>
-tables: List<Table>
-waitingQueue: WaitingQueue
-menu: List<MenuItem>
+Restaurant(tableCount: int)
+getAvailableTable(): Table
+getWaitingQueue(): WaitingQueue
+getOccupiedTables(): List<Table>
+findTableOf(c: Customer): Table
+getTables(): List<Table>
+getMenu(): List<MenuItem>

Host
<<Control>>
-restaurant: Restaurant
+Host(restaurant: Restaurant)
+seatCustomer(c: Customer, t: Table): void

Waiter
<<Control>>
-restaurant: Restaurant
+Waiter(restaurant: Restaurant)
+seatCustomer(c: Customer, t: Table): void
+takeOrder(c: Customer, pricing: PricingCalculation, happyHour: HappyHour, int turn): Order
+serve(o: Order, turn: int): void

Chef
<<Control>>
+prepareOrder(o: Order, turn: int): void

Cashier
<<Control>>
+processPayment(o: Order, r: GameResult): void

CustomerFactory
<<Control>>
-VIP_ARRIVAL: int = 2
-CRITIC_ARRIVAL: int = 4
+createCustomer(id: int): Customer

Arrival schedule (Stage 2)
Still six arrivals on turns 1, 4, 7, 10, 13, 16: Regular, VIP, Regular, Critic, Regular, Regular. CustomerFactory is the only class that names the concrete types.

HappyHour
<<Entity>>
-startTurn: int
-activated: boolean
-DISCOUNT: int = 20
-RECOVERY: int = 15
-duration: int = 2
+activate(turn: int): void
+isActive(turn: int): boolean
+hasBeenActivated(): boolean
+getRemainingTurns(turn: int): int
+getDiscount(turn: int): int
+getRecovery(): int

Table
<<Entity>>
-tableNumber: int
-occupant: Customer
+Table(tableNumber: int)
+isAvailable(): boolean
+seat(customer(c: Customer): void
+release(): void
+getTableNumber(): int
+getOccupant(): Customer

WaitingQueue
<<Entity>>
-customers: Queue<Customer>
+enqueue(c: Customer): void
+dequeueNext(): Customer
+remove(c: Customer): boolean
+isEmpty(): boolean
+getSize(): int
+getCustomers(): List<Customer>

Polymorphism
TurnController and Waiter only use the Customer type. VIPCustomer and CriticCustomer override getSatisfactionLoss(), calculateBill() and chooseMenuItem(), so the right behaviour is chosen at run time with no type checks.

Customer
<<Entity>>
-STARTING_SATISFACTION: int = 100
-REGULAR_SATISFACTION_LOSS: int = 8
-id: int
-satisfaction: int
-status: CustomerStatus
-turnServed: int
-order: Order
+Customer(id: int)
+getSatisfactionLoss(): int
+reduceSatisfaction(): void
+chooseMenuItem(menu: List<MenuItem>): MenuItem
+calculateBill(item: MenuItem): int
#getTypeLabel(): String
+setServed(turn: int): void
+getTurnServed(): int
+isWaitingForService(): boolean
+getId(): int
+getSatisfaction(): int
+getStatus(): CustomerStatus
+setStatus(status: CustomerStatus): void
+getOrder(): Order
+setOrder(order: Order): void
+toString(): String
+recoverSatisfaction(points: int): void

CustomerStatus
<<enumeration>>
WAITING
SEATED
ORDERED
EATING
READY_TO_PAY
PAID
ABANDONED

When the manager chooses **take order** for a SEATED customer, the Waiter creates the order and its default state is set to PREPARING. When the order is served, the customer status becomes EATING.

Dev Note
recoverSatisfaction() only applys to customers with the status of WAITING, SEATED and ORDERED while HappyHour is active. Recovery of satisfaction is capped at 100.

PricingCalculation
<<Control>>
+calculateFinalPrice(c: Customer, happyHour: HappyHour, turn: int): int

Single Responsibility Principle (SRP)
Each class manages seperate portions of the pricing. Customer handles the calculation for VIPs, ComboMeal calculates pricing for combo meals while PricingCalculation handles the final calculation of the meal, specifically for when happy hour is active.

Order
<<Entity>>
-customer: Customer
-status: OrderStatus
-preparationRemaining: int
-priceCents: int
-turnReady: int
-turnServed: int
-item: MenuItem
+Order(customer: Customer, item: MenuItem, priceCents: int)
+advancePreparation(): void
+isFullyPrepared(): boolean
+markReady(turn: int): void
+markServed(turn: int): void
+markPaid(): void
+markCancelled(): void
+getCustomer(): Customer
+getItem(): MenuItem
+getPrice(): int
+getStatus(): OrderStatus
+getPreparationRemaining(): int
+getTurnReady(): int
+getTurnServed(): int

OrderStatus
<<enumeration>>
PREPARING
READY
SERVED
PAID
CANCELLED

Encapsulation
Order keeps status and preparationRemaining private. Other classes can only change them through Order's own methods (advancePreparation(), markReady(), markServed(), markPaid(), markCancelled()); the controllers call these in the correct turn order.

Dependencies that appear only as attribute or parameter types are not drawn as separate lines, e.g. GameController -> GameConfig, TurnController -> GameConfig / GameResult, UserInterface -> Restaurant / GameConfig, Cashier -> GameResult, Decision -> Customer / Table / Order.

Menuitem
<<Entity>>
-name: String
-basePriceCents: int
-preparationUnits: int
+MenuItem(name: String, basePriceCents: int, preparationUnits: int)
+getName(): String
+getPrice(): int
+getPrepUnit(): int

ComboMeal
<<Entity>>
-itemOne: MenuItem
-itemTwo: MenuItem
-COMBO_DISCOUNT: int = 10
+ComboMeal(itemOne: MenuItem, itemTwo: MenuItem)
+getPrice(): int
+getPrepUnit(): int

Open/Closed Principle (OCP)
ComboMeal extends MenuItem and overrides the getPrice() and getPrepUnit() methods.
Dev Note
getPrice() and getPrepUnit() returns the combined price (rounded to the nearest cent) after discount and combined prep unit cost for both item one and two.

VIPCustomer
<<Entity>>
-VIP_SATISFACTION_LOSS: int = 5
-VIP_DISCOUNT_RATE: double = 0.10
+VIPCustomer(id: int)
+getSatisfactionLoss(): int
+calculateBill(item: MenuItem): int
#getTypeLabel(): String

CriticCustomer
<<Entity>>
-CRITIC_SATISFACTION_LOSS: int = 12
+CriticCustomer(id: int)
+getSatisfactionLoss(): int
+chooseMenuItem(menu: List<MenuItem>): MenuItem
#getTypeLabel(): String

Critic order preference
A critic always orders the most expensive item on the menu (ties: first listed). For stage 3 this would be the combo meal of Pasta + Burger at ($33 * 0.9 = $29.7)

<<creates>>
<<creates>>
<<creates>>
uses
uses
places
menu