

MYNG of Deliberation RuleML 1.01 Demo


From RuleML Wiki

Authors: Tara Athan, Harold Boley (<http://www.cs.unb.ca/~boley/>)

This page (http://wiki.ruleml.org/index.php/MYNG_of_Deliberation_RuleML_1.01_Demo) provides a quick demonstration of MYNG 1.01 for customizing sublanguages of Deliberation RuleML 1.01.

Key new features include:

- Integration of new Relax NG schema modules -- and the RuleML sublanguages they define -- into MYNG, e.g.
 - Datalog⁺, Hornlog⁺, and their many extensions
 - Improved functionality of the MYNG GUI and REST interface, e.g.
 - GUI access to automatically-generated monolithic XSD schemas that are compatible with XML tools, e.g. JAXB.
 - Display of myng-code and myng-code-based schema URLs.
-




Contents


- 1 Quick Tour of the GUI
- 2 Configuring a Custom Relax NG Schema
- 3 Usage of Customized Schemas
- 4 References

1 Quick Tour of the GUI

- Open the MYNG GUI at <http://deliberation.ruleml.org/1.01/myng>.
- The selection form opens with the supremum language selected:
 - Clicking the Reset Form button will always return to this selection.
 - The RNC field gives the myng-code for this language (myng-b3f-d7-a7-11-p3ff-i7f-tf3f-q7-ef-sf).
 - The XSD field gives the name of the best approximating anchor language (naffologeq).
 - The two rows of five boxes with blue backgrounds group the configuration options into semantically-related facets, which will be discussed in greater detail below.



- Below the facets, two URLs are given
 - Relax NG Schema URL = http://deliberation.ruleml.org/1.01/relaxng/schema_rnc.php?backbone=x3f&default=x7&termseq=x7&lng=x1&propo=x3ff&implies=x7f&terms=xf3f&quant=x7&expr=xf&serial=xf
This is the MYNG REST call with query string to obtain the driver schema corresponding to the selections, which can also be reached using the myng-code (<http://deliberation.ruleml.org/1.01/relaxng#myng-code>) URL
<http://deliberation.ruleml.org/1.01/myng-b3f-d7-a7-11-p3ff-i7f-tf3f-q7-ef-sf.rnc> .
 - XSD Anchor Schema URL = <http://deliberation.ruleml.org/1.01/xsd/naffologeq.xsd>
This is the URL for the monolithic XSD schema of the anchor language naffologeq.
- Clicking the Generate Schema button initiates a request to the MYNG REST interface which produces a copy of the Relax NG Schema at the bottom of the page.
- Buttons are also available for downloading the indicated RNC and XSD schemas.



2 Configuring a Custom Relax NG Schema

We will configure the RuleML sublanguage called "disdatalogplus_mid". Its features include Disjunctive Rules ("dis"), Datalog expressivity ("datalog"), Conjunctive Rules, Existential Rules, and Equality ("plus"), and an assortment of Deliberation RuleML extras such as reification and annotation ("_mid").

- Expressivity Backbone:
 - This is a radio button input where we Select One Expressivity Level.
 - For this example, we select the Datalog level of expressivity: corresponding to function-free Horn Logic.
 - Also all the Expression Options (second row of facets) become disabled, because Datalog is function-free, so expression options are irrelevant.
 - Notice that the "b" (backbone) and "e" (expressions) components of the myng-code change (from b3f to b7 and from e7 to e0).
 - Notice that the anchor language changes from "naffologeq" to "nafnegdishornlogplus". This anchor language is not an exact approximation of the selected language.



-
- Selection of Propositional Options**
No Rulebases, Fuzzy Logic or Negations
- Propositional Options: **Propositional** (circled), Fuzzy Logic, Negations, No Rulebases
- | Propositional Options | Fuzzy Logic Options | Negations Options | No Rulebases Options | Propositional Options |
|---|--|--|--|--|
| <ul style="list-style-type: none"> • Atomic Variables • Propositional • Fuzzy Logic • Negations • No Rulebases | <ul style="list-style-type: none"> • Atomic Variables • Fuzzy Logic • Negations • No Rulebases | <ul style="list-style-type: none"> • Atomic Variables • Fuzzy Logic • Negations • No Rulebases | <ul style="list-style-type: none"> • Atomic Variables • Fuzzy Logic • Negations • No Rulebases | <ul style="list-style-type: none"> • Atomic Variables • Fuzzy Logic • Negations • No Rulebases |



Selection of Implication Options No Equivalences

[Introduction](#)
[Equivalences](#)
[No Equivalences](#)
[No Equivalences](#)
[No Equivalences](#)

| Formal Logic | Propositional Logic | First-Order Logic | Second-Order Logic | Third-Order Logic |
|---|---|---|---|---|
| <ul style="list-style-type: none"> Quantifiers Connectives Equality Functions Variables First-Order Logic | <ul style="list-style-type: none"> Quantifiers Connectives Equality Functions Variables First-Order Logic | <ul style="list-style-type: none"> Quantifiers Connectives Equality Functions Variables First-Order Logic | <ul style="list-style-type: none"> Quantifiers Connectives Equality Functions Variables First-Order Logic | <ul style="list-style-type: none"> Quantifiers Connectives Equality Functions Variables First-Order Logic |

9/7/14 8:18 PM

- Term Sequences
 - We keep Polyadic Term Sequences
- Term Options
 - Disable the frame options: Object Identifiers and Slots.
 - Notice that the "t" (terms) component of the myng-code changes from tf3f to tf30.
- Quantification Options
 - Disable all of them.
 - Notice that the "q" (quantification) component of the myng-code changes from q7 to q0.
- The anchor language now reads "disdatalogplus_mid".
 - This is one of the RuleML sublanguages that is newly available in Version 1.01.
 - Recent research^[1] has shown that with some additional constraints, querying becomes decidable in these languages.
 - The additional constraints are too complex to implement directly in Relax NG or XSD, but may be possible in Schematron.



3 Usage of Customized Schemas

- Instructions for online validation of RuleML instances against the Relax NG schemas are presented at Validating with Relax NG for RuleML 1.01
- Example: Validating disdatalogplus_min.ruleml (http://validator.nu/?doc=http%3A%2F%2Fdeliberation.ruleml.org%2F1.01%2Fexa%2FDatalogPlus%2Fdisdatalogplus_min.ruleml&schema=http%3A%2F%2Fdeliberation.ruleml.org%2F1.01%2Fmyng-b7-d7-a7-11-p1-i78-t210-q0-e0-sf.rnc&showsource=yes) .



4 References

1. ↑ Georg Gottlob, Giorgio Orsi, Andreas Pieris, and Mantas Šimkus. Datalog and its extensions for semantic web databases. In Thomas Eiter and Thomas Krennwallner, editors, Reasoning Web. Semantic Technologies for Advanced Query Answering, volume 7487 of Lecture Notes in Computer Science, pages 54–77. Springer Berlin Heidelberg, 2012.

Retrieved from "http://wiki.ruleml.org/index.php?title=MYNG_of_Deliberation_RuleML_1.01_Demo&oldid=11599"

Categories: Training | MYNG | RuleML 1.01

-
- This page was last modified on 7 September 2014, at 20:17.
 - This page has been accessed 276 times.