

```
C:\Users\Harold Romero>mysql -u root -p
Enter password: *****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 23
Server version: 8.0.21 MySQL Community Server - GPL

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
```

```
mysql> show databases;
+-----+
| Database |
+-----+
| bdclase  |
| comandosinsert |
| enlaces  |
| information_schema |
| mysql    |
| performance_schema |
| pruebacomandos |
| sakila   |
| sys      |
| world    |
+-----+
10 rows in set (0.65 sec)
```

```
mysql> use comandosinsert;
Database changed
mysql> show tables;
+-----+
| Tables_in_comandosinsert |
+-----+
| cajero                    |
| factura                   |
| productos                 |
+-----+
3 rows in set (0.18 sec)
```

```
mysql> select * from productos;
```

idProducto	NombreProducto	ValorUnitario
1	Hamburguesa	3500
2	Pizza	3000
3	Mazorcada	10000

```
3 rows in set (0.04 sec)
```

```
mysql> select ValorUnitario*4 as ValorTotal from productos  
-> ;
```

ValorTotal
14000
12000
40000

```
3 rows in set (0.00 sec)
```

```
mysql> select * from cajero;
```

idCajero	Nombre	StatusConection	Apellido
1	Andres	1	Saenz
2	Maria	1	Gil
3	Juan	1	Saenz
4	Angelica	1	Ferrari

```
4 rows in set (0.04 sec)
```

```
mysql> select concat(Nombre, " ", Apellido) as NombreCompleto from cajero;
```

NombreCompleto
Andres Saenz
Maria Gil
Juan Saenz
Angelica Ferrari

```
4 rows in set (0.05 sec)
```

```
mysql> select * from factura;
```

idFactura	idProd	ValorTotal	idcajero	fecha
1	2	6000	NULL	2020-01-08
2	1	3000	NULL	2020-02-15
3	3	10000	NULL	2020-03-20

```
3 rows in set (0.35 sec)
```

```
mysql> select date_format(fecha, '%d/%b/%y') as FechaFactura from factura;
```

FechaFactura
08/Jan/20
15/Feb/20
20/Mar/20

```
3 rows in set (0.00 sec)
```

```
mysql> select * from cajero;
```

idCajero	Nombre	StatusConection	Apellido
1	Andres	1	Saenz
2	Maria	1	Gil
3	Juan	1	Saenz
4	Angelica	1	Ferrari

```
4 rows in set (0.00 sec)
```

```
mysql> select left(Nombre,2) as InicialesNombre, left(Apellido,2) as InicialesApellido from cajero;
```

InicialesNombre	InicialesApellido
An	Sa
Ma	Gi
Ju	Sa
An	Fe

```
4 rows in set (0.00 sec)
```