

```
C:\Users\Harold Romero>mysql -u root -p
```

```
Enter password: *****
```

```
Welcome to the MySQL monitor.  Commands end with ; or \g.
```

```
Your MySQL connection id is 11
```

```
Server version: 8.0.21 MySQL Community Server - GPL
```

```
Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.
```

```
Oracle is a registered trademark of Oracle Corporation and/or its  
affiliates. Other names may be trademarks of their respective  
owners.
```

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
```

```
mysql> show databases;
```

```
+-----+  
| Database |  
+-----+  
| bdclase  |  
| enlaces  |  
| fruteria |  
| information_schema |  
| mysql    |  
| performance_schema |  
| sakila   |  
| sys      |  
| world    |  
+-----+
```

```
9 rows in set (0.00 sec)
```

```
mysql> create database pruebacomandos  
-> ;
```

```
Query OK, 1 row affected (0.08 sec)
```

```
mysql> show databases;
```

```
+-----+  
| Database |  
+-----+  
| bdclase  |  
| enlaces  |  
| fruteria |  
| information_schema |  
| mysql    |  
| performance_schema |  
| pruebacomandos |  
| sakila   |  
| sys      |  
| world    |  
+-----+
```

10 rows in set (0.00 sec)

mysql> use pruebacomandos;

Database changed

```
mysql> create table TablaDePrueba(
    -> idPrueba int primary key not null,
    -> NombrePrueba varchar(45) not null
    -> );
```

Query OK, 0 rows affected (0.86 sec)

mysql> describe TablaDePrueba;

Field	Type	Null	Key	Default	Extra
idPrueba	int	NO	PRI	NULL	
NombrePrueba	varchar(45)	NO		NULL	

2 rows in set (0.15 sec)

```
mysql> insert into TablaDePrueba(idPrueba, NombrePrueba) values(1, prueba1);
ERROR 1054 (42S22): Unknown column 'prueba1' in 'field list'
```

```
mysql> insert into TablaDePrueba values(1, 'prueba1');
```

Query OK, 1 row affected (0.06 sec)

```
mysql> insert into TablaDePrueba values(2, 'prueba2');
```

Query OK, 1 row affected (0.14 sec)

```
mysql> insert into TablaDePrueba values(3, 'prueba3');
```

Query OK, 1 row affected (0.07 sec)

```
mysql> insert into TablaDePrueba values(4, 'pruebafinal');
```

Query OK, 1 row affected (0.09 sec)

```
mysql> select * from TablaDePrueba;
```

idPrueba	NombrePrueba
1	prueba1
2	prueba2
3	prueba3
4	pruebafinal

4 rows in set (0.00 sec)

```
mysql> rename table TablaDePrueba to testing;
```

Query OK, 0 rows affected (0.56 sec)

```

mysql> show databases
-> ;
+-----+
| Database |
+-----+
| bdclase  |
| enlaces |
| fruteria |
| information_schema |
| mysql    |
| performance_schema |
| pruebacomandos |
| sakila   |
| sys      |
| world    |
+-----+
10 rows in set (0.05 sec)

mysql> show tables;
+-----+
| Tables_in_pruebacomandos |
+-----+
| testing                  |
+-----+
1 row in set (0.17 sec)

mysql> rename table testing to TablaDePrueba;
Query OK, 0 rows affected (0.35 sec)

mysql> show tables;
+-----+
| Tables_in_pruebacomandos |
+-----+
| tabladeprueba           |
+-----+
1 row in set (0.00 sec)

mysql> truncate table tabladeprueba;
Query OK, 0 rows affected (0.76 sec)

mysql> select * from tabladeprueba;
Empty set (0.00 sec)

mysql> drop table tabladeprueba;
Query OK, 0 rows affected (0.79 sec)

mysql> show tables;
Empty set (0.07 sec)

mysql>

```