

VI Editor

Introduction

The VI editor is a screen-based editor used by many Unix users. The VI editor has powerful features to aid programmers, but many beginning users avoid using VI because the different features overwhelm them. This tutorial is written to help beginning users get accustomed to using the VI editor, but also contains sections relevant to regular users of VI as well. Examples are provided, and the best way to learn is to try these examples.

Conventions

In this tutorial, the following convention will be used:

^X denotes a control character. For example, if you see: **^d** in the tutorial, that means you hold down the control key and then type the corresponding letter. For this example, you would hold down the **control** key and then type **d**.

Starting the VI Editor

The VI editor lets a user create new files or edit existing files. The command to start the VI editor is `vi`, followed by the filename. For example, to edit a file called *temporary*, you would type `vi temporary` and then return. You can start VI without a filename, but when you want to save your work, you will have to tell VI which filename to save it into later.

When you start VI for the first time, you will see a screen filled with tildes (A tilde looks like this: ~) on the left side of the screen. Any blank lines beyond the end of the file are shown this way. At the bottom of your screen, the filename should be shown, if you specified an existing file, and the size of the file will be shown as well, like this:

```
"filename" 21 lines, 385 characters
```

If the file you specified does not exist, then it will tell you that it is a new file, like this:

```
"newfile" [New file]
```

If you started VI without a filename, the bottom line of the screen will just be blank when VI starts. If the screen does not show you these expected results, your terminal type may be set wrong. Just type `:q` and return to get out of VI, and fix your terminal type. If you don't know how, ask a lab monitor.

Getting Out of VI

Now that you know how to get into VI, it would be a good idea to know how to get out of it. The VI editor has two modes and in order to get out of VI, you have to be in *command* mode. Hit the key labeled "**Escape**" or "**Esc**" (If your terminal does not have such a key, then try `^[`, or control-`[`.) to get into *command* mode. If you were already in the *command* mode when you hit "**Escape**", don't worry. It might beep, but you will still be in the *command* mode.

The command to quit out of VI is `:q`. Once in *command* mode, type colon, and 'q', followed by return. If your file has been modified in any way, the editor will warn you of this, and not let you quit. To ignore this message, the command to quit out of VI without saving is `:q!`. This lets you exit VI without saving any of the changes.

Of course, normally in an editor, you would want to save the changes you have made. The command to save the contents of the editor is `:w`. You can combine the above command with the quit command, or `:wq`. You can specify a different file name to save to by specifying the name after the `:w`. For example, if you wanted to save the file you were working as another filename called *filename2*, you would type: `w filename2` and return.

Another way to save your changes and exit out of VI is the `zz` command. When in *command* mode, type `zz` and it will do the equivalent of `:wq`. If any changes were made to the file, it will be saved. This is the easiest way to leave the editor, with only two keystrokes.

The Two Modes of VI

The first thing most users learn about the VI editor is that it has two modes: ***command*** and ***insert***. The *command* mode allows the entry of commands to manipulate text. These commands are usually one or two characters long, and can be entered with few keystrokes. The *insert* mode puts anything typed on the keyboard into the current file.

VI starts out in *command* mode. There are several commands that put the VI editor into *insert* mode. The most commonly used commands to get into insert mode are `a` and `i`. These two commands are described below. Once you are in *insert* mode, you get out of it by hitting the **escape** key. If your terminal does not have an **escape** key, `^[` should work (control-`[`). You can hit escape two times in a row and VI would definitely be in *command* mode. Hitting **escape** while you are already in *command* mode doesn't take the editor out of *command* mode. It may beep to tell you that you are already in that mode.

How to Type Commands in Command Mode

The command mode commands are normally in this format: (Optional arguments are given in the brackets)

[*count*] command [*where*]

Most commands are one character long, including those which use control characters. The commands described in this section are those which are used most commonly the VI editor. The *count* is entered as a number beginning with any character from 1 to 9. For example, the *x* command deletes a character under the cursor. If you type *23x* while in *command* mode, it will delete 23 characters.

Some commands use an optional *where* parameter, where you can specify how many lines or how much of the document the command affects, the *where* parameter can also be any command that moves the cursor.

Some Simple VI Commands

Here is a simple set of commands to get a beginning VI user started. There are many other convenient commands, which will be discussed in later sections.

a
enter *insert* mode, the characters typed in will be inserted after the current cursor position. If you specify a count, all the text that had been inserted will be repeated that many times.

h
move the cursor to the left one character position.

i
enter *insert* mode, the characters typed in will be inserted before the current cursor position. If you specify a count, all the text that had been inserted will be repeated that many times.

j
move the cursor down one line.

k
move the cursor up one line.

l
move the cursor to the right one character position.

r

replace one character under the cursor. Specify *count* to replace a number of characters

u

undo the last change to the file. Typing **u** again will re-do the change.

x

delete character under the cursor. *Count* specifies how many characters to delete. The characters will be deleted after the cursor.

Text Buffers in VI

The VI editor has 36 buffers for storing pieces of text, and also a general purpose buffer. Any time a block of text is deleted or yanked from the file, it gets placed into the general purpose buffer. Most users of VI rarely use the other buffers, and can get along without the other buffers. The block of text is also stored in another buffer as well, if it is specified. The buffer is specified using the **"** command. After typing **"**, a letter or digit specifying the buffer must be entered. For example, the command: **"mdd** uses the buffer **m**, and the last two characters stand for delete current line.

Similarly, text can be pasted in with the **e p** or **P** command. **"mp** pastes the contents of buffer **m** after the current cursor position. For any of the commands used in the next two sections, these buffers can be specified for temporary storage of words or paragraphs.

Word and Character Searching

The VI editor has two kinds of searches: string and character. For a string search, the **/** and **?** commands are used. When you start these commands, the command just typed will be shown on the bottom line, where you type the particular string to look for. These two commands differ only in the direction where the search takes place.

The **/** command searches forwards (downwards) in the file, while the **?** command searches backwards (upwards) in the file. The **n** and **N** commands repeat the previous search command in the same or opposite direction, respectively. Some characters have special meanings to VI, so they must be preceded by a backslash (****) to be included as part of the search expression. Special characters:

^

Beginning of the line. (At the beginning of a search expression.)

.

Matches a single character.

*

Matches zero or more of the previous character.

\$

End of the line (At the end of the search expression.)

[

Starts a set of matching, or non-matching expressions... For example: /f[iae]t matches either of these: fit fat fet In this form, it matches anything except these: /a[^bcd] will not match any of these, but anything with an a and another letter: ab ac ad

<

Put in an expression escaped with the backslash to find the ending or beginning of a word. For example: /\<the\> should find only word the, but not words like these: there and other.

>

See the '<' character description above.

The character search searches within one line to find a character entered after the command. The `f` and `F` commands search for a character on the current line only. `f` searches forwards and `F` searches backwards and the cursor moves to the position of the found character.

The `t` and `T` commands search for a character on the current line only, but for `t`, the cursor moves to the position before the character, and `T` searches the line backwards to the position after the character.

These two sets of commands can be repeated using the `;` or `,` command, where `;` repeats the last character search command in the same direction, while `,` repeats the command in the reverse direction.

Summary of VI commands

This list is a summary of VI commands, categorized by function. For easy reference, you can save this file as text and delete any commands you don't think you would use and print out the resulting shorter file.

Cutting and Pasting/Deleting text

"

Specify a buffer to be used any of the commands using buffers. Follow the " with a letter or a number, which corresponds to a buffer.

D

Delete to the end of the line from the current cursor position.

P

Paste the specified buffer before the current cursor position or line. If no buffer is specified (with the " command.) then 'P' uses the general buffer.

X

Delete the character before the cursor.

Y

Yank the current line into the specified buffer. If no buffer is specified, then the general buffer is used.

d

Delete until *where*. "dd" deletes the current line. A count deletes that many lines.

Whatever is deleted is placed into the buffer specified with the " command. If no buffer is specified, then the general buffer is used.

p

Paste the specified buffer after the current cursor position or line. If no buffer is specified (with the " command.) then 'p' uses the general buffer.

x

Delete character under the cursor. A count tells how many characters to delete. The characters will be deleted after the cursor.

y

Yank until , putting the result into a buffer. "yy" yanks the current line. a count yanks that many lines. The buffer can be specified with the " command. If no buffer is specified, then the general buffer is used.

Inserting New Text

A

Append at the end of the current line.

I

Insert from the beginning of a line.

O

(letter oh) Enter *insert* mode in a new line above the current cursor position.

a

Enter *insert* mode, the characters typed in will be inserted after the current cursor position. A count inserts all the text that had been inserted that many times.

i

Enter *insert* mode, the characters typed in will be inserted before the current cursor position. A count inserts all the text that had been inserted that many times.

o

Enter *insert* mode in a new line below the current cursor position.

Moving the Cursor Within the File

^B

Scroll backwards one page. A count scrolls that many pages.

^D

Scroll forwards half a window. A count scrolls that many lines.

^F

Scroll forwards one page. A count scrolls that many pages.

^H

Move the cursor one space to the left. A count moves that many spaces.

^J

Move the cursor down one line in the same column. A count moves that many lines down.

^M

Move to the first character on the next line.

^N

Move the cursor down one line in the same column. A count moves that many lines down.

^P

Move the cursor up one line in the same column. A count moves that many lines up.

^U

Scroll backwards half a window. A count scrolls that many lines.

\$

Move the cursor to the end of the current line. A count moves to the end of the following lines.

%

Move the cursor to the matching parenthesis or brace.

^

Move the cursor to the first non-whitespace character.

(

Move the cursor to the beginning of a sentence.

)

Move the cursor to the beginning of the next sentence.

{

Move the cursor to the preceding paragraph.

}

Move the cursor to the next paragraph.

|

Move the cursor to the column specified by the count.

+

Move the cursor to the first non-whitespace character in the next line.

-

Move the cursor to the first non-whitespace character in the previous line.

⏪

Move the cursor to the first non-whitespace character in the current line.

0

(Zero) Move the cursor to the first column of the current line.

B

Move the cursor back one word, skipping over punctuation.

E

Move forward to the end of a word, skipping over punctuation.

G

Go to the line number specified as the count. If no count is given, then go to the end of the file.

H

Move the cursor to the first non-whitespace character on the top of the screen.

L

Move the cursor to the first non-whitespace character on the bottom of the screen.

M

Move the cursor to the first non-whitespace character on the middle of the screen.

W

Move forward to the beginning of a word, skipping over punctuation.

b

Move the cursor back one word. If the cursor is in the middle of a word, move the cursor to the first character of that word.

e

Move the cursor forward one word. If the cursor is in the middle of a word, move the cursor to the last character of that word.

h

Move the cursor to the left one character position.

j

Move the cursor down one line.

k

Move the cursor up one line.

l

Move the cursor to the right one character position.

w

Move the cursor forward one word. If the cursor is in the middle of a word, move the cursor to the first character of the next word.

Moving the Cursor Around the Screen

^E

Scroll forwards one line. A count scrolls that many lines.

^Y

Scroll backwards one line. A count scrolls that many lines.

z

Redraw the screen with the following options. "z<return>" puts the current line on the top of the screen; "z." puts the current line on the center of the screen; and "z-" puts the current line on the bottom of the screen. If you specify a count before the 'z' command, it changes the current line to the line specified. For example, "16z." puts line 16 on the center of the screen.

Replacing Text

C

Change to the end of the line from the current cursor position.

R

Replace characters on the screen with a set of characters entered, ending with the Escape key.

S

Change an entire line.

c

Change until . "cc" changes the current line. A count changes that many lines.

r

Replace one character under the cursor. Specify a count to replace a number of characters.

s

Substitute one character under the cursor, and go into insert mode. Specify a count to substitute a number of characters. A dollar sign (\$) will be put at the last character to be substituted.

Searching for Text or Characters

,
Repeat the last f, F, t or T command in the reverse direction.

/
Search the file downwards for the string specified after the /.

;
Repeat the last f, F, t or T command.

?
Search the file upwards for the string specified after the ?.

F
Search the current line backwards for the character specified after the 'F' command. If found, move the cursor to the position.

N
Repeat the last search given by '/' or '?', except in the reverse direction.

T
Search the current line backwards for the character specified after the 'T' command, and move to the column after the if it's found.

f
Search the current line for the character specified after the 'f' command. If found, move the cursor to the position.

n
Repeat last search given by '/' or '?'.

t
Search the current line for the character specified after the 't' command, and move to the column before the character if it's found.

Manipulating Character/Line Formatting

~
Switch the case of the character under the cursor.

<
Shift the lines up to *where* to the left by one shiftwidth. "<<" shifts the current line to the left, and can be specified with a count.

>

Shift the lines up to *where* to the right by one shiftwidth. ">>" shifts the current line to the right, and can be specified with a count.

J

Join the current line with the next one. A count joins that many lines.

Saving and Quitting

^\

Quit out of "VI" mode and go into "EX" mode. The EX editor is the line editor VI is build upon. The EX command to get back into VI is ":vi".

Q

Quit out of "VI" mode and go into "EX" mode. The ex editor is a line-by-line editor. The EX command to get back into VI is ":vi".

ZZ

Exit the editor, saving if any changes were made.

Miscellany

^G

Show the current filename and the status.

^L

Clear and redraw the screen.

^R

Redraw the screen removing false lines.

^[

Escape key. Cancels partially formed command.

^^

Go back to the last file edited.

!

Execute a shell. If a is specified, the program which is executed using ! uses the specified line(s) as standard input, and will replace those lines with the standard output of the program executed. "!!" executes a program using the current line as input. For example, "!4jsort" will take five lines from the current cursor position and execute sort. After typing the command, there will be a single exclamation point where you can type the command in.

&

Repeat the previous ":s" command.

.

Repeat the last command that modified the file.

:

Begin typing an EX editor command. The command is executed once the user types return. (See section below.)

@

Type the command stored in the specified buffer.

U

Restore the current line to the state it was in before the cursor entered the line.

m

Mark the current position with the character specified after the 'm' command.

u

Undo the last change to the file. Typing 'u' again will re-do the change.

EX Commands

The VI editor is built upon another editor, called EX. The EX editor only edits by line. From the VI editor you use the : command to start entering an EX command. This list given here is not complete, but the commands given are the more commonly used. If more than one line is to be modified by certain commands (such as ":s" and ":w") the range must be specified before the command. For example, to substitute lines 3 through 15, the command is ":3,15s/from/this/g".

:ab string strings

Abbreviation. If a word is typed in VI corresponding to string1, the editor automatically inserts the corresponding words. For example, the abbreviation ":ab usa United States of America" would insert the words, "United States of America" whenever the word "usa" is typed in.

:map keys new_seq

Mapping. This lets you map a key or a sequence of keys to another key or a sequence of keys.

`:q`

Quit VI. If there have been changes made, the editor will issue a warning message.

`:q!`

Quit VI without saving changes.

`:s/pattern/to_pattern/options`

Substitute. This substitutes the specified pattern with the string in the `to_pattern`. Without options, it only substitutes the first occurrence of the pattern. If a 'g' is specified, then all occurrences are substituted. For example, the command `:1,$s/Dwayne/Dwight/g` substitutes all occurrences of "Dwayne" to "Dwight".

`:set [all]`

Sets some customizing options to VI and EX. The `:set all` command gives all the possible options. (See the section on customizing VI for some options.)

`:una string`

Removes the abbreviation previously defined by `":ab"`.

`:unm keys`

Removes the remove mapping defined by `":map"`.

`:vi filename`

Starts editing a new file. If changes have not been saved, the editor will give you a warning.

`:w`

Write out the current file.

`:w filename`

Write the buffer to the filename specified.

`:w >> filename`

Append the contents of the buffer to the filename.

`:wq`

Write the buffer and quit.