
Table of Contents

PROBLEM 5	1
Local gravitational acceleration	2
Accelerometers	2
Rate gyros	2
Magnetometers	2
Remove bias	2
Initial Pitch, Roll, and Yaw	3
Final Pitch, Roll, Yaw	4
EKF	5
Function definitions	7

PROBLEM 5

```
clear variables; close all; clc

data_table_acc = readtable('Accelerometer_Att_EKF.csv');

data_table_gyro = readtable('Gyroscope_Att_EKF.csv');

data_table_mag = readtable('Magnetometer_Att_EKF.csv');
%=====

% CORRECT VALUES FOR THESE BIASES AND VARIANCES AS COMPUTED IN
% EXPERIMENT 1
bias_acc = [1.948244;
            1.926003;
            -3.76083]; % biases in accelerometer x,y,z

bias_mag = [-12.11214937;
            -19.67616054;
            22.73696197]; % biases in magnetometer x,y,z

bias_gyro = [0.00001194560806;
            -0.00000912316961;
            -0.00000169621783]; % biases in gyro x,y,z
var_acc = [4.94; 5.23; 13.5]*10^-5;
var_gyro = [2.1; 2.6; 4.9]*10^-6;
var_mag = [0.467657; 0.744017; 0.463155];

var_mag_heading = 1.3227*10^-5;

Warning: Column headers from the file were
modified to make them valid MATLAB
identifiers before creating variable names
for the table. The original column headers
are saved in the VariableDescriptions
property.
```

Set 'PreserveVariableNames' to true to use the original column headers as table variable names.

Warning: Column headers from the file were modified to make them valid MATLAB identifiers before creating variable names for the table. The original column headers are saved in the VariableDescriptions property.

Set 'PreserveVariableNames' to true to use the original column headers as table variable names.

Warning: Column headers from the file were modified to make them valid MATLAB identifiers before creating variable names for the table. The original column headers are saved in the VariableDescriptions property.

Set 'PreserveVariableNames' to true to use the original column headers as table variable names.

Local gravitational acceleration

```
g = 9.80333; % m/s/s
```

Accelerometers

```
time_stamps_acc = data_table_acc(:, 1);  
acc_x = data_table_acc(:, 2);  
acc_y = data_table_acc(:, 3);  
acc_z = data_table_acc(:, 4);
```

Rate gyros

```
time_stamps_gyro = data_table_gyro(:, 1);  
gyro_x = data_table_gyro(:, 2);  
gyro_y = data_table_gyro(:, 3);  
gyro_z = data_table_gyro(:, 4);
```

Magnetometers

```
time_stamps_mag = data_table_mag(:, 1);  
mag_xb = data_table_mag(:, 2);  
mag_yb = data_table_mag(:, 3);  
mag_zb = data_table_mag(:, 4);
```

Remove bias

```
acc_x_wo_bias = acc_x - bias_acc(1);
```

```

acc_y_wo_bias = acc_y - bias_acc(2);
acc_z_wo_bias = acc_z - bias_acc(3);

gyro_x_wo_bias= gyro_x - bias_gyro(1);
gyro_y_wo_bias= gyro_y - bias_gyro(2);
gyro_z_wo_bias= gyro_z - bias_gyro(3);

mag_xb_wo_bias = mag_xb - bias_mag(1);
mag_yb_wo_bias = mag_yb - bias_mag(2);
mag_zb_wo_bias = mag_zb - bias_mag(3);

```

Initial Pitch, Roll, and Yaw

```

initial_few_pts = 5;
roll_data = atan( acc_y_wo_bias(1:initial_few_pts) ./
    acc_z_wo_bias(1:initial_few_pts) );
pitch_data = asin( acc_x_wo_bias(1:initial_few_pts) / g );

initial_roll = mean( roll_data )
disp('rad')
initial_pitch = mean( pitch_data )
disp('rad')

tmp1 = [...
    cos(initial_pitch) sin(initial_pitch)*sin(initial_roll)
    sin(initial_pitch)*cos(initial_roll); ...
    0 cos(initial_roll) -sin(initial_roll); ...
    -sin(initial_pitch) cos(initial_pitch)*sin(initial_roll)
    cos(initial_pitch)*cos(initial_roll)] * ...
    [mag_xb_wo_bias(1:initial_few_pts)'; ...
    mag_yb_wo_bias(1:initial_few_pts)';
    mag_zb_wo_bias(1:initial_few_pts)'];

mag_x_wo_bias = tmp1(1,:)';
mag_y_wo_bias = tmp1(2,:)';

magnetic_heading_data = -atan2( mag_y_wo_bias, mag_x_wo_bias );
declination = -14.07*pi/180;
% Declination for Worcester, MA found using World Magnetic Model
% https://www.ngdc.noaa.gov/geomag/calculators/
magcalc.shtml#declination

true_heading_data = declination + magnetic_heading_data;
initial_yaw = mean(true_heading_data)
disp('rad')

initial_roll =

    -0.0704

rad

```

```

initial_pitch =

    -0.2026

rad

initial_yaw =

    -1.4858

rad

```

Final Pitch, Roll, Yaw

```

Final_few_pts = (670:679);
roll_data_f = atan( acc_y_wo_bias(Final_few_pts) ./
    acc_z_wo_bias(Final_few_pts) );
pitch_data_f = asin( acc_x_wo_bias(Final_few_pts) / g );

final_roll = mean( roll_data_f )
disp('rad')
final_pitch = mean( pitch_data_f )
disp('rad')

tmp2 = [...
    cos(final_pitch) sin(final_pitch)*sin(final_roll)
    sin(final_pitch)*cos(final_roll); ...
    0 cos(final_roll) -sin(final_roll); ...
    -sin(final_pitch) cos(final_pitch)*sin(final_roll)
    cos(final_pitch)*cos(final_roll)] * ...
    [mag_xb_wo_bias(Final_few_pts)'; ...
    mag_yb_wo_bias(Final_few_pts)'; mag_zb_wo_bias(Final_few_pts)'];

mag_x_wo_bias_f = tmp2(1,:);
mag_y_wo_bias_f = tmp2(2,:);

magnetic_heading_data_f = -atan2( mag_y_wo_bias_f, mag_x_wo_bias_f );
declination = -14.07*pi/180;
% Declination for Worcester, MA found using World Magnetic Model
% https://www.ngdc.noaa.gov/geomag/calculators/
magcalc.shtml#declination

true_heading_data_f = declination + magnetic_heading_data_f;
final_yaw = mean(true_heading_data_f)
disp('rad')

final_roll =

    -0.1627

rad

```

```
final_pitch =  
  
    -0.2027  
  
rad  
  
final_yaw =  
  
    -2.0483  
  
rad
```

EKF

```
Q = diag(var_gyro);  
R = diag([var_acc; var_mag_heading]);  
  
dt = 0.01;  
m1 = 1;  
t = max([time_stamps_acc(1), time_stamps_mag(1),  
        time_stamps_gyro(1)]);  
tfinal = min([time_stamps_acc(end), time_stamps_mag(end),  
             time_stamps_gyro(end)]);  
n_time_pts = round( tfinal /dt );  
  
V = 0;  
  
xhat = [initial_yaw; initial_pitch; initial_roll];  
P = diag([var_mag_heading var_acc(1) var_acc(2)]);  
  
time_stamps_store = zeros(1, n_time_pts);  
xhat_store = zeros(3, n_time_pts);  
P_store = zeros(9, n_time_pts);  
P_trace_store = zeros(1, n_time_pts);  
  
xhat_store(:, 1) = xhat;  
P_trace_store(:, 1) = trace(P);  
P_store(:, 1) = reshape(P, 9, 1);  
  
while (t < tfinal)  
  
    col_gyro = find(time_stamps_gyro <= t, 1, 'last');  
    col_acc = find(time_stamps_acc <= t, 1, 'last');  
    col_mag = find(time_stamps_mag <= t, 1, 'last');  
    t = t + dt;  
  
    u = [gyro_x_wo_bias(col_gyro); gyro_y_wo_bias(col_gyro);  
        gyro_z_wo_bias(col_gyro)];  
  
    psi_hat = xhat(1);  
    theta_hat = xhat(2);  
    phi_hat = xhat(3);
```

```

A = [[0;0;0] ...
    [ 0 sin(phi_hat)*tan(theta_hat)*sec(theta_hat)
sin(phi_hat)*tan(theta_hat)*sec(theta_hat); ...
    0 0 0;...
    0 sin(phi_hat)*sec(theta_hat)^2
cos(phi_hat)*sec(theta_hat)^2 ]*u ...
    [ 0 cos(phi_hat)*sec(theta_hat) -sin(phi_hat)*sec(theta_hat); ...
    0 -sin(phi_hat) -cos(phi_hat); ...
    0 cos(phi_hat)*tan(theta_hat) sin(phi_hat)*tan(theta_hat)]*u];
B2 = [...
    0 sin(phi_hat)*sec(theta_hat) cos(phi_hat)*sec(theta_hat); ...
    0 cos(phi_hat) -sin(phi_hat); ...
    1 sin(phi_hat)*tan(theta_hat) cos(phi_hat)*tan(theta_hat)];
C = [[0;0;0;1] ...
    [V*[0 cos(theta_hat) 0; -cos(theta_hat) 0 -sin(theta_hat); 0
sin(theta_hat) 0]*u + ...
    g*[cos(theta_hat); sin(theta_hat)*sin(phi_hat);
sin(theta_hat)*cos(phi_hat)]; 0] ...
    g*[0; -cos(theta_hat)*cos(phi_hat); cos(theta_hat)*sin(phi_hat);
0]]];

F = eye(3) + A*dt;
G2 = B2*dt;

tmp1 = [...
    cos(theta_hat) sin(theta_hat)*sin(phi_hat)
sin(theta_hat)*cos(phi_hat); ...
    0 cos(phi_hat) -sin(phi_hat); ...
    -sin(theta_hat) cos(theta_hat)*sin(phi_hat)
cos(theta_hat)*cos(phi_hat)] * ...
    [mag_xb_wo_bias(col_mag); mag_yb_wo_bias(col_mag);
mag_zb_wo_bias(col_mag)];

mag_x_wo_bias = tmp1(1);
mag_y_wo_bias = tmp1(2);

magnetic_heading_data = -atan2( mag_y_wo_bias, mag_x_wo_bias );
magnetometer_yaw = declination + magnetic_heading_data;

x_minus = xhat + attitude_kinematics_asg3(xhat, u)*dt;
P_minus = F*P*F' + G2*Q*G2';

L = (P_minus * C') / (C * P_minus * C' + R );
z = [acc_x_wo_bias(col_acc); ...
    acc_y_wo_bias(col_acc); acc_z_wo_bias(col_acc); ...
    magnetometer_yaw];
xhat = x_minus + L*(z - attitude_measurement_asg3(xhat, u, V));
P = (eye(3) - L*C)*P_minus;

time_stamps_store(m1 + 1) = t;
xhat_store(:, m1+1) = xhat;
P_store(:, m1+1) = reshape(P, 9, 1);
P_trace_store(:, m1+1) = trace(P);

```

```

    m1 = m1 + 1;
end

figure;
subplot(311)
plot(time_stamps_store(1:m1), xhat_store(1, 1:m1)*180/pi, 'LineWidth',
    2);
ylabel('$\psi$ (deg)', 'Interpreter', 'latex', 'FontSize', 14)
xlabel('$t$ (s)', 'Interpreter', 'latex', 'FontSize', 14)
title('Problem 5 Ground Truth Euler
    Angles', 'Interpreter', 'latex', 'FontSize', 18)

subplot(312)
plot(time_stamps_store(1:m1), xhat_store(2, 1:m1)*180/pi, 'LineWidth',
    2);
ylabel('$\theta$ (deg)', 'Interpreter', 'latex', 'FontSize', 14)
xlabel('$t$ (s)', 'Interpreter', 'latex', 'FontSize', 14)

subplot(313)
plot(time_stamps_store(1:m1), xhat_store(3, 1:m1)*180/pi, 'LineWidth',
    2);
ylabel('$\phi$ (deg)', 'Interpreter', 'latex', 'FontSize', 14)
xlabel('$t$ (s)', 'Interpreter', 'latex', 'FontSize', 14)

figure;
plot(time_stamps_store(1:m1), P_trace_store(1:m1), 'LineWidth', 2);
title('Problem 5 $\mathrm{tr}$
(P)$', 'Interpreter', 'latex', 'FontSize', 18)

disp('The resultant angles correctly discribe the devices movement and
    match ')
disp('those found in step 3.')

```

Function definitions

```

function x_dot = attitude_kinematics_asg3(x_, u_)
    theta_ = x_(2);
    phi_ = x_(3);

    x_dot = [-sin(theta_) 0 1; ...
        sin(phi_)*cos(theta_) cos(phi_) 0; ...
        cos(phi_)*cos(theta_) -sin(phi_) 0] \ u_;
end

function z_ = attitude_measurement_asg3(x_, u_, V)
    psi_ = x_(1);
    theta_ = x_(2);
    phi_ = x_(3);
    z_ = [ V*[...
        0 sin(theta_) 0; -sin(theta_) 0 cos(theta_); 0 -cos(theta_) 0]*u_
        + ...


```


```

    9.81*[sin(theta_); -cos(theta_)*sin(phi_); -cos(theta_)*cos(phi_)];
    psi_];
end

```

The resultant angles correctly describe the devices movement and match those found in step 3.





Published with MATLAB® R2020a