PROBLEM 2

```
clear variables; close all; clc

data_table_mag = readtable('Magnetometer_Prob_2.csv');

Warning: Column headers from the file were
modified to make them valid MATLAB
identifiers before creating variable names
for the table. The original column headers
are saved in the VariableDescriptions
property.
Set 'PreserveVariableNames' to true to use
the original column headers as table
variable names.
```

Magnetometers

```
bias mag = [-12.11214937;
           -19.67616054;
            22.73696197];
var mag = [0.467656955 0]
                                  0;
           0
                     0.744016854 0;
                          0.463154807];
           0
mag_x = data_table_mag{:, 2};
mag y = data table mag\{:, 3\};
mag_z = data_table_mag{:, 4};
mag_x_wo_bias = mag_x - bias_mag(1);
mag_y_wo_bias = mag_y - bias_mag(2);
mag_z_wo_bias = mag_z - bias_mag(3);
magnetic_heading_data = -atan2( mag_y_wo_bias, mag_x_wo_bias );
declination
             = -14.07*pi/180;
% Declination for Worcester, MA found using World Magnetic Model
% https://www.ngdc.noaa.gov/geomag/calculators/
magcalc.shtml#declination
true_heading_data = declination + magnetic_heading_data;
true_heading_mu = mean(true_heading_data)
disp('rad')
true heading var = var(true heading data)
disp('rad')
fprintf('The heading is %f deg +/- %f deg\n', ...
 true_heading_mu*180/pi, 3*sqrt(true_heading_var)*180/pi);
Validity = ['This heading is accurate given the orientation of the
 device '...
```

```
'and that the positive x axis faced west'];
disp(Validity)

true_heading_mu =
    -1.4815

rad

true_heading_var =
    1.3227e-05

rad
The heading is -84.881480 deg +/- 0.625142 deg
This heading is accurate given the orientation of the device and that the positive x axis faced west
```

Published with MATLAB® R2020a