

Article

Talk

Read

[Edit](#)

[View history](#)

Search




Rastrigin function

From Wikipedia, the free encyclopedia


In [mathematical optimization](#), the **Rastrigin function** is a non-[convex function](#) used as a performance test problem for optimization algorithms. It is a typical example of non-linear multimodal function. It was first proposed by Rastrigin ^[1] as a 2-dimensional function and has been generalized by Mühlenbein et al. ^[2] This function is a fairly difficult problem due to its large search space and its large number of local minima.

It is defined by:

Rastrigin function of two variables



In 3D



$$f(\mathbf{x}) = An + \sum_{i=1}^n [x_i^2 - A \cos(2\pi x_i)]$$

where $A = 10$ and $x_i \in [-5.12, 5.12]$. It has a global minimum at $\mathbf{x} = \mathbf{0}$ where $f(\mathbf{x}) = 0$.

See also [\[edit\]](#)

- [Test functions for optimization](#)

Notes [\[edit\]](#)

1. [^] A. Törn and A. Zilinskas. "Global Optimization". Lecture Notes in Computer Science, N° 350, Springer-Verlag, Berlin, 1989.

2. [^] H. Mühlenbein, D. Schomisch and J. Born. "The Parallel Genetic Algorithm as Function Optimizer ". Parallel Computing, 17, pages 619–632, 1991.



This *mathematical analysis*–related article is a *stub*. You can help Wikipedia by *expanding it*.

Categories: [Mathematical optimization](#) | [Mathematical analysis stubs](#)

This page was last modified on 21 March 2013 at 07:06.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#).

Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Mobile view](#)

