Base station physics: summary

Params: base/spec/params.py v1.0.1

Spring (each, A228, SF 1.2 on Shigley static limits)

Rate used / by formula	0.125 / 0.131 N/mm
Initial tension used	7.0 N
Body coils, mass	96, 54 g
Safe force (governed by)	43.6 N (hook torsion)
Safe extension (wire) / spec cap	293 / 280 mm
Surge (fixed-fixed)	25 Hz

Launch (chain spring model)

Stroke, ratio, pitch	245 mm, 1.0:1, 35 deg
Spring extension full / rest	280 / 35 mm
Stored energy (2 springs)	13.1 J
Carriage force at full draw	84 N
Muzzle speed	7.78 m/s
Peak acceleration, stroke time	22 g, 54 ms
Efficiency (dart KE / stored)	65 %
Carriage KE at stop, pad peak	1.82 J, 370 N (15 mm pad)
Spring KE at stop, coil clash	0.96 J, 8.2 m/s

Flight (bead-chain tether + reel model, level ground)

Range at 0.5 / 0.75 / 1.0 N brake	5.24 / 4.75 / 4.32 m (pitch 36)
Same shot, no tether	6.38 m
Flight time, apex (0.75 N)	0.91 s, 1.36 m
Impact speed, angle (0.75 N)	6.4 m/s, 54 deg down
Ballistics table	6 to 47 deg, best 36.0 deg: 4.75 m

Storage reel payout (LIGHT 0.5 N at full reel)

Reel empty mass, inertia full	43 g, 27.6 kg mm2
Line radius full / core	30.7 / 25.0 mm (brake +23 % at core)
Line pull in the stroke (spin-up)	4.73 N
Reel rpm max	2418 rpm
Overrun after landing	0.61 m in 0.25 s

Capstan and tow

Wraps for tow limit (mu 0.15)	3.0 raw, 5 design
Take-up needed (design wraps)	0.07 N
Tow at limit: torque, speed, current	3.01 N m, 0.147 m/s, 4.81 A
Line pull at limiter (5 N m) (12.6 V)	88 N (break 667 N)
Line pull, motor stall (no limiter, 12.6 V)	257 N
Tow sensing: line N per wiper amp above free	17.0 N/A (line = 17.0 x (I - I_free) - 6.2 N)

Drivetrain (wiper at 11.1 V with sag)

aim: peak torque, current, time	0.32 N m, 1.9 A, 7 s
cock: peak torque, current, time	3.07 N m, 4.9 A, 3 s
reel: peak torque, current, time	0.49 N m, 2.0 A, 107 s
tow: peak torque, current, time	3.01 N m, 4.8 A, 34 s
Wiper at limiter (5 N m), 12.6 V (with sag)	5.0 N m, 7.0 A
Wiper motor stall (no limiter), 12.6 V (with sag)	14.1 N m, 17.0 A

Harry must measure (then edit the parameter block and rerun: python summary.py)

- Spring hang test: hang 1, 2, 3 kg from one spring, measure the length each time. Slope = rate, intercept = initial tension. Every range number scales with the stored energy.
- Wiper: free speed (turns in 30 s at 12.0 V), free current, stall torque (arm + luggage scale, 1 s) and stall current. Edit common.Wiper or spec WIPER.
- Dart mass on a kitchen scale with ballast and tether knot (spec 0.279 kg).
- Slip clutch: pull the line off the full reel with a luggage scale; set 0.4 to 0.5 N (FINDINGS F5).
- Rail friction: tilt the rail with the dart on it until it slides (mu = tan angle).