

HTML Tag List

| Tags | Description |
|---------------------------|---|
| <a> | ANCHOR tag creates link to other internet location, or file. |
| <abbr> | ABBREVIATION tags indicate interpretation of the meaning to the browsers and search engines for such as kind of abbreviations as "Inc.", "etc.". |
| <acronym> | ACRONYM tags defines an acronym, like; <acronym title="World Wide Web"> WWW </acronym>. |
| <address> | ADDRESS tags are used to identify the author's contact information for a section or a document. |
| <applet> | APPLET element tags are used to embed and invoke a Java application within an HTML page. |
| <area> | AREA tag defines a section of an image. |
| | BOLD tag is specifying bold section within the text document. |
| <base> | BASE tag defines information regarding to the links on the page. |
| <basefont> | BASEFONT tags defines changes of all text appearance on the web page. |
| <bdo> | BDO tag is specifying the direction of text display by overwriting the default value from Left to Right. <bdo dir="rtl"> Right to Left </bdo> |
| <bgsound> | BGSOUND tag is defining a background sound for a webpage. <pre><html> <head> <bgsound src="JingleBells.wav" loop="3"> </head> <body> </body> </html></pre> |
| <big> | BIG tag makes the <big> text larger </big> then the rest of the text. |
| <blockquote> | BLOCKQUOTE tags <blockquote> separate a section </blockquote> of text from the surrounding text. |
| <blink> | BLINK tags defines text to <blink>blink</blink> repeatedly. Internet Explorer doesn't support this tag yet. |
| <body> | <pre><html> <head> </head> <body></pre> Body tags identify the content of a web page. <pre></body></pre> |

| | |
|-------------------------|--|
| | </html> |
| | Line Break tag is specifying a new line |
| <button> | BUTTON tag is used to create a <button type="button"> Push Button </button> Push Button |
| <caption> | <pre> <table> <caption>CAPTION tag adds a caption to a table.</caption> <tr> <td> </td> </tr> </table> </pre> |
| <center> | <center> CENTER tags center text, images, etc. </center> |
| <cite> | <cite> CITE tags defines a citation and displaying in italics. </cite> |
| <code> | CODE tags are used for example, to indicate a code of the current <code> htmltags.html </code> page. |
| <col> | COL tags are used to define column properties for table columns. <pre> <table> <colgroup span="2"> <col width="60" align="left"></col> <col width="80" align="center"></col> </colgroup> <tr> <td>1st Column</td> <td>2nd Column</td> </tr> </table> </pre> |
| <colgroup> | COLGROUP tags are used to define groups of table columns. <pre> <table> <colgroup span="2"> <col width="60" align="left"></col> <col width="80" align="center"></col> </colgroup> <tr> <td>1st Column</td> <td>2nd Column</td> </tr> </table> </pre> |
| <dd> | DD tag defines a definition description. <pre> <dl> <dt>NASA</dt> <dd>National Aeronautics and Space Administration</dd> <dt>MBA</dt> <dd>Master of Business Administration</dd> </dl> </pre> |

| | |
|-------------------------|--|
| <dfn> | DFN tags emphasize definition, for example; <dfn> PC </dfn>: Personal Computer. |
| | DEL tag indicates |
| <dir> | DIR tags define directory lists. <dir> First Second Third </dir> |
| <dl> | DL tag defines a definition list. <dl> <dt>CSU</dt> <dd>California State University</dd> <dt>UN</dt> <dd>United Nations</dd> </dl> |
| <div> | DIV tag is a logical section of a web document. <div> <h1>Home Pets</h1> <p>Cats</p> <p>Dogs</p> </div> |
| <dt> | DT tags defines a definition term. <dl> <dt>HTML</dt> <dd>HyperText Markup Language</dd> <dt>CSS</dt> <dd>Cascading Style Sheets</dd> </dl> |
| <embed> | EMBED tag gives a command to a browser to include a multimedia elements, such as video, sound files within a web document. <embed src="videofile.mov" width="100" height="100"> <embed src="musicfile.mid" width="50" height="50"> |
| | EM tags emphasize text. |
| <fieldset> | FIELDSET tag creates a form for all elements in it. <fieldset>Find a rounded-corner box around this text.</fieldset> |
| | FONT tags attribute text font, color, and size. |
| <form> | Form tags define a form. |



| | |
|--------------------------------|---|
| | <pre><form action="contact.html" method="post"> Your Email: <input type="text" name="visitor-email" maxlength="80" value="" /> Your Name: <input type="text" name="visitor-name" maxlength="80" value="" /> <input type="submit" value="Send" /> </form></pre> <p>Top of Form</p> <p>eMail: <input type="text"/></p> <p>Name: <input type="text"/></p> <p><input type="submit" value="Send"/></p> <p>Bottom of Form</p> |
| <frame> | <p>Frame tags define each frame within a frameset.</p> <pre><html> <head> <title>Frame Tags in Action</title> </head> <noframes> <body> <h1>Sorry, your browser doesn't support this feature!</h1> </body> </noframes> <frameset cols="35%, 65%"> <frame src ="/htmlcodes/left-frame.html" /> <frame src ="/htmlcodes/right-frame.html" /> </frameset> </html></pre> |
| <frameset> | <p>FRAMESET tags define a layout of frames.</p> <pre><html> <frameset cols="45%, *"> <frame src ="/htmlcodes/left-frame.html" /> <frame src ="/htmlcodes/right-frame.html" /> </frameset> </html></pre> |
| <h1> - <h6> | <p>H1 - H6 define level 1-6 headers.</p> <pre><h1>Header 1</h1> <h2>Header 2</h2> <h3>Header 3</h3> <h4>Header 4</h4> <h5>Header 5</h5> <h6>Header 6</h6></pre> |
| <head> | <p>Head tags define general information about the document, page title, meta-</p> |

| | |
|-----------------------|--|
| | <p>tags, scripts and links to follow, and other commands to browsers.</p> <pre> <html> <head> <title>HTML Tags - Head Tag</title> <meta name="keywords" content="html tags, head tag" /> <link rel="stylesheet" type="text/css" href="style.css" /> <script src="javaexample.js" type="text/javascript"></script> </head> <body> </body> </html> </pre> |
| <hr> | <p>HR tag draws a horizontal break line.</p> <hr/> <p>Two choices for the same result: <hr> or <hr /></p> |
| <html> | <p>HTML tags contain HTML elements, and give a command to browsers to read the document as an HTML document.</p> <pre> <html> <head> </head> <body> </body> </html> </pre> |
| <iframe> | <p>iFrame tag creates an inline frame that contains another web page in it.</p> |
| | <p>IMG tag attributes an image.</p> <pre> </pre> |
| <input> | <p>INPUT tags define input fields, check boxes, radio buttons.</p> <pre> <form action="contact.html" method="post"> Your Email: <input type="text" name="visitor-email" maxlength="80" value="" /> Your Name: <input type="text" name="visitor-name" maxlength="80" value="" /> <input type="radio" name="Level" value="Web Designer" />Web Designer <input type="radio" name="Level" value="Web Developer" checked="checked" />Web Developer <input type="checkbox" name="Computer" value="Windows" />Windows <input type="checkbox" name="Computer" value="Mac" />Mac </pre> |

| | |
|------------------------|---|
| | <pre><input type="submit" value="Send" /> </form></pre> <p>Top of Form</p> <p>eMail: <input type="text"/></p> <p>Name: <input type="text"/></p> <p> <input checked="" type="radio"/> Web Designer <input checked="" type="radio"/> Web Developer <input type="checkbox"/> Windows <input type="checkbox"/> Mac </p> <p><input type="button" value="Send"/></p> <p>Bottom of Form</p> |
| <ins> | INS tag defines an <ins>inserted text</ins>. |
| <isindex> | <p>ISINDEX tag defines a single-line input field.</p> <pre><isindex prompt="Example: "></pre> <p>Top of Form</p> <hr/> <p>Example: <input type="text"/></p> <hr/> <p>Bottom of Form</p> |
| <i> | <I> tag is specifying <i>italic text</i>. |
| <kbd> | KBD tag stands for <kbd>keyboard text</kbd>. |
| <label> | <p>LABEL tag defines a label to a form control.</p> <pre><p>Where do you live?</p> <form action=""> <input type="radio" name="country" id="us" /> <label for="usa">USA</label> <input type="radio" name="country" id="uk" /> <label for="uk">UK</label> </form></pre> <p>Where do you live?</p> <p>Top of Form</p> <p> <input checked="" type="radio"/> USA <input checked="" type="radio"/> UK </p> <p>Bottom of Form</p> |

| | |
|------------------------|--|
| <legend> | <p>LEGEND tag assigns a caption in a fieldset element.</p> <pre> <legend>Questionnaire</legend> <p>Where do you live?</p> <form action=""> <input type="radio" name="country" id="usa" /> <label for="usa">USA</label> <input type="radio" name="country" id="canada" /> <label for="canada">Canada</label> </form> </pre> <p>Questionnaire Where do you live? Top of Form</p> <p><input type="radio"/> USA <input type="radio"/> Canada</p> <p>Bottom of Form</p> |
| | <p>LI tag defines a list of ordered and unordered items.</p> <pre> HTML PHP JavaScript HTML PHP JavaScript </pre> <p>1. HTML 2. PHP 3. JavaScript</p> <ul style="list-style-type: none"> HTML PHP JavaScript |
| <link> | <p>LINK tag defines a link to an external document, such as External Style Sheets.</p> <pre> <head> <link rel="stylesheet" type="text/css" href="style.css" /> </head> </pre> |
| <marquee> | MARQUEE tags define different movement behaviors. |
| <menu> | MENU tag defines a menu list. |


| | |
|-------------------------|---|
| | <pre> <menu> Google Yahoo MSN </menu> </pre> <p> <input type="checkbox"/> Google <input type="checkbox"/> Yahoo <input type="checkbox"/> MSN </p> |
| <meta> | <p>META tags are declaring information for the search engine robots and crawlers.</p> <pre> <html> <head> <meta name="description" content="Page description goes here."> <meta name="keywords" content="meta tags, html tags, meta"> </head> <body> </body> </html> </pre> |
| <noframe> | <p>NOFRAME tag is specifying an alternate web page layout for browsers that don't support frames.</p> <pre> <html> <head> <title>Frame Tags in Action</title> </head> <noframes> <body> <h1>Sorry, your browser doesn't support this feature!</h1> </body> </noframes> <frameset cols="35%, 65%"> <frame src ="/htmlcodes/left-frame.html" /> <frame src ="/htmlcodes/right-frame.html" /> </frameset> </html> </pre> |
| <noscript> | <p>NOSCRIPT tag is specifying a "NOSCRIPT" version page layout for browsers that don't support "SCRIPT" version. NOSCRIP tags are used in conjunction with the JavaScript or VBScript elements.</p> <pre> <script type="text/javascript" language="javascript"> document.write("We are here to learn HTML"); </script> <noscript> Sorry, your browser doesn't support JavaScript, VBScript. </noscript> </pre> |
| optgroup> | <p>OPTGROUP tag creates an option drop-down group menu.</p> |

| | |
|-----------------------|---|
| | <pre> <select> <optgroup label="Fruits"> <option value ="banana">Banana</option> <option value ="pineapple">Pineapple</option> </optgroup> <optgroup label="Vegetables"> <option value ="tomato">Tomato</option> <option value ="potato">Potato</option> </optgroup> </select> </pre>  |
| <option> | <p>OPTION tag creates a drop-down menu. OPTION tag works only in conjunction with a SELECT tag.</p> <pre> <select> <option value ="beginner" selected="selected">Beginner</option> <option value ="intermediate">Intermediate</option> <option value ="advanced">Advanced</option> </select> </pre>  |
| | <p>OL tags define an ordered list of items.</p> <pre> Red Green Blue </pre> <pre> 1. Red 2. Green 3. Blue </pre> |
| <p> | <p><P> tag is specifying a paragraph and creates a new line.</p> <pre> <h4>Header 4</h4> </pre> <pre> <p>This is a paragraph.</p> </pre> |
| <pre> | <p>PRE tag is specifying a preformatted text. This tag does,t let the browsers to eliminate "white spaces" in the text.</p> <pre> <pre> City London Cool City Paris Awesome </pre> |

| | |
|-----------------------|--|
| | <pre> City New York Great </pre> <p style="text-align: center;">EXAMPLE</p> <pre> City London Cool City Paris Awesome City New York Great </pre> </pre> |
| <q> | <p><Q> tag is specifying short quotations. The function is similar to <blockquote> tag except that <Q> tag doesn't break lines of the text.</p> <p><q>I'll be back</q> - is a popular phrase associated with Arnold Schwarzenegger.</p> |
| <s> | <p><S> tag produces a strike throughout a text. <S> tag is depreciated and is not supported in XHTML 1.0 Strict DTD, therefore it's recommended to use DEL tag instead.</p> <p>Strike through <s>the following text.</s></p> |
| <samp> | <p>SAMP tag is specifying a fixed-width font.</p> <p>Compare for yourself - 1 <samp>Compare for yourself - 2</samp></p> |
| <script> | <p>SCRIPT tags define scripts within a web page and let the web browsers know that it's not an HTML section. You can place a <SCRIPT> tag anywhere within HTML, but the best practice is to place it between the <HEAD></HEAD> tags.</p> <pre> <html> <head> <script src="javascript.js" type="text/javascript"></script> </head> <body> <script type="text/javascript"> document.write("This is a script tag placement tutorial.") </script> </body> </html> </pre> |
| <select> | <p>SELECT tag creates a menu on a form.</p> <pre> <select> <option value = "planes" selected="selected">Planes</option> <option value = "trains">Trains</option> <option value = "automobiles">Automobiles</option> </select> </pre> |

| | |
|-----------------------|---|
| | <div>Planes</div> |
| <small> | <p>SMALL tag creates a small text.</p> <p>Compare normal text in relationship to <small>small text</small></p> |
| | <p>SPAN tag is specifying a section of a document.</p> <pre><div> <p>Cats and Dogs are our friends.</p> </div></pre> |
| <strike> | <p>STRIKE tag creates a strike through words or text. Strike tag is depreciated and is not supported in XHTML 1.0 Strict DTD, therefore it's recommended to use DEL tag instead.</p> <pre><strike>striking through</strike></pre> |
| | <p>STRONG tag is specifying a strong text.</p> <pre><div> <p>Weightlifters are strong people.</p> </div></pre> |
| <style> | <p>STYLE tag specifies a link and location to a style sheet, and gives a command to browsers regarding to a layout for a web page. Please find; First bold line is an External Style, and the next bold lines are for the Internal Style web page presentation.</p> <pre><html> <head> <title>HTML Tags - Head Tag</title> <link rel="stylesheet" type="text/css" href="style.css" /> <style type="text/css"> h1{text-align: center; font-style: italic} p{color: #ff0000} </style> </head> <body> </body> </html></pre> |
| <sub> | <p>SUB tag is defining a subscripted text.</p> <p>SUB tag is creating <sub>a subscripted text.</sub></p> |
| <sup> | <p>SUP tag is defining a superscripted text.</p> <p>SUP tag is creating <sup>a superscripted text.</sup></p> |
| <table> | <p>TABLE tag is defining a table.</p> <pre><table> <tr> <td>First Cell</td> <td>Second Cell</td></pre> |

| | |
|-------------------------|---|
| | <pre> </tr> </table> </pre> |
| <td> | <p>TD tag creates a data cell.</p> <pre> <table> <tr> <td>First Data Cell</td> <td>Second Data Cell</td> </tr> </table> </pre> |
| <th> | <p>TH tag creates a header cell.</p> <pre> <table> <tr> <th colspan="2">My Shopping List</th> </tr> <tr> <td>Apples</td> <td>Pears</td> </tr> </table> </pre> |
| <tr> | <p>TR tag creates a row in a table.</p> <pre> <table> <tr> <td>Data Cell 1</td> <td>Data Cell 2</td> </tr> </table> </pre> |
| <tbody> | <p>TBODY tag creates a table body.</p> <pre> <table> <thead> <tr> <td colspan="2">>Header - Complete List of Basic HTML Tags</td> </tr> </thead> <tbody> <tr> <td>Tags</td> <td>Attributes</td> </tr> </tbody> <tfoot> <tr> <td colspan="2">>Footer - Created by Fillster.com</td> </tr> </tfoot> </table> </pre> |
| <textarea> | <p>TEXTAREA tag creates a text area.</p> |

| | |
|----------------------|--|
| | <pre><textarea rows="4" cols="30"> Place you text in here... </textarea></pre>  |
| <tfoot> | <p>TFOOT tag creates a table footer.</p> <pre><table> <thead> <tr> <td colspan="2">>Header - HTML Tags List</td> </tr> </thead> <tbody> <tr> <td>HTML Tags</td> <td>HTML Attributes</td> </tr> </tbody> <tfoot> <tr> <td colspan="2">>Footer - Copyright © Fillster.com</td> </tr> </tfoot> </table></pre> |
| <thead> | <p>THEAD tag creates a table header.</p> <pre><table> <thead> <tr> <td colspan="2">>Header text place here.</td> </tr> </thead> <tbody> <tr> <td>Element - 1</td> <td>Element - 2</td> </tr> </tbody> <tfoot> <tr> <td colspan="2">>Footer notes put here.</td> </tr> </tfoot> </table></pre> |
| <title> | <p>TITLE tag declares a title of an HTML document.</p> <pre><html></pre> |

| | |
|--------------------|--|
| | <pre> <head> <title>Brief description of the web page.</title> </head> <body> </body> </html> </pre> |
| <tt> | <p>TT tag creates a teletype text.</p> <p>This is a default font of the text, <tt>but this is a teletype font.</tt></p> |
| <u> | <p>U tag makes an underlined text.</p> <p>This text has the <u>underlined words.</u></p> |
| | <p>UL tags define an unordered list of items.</p> <pre> Code Script Tag </pre> <ul style="list-style-type: none"> • Code • Script • Tag |
| <var> | <p>VAR tag indicates a variable parameter.</p> <p>This is a <var>variable parameter<var> of the sentence.</p> |