Mission Pinball Framework API Reference

Release 0.19.2

Brian Madden, Gabe Knuth

CONTENTS

1	1 Subpackages						
	1.1	mpf.devices package	1				
	1.2	mpf.game package	23				
	1.3	mpf.media_controller package	27				
	1.4	mpf.platform package	41				
	1.5	mpf.plugins package	60				
	1.6	mpf.system package	64				
2 Module contents							
Python Module Index							
In	Index						

CHAPTER

ONE

SUBPACKAGES

1.1 mpf.devices package

1.1.1 Submodules

mpf.devices.autofire module

Contains the base class for autofire coil devices.

```
class mpf.devices.autofire.AutofireCoil (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Base class for coils in the pinball machine which should fire automatically based on switch activity using hardware switch rules.

autofire_coils are used when you want the coils to respond "instantly" without waiting for the lag of the python game code running on the host computer.

Examples of autofire_coils are pop bumpers, slingshots, and flippers.

Args: Same as Device.

Parameters

- config A dictionary which contains all the settings this
- should be configured with. (coil) -

```
disable(**kwargs)
```

Disables the autofire coil rule.

```
enable(**kwargs)
```

Enables the autofire coil rule.

validate()

Autofire rules only work if the switch is on the same platform as the coil.

In the future we may expand this to support other rules various platform vendors might have.

mpf.devices.ball_device module

Contains the base class for ball devices.

```
class mpf.devices.ball_device.BallDevice (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Base class for a 'Ball Device' in a pinball machine.

A ball device is anything that can hold one or more balls, such as a trough, an eject hole, a VUK, a catapult, etc.

Args: Same as Device.

balls = None

Number of balls currently contained (held) in this device.

```
class_label = 'ball_device'
collection = 'ball_devices'
config_section = 'ball_devices'
count_balls (stealth=False, **kwargs)
```

Counts the balls in the device and processes any new balls that came in or balls that have gone out.

Parameters

- **stealth** Boolean value that controls whether any events will be posted based on any ball count change info. If True, results will not be posted. If False, they will. Default is False.
- **kwargs Catches unexpected args since this method is used as an event handler.

```
eject (balls=1, target=None, timeout=None, get_ball=False)
```

Ejects one or more balls from the device.

Parameters

- balls Integer of the number of balls to eject. Default is 1.
- **target** Optional target that should receive the ejected ball(s), either a string name of the ball device or a ball device object. Default is None which means this device will eject this ball to the first entry in the eject_targets list.
- **timeout** How long (in ms) to wait for the ball to make it into the target device after the ball is ejected. A value of None means the default timeout from the config file will be used. A value of 0 means there is no timeout.
- **get_ball** Boolean as to whether this device should attempt to get a ball to eject if it doesn't have one. Default is False.

Note that if this device's 'balls_per_eject' configuration is more than 1, then it will eject the nearest number of balls it can.

```
eject_all(target=None)
```

Ejects all the balls from this device

Parameters target – The string or BallDevice target for this eject. Default of None means *playfield*.

Returns True if there are balls to eject. False if this device is empty.

```
eject_failed(retry=True, force_retry=False)
```

Marks the current eject in progress as 'failed.'

Note this is not typically a method that would be called manually. It's called automatically based on ejects timing out or balls falling back into devices while they're in the process of ejecting. But you can call it

manually if you want to if you have some other way of knowing that the eject failed that the system can't figure out on it's own.

Parameters

- **retry** Boolean as to whether this eject should be retried. If True, the ball device will retry the eject again as long as the 'max_eject_attempts' has not been exceeded. Default is True.
- force_retry Boolean that forces a retry even if the 'max_eject_attempts' has been exceeded. Default is False.

eject_in_progress_target = None

The ball device this device is currently trying to eject to.

eject_queue = None

Queue of the list of eject targets (ball devices) for the balls this device is trying to eject.

flag_confirm_eject_via_count = None

Notifies the count_balls() method that it should confirm an eject if it finds a ball missing. We need this to be a standalone variable since sometimes other eject methods will have to "fall back" on count -based confirmations.

get_additional_ball_capacity()

Returns an integer value of the number of balls this device can receive. A return value of 0 means that this device is full and/or that it's not able to receive any balls at this time due to a current eject_in_progress.

get status(request=None)

Returns a dictionary of current status of this ball device.

Parameters request – A string of what status item you'd like to request. Default will return all status items. Options include: * balls * eject_in_progress_target * eject_queue

Returns

- balls
- eject_in_progress_target
- eject_queue

Return type A dictionary with the following keys

is full()

Checks to see if this device is full, meaning it is holding either the max number of balls it can hold, or it's holding all the known balls in the machine.

Returns: True or False

is playfield()

Returns True if this ball device is a Playfield-type device, False if it's a regular ball device.

num_balls_ejectable

How many balls are in this device that could be ejected.

num_balls_ejecting = None

The number of balls that are currently in the process of being ejected. This is either 0, 1, or whatever the balls was for devices that eject all their balls at once.

num_balls_in_transit = None

The number of balls in transit to this device.

$num_balls_requested = None$

The number of balls this device is in the process of trying to get.

num_eject_attempts = None

Counter of how many attempts to eject the current ball this device has tried. Eventually it will give up.

```
num_jam_switch_count = None
```

How many times the jam switch has been activated since the last successful eject.

```
request_ball(balls=1)
```

Request that one or more balls is added to this device.

Parameters balls – Integer of the number of balls that should be added to this device. A value of -1 will cause this device to try to fill itself.

Note that a device will never request more balls than it can hold. Also, only devices that are fed by other ball devices (or a combination of ball devices and diverters) can make this request. e.g. if this device is fed from the playfield, then this request won't work.

```
status_dump()
```

Dumps the full current status of the device to the log.

```
stop()
```

Stops all activity in this device.

Cancels all pending eject requests. Cancels eject confirmation checks.

mpf.devices.diverter module

Parent contains the base class for diverter devices.

```
class mpf.devices.diverter.Diverter(machine, name, config, collection=None)
```

Bases: mpf.system.devices.Device (page 75)

Represents a diverter in a pinball machine.

Args: Same as the Device parent class.

```
activate()
```

Physically activates this diverter's coil.

```
class_label = 'diverter'
collection = 'diverters'
config_section = 'diverters'
deactivate()
```

Deactivates this diverter.

This method will disable the activation_coil, and (optionally) if it's configured with a deactivation coil, it will pulse it.

```
disable (auto=False, **kwargs)
```

Disables this diverter.

This method will remove the hardware rule if this diverter is activated via a hardware switch.

Parameters

- **auto** Boolean value which is used to indicate whether this diverter disabled itself automatically. This is passed to the event which is posted.
- **kwargs This is here because this disable method is called by whatever event the game programmer specifies in their machine configuration file, so we don't know what event that might be or whether it has random kwargs attached to it.

disable held coil()

Physically disables the coil holding this diverter open.

disable hw switch()

Removes the hardware rule to disable the hardware activation switch for this diverter.

```
enable (auto=False, activations=-1, **kwargs)
```

Enables this diverter.

Parameters

- **auto** Boolean value which is used to indicate whether this diverter enabled itself automatically. This is passed to the event which is posted.
- activations Integer of how many times you'd like this diverter to activate before it will automatically disable itself. Default is -1 which is unlimited.

If an 'activation_switches' is configured, then this method writes a hardware autofire rule to the pinball controller which fires the diverter coil when the switch is activated.

If no *activation_switches* is specified, then the diverter is activated immediately.

enable_hw_switches()

Enables the hardware switch rule which causes this diverter to activate when the switch is hit.

This is typically used for diverters on loops and ramps where you don't want the diverter to phsyically activate until the ramp entry switch is activated.

If this diverter is configured with a activation_time, this method will also set switch handlers which will set a delay to deactivate the diverter once the activation activation time expires.

If this diverter is configured with a deactivation switch, this method will set up the switch handlers to deactivate the diverter when the deactivation switch is activated.

schedule_deactivation (time=None)

Schedules a delay to deactivate this diverter.

Parameters time – The MPF string time of how long you'd like the delay before deactivating the diverter. Default is None which means it uses the 'activation_time' setting configured for this diverter. If there is no 'activation_time' setting and no delay is passed, it will disable the diverter immediately.

mpf.devices.driver module

Contains the Driver parent class.

```
class mpf.devices.driver.Driver (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Generic class that holds driver objects.

A 'driver' is any device controlled from a driver board which is typically the high-voltage stuff like coils and flashers.

This class exposes the methods you should use on these driver types of devices. Each platform module (i.e. P-ROC, FAST, etc.) subclasses this class to actually communicate with the physical hardware and perform the actions.

Args: Same as the Device parent class

```
class_label = 'coil'
collection = 'coils'
```

```
config section = 'coils'
```

disable()

Disables this driver

enable()

Enables a driver by holding it 'on'.

If this driver is configured with a holdpatter, then this method will use that holdpatter to pwm pulse the driver.

If not, then this method will just enable the driver. As a safety precaution, if you want to enable() this driver without pwm, then you have to add the following option to this driver in your machine configuration files:

allow_enable: True

pulse (milliseconds=None, power=1.0)

Pulses this driver.

Parameters

- milliseconds The number of milliseconds the driver should be enabled for. If no value is provided, the driver will be enabled for the value specified in the config dictionary.
- **power** A multiplier that will be applied to the default pulse time, typically a float between 0.0 and 1.0. (Note this is only used if milliseconds is not specified.)

```
pwm (on_ms, off_ms, orig_on_ms=0)
```

Quickly turns this driver on and off to have the effect of holding this driver 'on' without burning up the coil.

Parameters

- on_ms Integer of how long this driver is on in the 'on' portion.
- off_ms Integer of how long this driver is off in the 'off' portion.
- **orig_on_ms** Integer of how long this driver should be held on initially before the on/off pulsing starts.

For example, to rapidly pulse a driver 1ms and then off 4ms, pass the values on_ms=1, off_ms=4.

```
timed_pwm (on_ms, off_ms, runtime_ms)
```

Quickly pulses a driver on/off for a specified number of milliseconds.

Parameters

- on ms Integer of how long this driver is on in the 'on' portion.
- off_ms Integer of how long this driver is off in the 'off' portion.
- runtime_ms Integer of the total number of milliseconds this driver should pulse on and off for.

mpf.devices.drop_target module

Contains the base classes for drop targets and drop target banks.

```
class mpf.devices.drop_target.DropTarget (machine, name, config, collection=None)
    Bases: mpf.devices.target.Target (page 21)
```

Represents a single drop target in a pinball machine.

```
Args: Same as the Target parent class
```

```
class label = 'drop target'
collection = 'drop_targets'
config_section = 'drop_targets'
knockdown (**kwargs)
```

Pulses the knockdown coil to knock down this drop target.

```
reset (**kwargs)
```

Resets this drop target.

If this drop target is configured with a reset coil, then this method will pulse that coil. If not, then it checks to see if this drop target is part of a drop target bank, and if so, it calls the reset() method of the drop target bank.

This method does not reset the target profile, however, the switch event handler should reset the target profile on its own when the drop target physically moves back to the up position.

```
update state from switch()
```

Reads the state of this drop target's switch and updates this drop target's "complete" status.

If this method sees that this target has changed back to its up state, then it will also reset the target profile back to its first step.

```
class mpf.devices.drop_target.DropTargetBank (machine, name, config, collection, mem-
                                                   ber collection=None, device str=None)
    Bases: mpf.devices.target.TargetGroup (page 22)
```

Represents a bank of drop targets in a pinball machine by grouping together multiple *DropTarget* class devices.

```
class label = 'drop target bank'
collection = 'drop target banks'
config_section = 'drop_target_banks'
reset (**kwargs)
    Resets this bank of drop targets.
```

This method has some intelligence to figure out what coil(s) it should fire. It builds up a set by looking at its own reset_coil and reset_coils settings, and also scanning through all the member drop targets and collecting their coils. Then it pulses each of them. (This coil list is a "set" which means it only sends a single pulse to each coil, even if each drop target is configured with its own coil.)

mpf.devices.flasher module

Contains the Flasher parent class.

```
class mpf.devices.flasher.Flasher (machine, name, config, collection=None)
     Bases: mpf.system.devices.Device (page 75)
     Generic class that holds flasher objects.
     class label = 'flasher'
     collection = 'flashers'
     config_section = 'flashers'
     flash (milliseconds=None)
          Flashes the flasher.
```

Parameters milliseconds – Int of how long you want the flash to be, in ms. Default is None which causes the flasher to flash for whatever its default config is, either its own flash_ms or the system- wide default_flash_ms settings. (Current default is 50ms.)

mpf.devices.flipper module

Contains the base class for flippers.

```
class mpf.devices.flipper.Flipper (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Represents a flipper in a pinball machine. Subclass of Device.

Contains several methods for actions that can be performed on this flipper, like enable() (page 8), disable() (page 8), etc.

Flippers have several options, including player buttons, EOS swtiches, multiple coil options (pulsing, hold coils, etc.)

More details: http://missionpinball.com/docs/devices/flippers/

Parameters

- machine A reference to the machine controller instance.
- name A string of the name you'll refer to this flipper object as.
- **config** A dictionary that holds the configuration values which specify how this flipper should be configured. If this is None, it will use the system config settings that were read in from the config files when the machine was reset.
- collection A reference to the collection list this device will be added
- to. –

Parameters config – A dictionary that holds the configuration values which specify how this flipper should be configured. If this is None, it will use the system config settings that were read in from the config files when the machine was reset.

```
disable (**kwargs)
```

Disables the flipper.

This method makes it so the cabinet flipper buttons no longer control the flippers. Used when no game is active and when the player has tilted.

```
enable(**kwargs)
```

Enables the flipper by writing the necessary hardware rules to the hardware controller.

The hardware rules for coils can be kind of complex given all the options, so we've mapped all the options out here. We literally have methods to enable the various rules based on the rule letters here, which we've implemented below. Keeps it easy to understand. :)

Note there's a platform feature saved at: self.machine.config['platform']['hw_enable_auto_disable']. If True, it means that the platform hardware rules will automatically disable a coil that has been enabled when the trigger switch is disabled. If False, it means the hardware platform needs its own rule to disable

the coil when the switch is disabled. Methods F and G below check for that feature setting and will not be applied to the hardware if it's True.

Two coils, using EOS switch to indicate the end of the power stroke: Rule Type Coil Switch Action A. Enable Main Button active D. Enable Hold Button active E. Disable Main EOS active F. Disable Main Button inactive G. Disable Hold Button inactive

One coil, using EOS switch Rule Type Coil Switch Action A. Enable Main Button active H. PWM Main EOS active F. Disable Main Button inactive

Two coils, not using EOS switch: Rule Type Coil Switch Action B. Pulse Main Button active D. Enable Hold Button active F. Disable Main Button inactive G. Disable Hold Button inactive

One coil, not using EOS switch Rule Type Coil Switch Action C. Pulse/PWM Main button active F. Disable Main button inactive

Use EOS switch for safety (for platforms that support mutiple switch rules). Note that this rule is the letter "i", not a numeral 1. I. Enable power if button is active and EOS is not active

enable_no_hold()

Enables the flippers in 'no hold' mode.

No Hold is a novelty mode where the flippers to not stay up even when the buttons are held in.

This mode is not yet implemented.

enable_partial_power (percent)

Enables flippers which operated at less than full power.

This is a novelty mode, like "weak flippers" from the Wizard of Oz.

Parameters percent – A floating point value between 0 and 1.0 which represents the percentage of power the flippers will be enabled at.

This mode is not yet implemented.

classmethod invert()

Enables inverted flippers.

Inverted flippers is a novelty mode where the left flipper button controls the right flippers and vice-versa.

This mode is not yet implemented.

sw_flip()

Activates the flipper via software as if the flipper button was pushed.

This is needed because the real flipper activations are handled in hardware, so if you want to flip the flippers with the keyboard or OSC interfaces, you have to call this method.

Note this method will keep this flipper enabled until you call sw release().

sw_release()

Deactives the flipper via software as if the flipper button was released. See the documentation for sw_flip() for details.

mpf.devices.gi module

Contains the GI (General Illumination) parent classes.

```
class mpf.devices.gi.GI (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Represents a light connected to a traditional lamp matrix in a pinball machine.

This light could be an incandescent lamp or a replacement single-color LED. The key is that they're connected up to a lamp matrix.

```
add handler(callback)
```

Registers a handler to be called when this light changes state.

```
class_label = 'gi'
collection = 'gi'
config_section = 'gis'
disable (**kwargs)
    Disables this GI string.
enable (brightness=255, fade_ms=0, start_brightness=None, **kwargs)
    Enables this GI string.
```

Parameters

- **brightness** Int from 0-255 of how bright you want this to be. 255 is on. 0 os iff. Note that not all GI strings on all machines support this.
- **fade_ms** How quickly you'd like this GI string to fade to this brightness level. This is not implemented.
- **start_brightness** Starting brightness level for a fade.

```
remove_handler(callback=None)
```

Removes a handler from the list of registered handlers.

mpf.devices.led module

Contains the LED parent classes.

```
class mpf.devices.led.LED (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Represents an light connected to an new-style interface board. Typically this is an LED.

DirectLEDs can have any number of elements. Typically they're either single element (single color), or three element (RGB), though dual element (red/green) and quad-element (RGB + UV) also exist and can be used.

Parameters

- **color** a list of integers which represent the red, green, and blue values the LED will be set to. If this list is fewer than three items, it assumes zeros for the rest.
- **fade_ms** Integer value of how long the LED should fade from its current color to the color you're passing it here.
- **brightness_compensation** Boolean value which controls whether this LED will be light using the current brightness compensation. Default is True.

- **priority** Arbitrary integer value of the priority of this request. If the incoming priority is lower than the current priority, this incoming color request will have no effect. Default is 0
- cache Boolean which controls whether this new color command will update the LED's cache. Default is True.
- **force** Boolean which will force this new color command to be applied to the LED, regardless of the incoming or current priority. Default is True.
- **blend** Not yet implemented.

compensate (color)

Applies the current brightness compensation values to the passed color.

Parameters color – a 3-item color list of ints

Returns The brightness-compensated 3-item color list of ints

```
config_section = 'leds'
classmethod device_class_init (machine)
disable (fade_ms=0, priority=0, cache=True, force=False)
    Disables an LED, including all elements of a multi-color LED.
get_state()
    Returns the current state of this LED
```

hexstring_to_list(input_string, output_length=3)

Takes a string input of hex numbers and returns a list of integers.

This always groups the hex string in twos, so an input of ffff00 will be returned as [255, 255, 0]

Parameters

- input_string A string of incoming hex colors, like ffff00.
- output_length Integer value of the number of items you'd like in your returned list. Default is 3. This method will ignore extra characters if the input_string is too long, and it will pad with zeros if the input string is too short.

Returns List of integers, like [255, 255, 0]

```
off (fade_ms=0, priority=0, cache=True, force=False)
on (brightness=255, fade_ms=0, start_brightness=None, priority=0, cache=True, force=False)
restore()
```

Sets this LED to the cached state.

mpf.devices.matrix light module

Contains the MatrixLight parent classes.

```
class mpf.devices.matrix_light.MatrixLight (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

Represents a light connected to a traditional lamp matrix in a pinball machine.

This light could be an incandescent lamp or a replacement single-color LED. The key is that they're connected up to a lamp matrix.

```
add_handler(callback)
```

Registers a handler to be called when this light changes state.

```
class_label = 'light'
collection = 'lights'
config_section = 'matrix_lights'
off (fade_ms=0, priority=0, cache=True, force=False)
on (brightness=255, fade_ms=0, start_brightness=None, priority=0, cache=True, force=False)
    Turns on this matrix light.
```

Parameters

- **brightness** How bright this light should be, as an int between 0 and 255. 0 is off. 255 is full on. Note that intermediary values are not yet implemented, so 0 is off, anything from 1-255 is full on.
- fade_ms Not yet implemented
- start_brightness Not yet implemented.
- **priority** The priority of the incoming request. If this priority is lower than the current cached priority, this on command will have no effect. (Unless force=True)
- cache Boolean as to whether this light should cache these new settings. This cache can be used for the light to "go back" to it's previous state. Default is True.
- **force** Whether the light should be forced to go to the new state, regardless of the incoming and current priority. Default is False.

```
remove_handler(callback=None)
```

Removes a handler from the list of registered handlers.

```
restore()
```

Restores the light state from cache.

mpf.devices.new_device_template module

Template file for a new device driver.

```
class label = 'your new device'
```

The two class attributes above control how devices based on this class are configured and how they're presented to the MPF.

config_section is the name of the section in the machine configuration files that contains settings for this type of device. The game programmer would then create subsections for each device of this type, with individual settings under each one.

For example, in the machine configuration files:

YourNewDevices:

```
device1: setting1: foo setting2: bar tags: tag2, tag3 label: A plain english description of this device device2: setting1: foo setting2: bar tags: tag1, tag2 label: A plain english description of this device
```

collection is the DeviceCollection instance that will be created to hold all the devices of this new type. For example, if collection is 'yournewdevice', a collection will be created which is accessible via self.machine.yournewdevices.

```
collection = 'your_new_devices'
config_section = 'your_new_devices'
classmethod device_class_init (machine)
```

This @classmethod is optional, but is called automatically before individual devices based on this device class are created. You can use it for any system-wide settings, configurations, or objects that you might need for these types of devices outside of the individual devices themselves.

For example, led.py uses this to make sure the global fade_ms default fade time is a float. The EM score reels devices use this to set up the score controller that has to exist to manage them.

You can safely delete this method if your device doesn't need it. (Most don't need it.)

mpf.devices.playfield module

Contains the Playfield device class which represents the actual playfield in a pinball machine.

```
class mpf.devices.playfield.Playfield(machine, name, collection)
    Bases: mpf.devices.ball_device.BallDevice(page 2)

add_ball(balls=1, source_name=None, source_device=None, trigger_event=None)
    Adds live ball(s) to the playfield.
```

Parameters

- balls Integer of the number of balls you'd like to add.
- source_name Optional string name of the ball device you'd like to add the ball(s) from.
- source_device Optional ball device object you'd like to add the ball(s) from.
- **trigger_event** The optional name of an event that MPF will wait for before adding the ball into play. Typically used with player- controlled eject tag events. If None, the ball will be added immediately.

Returns True if it's able to process the add_ball() request, False if it cannot.

Both source_name and source_device args are included to give you two options for specifying the source of the ball(s) to be added. You don't need to supply both. (it's an "either/or" thing.) Both of these args are optional, so if you don't supply them then MPF will look for a device tagged with 'ball_add_live'. If you don't provide a source and you don't have a device with the 'ball_add_live' tag, MPF will quit.

This method does *not* increase the game controller's count of the number of balls in play. So if you want to add balls (like in a ball scenario(, you need to call this method along with self.machine.game.add_balls_in_play().)

MPF tracks the number of balls in play separately from the actual balls on the playfield because there are numerous situations where the two counts are not the same. For example, if a ball is in a VUK while some animation is playing, there are no balls on the playfield but still one ball in play, or if the player has a two-ball multiball and they shoot them both into locks, there are still two balls in play even though there are no balls on the playfield, or if the player tilts then there are still balls on the playfield but no balls in play.

```
ball_found(num=1)
```

Used when a previously missing ball is found. Updates the balls known and balls missing variables.

Parameters num (*int*) – Specifies how many balls have been found. Default is 1.

```
ball_lost()

Mark a ball as lost
```

ball_search_begin (force=False)

Begin the ball search process

ball_search_disable()

Disables ball search.

Note this is used to prevent a future ball search from happening (like when all balls become contained). This method is not used to cancel an existing ball search. (Use *ball_search_end* for that.)

ball search end()

End the ball search, either because we found the ball or are giving up.

ball_search_failed()

Ball Search did not find the ball.

ball_search_schedule (secs=None, force=False)

Schedules a ball search to start. By default it will schedule it based on the time configured in the machine configuration files.

If a ball search is already scheduled, this method will reset that schedule to the new time passed.

Parameters

- secs Schedules the ball search that many secs from now.
- **force** Boolean to force a ball search. Set True to force a ball search. Otherwise it will only schedule it if self.flag_no_ball_search is False. Default is False

balls

count balls(**kwargs)

Used to count the number of balls that are contained in a ball device. Since this is the playfield device, this method always returns zero.

Returns: 0

```
eject(*args, **kwargs)
```

```
eject_all(*args, **kwargs)
```

get_additional_ball_capacity()

Used to find out how many more balls this device can hold. Since this is the playfield device, this method always returns 999.

Returns: 999

ok_to_confirm_ball_via_playfield_switch()

Used to check whether it's ok for a ball device which ejects to the playfield to confirm its eject via a playfield switch being hit.

Returns: True or False

Right now this is simple. If there are no playfield balls, then any playfield switch hit is assumed to be from the newly-ejected ball. If there are other balls on the playfield, then we can't use this confirmation method since we don't know whether a playfield switch hit is from the newly-ejected ball(s) or a current previously-live playfield ball.

player_eject_request (balls, device)

A player has hit a switch tagged with the player_eject_request_tag.

Parameters

- balls Integer of the number of balls that will be ejected.
- **device** The ball device object that will eject the ball(s).

playfield switch hit()

A switch tagged with '<this playfield name>_active' was just hit, indicating that there is at least one ball on the playfield.

```
remove_player_controlled_eject()
```

Removed the player-controlled eject so a player hitting a switch no longer calls the device(s) to eject a ball.

```
setup_player_controlled_eject (balls, device, trigger_event)
```

Used to set up an eject from a ball device which will eject a ball to the playfield.

Parameters

- balls Integer of the number of balls this device should eject.
- **device** The ball device object that will eject the ball(s) when a switch with the player-controlled eject tag is hit.
- **trigger_event** The name of the MPF event that will trigger the eject.

When this method it called, MPF will set up an event handler to look for the trigger_event.

mpf.devices.playfield_transfer module

Transfer a ball between two playfields. E.g. lower to upper playfield via a ramp

mpf.devices.score reel module

Contains the base classes for mechanical EM-style score reels.

```
class mpf.devices.score_reel.ScoreReel (machine, name, config, collection=None)
     Bases: mpf.system.devices.Device (page 75)
```

Represents an individual electro-mechanical score reel in a pinball machine.

Multiples reels of this class can be grouped together into ScoreReelGroups which collectively make up a display like "Player 1 Score" or "Player 2 card value", etc.

This device class is used for all types of mechanical number reels in a machine, including reels that have more than ten numbers and that can move in multiple directions (such as the credit reel).

```
advance (direction=None)
```

Performs the coil firing to advance this reel one position (up or down).

This method also schedules delays to post the following events:

reel_<name>_pulse_done: When the coil is done pulsing reel_<name>_ready: When the config['repeat_pulse_time'] time is up reel_<name>_hw_value: When the config['hw_confirm_time'] time is up

Parameters direction (*int*, *optional*) – If direction is 1, advances the reel to the next higher position. If direction is -1, advances the reel down one position (if the reel has a decrement coil). If direction is not passed, this method will compare the reel's _destination_index to its assumed_value and will advance it in the direction it needs to go if those values do not match.

Returns: If this method is unable to advance the reel (either because it's not ready, because it's at its maximum value and does not have rollover capabilities, or because you're trying to advance it in a direction but it doesn't have a coil for that direction), it will return *False*. If it's able to pulse the advance coil, it returns *True*.

check_hw_switches (no_event=False)

Checks all the value switches for this score reel.

This check only happens if *self.ready* is *True*. If the reel is not ready, it means another advance request has come in after the initial one. In that case then the subsequent advance will call this method again when after that advance is done.

If this method finds an active switch, it sets *self.physical_value* to that. Otherwise it sets it to -999. It will also update *self.assumed_value* if it finds an active switch. Otherwise it leaves that value unchanged.

This method is automatically called (via a delay) after the reel advances. The delay is based on the config value *self.config['hw_confirm_time']*.

TODO: What happens if there are multiple active switches? Currently it will return the highest one. Is that ok?

Parameters no_event – A boolean switch that allows you to suppress the event posting from this call if you just want to update the values.

Returns: The hardware value of the switch, either the position or -999. If the reel is not ready, it returns *False*.

```
class_label = 'score_reel'
collection = 'score_reels'
config_section = 'score_reels'
logical_to_physical (value)
```

Converts a logical reel displayed value to what the physical switch value should be.

For example, if a reel has switches for the 0 and 9 values, then an input of 0 will return 0 (since that's what the physical value should be for that logical value). In that case it will return 9 for an input of 9, but it will return -999 for any input value of 1 through 8 since there are no switches for those values.

Note this method does not perform any physical or logical check against the reel's actual position, rather, it's only used to indicate what hardware switch value should be expected for the display value passed.

Parameters value (*int*) – The value you want to check.

Returns The phsyical switch value, which is same as the input value if there's a switch there, or -999 if not.

pulse_ms

Returns an integer representing the number of milliseconds the coil will pulse for.

This method is used by the jump and step advances so they know when a reel's coil is done firing so they can fire the next reel in the group.

Parameters

- direction (int, optional) Lets you specify which coil you want to
- the time for. Default is 1 (get) –
- down). -

Returns: Interger of the coil pulse time. If there is no coil for the direction you specify, returns 0.

set_destination_value(direction=1)

Returns the integer value of the destination this reel is moving to.

Parameters

- direction (int, optional) The direction of the reel movement this
- should get the value for. Default is 1 which means of 'up'. (method) -
- can pass -1 the next lower value. (You) –

Returns: The value of the destination. If the current *self.assumed_value* is -999, this method will always return -999 since it doesn't know where the reel is and therefore doesn't know what the destination value would be.

${\bf class} \; {\tt mpf.devices.score_reel.ScoreReelController} \; ({\it machine}) \\$

Bases: object

The overall controller that is in charge of and manages the score reels in a pinball machine.

The main thing this controller does is keep track of how many ScoreReelGroups there are in the machine and how many players there are, as well as maps the current player to the proper score reel.

This controller is also responsible for working around broken ScoreReelGroups and "stacking" and switching out players when there are multiple players per ScoreReelGroup.

active_scorereelgroup = None

Pointer to the active ScoreReelGroup for the current player.

game_starting(queue, game)

Resets the score reels when a new game starts.

This is a queue event so it doesn't allow the game start to continue until it's done.

Parameters

- queue A reference to the queue object for the game starting event.
- game A reference to the main game object. This is ignored and only included because the game starting event passes it.

map_new_score_reel_group()

Creates a mapping of a player to a score reel group.

player_to_scorereel_map = None

This is a list of ScoreReelGroup objects which corresponds to player indexes. The first element [0] in this list is the first player (which is player index [0], the next one is the next player, etc.

queue = None

Holds any active queue event queue objects

reset_queue = None

List of score reel groups that still need to be reset

rotate player()

Called when a new player's turn starts.

The main purpose of this method is to map the current player to their ScoreReelGroup in the backbox. It will do this by comparing length of the list which holds those mappings (*player_to_scorereel_map*) to the length of the list of players. If the player list is longer that means we don't have a ScoreReelGroup for that player.

In that case it will check the tags of the ScoreReelGroups to see if one of them is tagged with playerX which corresponds to this player. If not then it will pick the next free one. If there are none free, then it will "double up" that player on an existing one which means the same Score Reels will be used for both players, and they will reset themselves automatically between players.

score_change (score, change)

Called whenever the score changes and adds the score increase to the current active ScoreReelGroup.

This method is the handler for the score change event, so it's called automatically.

Parameters

- **score** Integer value of the new score. This parameter is ignored, and included only because the score change event passes it.
- **change** Interget value of the change to the score.

Represents a logical grouping of score reels in a pinball machine, where multiple individual ScoreReel object make up the individual digits of this group. This group also has support for the blank zero "inserts" that some machines use. This is a subclass of mpf.system.devices.Device.

```
add_value (value, jump=False, target=None)
```

Adds value to a ScoreReelGroup.

You can also pass a negative value to subtract points.

You can control the logistics of how these pulses are applied via the *jump* parameter. If jump is False (default), then this method will respect the proper "sequencing" of reel advances. For example, if the current value is 1700 and the new value is 2200, this method will fire the hundreds reel twice (to go to 1800 then 1900), then on the third pulse it will fire the thousands and hundreds (to go to 2000), then do the final two pulses to land at 2200.

Parameters

- value The integer value you'd like to add to (or subtract from) the current value
- **jump** Optional boolean value which controls whether the reels should "count up" to the new value in the classic EM way (jump=False) or whether they should just jump there as fast as they can (jump=True). Default is False.
- target Optional integer that's the target for where this reel group should end up after it's done advancing. If this is not specified then the target value will be calculated based on the current reel positions, though sometimes this get's wonky if the reel is jumping or moving, so it's best to specify the target if you can.

```
assumed_value_int
assumed_value_list
chime(chime)
class label = 'score reel group'
```

```
collection = 'score_reel_groups'
```

config section = 'score reel groups'

classmethod device_class_init (machine)

get_physical_value_list()

Queries all the reels in the group and builds a list of their actual current physical state, with either the value of the current switch or -999 if no switch is active.

This method also updates each reel's physical value.

Returns: List of physical reel values.

initialize()

Initialized the score reels by reading their current physical values and setting each reel's rollover reel. This is a separate method since it can't run int __init__() because all the other reels have to be setup first.

int_to_reel_list(value)

Converts an integer to a list of integers that represent each positional digit in this ScoreReelGroup.

The list returned is in reverse order. (See the example below.)

The list returned is customized for this ScoreReelGroup both in terms of number of elements and values of *None* used to represent blank plastic zero inserts that are not controlled by a score reel unit.

For example, if you have a 5-digit score reel group that has 4 physicial reels in the tens through tenthousands position and a fake plastic "0" insert for the ones position, if you pass this method a value of 12300, it will return [None, 0, 3, 2, 1]

This method will pad shorter ints with zeros, and it will chop off leading digits for ints that are too long. (For example, if you pass a value of 10000 to a ScoreReelGroup which only has 4 digits, the returns list would correspond to 0000, since your score reel unit has rolled over.)

Parameters value – The interger value you'd like to convert.

Returns A list containing the values for each corresponding score reel, with the lowest reel digit position in list position 0.

is_desired_valid (notify_event=False)

Tests to see whether the machine thinks the ScoreReelGroup is currently showing the desired value. In other words, is the ScoreReelGroup "done" moving?

Note this ignores placeholder non-controllable digits.

Returns: True or False

light (relight_on_valid=False, **kwargs)

Lights up this ScoreReelGroup based on the 'light tag' in its config.

reel_list_to_int (reel_list)

Converts an list of integers to a single integer.

This method is like *int_to_reel_list* except that it works in the opposite direction.

The list inputted is expected to be in "reverse" order, with the ones digit in the [0] index position. Values of *None* are converted to zeros. For example, if you pass [None, 0, 3, 2, 1], this method will return an integer value of 12300.

Note this method does not take into consideration how many reel positions are in this ScoreReelGroup. It just converts whatever you pass it.

Parameters value – The list containing the values for each score reel position.

Returns The resultant integer based on the list passed.

set rollover reels()

Calls each reel's _set_rollover_reel method and passes it a pointer to the next higher up reel. This is how we know whether we're able to advance the next higher up reel when a particular reel rolls over during a step advance.

```
set_value(value=None, value_list=None)
```

Resets the score reel group to display the value passed.

This method will "jump" the score reel group to display the value that's passed as an it. (Note this "jump" technique means it will just move the reels as fast as it can, and nonsensical values might show up on the reel while the movement is in progress.)

This method is used to "reset" a reel group to all zeros at the beginning of a game, and can also be used to reset a reel group that is confused or to switch a reel to the new player's score if multiple players a sharing the same reel group.

Note you can choose to pass either an integer representation of the value, or a value list.

Parameters

- **value** An integer value of what the new displayed value (i.e. score) should be. This is the default option if you only pass a single positional argument, e.g. *set_value*(2100).
- value_list A list of the value you'd like the reel group to display.

tick()

Automatically called once per machine tick and checks to see if there are any jumps or advances in progress, and, if so, calls those methods.

```
unlight (relight on valid=False, **kwargs)
```

Turns off the lights for this ScoreReelGroup based on the 'light_tag' in its config.

```
validate(value=None)
```

Called to validate that this score reel group is in the position the machine wants it to be in.

If lazy or strict confirm is enabled, this method will also make sure the reels are in their proper physical positions.

Parameters value (*ignored*) – This method takes an argument of *value*, but it's not used. It's only there because when reels post their events after they're done moving, they include a parameter of *value* which is the position they're in. So we just need to have this argument listed so we can use this method as an event handler for those events.

mpf.devices.switch module

Contains the Switch parent class.

```
class mpf.devices.switch.Switch (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
```

A switch in a pinball machine.

```
class_label = 'switch'
collection = 'switches'
config_section = 'switches'
hw state = None
```

The physical hardware state of the switch. 1 = active, 0 = inactive. This is what the actual hardware is reporting and does not consider whether a switch is NC or NO.

state = None

The logical state of a switch. 1 = active, 0 = inactive. This takes into consideration the NC or NO settings for the switch.

type = None

Specifies whether the switch is normally open ('NO', default) or normally closed ('NC').

mpf.devices.target module

Contains the base classes for Targets and TargetGroups.

```
class mpf.devices.target.Target (machine, name, config, collection=None)
    Bases: mpf.system.devices.Device (page 75)
    advance (**kwargs)
```

Advances the active target profile one step forward.

If this profile is at the last step and configured to roll over, it will roll over to the first step. If this profile is at the last step and not configured to roll over, this method has no effect.

```
\verb"apply_profile" (profile", priority", removal\_key=None")
```

Applies a target profile to this target.

Parameters

- **profile** String name of the profile to apply.
- **priority** Priority of this profile. Only one profile is active at a time. If this profile is the highest, then it will be active. If not then it will still be applied and will become active if higher priority profiles are removed.
- **removal_key** Optional hashable that can be used to identify this profile so it can be removed later.

```
class_label = 'target'
collection = 'targets'
config_section = 'targets'
disable (**kwargs)
```

Disables this target. If the target is not enabled, hits to it will not be processed.

```
enable(**kwargs)
```

Enables this target. If the target is not enabled, hits to it will not be processed.

```
hit (force=False, stealth=False, **kwargs)
```

Method which is called to indicate this target was just hit. This method will advance the currently-active target profile.

Parameters

- **force** Boolean that forces this hit to be registered. Default is False which means if there are no balls in play (e.g. after a tilt) then this hit isn't processed. Set this to True if you want to force the hit to be processed even if no balls are in play.
- **stealth** Boolean that controls whether this hit will post hit events. Useful if you want to just advance the step without triggering scoring, etc. Default is False.

Note that the target must be enabled in order for this hit to be processed.

```
jump (step, update_group=True, current_show_step=0)
Jumps to a certain step in the active target profile.
```

Parameters

- **step** int of the step number you want to jump to. Note that steps are zero-based, so the first step is 0.
- update_group Boolean which controls whether this jump event should also contact the target group this target belongs to to see if it should update this group's complete status. Default is True. False is used for things like target rotation where a target needs to jump to a new position but you don't want to post the group complete events again.

```
player_turn_start (player)
```

Called when a player's turn starts to update the player reference to the current player and to apply the default machine-wide target profile.

```
remove_profile (removal_key=None, **kwargs)
```

Removes a target profile from this target.

Parameters removal_key – The key that was returned when the profile was applied to the target which is how the profile you want to remove is identified. Default is None, in which case whichever profile is active will be removed.

If the profile removed is the active one (because it was the highest priority), then this method activates the next-highest priority profile.

Note that if there is only one profile applied, then it will not be removed.

```
reset (**kwargs)
```

Resets the active target profile back to the first step (Step 0). This method is the same as calling jump(0).

```
class mpf.devices.target.TargetGroup (machine, name, config, collection=None, mem-
ber_collection=None, device_str=None)
Bases: mpf.system.devices.Device (page 75)
```

Represents a group of targets in a pinball machine by grouping together multiple *Target* class devices. This is used so you get get "group-level" functionality, like target rotation, target group completion, etc. This would be used for a group of rollover lanes, a bank of standups, etc.

```
advance (**kwargs)
```

Advances the current active profile from every target in the group one step forward.

```
check_for_complete()
```

Checks all the targets in this target group. If they are all in the same step, then that step number is returned. If they are in different steps, False is returned.

```
class_label = 'target_group'
collection = 'target_groups'
config_section = 'target_groups'
disable (**kwargs)
    Disables this target group. Also disables all the targets in this group.
enable (**kwargs)
```

Enables this target group. Also enables all the targets in this group.

```
\verb+hit+ (profile\_name, profile\_step\_name, **kwargs)
```

One of the member targets in this target group was hit.

This method is only processed if this target group is enabled.

Parameters

• **profile_name** – String name of the active profile of the target that was hit.

• profile_step_name – String name of the step name of the profile of the target that was hit.

```
remove profile(**kwargs)
```

Removes the current active profile from every target in the group.

```
reset (**kwargs)
```

Resets each of the targets in this group back to the initial step in whatever target profile they have applied. This is the same as calling each target's reset() method one-by-one.

```
rotate (direction='right', steps=1, **kwargs)
```

Rotates (or "shifts") the state of all the targets in this group. This is used for things like lane change, where hitting the flipper button shifts all the states of the targets in the group to the left or right.

This method actually transfers the current state of each target profile to the left or the right, and the target on the end rolls over to the target on the other end.

Parameters

- **direction** String that specifies whether the rotation direction is to the left or right. Values are 'right' or 'left'. Default is 'right'.
- steps Integer of how many steps you want to rotate. Default is 1.

```
rotate_left (steps=1, **kwargs)
```

Rotates the state of the targets to the left. This method is the same as calling rotate('left', steps)

Parameters steps – Integer of how many steps you want to rotate. Default is 1.

```
rotate_right (steps=1, **kwargs)
```

Rotates the state of the targets to the right. This method is the same as calling rotate('right', steps)

Parameters steps – Integer of how many steps you want to rotate. Default is 1.

1.1.2 Module contents

1.2 mpf.game package

1.2.1 Submodules

mpf.game.attract module

Contains the Attract class which is the attract mode in a pinball machine.

Note: Still need to add the code to watch for combinations of button presses, like a long-press, pressing start while holding a flipper button, holding a flipper button to start tournament mode, etc.

```
class mpf.game.attract.Attract(machine, name)
    Bases: mpf.system.machine_mode.MachineMode(page 91)
```

Base class for the active mode for a machine when a game is not in progress. It's main job is to watch for the start button to be pressed, to post the requests to start games, and to move the machine flow to the next mode if the request to start game comes back as approved.

Parameters machine (MachineController) – A reference to the instance of the MachineController object.

```
result_of_start_request (ev_result=True)
```

Called after the *request_to_start_game* event is posted.

If *result* is True, this method posts the event *machineflow_advance*. If False, nothing happens, as the game start request was denied by some handler.

Parameters result (*bool*) – Result of the boolean event *request_to_start_game. If any registered event handler did not want the game to start, this will be False. Otherwise it's True.

```
start (**kwargs)
```

Automatically called when the Attract game mode becomes active.

```
start_button_pressed()
start_button_released()
```

Called when the a switch tagged with *start* is activated.

Since this is the Attract mode, this method posts a boolean event called *request_to_start_game*. If that event comes back True, this method calls result_of_start_request() (page 23).

stop()

mpf.game.game module

Contains the Game class which is the Machine Mode that actually runs and manages an the game in a pinball machine.

Note that in the Mission Pinball Framework, a distinction is made between a *game* and a *machine*. A *game* refers to a game in progress, whereas a *machine* is the physical pinball machine.

```
class mpf.game.game.Game (machine, name)
    Bases: mpf.system.machine_mode.MachineMode (page 91)
```

Base class that runs an active game on a pinball machine.

Responsible for creating players, starting and ending balls, rotating to the next player, etc.

```
add_balls_in_play(balls=1)
```

Adds one or more balls to the current balls in play value.

Parameters balls – Int of the balls to add.

This method does not actually eject any new balls onto the playfield, rather, it just changes the game controller's count of the number of balls in play.

Note that if the number of balls added exceeds the number of balls known, it will be set to the number of balls known.

```
award_extra_ball (num=1, force=False)
```

Awards the player an extra ball.

Parameters

- **num** Integer of the number of extra balls to award. Default is 1.
- force Boolean which allows you to force the extra ball even if it means the player would go above the max extra balls specified in the config files. Default is False.

TODO: The limit checking is not yet implemented

```
{\tt ball\_drained}\,(balls{=}0)
```

```
ball_ended(ev_result=True)
```

Called when the ball has successfully ended.

This method is called after all the registered handlers of the queue event *ball_ended* finish. (So typically this means that animations have finished, etc.)

This method also decides if the same player should shoot again (if there's an extra ball) or whether the machine controller should rotate to the next player. It will also end the game if all players and balls are done.

ball_ending()

Starts the ball ending process.

This method posts the queue event *ball_ending*, giving other modules an opportunity to finish up whatever they need to do before the ball ends. Once all the registered handlers for that event have finished, this method calls ball ended() (page 24).

Currently this method also disables the autofire_coils and flippers, though that's temporary as we'll move those into config file options.

ball_started(ev_result=True)

ball starting()

Called when a new ball is starting.

Note this method is called for each ball that starts, even if it's after a Shoot Again scenario for the same player.

Posts a queue event called *ball_starting*, giving other modules the opportunity to do things before the ball actually starts. Once that event is clear, this method calls ball_started() (page 25).

balls_in_play

game_ended(**kwargs)

Actually ends the game once the game_ending event is clear.

Eventually this method will do lots of things. For now it just advances the machine flow which ends the Game (page 24) mode and starts the Attract mode.

game_ending()

Called when the game decides it should end.

This method posts the queue event *game_ending*, giving other modules an opportunity to finish up whatever they need to do before the game ends. Once all the registered handlers for that event have finished, this method calls game_end().

game_started(ev_result=True, **kwargs)

All the modules that needed to do something on game start are done, so our game is officially 'started'.

player add success(player, **kwargs)

Called when a new player is successfully added to the current game (including when the first player is added).

player rotate(player num=None)

Rotates the game to the next player.

This method is called after a player's turn is over, so it's even used in single-player games between balls.

All it does really is set player to the next player's number.

Parameters player_num (*int*) – Lets you specify which player you want to rotate to. If None, it just rotates to the next player in order.

player_turn_start()

Called at the beginning of a player's turn.

Note this method is only called when a new player is first up. So if the same player shoots again due to an extra ball, this method is not called again.

```
remove_balls_in_play(balls=1)
```

Removes one or more balls from the current balls in play value.

Parameters balls – Int of the balls to add.

Note that if the number of balls removed would take the current balls in play count to less than zero, the number of balls in play will be set to zero.

If balls in play drops to zero, ball_ending() will be called.

```
request_player_add()
```

Called by any module that wants to add a player to an active game.

This method contains the logic to verify whether it's ok to add a player. (For example, the game must be on ball 1 and the current number of players must be less than the max number allowed.)

Assuming this method believes it's ok to add a player, it posts the boolean event *player_add_request* to give other modules the opportunity to deny it. (For example, a credits module might deny the request if there are not enough credits in the machine.)

If player_add_request comes back True, the event player_add_success is posted with a reference to the new player object as a player kwarg.

```
set_balls_in_play(balls)
```

Sets the number of balls in play to the value passed.

Parameters balls – Int of the new value of balls in play.

This method does not actually eject any new balls onto the playfield, rather, it just changes the game controller's count of the number of balls in play.

The balls in play value cannot be lower than 0 or higher than the number of balls known. This message will automatically set the balls in play to the nearest valid value if it's outside of this range.

If balls in play drops to zero, ball_ending() will be called.

```
\verb|setup_midgame_restart| (\textit{tag='start'}, \textit{time='1s'}, \textit{min\_ball=0})
```

Allows a long button press to restart the game.

```
shoot_again()
```

Called when the same player should shoot again.

```
slam_tilt()
```

```
start (buttons=None, hold time=None)
```

Automatically called when the Game machine mode becomes active.

```
stop()
```

tilt()

Called when the 'tilt' event is posted indicated the ball has tilted.

mpf.game.player module

Contains the Player class which reprsents a player in a pinball game.

```
class mpf.game.player.Player(machine)
    Bases: object
```

Base class for a player. One instance of this class is created for each player.

The Game class maintains a "player" attribute which always points to the current player. You can access this via game.player. (Or self.machine.game.player).

This class is responsible for tracking per-player variables. There are several ways they can be used:

player.ball = 0 (sets the player's 'ball' value to 0) print player.ball (prints the value of the player's 'ball' value)

If the value of a variable is requested but that variable doesn't exist, that variable will automatically be created (and returned) with a value of 0.

Every time a player variable is changed, an MPF is posted with the name "player_<name>". That event will have three parameters posted along with it:

•value (the new value)

•prev_value (the old value before it was updated)

•change (the change in the value)

For the 'change' parameter, it will attempt to subtract the old value from the new value. If that works, it will return the result as the change. If it doesn't work (like if you're not storing numbers in this variable), then the change parameter will be True if the new value is different and False if the value didn't change.

Some examples:

player.score = 0

Event posted: 'player_score' with Args: value=0, change=0, prev_value=0

player.score += 500

Event posted: 'player_score' with Args: value=500, change=500, prev_value=0

player.score = 1200

Event posted: 'player_score' with Args: value=1200, change=700, prev_value=500

monitor_enabled = False

Class attribute which specifies whether any monitors have been registered to track player variable changes.

$total_players = 0$

Tracks the the number of players in the game (starting with 1).

1.2.2 Module contents

1.3 mpf.media_controller package

1.3.1 Subpackages

mpf.media_controller.core package

Submodules

mpf.media_controller.core.display module

 $mpf.media_controller.core.font_manager\ module$

mpf.media_controller.core.keyboard module MC keyboard processor

```
{f class} \ {f mpf.media\_controller.core.keyboard.Keyboard} \ ({\it mc})
```

Bases: object

Base class which allows a computer keyboard to be used to similate switch activity in a pinball machine. This is good for testing purposes when you aren't sitting at the actual machine.

The Keyboard class gets its settings from the Machine Configuration Files in the [keymap] section.

This module uses a Pygame window to capture the key events.

Parameters mc – The main media controller object.

add_key_map (key, switch_name=None, toggle_key=False, invert=False, event_dict=None)
Adds an entry to the key_map which is used to see what to do when key events are received.

Parameters

- **key** The built-up string of the key combination which optionally includes modifier keys.
- **switch_name** String name of the switch this key combination is tied to.
- **toggle_key** Boolean as to whether this key should be a toggle key. (i.e. push on / push off).
- **invert** Boolean as to whether this key combination should be inverted. (Key down = switch inactive, key up = switch active.) Default is False.
- **event_dict** Dictionary of events with parameters that will be posted when this key combination is pressed. Default is None.

get_key_press_string(symbol, modifiers)

Converts a Pygame key symbol with modifiers into the string format that MPF uses in its internal key map.

Parameters

- symbol The Pygame symbol of the key.
- **modifiers** The Pygame modifier value for any modifier keys that were active along with this key event.

Returns: A string in the proper format MPF uses.

process_key_press (symbol, modifiers)

Processes a key press (key down) event by setting the switch and/or posting the event to MPF.

Parameters

- **symbol** The Pygame symbol of the key that was just pressed.
- **modifiers** The Pygame modifier value for any modifier keys that were active along with this key event.

process_key_release(symbol, modifiers)

Processes a key release (key up) event by setting the switch and/or posting the event to MPF.

Parameters

- **symbol** The Pygame symbol of the key that was just released.
- **modifiers** The Pygame modifier value for any modifier keys that were active along with this key event.

```
send_switch (name, state)
```

 ${\tt mpf.media_controller.core.keyboard.preload_check}\ ({\it mc})$

mpf.media_controller.core.language module Contains the parent class for MPF's Language module.

```
{\bf class} \; {\tt mpf.media\_controller.core.language.Language} \; ({\it machine}) \\
```

Bases: object

MPF module which handles text, audio, and video replacement of objects for multi-language environments.

Parameters machine – The main machine object

get_language()

Returns the string name of the current language.

get_text (text, language)

Returns a translated text string for a specific language string.

Parameters

- **text** The text string you'd like to get the replacement for.
- language The language you'd like to lookup for the replacement.

If the specific text string and language combination doesn't exist in the translation file, the original string is returned.

The string lookup is case-sensitive.

This method is similar to text(), except this method doesn't strip out the parentheses. (i.e. it's just used to look up what's "inside" the parentheses.)

set_language (language_string)

Sets the current language based on the string passed.

Parameters language_string – The string name of the language you want to set the machine to.

Language strings can be whatever you want, based on how you define them in your config file. It can be an actual language, like English or French, or it can simply be alternate assets, like "Kid-Friendly" versus "Mature."

This language change is instant, and you can safely call it often. Change languages for each player in the same game, or even in the middle of a ball!

text (text)

Translates a text string (or part of a text string) based on the current language setting.

Parameters text – The string of text you want to translate.

Returns: A translated string.

The incoming text string is searched for text within parentheses, and each of those segments is looked up for replacement. You can wrap the entire string in parentheses, or just part of it, or multiple parts.

A new, translated string is returned with the parentheses removed. If a translation is not found in the current language's translation strings, the original text is returned.

The string lookup is case-sensitive since different languages have different rules around casing.

It is not possible to display text with parentheses in it since this method will remove them. If this is something you need, contact us and we can add that feature.

mpf.media_controller.core.media_controller module

mpf.media_controller.core.modes module

```
\textbf{class} \; \texttt{mpf.media\_controller.core.modes.Mode} \, (\textit{machine}, \textit{config}, \textit{name}, \textit{path})
```

Bases: object

Parent class for in-game mode code.

active

configure_mode_settings(config)

Processes this mode's configuration settings from a config dictionary.

```
start (priority=None, callback=None, **kwargs)
```

Starts this mode.

Parameters

- **priority** Integer value of what you want this mode to run at. If you don't specify one, it will use the "Mode: priority" setting from this mode's configuration file.
- **kwargs Catch-all since this mode might start from events with who-knows-what keyword arguments.

Warning: You can safely call this method, but do not override it in your mode code. If you want to write your own mode code by subclassing Mode, put whatever code you want to run when this mode starts in the mode start method which will be called automatically.

```
stop(callback=None, **kwargs)
```

Stops this mode.

Parameters **kwargs – Catch-all since this mode might start from events with who-knows-what keyword arguments.

Warning: You can safely call this method, but do not override it in your mode code. If you want to write your own mode code by subclassing Mode, put whatever code you want to run when this mode stops in the mode stop method which will be called automatically.

```
class mpf.media_controller.core.modes.ModeController(machine)
     Bases: object
```

Parent class for the Mode Controller. There is one instance of this in MPF and it's responsible for loading, unloading, and managing all game modes.

dump()

Dumps the current status of the running modes to the log file.

```
register_load_method(load_method, config_section_name=None, **kwargs)
```

Used by system components, plugins, etc. to register themselves with the Mode Controller for anything that they a mode to do when its registered.

Parameters

- **load_method** The method that will be called when this mode code loads.
- **config_section_name** An optional string for the section of the configuration file that will be passed to the load_method when it's called.
- **kwargs Any additional keyword arguments specified will be passed to the load method.

Note that these methods will be called once, when the mode code is first initialized.

```
register_start_method (start_method, config_section_name=None, **kwargs)
```

Used by system components, plugins, etc. to register themselves with the Mode Controller for anything that they a mode to do when it starts.

Parameters

- **start_method** The method that will be called when this mode code loads.
- **config_section_name** An optional string for the section of the configuration file that will be passed to the start_method when it's called.
- **kwargs Any additional keyword arguments specified will be passed to the start_method.

Note that these methods will be called every single time this mode is started.

RemotedMethod is used by other modules that want to register a method to be called on mode_start or mode_stop.

```
__getnewargs___()
Return self as a plain tuple. Used by copy and pickle.
__getstate___()
Exclude the OrderedDict from pickling
__repr___()
Return a nicely formatted representation string

config_section
Alias for field number 1

kwargs
Alias for field number 2

method
Alias for field number 0
```

mpf.media_controller.core.show_controller module Manages the show effects in a pinball machine.

Parameters tocks_per_sec – The new tocks_per_second play rate.

If you want to change the playback speed by a percentage, you can access the current tocks_per_second rate via Show's tocks_per_second variable. So if you want to double the playback speed of your show, you could do something like:

```
self.your_show.change_speed(self.your_show.tocks_per_second*2)
```

Note that you can't just update the show's tocks_per_second directly because we also need to update self.secs_per_tock.

```
load_show_from_disk()
```

Plays a Show. There are many parameters you can use here which affect how the show is played. This includes things like the playback speed, priority, whether this show blends with others, etc. These are

all set when the show plays. (For example, you could have a Show file which lights a bunch of lights sequentially in a circle pattern, but you can have that circle "spin" as fast as you want depending on how you play the show.)

Parameters

- repeat Boolean of whether the show repeats when it's done.
- **priority** Integer value of the relative priority of this show. If there's ever a situation where multiple shows want to control the same item, the one with the higher priority will win. ("Higher" means a bigger number, so a show with priority 2 will override a priority 1.)
- **blend** Boolean which controls whether this show "blends" with lower priority shows and scripts. For example, if this show turns a light off, but a lower priority show has that light set to blue, then the light will "show through" as blue while it's off here. If you don't want that behavior, set blend to be False. Then off here will be off for sure (unless there's a higher priority show or command that turns the light on). Note that not all item types blend. (You can't blend a coil or event, for example.)
- hold Boolean which controls whether the lights or LEDs remain in their final show state when the show ends.
- tocks_per_sec Integer of how fast your show runs ("Playback speed," in other words.) Your Show files specify action times in terms of 'tocks', like "make this light red for 3 tocks, then off for 4 tocks, then a different light on for 6 tocks. When you play a show, you specify how many tocks per second you want it to play. Default is 30, but you might even want tocks_per_sec of only 1 or 2 if your show doesn't need to move than fast. Note this does not affect fade rates. So you can have tocks_per_sec of 1 but still have lights fade on and off at whatever rate you want. Also the term "tocks" was chosen so as not to confuse it with "ticks" which is used by the machine run loop.
- **start_location** Integer of which position in the show file the show should start in. Usually this is 0 but it's nice to start part way through. Also used for restarting shows that you paused.
- callback A callback function that is invoked when the show is stopped.
- num_repeats Integer of how many times you want this show to repeat before stopping. A value of 0 means that it repeats indefinitely. Note this only works if you also have repeat=True.

```
stop (reset=True, hold=None) Stops a Show.
```

Note you can also use this method to clear a stopped show's held lights and LEDs by passing hold=False.

Parameters reset – Boolean which controls whether the show will reset its current position back to zero. Default is True.

Manages all the shows in a pinball machine.

'shows' are coordinated display & event sequences. The ShowController handles priorities, restores, running and stopping Shows, etc. There should be only one per machine.

Parameters machine – Parent machine object.

```
add_show_player_show(event, settings)
```

Bases: object

Parent class for a Slide object.

MPF uses the concept of "slides" (think PowerPoint) as a collection of various display elements that should be shown on the display. There can be more than one slides defined at any given time, though only one is active at any given time. (Unless a transitioning is happening which transitions between an old slide and a new slide.

Parameters

- **mpfdisplay** The display object this slide is for.
- name String name of this slide.
- **persist** Boolean as for whether this slide should be automatically destroyed once it's not shown on the display anymore.
- removal_key A unique key that can identify this slide for its removal later.
- **expire_ms** How many ms this slide should live for. Default is 0 which means it will not automatically be removed.
- mode A reference to the Mode which created this slide.

name

The string name of this slide.

elements

List of display elements that are active on this slide.

surface

Reference to the Pygame surface this slide uses.

priority

Integer of the relative priority of this slide. Lower priority slides won't be shown if a higher priority slide is currently active. (A slide of the same priority as the active slide can displace it.) Note that 'higher' numbers equal 'higher' priority, i.e. Priority 2 is higher than Priority 1.

active

Boolean as to whether this slide is currently active. Active slides will constantly ensure that their display elements are refreshed, so this saves CPU cycles by not keeping non-active slides up-to-date.

persist

Boolean as to whether this slide should persist when it becomes non-active. A value of False means that this slide will be destroyed as soon as it's no longer active.

width

Width of this slide, in pixels.

height

Height of this slide, in pixels.

depth

Integer value of the color depth, either 8 or 24.

palette

The Pygame palette this slide uses. (8-bit only)

removal key

Unique identifier that can be used later to remove this slide.

expire_ms

Integer of ms that will cause this slide to automatically remove itself. The timer doesn't start until the slide is shown.

add_element (*element_type*, *name=None*, *x=None*, *y=None*, *h_pos=None*, *v_pos=None*, **kwargs) Adds a display element to the slide.

Parameters

- **element_type** String name of the type of element you're adding. (i.e. 'Text', 'Image', 'Shape', etc.).
- name Friendly name of the new element.
- x 'x' position of the upper left corner of this element. This is either the 'x' position, or an offset in pixels, or an offset percentage. See the documentation for the calc_position method for details.
- y 'y' position or offset, like x above.
- **h_pos** Relative horizontal position: left, center, or right.
- **v_pos** Relative verical position: top, center, or bottom.
- **kwargs A list of key/value settings for the element you're adding.

Returns

slide.

name: String name of the element. element: The newly-created display element object. layer: Integer of the relative layer of this element on the

x: x position of the upper left corner of this element on the slide.

y: y position of the upper left corner of this element on the slide.

Return type An element dictionary, which includes

```
add_ready_callback (callback, **kwargs)
```

```
blit_8bit_alpha (source_surface, dest_surface, x, y)
```

Blits an 8-bit surface onto another using the DMD-style alpha values.

Parameters

- **source_surface** Source 8-bit pygame surface
- **dest_surface** Destination 8-bit Pygame surface the source surface will be blitted to.
- x x position of the upper left corner of where the source surface will be blitted to on the destination surface.
- y y position (goes with x above)

Note this blit is expensive, so it's only used when it's specifically called for.

clear()

Removes all elements from the slide and resets the slide to all black.

get_subsurface (rect, layer=0)

Returns a surface of the slide based on the rect passed, but only for the elements of the passed layer and lower

Parameters

- rect A pygame Rect object which defines the rectangle that will be returned.
- layer Optional layer which defines the highest layer element that should be included in the surface.

Returns: A Pygame surface.

pending_elements = None

Elements which have related assets that are still loading in a background thread.

ready()

ready_callbacks = None

List of callback/kwarg tuples which will be called when all the elements of this slide are ready to be shown.

refresh(force dirty=False)

Refreshes the slide by clearing it, and updating all the display elements.

Parameters force_dirty – Boolean which controls whether you want to force all the elements to be marked as dirty so they're regenerated.

remove()

Removes the slide. If this slide is active, the next-highest priority slide will automatically be shown.

remove element(name)

Removes a display element from the slide.

Parameters name – String name of the display element you want to remove.

schedule_removal (removal_time=None)

Schedules this slide to automatically be removed.

Parameters removal_time – MPF time string of when this slide should be removed. If no time is specified, the slide's existing removal time is used. If the slide has no existing time, the slide will not be removed.

show()

Shows this slide by making it active.

This is immediate. If you want a transition, use the MPFDisplay.transition() method.

This method will only show the slide if its priority is the same or higher than the existing slide.

update()

Updates this slide by calling each display element's update() method, and blits the results if there's an update.

mpf.media_controller.core.slide_builder module Contains the parent classes for MPF's display SlideBuilder class.

```
class mpf.media_controller.core.slide_builder.SlideBuilder (machine)
    Bases: object
```

Parent class for SlideBuilder objects which are things you configure via the machine config files that let you display text messages based on game events. You can use this to show game status, players, scores, etc. Any setting that is available via the text method of the display controller is available here, including positioning, fonts, size, delays, etc.

Parameters machine – The main machine object.

build_slide (*settings*, *display=None*, *slide_name=None*, *priority=None*, *mode=None*, **kwargs)
Builds a slide from a SlideBuilder set of keyword arguments.

Parameters

- **settings** Python dictionary of settings for this slide. This includes settings for the various Display Elements as well as any transition.
- **display** String name of the display this slide is being built for.
- **slide_name** String name of the slide that's being built. If this slide exists, the elements here will be added to that slide. If it doesn't exist, a new slide will be created. If no slide name is passed, a new slide will be created and given a UUID4 name.
- **priority** Integer of the priority of this slide.
- mode A reference to the Mode instance that built this slide. Used to make sure that each mode keeps at least one active slide.
- **kwargs Catch all since this method is often registered as a callback for events which means there could be random event keyword argument pairs attached.

Returns: Slide object from the slide it built (whether or not it's showing now).

```
preprocess_settings (settings, base_priority=0)
```

Takes an unstructured list of slide_player settings and processed them so they can be displayed.

Parameters

- settings A list of dictionary of slide_player settings for a slide.
- base_priority An integer that will be added to slide's priority from the config settings.

Returns: A python list with all the settings in the right places.

This method does a bunch of things, like making sure all the needed values are there, and moving certain things to the first and last elements when there are multiple elements used on one slide. (For example, if one of the elements wants to clear the slide, it has to happen first. If there's a transition, it has to happen last after the slide is built, etc.

The returned settings list can be safely called with the by display() with the preprocessed=True flag.

```
process_config (config, mode=None, priority=0)
unload_slide_events (removal_tuple)
```

mpf.media_controller.core.sound module MPF plugin for sounds. Includes SoundController, Channel, Sound, Track, and StreamTrack parent classes.

Parent class that holds a Pygame sound channel. One or more of these are tied to an MPF Track.

Parameters

• machine – The main machine object.

- parent_track The MPF track object this channel belongs to.
- **channel_number** Integer number that is used to identify this channel.

```
play (sound, **settings)
```

Plays a sound on this channel.

Parameters

- sound The sound object to play.
- **settings Additional settings for this sound's playback.

sound_is_done()

Indicates that the sound that was playing on this channel is now done.

This is the callback method that's automatically called by Pygame. It will check the queue and automatically play any queued sounds.

```
class mpf.media_controller.core.sound.Sound (machine, config, file_name, asset_manager)
    Bases: mpf.system.assets.Asset (page 64)

play (loops=0, priority=0, fade_in=0, volume=1, **kwargs)
    Plays this sound.
```

Parameters

- **loops** Integer of how many times you'd like this sound to repeat. A value of -1 means it will loop forever.
- **priority** The relative priority of this sound which controls what happens if the track this sound is playing on is playing the max simultaneous sounds.
- fade_in MPF time string for how long this sound should fade in when it starts.
- **volume** Volume for this sound as a float between 0.0 and 1.0. Zero is mute, 1 is full volume, anything in between is in between.
- **kwargs Catch all since this method might be used as an event callback which could include random kwargs.

```
stop (fade_out=0, reset=True, **kwargs)
Stops this sound playing.
```

Parameters

- fade_out MPF time string for how long this sound will fade out as it stops.
- reset Boolean for whether this sound should reset its playback position to the beginning.
 Default is True.
- **kwargs Catch all since this method might be used as an event callback which could include random kwargs.

Parent class for the sound controller which is responsible for all audio, sounds, and music in the machine. There is only one of these per machine.

Parameters machine – The main machine controller object.

```
create_track (name, config=None)
```

Creates a new MPF track add registers in the central track list.

Parameters

- name String name of this track used for identifying where sounds are played.
- config Config dictionary for this track.

Note: "Tracks" in MPF are like channels.. you might have a "music" track, a "voice" track, a "sound effects" track, etc.

```
get_volume()
```

```
register_sound_event (config, priority=0, block=False)
```

Sets up game sounds from the config file.

Parameters config – Python dictionary which contains the game sounds settings.

```
register_sound_events (config, mode=None, priority=0)
```

```
set_volume (volume=None, change=None, **kwargs)
```

Sets the overall volume of the sound system.

Parameters

- **volume** The new volume level, a floating point value between 0.0 and 1.0. 1.0 is full volume. 0.0 is mute.
- change A positive or negative value between 0.0 and 1.0 of a change in volume that will be made.
- **kwargs** Not used here. Included because this method is often called from events which might contain additional kwargs.

Note that the volume can never be increased above 1.0. This sound volume level only affects MPF. You might have to set the overall system sound to in the OS.

```
unregister_sound_event (key)
unregister_sound_events (key_list)
class mpf.media_controller.core.sound.StreamTrack (machine, config)
    Bases: object
```

Parent class for MPF's "Stream" track which corresponds to Pygame's music channel.

Parameters

- machine The main machine object.
- **config** Python dictionary containing the configuration settings for this track.

Sounds played on this track are streamed from disk rather than loaded into memory. This is good for background music since those files can be large and there's only one playing at a time.

```
fadeout (ms)
```

Fades the sound out.

Parameters ms – The number of milliseconds to fade out the sound.

```
pause()
```

Pauses the current sound and remembers the current position so playback can be resumed from the same point via the unpause() method.

```
play (sound, **settings)
```

Plays a sound on this track.

Parameters

• sound – The MPF sound object to play.

• **settings – Additional settings for this sound's playback.

This stream track only supports playing one sound at a time, so if you call this when a sound is currently playing, the new sound will stop the current sound.

stop (sound=None)

Stops the playing sound and resets the current position to the beginning.

unpause()

Resumes playing of a previously-paused sound. If the sound was not paused, it starts playing it from the beginning.

Parent class for an MPF track. Each sound track in MPF can be made up of one or more Pygame sound channels to support multiple simultaneous sounds.

Parameters

- machine The main machine controller object.
- name A string of the name this channel will be referred to, such as "voice" or "sfx."
- global_channel_list A python list which keeps track of the global Pygame channels in
 use.
- **config** A python dictionary containing the configuration settings for this track.

create_channel (machine, global_channel_list)

Factory method which creates a Pygame sound channel to be used with this track.

Parameters

- machine The main machine object.
- global_channel_list A list which contains the global list of Pygame channels in use by MPF.

get_sound()

Returns the next sound from the queue to be played.

Returns: A tuple of the sound object, the priority, and dictionary of additional settings for tha sound. If the queue is empty, returns None.

This method will ensure that the sound returned has not expired. If the next sound in the queue is expired, it removes it and returns the next one.

```
play (sound, priority, **settings)
```

Plays a sound on this track.

Args: sound: The MPF sound object you want to play. priority: The relative priority of this sound. **settings: One or more additional settings for this playback.

This method will automatically find an available Pygame channel to use.

If this new sound has a higher priority than the lowest playing sound, it will interrupt that sound to play. Otherwise it will be added to the queue to be played when a channel becomes available.

```
queue_sound (sound, priority, exp_time=None, **settings)
```

Adds a sound to the queue to be played when a Pygame channel becomes free.

Parameters

• sound – The MPF sound object.

- **priority** The priority of this sound.
- **exp_time** Real world time of when this sound will expire. (It will not play if the queue is freed up after it expires.)
- **settings Additional settings for this sound's playback.

Note that this method will insert this sound into a position in the queue based on its priority, so highest-priority sounds are played first.

```
stop(sound)
mpf.media_controller.core.sound.asset_class
    alias of Sound(page 37)
mpf.media_controller.core.sound.preload_check(machine)
mpf.media_controller.core.window module
```

Module contents

mpf.media controller.decorators package

Submodules

mpf.media_controller.decorators.blink module

Module contents

mpf.media controller.display modules package

Submodules

mpf.media_controller.display_modules.dmd module

 $mpf.media_controller.display_modules.playfield_lights\ module$

Module contents

mpf.media controller.elements package

Submodules

mpf.media_controller.elements.animation module

mpf.media_controller.elements.image module

mpf.media controller.elements.movie module

mpf.media_controller.elements.shape module

mpf.media_controller.elements.text module

mpf.media_controller.elements.virtualdmd module

Module contents

mpf.media_controller.transitions package

Submodules

mpf.media_controller.transitions.move_in module

mpf.media_controller.transitions.move_out module

Module contents

1.3.2 Submodules

mpf.media_controller.version module

1.3.3 Module contents

1.4 mpf.platform package

1.4.1 Submodules

mpf.platform.fadecandy module

Contains code for an FadeCandy hardware for RGB LEDs.

```
class mpf.platform.fadecandy.FadeCandyOPClient (machine, config)
     Bases: mpf.platform.openpixel.OpenPixelClient (page 47)
```

Base class of an OPC client which connects to a FadeCandy server.

Parameters

- machine The main MachineController instance.
- config Dictionary which contains configuration settings for the OPC client.

This class implements some FadeCandy-specific features that are not available with generic OPC implementations.

disable_dithering()

Disables the FadeCandy's smooth dithering of color values.

Note that this setting is written to the FadeCandy's firmware. It will persist until it's changed. It is enabled by default.

disable_interpolation()

Disables the FadeCandy's keyframe interpolation.

See the documentation for the enable_interpolation() method for a description of how this works.

Note that this setting is written to the FadeCandy's firmware. It will persist until it's changed. It is enabled by default.

enable dithering()

Enables the FadeCandy's smooth dithering of color values.

Note that this setting is written to the FadeCandy's firmware. It will persist until it's changed. It is enabled by default.

From the FadeCandy documentation:

Fadecandy internally represents colors with 16 bits of precision per channel, or 48 bits per pixel. Why 48-bit color? In combination with our dithering algorithm, this gives a lot more color resolution. It's especially helpful near the low end of the brightness range, where stair-stepping and color popping artifacts can be most apparent.

enable_interpolation()

Enables the FadeCandy's keyframe interpolation.

From the FadeCandy documentation:

By default, Fadecandy interprets each frame it receives as a keyframe. In-between these keyframes, Fadecandy will generate smooth intermediate frames using linear interpolation. The interpolation duration is determined by the elapsed time between when the final packet of one frame is received and when the final packet of the next frame is received.

This scheme works well when frames are arriving at a nearly constant rate. If frames suddenly arrive slower than they had been arriving, interpolation will proceed faster than it optimally should, and one keyframe will hold steady until the next keyframe arrives. If frames suddenly arrive faster than they had been arriving, Fadecandy will need to jump ahead in order to avoid falling behind.

When enabled, MPF will send an update to the FadeCandy on every machine tick (regardless of whether there are updates for the LEDs) in order to maintain a consistent update rate.

Note that this setting is written to the FadeCandy's firmware. It will persist until it's changed. It is enabled by default.

set_gamma (gamma)

Sets the gamma correction of the FadeCandy. Specifically this is the exponent for the nonlinear portion of the brightness curve.

Parameters gamma – Float of the new gamma. Default is 2.5.

set_global_color_correction()

Writes the current global color correction settings (gamma, white point, linear slope, and linear cutoff) to the FadeCandy server.

set_linear_cutoff(linearcutoff)

Sets the of the linear cutoff of the FadeCandy.

From the FadeCandy documentation:

By default, brightness curves are entirely nonlinear. By setting *linearcutoff* to a nonzero value, though, a linear area may be defined at the bottom of the brightness curve.

The linear section, near zero, avoids creating very low output values that will cause distracting flicker when dithered. This isn't a problem when the LEDs are viewed indirectly such that the flicker is below the threshold of perception, but in cases where the flicker is a problem this linear section can eliminate it entierly at the cost of some dynamic range. To enable the linear section, set *linearcutoff* to some nonzero value. A good starting point is 1/256.0, corresponding to the lowest 8-bit PWM level.

Parameters linearcutoff – Float of the new linear cutoff. Default is 0.0.

```
set_linear_slope (linearslope)
```

Sets the linear slope (output / input) of the linear section of the brightness curve.

Parameters linearslope – Float of the new linear slope. Default is 1.0.

```
set_whitepoint (whitepoint)
```

Sets the white point of the FadeCandy. This is a vector of [red, green, blue] values to multiply by colors prior to gamma correction.

Parameters whitepoint – A three-item list of floating point values. Default is [1.0, 1.0, 1.0]

```
write_firmware_options()
```

Writes the current firmware settings (keyframe interpolation and dithering) to the FadeCandy hardware.

```
class mpf.platform.fadecandy.HardwarePlatform(machine)
    Bases: mpf.platform.openpixel.HardwarePlatform(page 47)
```

Base class for the open pixel hardware platform.

Parameters machine - The main MachineController object.

mpf.platform.fast module

Contains the hardware interface and drivers for the FAST Pinball platform hardware, including the FAST Core and WPC controllers as well as FAST I/O boards.

```
class mpf.platform.fast.FASTDMD (machine, sender)
     Bases: object
     tick()
     update (data)
class mpf.platform.fast.FASTDirectLED (number)
     Bases: object
     color (color)
          Instantly sets this LED to the color passed.
              Parameters
                   • color – a 3-item list of integers representing R, G, and B values,
                   • each. (0-255) -
     disable()
          Disables (turns off) this LED instantly. For multi-color LEDs it turns all elements off.
     enable()
     fade (color, fade_ms)
     hex_to_rgb (value)
```

```
rgb_to_hex(rgb)
class mpf.platform.fast.FASTDriver(config, sender)
     Bases: object
     Base class for drivers connected to a FAST Controller.
     disable()
          Disables (turns off) this driver.
     enable()
          Enables (turns on) this driver.
     pulse(milliseconds=None)
          Pulses this driver.
     pwm (on_ms=10, off_ms=10, original_on_ms=0, now=True)
          Enables this driver in a pwm pattern.
class mpf.platform.fast.FASTGIString(number, sender)
     Bases: object
     off()
     on (brightness=255, fade\_ms=0, start=0)
class mpf.platform.fast.FASTMatrixLight (number, sender)
     Bases: object
     off()
          Disables (turns off) this matrix light.
     on (brightness=255, fade_ms=0, start=0)
          Enables (turns on) this driver.
class mpf.platform.fast.FASTSwitch (number, debounce_open, debounce_close, sender)
     Bases: object
class mpf.platform.fast.HardwarePlatform(machine)
     Bases: mpf.system.platform.Platform(page 95)
     Platform class for the FAST hardware controller.
          Parameters machine - The main MachineController instance.
     clear hw rule(sw name)
          Clears a hardware rule.
          This is used if you want to remove the linkage between a switch and some driver activity. For example, if
          you wanted to disable your flippers (so that a player pushing the flipper buttons wouldn't cause the flippers
          to flip), you'd call this method with your flipper button as the sw_num.
              Parameters sw_name – The string name of the switch whose rule you want to clear.
     configure_dmd()
          Configures a hardware DMD connected to a FAST controller.
     configure_driver (config, device_type='coil')
     configure_gi (config)
     configure_led(config)
     configure matrixlight (config)
```

configure switch (config)

Configures the switch object for a FAST Pinball controller.

FAST Controllers support two types of switches: *local* and *network*. Local switches are switches that are connected to the FAST controller board itself, and network switches are those connected to a FAST I/O board.

MPF needs to know which type of switch is this is. You can specify the switch's connection type in the config file via the connection: setting (either local or network).

If a connection type is not specified, this method will use some intelligence to try to figure out which default should be used.

If the DriverBoard type is fast, then it assumes the default is network. If it's anything else (wpc, system11, bally, etc.) then it assumes the connection type is local. Connection types can be mixed and matched in the same machine.

```
get_switch_states()
int_to_hex_string(source_int)
```

Converts an int from 0-255 to a one-byte (2 chars) hex string, with uppercase characters.

```
normalize_hex_string(source_hex, num_chars=2)
```

Takes an incoming hex value and converts it to uppercase and fills in leading zeros.

Parameters

- **source_hex** Incoming source number. Can be any format.
- num_chars Total number of characters that will be returned. Default is two.

Returns: String, uppercase, zero padded to the num_chars.

Example usage: Send "c" as source_hex, returns "0C".

```
null_dmd_sender(*args, **kwargs)
process_received_message(msg)
```

Sends an incoming message from the FAST controller to the proper method for servicing.

```
receive_dx (msg)

receive_id (msg)

receive_local_closed (msg)

receive_local_open (msg)

receive_lx (msg)

receive_ni (msg)

receive_nw_closed (msg)

receive_nw_open (msg)

receive_px (msg)

receive_rx (msg)

receive_sa (msg)

receive_sx (msg)

receive_wd (msg)

receive_wd (msg)
```

register processor connection (name, communicator)

Once a communication link has been established with one of the processors on the FAST board, this method lets the communicator let MPF know which processor it's talking to.

This is a separate method since we don't know which processor is on which serial port ahead of time.

tick()

update_leds()

Updates all the LEDs connected to a FAST controller. This is done once per game loop for efficiency (i.e. all LEDs are sent as a single update rather than lots of individual ones).

Also, every LED is updated every loop, even if it doesn't change. This is in case some interference causes a LED to change color. Since we update every loop, it will only be the wrong color for one tick.

Hardware Rules are used to configure the hardware controller to automatically change driver states based on switch changes. These rules are completely handled by the hardware (i.e. with no interaction from the Python game code). They're used for things that you want to happen fast, like firing coils when flipper buttons are pushed, slingshots, pop bumpers, etc.

You can overwrite existing hardware rules at any time to change or remove them.

Parameters

- sw Which switch you're creating this rule for. The parameter is a reference to the switch object itsef.
- **sw_activity** Int which specifies whether this coil should fire when the switch becomes active (1) or inactive (0)
- coil_action_ms Int of the total time (in ms) that this coil action should take place. A value of -1 means it's forever. A value of 0 means the coil disables itself when this switch goes into the state specified.
- coil The coil object this rule is for.
- pulse_ms How long should the coil be pulsed (ms)
- pwm_on Integer 0 (off) through 8 (100% on) for the initial pwm power of this coil
- **pwm_off** pwm level 0-8 of the power of this coil during the hold phase (after the initial kick).
- delay Not currently implemented
- recycle_time How long (in ms) should this switch rule wait before firing again. Put another way, what's the "fastest" this rule can fire? This is used to prevent "machine gunning" of slingshots and pop bumpers. Do not use it with flippers.
- **debounced** Should the hardware fire this coil after the switch has been debounced?
- **drive_now** Should the hardware check the state of the switches when this rule is firts applied, and fire the coils if they should be? Typically this is True, especially with flippers because you want them to fire if the player is holding in the buttons when the machine enables the flippers (which is done via several calls to this method.)

Bases: object

```
identify connection()
```

Identifies which processor this serial connection is talking to.

```
query_fast_io_boards()
```

Queries the NET processor to see if any FAST IO boards are connected, and if so, queries the IO boards to log them and make sure they're the proper firmware version.

```
send (msg)
```

Sends a message to the remote processor over the serial connection.

Parameters msg – String of the message you want to send. THe <CR> character will be added automatically.

```
stop()
```

Stops and shuts down this serial connection.

mpf.platform.openpixel module

Contains code for an Open Pixel Controller hardware for RGB LEDs.

```
class mpf.platform.openpixel.HardwarePlatform(machine)
```

Bases: mpf.system.platform.Platform(page 95)

Base class for the open pixel hardware platform.

Parameters machine - The main MachineController object.

```
configure_led(config)
```

```
class mpf.platform.openpixel.OPCThread(machine, sending_queue, config)
```

Bases: threading. Thread

Base class for the thread that connects to the OPC server.

Parameters

- machine The main MachineController instance.
- queue The Queue() object that receives OPC messages for the OPC server.
- config Dictionary of configuration settings.

The OPC connection is handled in a separate thread so it doesn't bog down the main MPF machine loop if there are connection problems.

connect()

Connects to the OPC server.

Returns True on success. False if it was unable to connect.

This method also tracks and respects connection_attempts and max_connection_attempts.

disconnect()

Disconnects from the OPC server.

done()

Exits the thread and causes MPF to shut down.

run()

Thread run loop.

```
class mpf.platform.openpixel.OpenPixelClient (machine, config)
```

Bases: object

Base class of an OPC client which connects to a FadeCandy server.

Parameters

- machine The main MachineController instance.
- **server** String name of the server to connect to.
- **port** Int of the TCP port of the server to connect to.

add pixel(channel, led)

Adds a pixel to the list that will be sent to the OPC server.

Parameters

- **channel** Integer of the OPC channel this pixel is on.
- **led** Integer of the pixel number (i.e. its position in the list) for this pixel.

This is needed since MPF will process LED device entries in random order, so if (for example) we get a call to setup LED #20, then we need we make sure we have 19 items on the list before it.

send (message)

Puts a message on the queue to be sent to the OPC server.

Parameters message – The raw message you want to send. No processing is done on this. It's sent however it comes in.

```
set_pixel_color (channel, pixel, color)
```

Sets an invidual pixel color.

Parameters

- channel Int of the OPC channel for this pixel.
- **pixel** Int of the number for this pixel on that channel.
- **color** 3-item list or tuple of (red, green, blue) color values, each an integer between 0-255.

tick()

Called once per machine loop to update the pixels.

update_pixels (pixels, channel=0)

Send the list of pixel colors to the OPC server

Parameters

- **pixels** A list of 3-item iterables (tuples or lists). Each item is a 0-255 value of the intensity of the red, green, and blue values for the pixel. The first item in the list is the first pixel on the channel, the second item is the second one, etc.
- channel Which OPC channel the pixel data will be written to.

Returns True on success. False if it was unable to connect to the OPC server.

Note that you must send color data for all the pixels in a channel (or all the pixels up until the point you want. e.g. if you have 30 LEDs on the channel and you just want to update LED #10, then you need to send pixel data for the first 10 pixels.)

```
class mpf.platform.openpixel.OpenPixelLED (opc_client, channel, led)
    Bases: object
```

color (color)

mpf.platform.p3_roc module

Contains the drivers and interface code for pinball machines which use the Multimorphic P3-ROC hardware controllers.

This code can be used with P-ROC driver boards, or with Stern SAM, Stern Whitestar, Williams WPC, or Williams WPC95 driver boards.

Much of this code is from the P-ROC drivers section of the pyprocgame project, written by Adam Preble and Gerry Stellenberg. It was originally released under the MIT license and is released here under the MIT License.

More info on the P3-ROC hardware platform: http://pinballcontrollers.com/

Original code source on which this module was based: https://github.com/preble/pyprocgame

If you want to use the Mission Pinball Framework with P3-ROC hardware, you also need libpinproc and pypinproc. More info: http://www.pinballcontrollers.com/forum/index.php?board=10.0

```
class mpf.platform.p3_roc.DriverAlias (key, value)
    Bases: object
    decode (addr)
    matches (addr)

class mpf.platform.p3_roc.HardwarePlatform (machine)
    Bases: mpf.system.platform.Platform (page 95)
```

Platform class for the P3-ROC hardware controller.

Parameters machine – The MachineController instance.

machine

The MachineController instance.

proc

The P3-ROC pinproc.PinPROC device.

machine_type

Constant of the pinproc.MachineType

```
clear hw rule(sw name)
```

Clears a hardware rule.

This is used if you want to remove the linkage between a switch and some driver activity. For example, if you wanted to disable your flippers (so that a player pushing the flipper buttons wouldn't cause the flippers to flip), you'd call this method with your flipper button as the *sw_num*.

Parameters sw_num (*int*) – The number of the switch whose rule you want to clear.

```
configure_dmd()
```

The P3-ROC does not support a physical DMD, so this method does nothing. It's included here in case it's called by mistake.

```
configure_driver (config, device_type='coil')
```

Creates a P3-ROC driver.

Typically drivers are coils or flashers, but for the P3-ROC this is also used for matrix-based lights.

Parameters

- config Dictionary of settings for the driver.
- **device_type** String with value of either 'coil' or 'switch'.

Returns A reference to the PROCDriver object which is the actual object you can use to pulse(), patter(), enable(), etc.

configure_gi(config)

Configures a P3-ROC GI string light.

configure_led(config)

Configures a P3-ROC RGB LED controlled via a PD-LED.

configure matrixlight (config)

Configures a P3-ROC matrix light.

configure_switch(config)

Configures a P3-ROC switch.

Parameters

- **config** Dictionary of settings for the switch. In the case of the P3-ROC, it uses the following:
- **number** The number (or number string) for the switch as specified in the machine configuration file.
- **debounce** Boolean which specifies whether the P3-ROC should debounce this switch first before sending open and close notifications to the host computer.

Returns

A reference to the switch object that was just created. proc_num: Integer of the actual hardware switch number the P3-ROC

uses to refer to this switch. Typically your machine configuration files would specify a switch number like *SD12* or 7/5. This *proc_num* is an int between 0 and 255.

state [An integer of the current hardware state of the switch, used] to set the initial state state in the machine. A value of 0 means the switch is open, and 1 means it's closed. Note this state is the physical state of the switch, so if you configure the switch to be normally-closed (i.e. "inverted" then your code will have to invert it too.) MPF handles this automatically if the switch type is 'NC'.

Return type switch

tick()

Checks the P3-ROC for any events (switch state changes).

Also tickles the watchdog and flushes any queued commands to the P3-ROC.

write_hw_rule (sw, sw_activity, coil_action_ms, coil=None, pulse_ms=0, pwm_on=0, pwm_off=0, delay=0, recycle_time=0, debounced=True, drive_now=False)

Used to write (or update) a hardware rule to the P3-ROC.

Hardware Rules are used to configure the P3-ROC to automatically change driver states based on switch changes. These rules are completely handled by the P3-ROC hardware (i.e. with no interaction from the Python game code). They're used for things that you want to happen fast, like firing coils when flipper buttons are pushed, slingshots, pop bumpers, etc.

You can overwrite existing hardware rules at any time to change or remove them.

Parameters

• sw – switch object Which switch you're creating this rule for. The parameter is a reference to the switch object itsef.

- sw_activity int Do you want this coil to fire when the switch becomes active (1) or inactive (0)
- **coil_action_ms** int The total time (in ms) that this coil action should take place. A value of -1 means it's forever.
- coil coil object Which coil is this rule controlling
- pulse_ms int How long should the coil be pulsed (ms)
- **pwm_on** int If the coil should be held on at less than 100% duty cycle, this is the "on" time (in ms).
- **pwm_off** int If the coil should be held on at less than 100% duty cycle, this is the "off" time (in ms).
- **delay** int Not currently implemented for the P3-ROC hardware
- recycle_time int How long (in ms) should this switch rule wait before firing again. Put another way, what's the "fastest" this rule can fire? This is used to prevent "machine gunning" of slingshots and pop bumpers. Do not use it with flippers. Note the P3-ROC has a non-configurable delay time of 125ms. (So it's either 125ms or 0.) So if you set this delay to anything other than 0, it will be 125ms.
- debounced bool Should the P3-ROC fire this coil after the switch has been debounced?
 Typically no.
- **drive_now** bool Should the P3-ROC check the state of the switches when this rule is firts applied, and fire the coils if they should be? Typically this is True, especially with flippers because you want them to fire if the player is holding in the buttons when the machine enables the flippers (which is done via several calls to this method.)

Base class for coils connected to a P3-ROC that are controlled via P3-ROC driver boards (i.e. the PD-16 board).

This class is only used when the P3-ROC is configured to use P3-ROC driver boards such as the PD-16 or PD-8x8. i.e. not when it's operating in WPC or Stern mode.

```
aliases = None
configure_globals (proc, lamp_source_bank_list, enable=True)
get_globals (config)
get_proc_number (device_type, number_str)
    Returns the P3-ROC number for the requested driver string.
```

This most of most harding to the requested driver string.

This method uses the driver string to look in the indexes list that was set up when the PDBs were configured. The resulting P3-ROC index * 3 is the first driver number in the group, and the driver offset is to that.

```
indexes = []
     initialize_drivers(proc)
     proc = None
class mpf.platform.p3_roc.PDBLED (board, address, proc_driver, invert=False)
     Bases: object
     Represents an RGB LED connected to a PD-LED board.
     color (color)
          Instantly sets this LED to the color passed.
              Parameters
                  • color – a 3-item list of integers representing R, G, and B values,
                  • each. (0-255) -
     disable()
          Disables (turns off) this LED instantly. For multi-color LEDs it turns all elements off.
     enable()
          Enables (turns on) this LED instantly. For multi-color LEDs it turns all elements on.
     fade (color, fade_ms)
     normalize_color(color)
class mpf.platform.p3_roc.PDBLight (pdb, number_str)
     Bases: object
     Base class for lights connected to a PD-8x8 driver board.
     dedicated_bank()
     dedicated_output()
     is_direct_lamp(string)
     is_pdb_lamp (string)
     sink_bank()
     sink_board()
     sink_output()
     source bank()
     source board()
     source_output()
     split_matrix_addr_parts (string)
          Input is of form C-Ax-By-z:R-Ax-By-z or C-x/y/z:R-x/y/z or aliasX:aliasY. We want to return only the
          address part: Ax-By-z, x/y/z, or aliasX. That is, remove the two character prefix if present.
class mpf.platform.p3_roc.PDBSwitch (pdb, number_str)
     Bases: object
     Base class for switches connected to a P3-ROC.
     parse_matrix_num (num_str)
     proc_num()
```

```
class mpf.platform.p3_roc.PROCDriver (number, proc_driver)
     Bases: object
     Base class for drivers connected to a P3-ROC. This class is used for all drivers, regardless of whether they're
     connected to a P-ROC driver board (such as the PD-16 or PD-8x8) or an OEM driver board.
     disable()
          Disables (turns off) this driver.
     enable()
          Enables (turns on) this driver.
     future_pulse (milliseconds=None, timestamp=0)
           Enables this driver for milliseconds at P3-ROC timestamp: timestamp. If no parameter is provided for
           milliseconds, pulse_ms is used. If no parameter is provided or timestamp, 0 is used. ValueError will
           be raised if milliseconds is outside of the range 0-255.
     pulse (milliseconds=None)
           Enables this driver for milliseconds.
           ValueError will be raised if milliseconds is outside of the range 0-255.
     pwm (on_ms=10, off_ms=10, original_on_ms=0, now=True)
           Enables a pitter-patter sequence.
           It starts by activating the driver for original_on_ms milliseconds. Then it repeatedly turns the driver on for
           on_ms milliseconds and off for off_ms milliseconds.
     schedule (schedule, cycle_seconds=0, now=True)
           Schedules this driver to be enabled according to the given schedule bitmask.
     state()
           Returns a dictionary representing this driver's current configuration state.
     tick()
     timed_pwm (on_ms=10, off_ms=10, run_time=0, now=True)
           Enables a pitter-patter sequence that runs for run_time milliseconds.
           Until it ends, the sequence repeatedly turns the driver on for on_ms milliseconds and off for off_ms mil-
           liseconds.
class mpf.platform.p3 roc.PROCMatrixLight (number, proc driver)
     Bases: object
     off()
           Disables (turns off) this driver.
     on (brightness=255, fade ms=0, start=0)
           Enables (turns on) this driver.
class mpf.platform.p3_roc.PROCSwitch (number)
     Bases: object
mpf.platform.p3_roc.decode_pdb_address(addr, aliases=[])
     Decodes Ax-By-z or x/y/z into PDB address, bank number, and output number.
     Raises a ValueError exception if it is not a PDB address, otherwise returns a tuple of (addr, bank, number).
```

mpf.platform.p3_roc.is_pdb_address (addr, aliases=[])
Returne True if the given address is a valid PDB address.

mpf.platform.p roc module

Contains the drivers and interface code for pinball machines which use the Multimorphic R-ROC hardware controllers.

This code can be used with P-ROC driver boards, or with Stern SAM, Stern Whitestar, Williams WPC, or Williams WPC95 driver boards.

Much of this code is from the P-ROC drivers section of the pyprocgame project, written by Adam Preble and Gerry Stellenberg. It was originally released under the MIT license and is released here under the MIT License.

More info on the P-ROC hardware platform: http://pinballcontrollers.com/

Original code source on which this module was based: https://github.com/preble/pyprocgame

If you want to use the Mission Pinball Framework with P-ROC hardware, you also need libpinproc and pypinproc. More info: http://www.pinballcontrollers.com/forum/index.php?board=10.0

```
class mpf.platform.p_roc.DriverAlias (key, value)
    Bases: object
    decode (addr)
    matches (addr)
class mpf.platform.p_roc.HardwarePlatform (machine)
    Bases: mpf.system.platform.Platform (page 95)
```

Platform class for the P-ROC hardware controller.

Parameters machine – The MachineController instance.

machine

The MachineController instance.

proc

The P-ROC pinproc.PinPROC device.

machine type

Constant of the pinproc.MachineType

```
clear_hw_rule(sw_name)
```

Clears a hardware rule.

This is used if you want to remove the linkage between a switch and some driver activity. For example, if you wanted to disable your flippers (so that a player pushing the flipper buttons wouldn't cause the flippers to flip), you'd call this method with your flipper button as the *sw_num*.

Parameters sw_num (*int*) – The number of the switch whose rule you want to clear.

```
configure_dmd()
```

Configures a hardware DMD connected to a classic P-ROC.

```
configure_driver (config, device_type='coil')
```

Creates a P-ROC driver.

Typically drivers are coils or flashers, but for the P-ROC this is also used for matrix-based lights.

Parameters

- config Dictionary of settings for the driver.
- **device_type** String with value of either 'coil' or 'switch'.

Returns A reference to the PROCDriver object which is the actual object you can use to pulse(), patter(), enable(), etc.

configure_gi (config)

Configures a P-ROC GI string light.

configure_led(config)

Configures a P-ROC RGB LED controlled via a PD-LED.

configure_matrixlight (config)

Configures a P-ROC matrix light.

configure switch (config)

Configures a P-ROC switch.

Parameters

- **config** Dictionary of settings for the switch. In the case of the P-ROC, it uses the following:
- **number** The number (or number string) for the switch as specified in the machine configuration file.
- **debounce** Boolean which specifies whether the P-ROC should debounce this switch first before sending open and close notifications to the host computer.

Returns

A reference to the switch object that was just created. proc_num : Integer of the actual hardware switch number the P-ROC

uses to refer to this switch. Typically your machine configuration files would specify a switch number like *SD12* or 7/5. This *proc_num* is an int between 0 and 255.

state [An integer of the current hardware state of the switch, used] to set the initial state state in the machine. A value of 0 means the switch is open, and 1 means it's closed. Note this state is the physical state of the switch, so if you configure the switch to be normally-closed (i.e. "inverted" then your code will have to invert it too.) MPF handles this automatically if the switch type is 'NC'.

Return type switch

tick()

Checks the P-ROC for any events (switch state changes or notification that a DMD frame was updated).

Also tickles the watchdog and flushes any queued commands to the P-ROC.

Hardware Rules are used to configure the P-ROC to automatically change driver states based on switch changes. These rules are completely handled by the P-ROC hardware (i.e. with no interaction from the Python game code). They're used for things that you want to happen fast, like firing coils when flipper buttons are pushed, slingshots, pop bumpers, etc.

You can overwrite existing hardware rules at any time to change or remove them.

Parameters

- **sw** (*switch object*) Which switch you're creating this rule for. The parameter is a reference to the switch object itsef.
- **sw_activity** (*int*) Do you want this coil to fire when the switch becomes active (1) or inactive (0)

- **coil_action_ms** (*int*) The total time (in ms) that this coil action should take place. A value of -1 means it's forever.
- coil (coil object) Which coil is this rule controlling
- pulse_ms (int) How long should the coil be pulsed (ms)
- **pwm_on** (*int*) If the coil should be held on at less than 100% duty cycle, this is the "on" time (in ms).
- **pwm_off** (*int*) If the coil should be held on at less than 100% duty cycle, this is the "off" time (in ms).
- **delay** (int) Not currently implemented for the P-ROC hardware
- recycle_time (int) How long (in ms) should this switch rule wait before firing again. Put another way, what's the "fastest" this rule can fire? This is used to prevent "machine gunning" of slingshots and pop bumpers. Do not use it with flippers. Note the P-ROC has a non-configurable delay time of 125ms. (So it's either 125ms or 0.) So if you set this delay to anything other than 0, it will be 125ms.
- **debounced** (*bool*) Should the P-ROC fire this coil after the switch has been debounced? Typically no.
- **drive_now** (*bool*) Should the P-ROC check the state of the switches when this rule is firts applied, and fire the coils if they should be? Typically this is True, especially with flippers because you want them to fire if the player is holding in the buttons when the machine enables the flippers (which is done via several calls to this method.)

Base class for coils connected to a P-ROC that are controlled via P-ROC driver boards (i.e. the PD-16 board).

This class is only used when the P-ROC is configured to use P-ROC driver boards such as the PD-16 or PD-8x8. i.e. not when it's operating in WPC or Stern mode.

```
aliases = None
configure_globals (proc, lamp_source_bank_list, enable=True)
get_proc_number (device_type, number_str)
    Returns the P-ROC number for the requested driver string.
```

This method uses the driver string to look in the indexes list that was set up when the PDBs were configured. The resulting P-ROC index * 3 is the first driver number in the group, and the driver offset is to that.

```
indexes = []
initialize_drivers (proc)
proc = None
```

```
class mpf.platform.p_roc.PDBLED (board, address, proc_driver, invert=False)
     Bases: object
     Represents an RGB LED connected to a PD-LED board.
     color (color)
          Instantly sets this LED to the color passed.
              Parameters
                  • color – a 3-item list of integers representing R, G, and B values,
                  • each. (0-255) -
     disable()
          Disables (turns off) this LED instantly. For multi-color LEDs it turns all elements off.
     enable()
          Enables (turns on) this LED instantly. For multi-color LEDs it turns all elements on.
     fade (color, fade_ms)
     normalize color(color)
class mpf.platform.p_roc.PDBLight (pdb, number_str)
     Bases: object
     Base class for lights connected to a PD-8x8 driver board.
     dedicated bank()
     dedicated output()
     is_direct_lamp (string)
     is_pdb_lamp (string)
     sink_bank()
     sink_board()
     sink_output()
     source_bank()
     source_board()
     source_output()
     split_matrix_addr_parts(string)
          Input is of form C-Ax-By-z:R-Ax-By-z or C-x/y/z:R-x/y/z or aliasX:aliasY. We want to return only the
          address part: Ax-By-z, x/y/z, or aliasX. That is, remove the two character prefix if present.
class mpf.platform.p_roc.PDBSwitch (pdb, number_str)
     Bases: object
     Base class for switches connected to a P-ROC.
     parse_matrix_num(num_str)
     proc_num()
class mpf.platform.p_roc.PROCDMD (proc, machine)
     Bases: object
     Parent class for a physical DMD attached to a P-ROC.
```

Parameters

- proc Reference to the MachineController's proc attribute.
- machine Reference to the MachineController

dmd

Rerence to the P-ROC's DMD buffer.

tick()

Updates the physical DMD with the latest frame data. Meant to be called once per machine tick.

update (data)

Updates the DMD with a new frame.

Parameters data – A 4096-byte raw string.

```
{\bf class} \; {\tt mpf.platform.p\_roc.PROCDriver} \; ({\it number, proc\_driver})
```

Bases: object

Base class for drivers connected to a P-ROC. This class is used for all drivers, regardless of whether they're connected to a P-ROC driver board (such as the PD-16 or PD-8x8) or an OEM driver board.

disable()

Disables (turns off) this driver.

enable()

Enables (turns on) this driver.

```
future_pulse (milliseconds=None, timestamp=0)
```

Enables this driver for *milliseconds* at P-ROC timestamp: *timestamp*. If no parameter is provided for *milliseconds*, pulse_ms is used. If no parameter is provided or *timestamp*, 0 is used. ValueError will be raised if *milliseconds* is outside of the range 0-255.

```
pulse (milliseconds=None)
```

Enables this driver for milliseconds.

ValueError will be raised if *milliseconds* is outside of the range 0-255.

```
pwm (on_ms=10, off_ms=10, original_on_ms=0, now=True)
```

Enables a pitter-patter sequence.

It starts by activating the driver for *original_on_ms* milliseconds. Then it repeatedly turns the driver on for *on_ms* milliseconds and off for *off_ms* milliseconds.

```
schedule (schedule, cycle_seconds=0, now=True)
```

Schedules this driver to be enabled according to the given schedule bitmask.

state()

Returns a dictionary representing this driver's current configuration state.

tick()

```
timed_pwm (on_ms=10, off_ms=10, run_time=0, now=True)
```

Enables a pitter-patter sequence that runs for *run_time* milliseconds.

Until it ends, the sequence repeatedly turns the driver on for *on_ms* milliseconds and off for *off_ms* milliseconds.

```
class mpf.platform.p_roc.PROCMatrixLight (number, proc_driver)
```

Bases: object

off()

Disables (turns off) this driver.

```
on (brightness=255, fade_ms=0, start=0)
```

Enables (turns on) this driver.

```
class mpf.platform.p_roc.PROCSwitch (number)
    Bases: object

mpf.platform.p_roc.decode_pdb_address (addr, aliases=[])
    Decodes Ax-By-z or x/y/z into PDB address, bank number, and output number.
    Raises a ValueError exception if it is not a PDB address, otherwise returns a tuple of (addr, bank, number).

mpf.platform.p_roc.is_pdb_address (addr, aliases=[])
    Returne True if the given address is a valid PDB address.
```

mpf.platform.virtual module

Contains code for a virtual hardware platform. At this point this is more for testing before you have a P-ROC or FAST board installed. Eventually this can be used to allow the MPF to drive PinMAME and Virtual Pinball machines.

This is similar to the P-ROC's 'FakePinPROC' mode of operation, though unlike that it doesn't require any P-ROC drivers or modules to be installed.

```
class mpf.platform.virtual.HardwarePlatform(machine)
    Bases: mpf.system.platform.Platform (page 95)
    Base class for the virtual hardware platform.
    clear_hw_rule(sw_name)
    configure_dmd()
    configure_driver (config, device_type='coil')
    configure_gi (config)
    configure_led(config)
    configure_matrixlight (config)
    configure_switch(config)
    write_hw_rule(*args, **kwargs)
class mpf.platform.virtual.VirtualDMD (machine)
    Bases: object
    update (data)
class mpf.platform.virtual.VirtualDriver(number)
    Bases: object
    disable()
    enable()
    future_pulse (milliseconds=None, timestamp=0)
    pulse(milliseconds=None)
    pulsed patter(on ms=10, off ms=10, run time=0, now=True)
    pwm (on_ms=10, off_ms=10, original_on_ms=0, now=True)
    reconfigure (polarity)
    schedule (schedule, cycle_seconds=0, now=True)
    state()
    tick()
```

```
class mpf.platform.virtual.VirtualGI(number)
     Bases: object
     off()
     on (brightness, fade_ms, start)
class mpf.platform.virtual.VirtualLED (number)
     Bases: object
     color (color, fade_ms=0, brightness_compensation=True)
     disable()
     enable (brightness_compensation=True)
class mpf.platform.virtual.VirtualMatrixLight (number)
     Bases: object
     off()
     on (brightness=255, fade\_ms=0, start=0)
class mpf.platform.virtual.VirtualSwitch (number)
     Bases: object
     Represents a switch in a pinball machine used with virtual hardware.
```

1.4.2 Module contents

1.5 mpf.plugins package

1.5.1 Submodules

mpf.plugins.auditor module

MPF plugin for an auditor which records switch events, high scores, shots, etc.

```
class mpf.plugins.auditor.Auditor(machine)
    Bases: object
    audit(audit_class, event, **kwargs)
        Called to log an auditable event.
```

Parameters

- audit_class A string of the section we want this event to be
- **to.** (logged) -
- event A string name of the event we're auditing.
- **kawargs Not used, but included since some of the audit events might include random kwargs.

```
audit_event (eventname, **kwargs)
```

Registered as an event handlers to log an event to the audit log.

Parameters

- eventname The string name of the event.
- not used, but included since some types of events include (**kwargs,) kwargs.

```
audit player (**kwargs)
```

Called to write player data to the audit log. Typically this is only called at the end of a game.

Parameters not used, but included since some types of events include (**kwargs,) – kwargs.

```
audit_shot (name)
audit_switch (switch_name, state, ms)
disable (**kwargs)
    Disables the auditor.
enable (**kwags)
    Enables the auditor.
```

This method lets you enable the auditor so it only records things when you want it to. Typically this is called at the beginning of a game.

enabled = None

Attribute that's viewed by other system components to let them know they should send auditing events. Set this via the enable() and disable() methods.

```
load_from_disk(filename)
```

Loads an audit log from disk.

Parameters filename – The path and file of the audit file location.

```
make_sure_path_exists(path)
```

Checks to see if the audits folder exists and creates it if not.

```
save to disk(filename)
```

Dumps the audits from memory to disk.

Parameters filename – The path and file the audits will be written to.

```
mpf.plugins.auditor.plugin_class
    alias of Auditor (page 60)
```

mpf.plugins.ball_save module

MPF plugin for a ball saver code which is used to give the player another ball if their first ball drains too fast.

This plugin is not yet finished and doesn't work yet.

```
class mpf.plugins.ball_save.BallSave(game)
    Bases: object
```

Base class which implements a ball saver instance. You can use this as-is, enhance it, or replace it altogether.

```
ball_drain (balls)
  enable (time=None, balls=None)

mpf.plugins.ball_save.plugin_class
  alias of BallSave (page 61)
```

mpf.plugins.ball search module

MPF plugin for a ball search module which actually controls the coils to search for a missing pinball.

This module is not yet complete and does not work.

Base class which implements the ball search functionality.

This module is responsible for actually firing the coils and moving motors, etc. when the ball search begins. It can respond to multiple "phases" of ball search. (For example, for the few round it might only do easy things like fire pop bumpers. If it doesn't find the ball after that, it will start trying to eject balls from ball devices.)

This ball search module is not responsible for deciding to start or stop a ball search—that is something that Ball Controller does. Also this ball search module doesn't know when a ball is actually found. If a playfield switch is hit then the ball live event will be raised and the ball controller will tell this ball search module that it can stop looking.

Parameters machine (MachineController) - A reference to the instance of the MachineController object.

```
end()
```

Ends the active ball search.

```
pop_coil (coil)
```

Sctviates the 'coil' based on it's default pulse time. Holds a coil open for the hold time in sec.

This is not yet implemented. (It's copied in from our ball_controller code from our old python project.)

```
start()
```

Begin the ball search process

tick()

Method that runs as a task

```
mpf.plugins.ball_search.plugin_class
    alias of BallSearch (page 61)
```

mpf.plugins.info_lights module

MPF plugin which uses lights to represent Game functions. Typically in an EM machine

```
class mpf.plugins.info_lights.InfoLights (machine)
    Bases: object

ball_started()

game_ended()

game_starting(**kwargs)

match(match)

player_added(player)

reset_game_lights()

tilt()

mpf.plugins.info_lights.plugin_class
    alias of InfoLights (page 62)
```

mpf.plugins.osc module

MPF plugin allows a machine to be controlled by an OSC client.

```
class mpf.plugins.osc.OSC (machine)
     Bases: object
     client_send_OSC_message (category, name, data)
          Sends an OSC message to the client to update it Parameters: category - type of update, sw, coil, lamp, led,
          etc. name - the name of the object we're updating data - the data we're sending
     client_update_all()
          Update the OSC client. Good for when it switches to a new tab or connects a new client
     client_update_all_switches()
          Updates all the switch states on the OSC client.
     client_update_light (light_name, brightness)
     client_update_switch (switch_name, ms, state)
     found_new_OSC_client (address)
     process_coil (coil, data)
          Processes a coil event received from the OSC client.
     process_config(event, data)
     process_event (event, data)
          Posts an MPF event based on an event received from the OSC client.
     process_flipper (flipper, data)
          Calls the flipper's sw_flip() or sw_release() event.
     process light (light, data)
          Processes a light event received from the OSC client.
     process_message (addr, tags, data, client_address)
          Receives OSC messages and acts on them.
     process_switch (switch, data)
          Processes a switch event received from the OSC client.
     register_data()
     register_lights()
          Adds handlers to all lights so the OSC client can receive updates.
     register switches()
          Adds switch handlers to all switches so the OSC client can receive updates.
     setup_OSC_client (address)
          Setup a new OSC client
     start()
          Starts the OSC server.
     stop()
          Stops the OSC server.
     update_audits(event, data)
          Sends audit data to the OSC client.
     update_ball (**kwargs)
     update_config(event, data)
          Sends config data to the OSC client.
     update_player(**kwargs)
```

```
update_score (**kwargs)
mpf.plugins.osc.plugin_class
     alias of OSC (page 62)
mpf.plugins.socket events module
MPF plugin which sends events to sockets
class mpf.plugins.socket_events.SocketClient (machine)
     Bases: object
     process_config(config)
          Processes the SocketEvents from the config.
              Parameters config – Dictionary of the config to process.
     send_message (message)
          Sends a message to the remote socket host.
              Parameters message – String of the message to send.
     setup_client (host, port)
          Sets up the socket client.
              Parameters
                  • host – String of the host name.
                  • port – Int of the port name.
     stop_client()
          Stops and shuts down the socket client.
```

mpf.plugins.switch_player module

MPF plugin which automatically plays back switch events from the config file.

```
class mpf.plugins.switch_player.SwitchPlayer (machine)
    Bases: object

mpf.plugins.switch_player.plugin_class
    alias of SwitchPlayer (page 64)
```

mpf.plugins.socket_events.plugin_class

alias of SocketClient (page 64)

1.5.2 Module contents

1.6 mpf.system package

1.6.1 Submodules

mpf.system.assets module

Contains AssetManager, AssetLoader, and Asset parent classes

```
class mpf.system.assets.Asset (machine, config, file_name, asset_manager)
    Bases: object
```

load(callback=None)

unload()

class mpf.system.assets.AssetLoader (name, queue, machine)

Bases: threading. Thread

Base class for the Asset Loader with runs as a separate thread and actually loads the assets from disk.

Parameters

- name String name of what this loader will be called. (Only really used to give a friendly name to it in logs.)
- queue A reference to the asset loader Queue which holds assets waiting to be loaded.
- machine The main MachineController object.

run()

Run loop for the loader thread.

Bases: object

Base class for an Asset Manager.

Parameters

- machine The main MachineController object.
- **config_section** String of the name of the section in the config file for the asset settings that this Asset Manager will machine. e.g. 'image'.
- path_string The setting in the paths section of the config file that specifies what path these asset files are in. e.g. 'images'.
- asset_class A class object of the base class for the assets that this Asset Manager will manage. e.g. Image.
- asset_attribute The string name that you want to refer to this asset collection as. e.g. a value of 'images' means that assets will be accessible via self.machine.images.
- file_extensions A tuple of strings of valid file extensions that files for this asset will use. e.g. ('png', 'jpg', 'jpeg', 'bmp')

There will be one Asset Manager for each different type of asset. (e.g. one for images, one for movies, one for sounds, etc.)

create_loader_thread()

Creates a loader thread which will handle the actual reading from disk and loading into memory for assets of this class. Note that one loader thread is created for each class of assets used in your game.

Note that this asset loader as a separate *thread*, not a separate *process*. It will run on the same core as your main MPF Python instance.

Note that it's possible to call this method multiple times to create multiple loader threads, but that will not make things load any faster since this process is limited by CPU and disk I/O. In fact if it's a magnetic disk, think multiple threads would make it slower.

```
load_asset (asset, callback, priority=10)
```

Loads an asset into memory.

Parameters

- asset The Asset object to load.
- callback The callback that will be called once the asset has been loaded by the loader thread.
- **priority** The relative loading priority of the asset. If there's a queue of assets waiting to be loaded, this load request will be inserted into the queue in a position based on its priority.

load_assets (config, mode=None, load_key=None, callback=None, **kwargs)
Loads the assets from a config dictionary.

Parameters

- config Dictionary that holds the assets to load.
- mode Not used. Included here since this method is registered as a mode start handler.
- load_key String name of the load key which specifies which assets should be loaded.
- callback Callback method which is called by each asset once it's loaded.
- **kwargs Not used. Included to allow this method to be used as an event handler.

The assets must already be registered in order for this method to work.

locate_asset_file (file_name, path=None)

Takes a file name and a root path and returns a link to the absolute path of the file

Parameters

- file_name String of the file name
- path root of the path to check (without the specific asset path string)

Returns: String of the full path (path + file name) of the asset.

Note this method will add the path string between the path you pass and the file. Also if it can't find the file in the path you pass, it will look for the file in the machine root plus the path string location.

process_assets_from_disk(config, path=None)

Looks at a path and finds all the assets in the folder. Looks in a subfolder based on the asset's path string. Crawls subfolders too. The first subfolder it finds is used for the asset's default config section. If an asset has a related entry in the config file, it will create the asset with that config. Otherwise it uses the default

Parameters

- **config** A dictionary which contains a list of asset names with settings that will be used for the specific asset. (Note this is not needed for all assets, as any asset file found not in the config dictionary will be set up with the folder it was found in's asset_defaults settings.)
- path A full system path to the root folder that will be searched for assetsk. This should *not* include the asset-specific path string. If omitted, only the machine's root folder will be searched.

register_and_load_machine_assets()

Called on MPF boot to register any assets found in the machine-wide configuration files. (i.e. any assets not specified in mode config files.)

If an asset is set with the load type of 'preload', this method will also load the asset file into memory.

register_asset (asset, config)

Registers an asset with the Asset Manager.

Parameters

- asset String name of the asset to register.
- config Dictionary which contains settings for this asset.

Registering an asset is what makes it available to be used in the game. Note that registering an asset is separate from loading an asset. All assets will be registered on MPF boot, but they can be loaded and unloaded as needed to save on memory.

register_assets (config, mode_path=None)

Scans a config dictionary and registers any asset entries it finds.

Args:

config: A dictionary of asset entries. This dictionary needs to be "localized" to just the section for this particular asset type. e.g. if you're loading "Images" the keys of this dictionary should be image_1, image_2, etc., not "Images".

mode_path: The full path to the base folder that will be seaerched for the asset file on disk. This folder should not include the asset-specific folder. If omitted, the base machine folder will be searched.

Note that this method merely registers the assets so they can be referenced in MPF. It does not actually load the asset files into memory.

setup_defaults(config)

Processed the asset_defaults section of the machine config files.

unload_assets (asset_set)

Unloads assets from memory.

Parameters asset_set – A set (or any iterable) of Asset objects which will be unloaded.

Unloading an asset does not de-register it. It's still available to be used, but it's just unloaded from memory to save on memory.

mpf.system.ball_controller module

Contrains the BallController class which manages and tracks all the balls in a pinball machine.

```
class mpf.system.ball_controller.BallController(machine)
     Bases: object
```

Base class for the Ball Controller which is used to keep track of all the balls in a pinball machine.

Parameters machine (MachineController) – A reference to the instance of the MachineController object.

```
are_balls_gathered(target=['home', 'trough'])
```

Checks to see if all the balls are contained in devices tagged with the parameter that was passed.

Note if you pass a target that's not used in any ball devices, this method will return True. (Because you're asking if all balls are nowhere, and they always are. :)

Parameters

- target String value of the tag you'd like to check. Default is
- 'home' -

balls

create playfield device()

Creates the actual playfield ball device and assigns it to self.playfield.

```
gather_balls (target='home', antitarget=None)
```

Used to ensure that all balls are in (or not in) ball devices with the tag you pass.

Typically this would be used after a game ends, or when the machine is reset or first starts up, to ensure that all balls are in devices tagged with 'home'.

Parameters

- **target** A string of the tag name of the ball devices you want all the balls to end up in. Default is 'home'.
- antitarget The opposite of target. Will eject all balls from all devices with the string you pass. Default is None.

Note you can't pass both a target and antitarget in the same call. (If you do it will just use the target and ignore the antitarget.)

TODO: Add support to actually move balls into position. e.g. STTNG, the lock at the top of the playfield wants to hold a ball before a game starts, so when a game ends the machine will auto eject one from the plunger with the diverter set so it's held in the rear lock.

num_balls_known

```
request_to_start_game()
```

Method registered for the *request_to_start_game* event.

Checks to make sure that the balls are in all the right places and returns. If too many balls are missing (based on the config files 'Min Balls' setting), it will return False to reject the game start request.

mpf.system.bcp module

MPF plugin which enables the Backbox Control Protocol (BCP) v1.0alpha

```
class mpf.system.bcp.BCP (machine)
    Bases: object
```

The parent class for the BCP client.

This class can support connections with multiple remote hosts at the same time using multiple instances of the BCPClientSocket class.

Parameters machine – A reference to the main MPF machine object.

The following BCP commands are currently implemented: attract_start

attract_stop

ball_start?player=x&ball=x ball_end config?volume=0.5 error game_start game_end get goodbye hello?version=xxx mode_start?name=xxx&priority=xxx mode_stop?name=xxx player_added?number=x player_score?value=x&prev_value=x&change=x player_turn_start?player=x player_variable?name=x&value=x&prev_value=x&change=x set switch?name=x&state=x timer trigger?name=xxx

```
bcp_game_start(**kwargs)
```

Sends the BCP 'game_start' and 'player_added?number=1' commands to the remote BCP hosts.

```
bcp_mode_start (config, priority, mode, **kwargs)
```

Sends BCP 'mode_start' to the connected BCP hosts and schedules automatic sending of 'mode_stop' when the mode stops.

bcp_mode_stop (name, **kwargs)

Sends BCP 'mode_stop' to the connected BCP hosts.

bcp_player_added(player, num)

Sends BCP 'player_added' to the connected BCP hosts.

bcp_receive_dmd_frame (data)

Called when the BCP client receives a new DMD frame from the remote BCP host. This method forwards the frame to the physical DMD.

bcp_receive_error(**kwargs)

A remote BCP host has sent a BCP error message, indicating that a command from MPF was not recognized.

This method only posts a warning to the log. It doesn't do anything else at this point.

bcp_receive_get (**kwargs)

Processes an incoming BCP 'get' command.

Note that this media controller doesn't implement the 'get' command at this time, but it's included here for completeness since the 'get' command is part of the BCP 1.0 specification so we don't want to return an error if we receive an incoming 'get' command.

bcp_receive_set (**kwargs)

Processes an incoming BCP 'set' command.

Note that this media controller doesn't implement the 'set' command at this time, but it's included here for completeness since the 'set' command is part of the BCP 1.0 specification so we don't want to return an error if we receive an incoming 'set' command.

bcp_receive_switch(**kwargs)

Processes an incoming switch state change request from a remote BCP host.

bcp_receive_trigger (name=None, **kwargs)

Processes an incoming trigger command from a remote BCP host.

bcp reset()

Sends the 'reset' command to the remote BCP host.

bcp_trigger (name, **kwargs)

Sends BCP 'trigger' to the connected BCP hosts.

create_trigger_event (event)

Registers a BCP trigger based on an MPF event.

Parameters event – String name of the event you're registering this trigger for.

The BCP trigger will be registered with the same name as the MPF event. For example, if you pass the event "foo_event", the BCP command that will be sent when that event is posted will be trigger?name=foo_event.

decrease_volume (track='master', **kwargs)

Sends a command to the remote BCP host to decrease the volume of a track by 1 unit.

Parameters

- track The string name of the track you want to decrease the volume on. Default is 'master'.
- **kwargs Ignored. Included in case this method is used as a callback for an event which
 has other kwargs.

If this decrease causes the volume to go below zero, the decrease is ignored.

disable bcp switch(name)

Disables sending BCP switch commands when this switch changes state.

Parameters name – string name of the switch

disable bcp switches (tag)

Disables sending BCP switch commands when a switch with a certain tag changes state.

Parameters tag – string name of the tag for the switches you want to stop sending

```
disable_volume_keys (up_tag='volume_up', down_tag='volume_down')
```

Disables switch handlers so that the switches no longer affect the master system volume.

Parameters

- up_tag String of a switch tag name of the switches that will no longer be used to increase the volume.
- down_tag String of a switch tag name of the switches that will no longer be used to decrease the volume.

enable bcp switch(name)

Enables sending BCP switch commands when this switch changes state.

Parameters name – string name of the switch

enable bcp switches(tag)

Enables sending BCP switch commands when a switch with a certain tag changes state.

Parameters tag – string name of the tag for the switches you want to start sending

```
enable_volume_keys (up_tag='volume_up', down_tag='volume_down')
```

Enables switch handlers to change the master system volume based on switch tags.

Parameters

- **up_tag** String of a switch tag name that will be used to set which switch(es), when activated, increase the volume.
- **down_tag** String of a switch tag name that will be used to set which switch(es), when activated, decrease the volume.

get_bcp_messages()

Retrieves and processes new BCP messages from the receiving queue.

```
increase_volume (track='master', **kwargs)
```

Sends a command to the remote BCP host to increase the volume of a track by 1 unit.

Parameters

- **track** The string name of the track you want to increase the volume on. Default is 'master'.
- **kwargs Ignored. Included in case this method is used as a callback for an event which has other kwargs.

The max value of the volume for a track is set in the Volume: Steps: entry in the config file. If this increase causes the volume to go above the max value, the increase is ignored.

process_bcp_events()

Processes the BCP Events from the config.

register_mpfmc_trigger_events(config, **kwargs)

Scans an MPF config file and creates trigger events for the config settings that need them.

- config An MPF config dictionary (can be the machine-wide or a mode-specific one).
- **kwargs Not used. Included to catch any additional kwargs that may be associted with this method being registered as an event handler.

register_triggers (config, priority=0, mode=None)

Sets up trigger events based on a 'triggers:' section of a config dictionary.

Parameters

- **config** A python config dictionary.
- **priority** (not used) Included since this method is called as part of a mode start which passed this parameter.
- **mode** (not used) Included since this method is called as part of a mode start which passed this parameter.

remove_bcp_connection(bcp_client)

Removes a BCP connection to a remote BCP host.

Parameters bcp_client – A reference to the BCPClientSocket instance you want to remove.

```
send(bcp_command, callback=None, **kwargs)
```

Sends a BCP message.

Parameters

- **bcp_command** String name of the BCP command that will be sent.
- callback An optional callback method that will be called as soon as the BCP command is sent.
- **kwargs Optional kwarg pairs that will be sent as parameters along with the BCP command.

Example

If you call this method like this: send('trigger', ball=1, string'hello')

The BCP command that will be sent will be this: trigger?ball=1&string=hello

```
set volume (volume, track='master', **kwargs)
```

Sends a command to the remote BCP host to set the volume of a track to the value specified.

Parameters

- **volume** Int of the volume level. Valid range is 0 to the "steps" configuration in your config file. Values outside this range are ignored.
- track The string name of the track you want to set the volume on. Default is 'master'.
- **kwargs Ignored. Included in case this method is used as a callback for an event which
 has other kwargs.

shutdown()

Prepares the BCP clients for MPF shutdown.

```
\textbf{class} \; \texttt{mpf.system.bcp.BCPClientSocket} \; (\textit{machine}, \textit{name}, \textit{config}, \textit{receive\_queue})
```

Bases: object

Parent class for a BCP client socket. (There can be multiple of these to connect to multiple BCP media controllers simultaneously.)

Parameters

- machine The main MachineController object.
- name String name this client.
- **config** A dictionary containing the configuration for this client.
- receive queue The shared Queue() object that holds incoming BCP messages.

create socket threads()

Creates and starts the sending and receiving threads for the BCP socket.

Returns True if the socket exists and the threads were started. False if not.

```
get_from_socket (num_bytes=8192)
```

Reads and returns whatever data is sitting in the receiving socket.

Parameters num_bytes - Int of the max number of bytes to read.

Returns The data in raw string format.

```
receive_goodbye()
```

Processes incoming BCP 'goodbye' command.

```
receive_hello(**kwargs)
```

Processes incoming BCP 'hello' command.

receive_loop()

Receive loop which reads incoming data, assembles commands, and puts them onto the receive queue.

This method is run as a thread.

send (message)

Sends a message to the BCP host.

Parameters message – String of the message to send.

send_goodbye()

Sends BCP 'goodbye' command.

send hello()

Sends BCP 'hello' command.

sending_loop()

Sending loop which transmits data from the sending queue to the remote socket.

This method is run as a thread.

setup_client_socket()

Sets up the client socket.

stop()

Stops and shuts down the socket client.

```
mpf.system.bcp.decode_command_string(bcp_string)
```

Decodes a BCP command string into separate command and paramter parts.

Parameters bcp_string - The incoming UTF-8, URL encoded BCP command string.

Returns A tuple of the command string and a dictionary of kwarg pairs.

Example

Input: trigger?name=hello&foo=Foo%20Bar Output: ('trigger', {'name': 'hello', 'foo': 'Foo Bar'})

Note that BCP commands and parameter names are not case-sensitive and will be converted to lowercase. Parameter values are case sensitive, and case will be preserved.

```
mpf.system.bcp.encode_command_string(bcp_command, **kwargs)
```

Encodes a BCP command and kwargs into a valid BCP command string.

Parameters

- **bcp_command** String of the BCP command name.
- **kwargs Optional pair(s) of kwargs which will be appended to the command.

Returns A string.

Example

Input: encode_command_string('trigger', {'name': 'hello', 'foo': 'Bar'}) Output: trigger?name=hello&foo=Bar

Note that BCP commands and parameter names are not case-sensitive and will be converted to lowercase. Parameter values are case sensitive, and case will be preserved.

mpf.system.config module

Contains the Config class with utility configuration methods

```
class mpf.system.config.CaseInsensitiveDict
    Bases: dict
```

A class based on Python's 'dict' class that internally stores all keys as lowercase. Set, get, contains, and del methods have been overwritten to automatically convert incoming calls to lowercase.

```
class mpf.system.config.Config
    Bases: object
```

static check_config_file_version (file_location)

Checks a configuration file to see if it's the proper version for this version of MPF.

Parameters file_location – The path to the file to check.

Returns: True if the config version of the file matches. False if not.

This method checks that the a string 'config_version=x' exists in the first line of the file. If so, it checks that 'x' matches MPF's config_version specification.

This check is done as integers.

```
static dict_merge (a, b, combine_lists=True)
```

Recursively merges dictionaries.

Used to merge dictionaries of dictionaries, like when we're merging together the machine configuration files. This method is called recursively as it finds sub-dictionaries.

For example, in the traditional python dictionary update() methods, if a dictionary key exists in the original and merging-in dictionary, the new value will overwrite the old value.

Consider the following example:

Original dictionary: config['foo']['bar'] = 1

New dictionary we're merging in: $config['foo']['other\ bar'] = 2$

Default python dictionary update() method would have the updated dictionary as this:

```
{'foo': {'other_bar': 2}}
```

This happens because the original dictionary which had the single key *bar* was overwritten by a new dictionary which has a single key *other bar*.)

But really we want this:

```
{'foo': {'bar': 1, 'other_bar': 2}}
```

This code was based on this: https://www.xormedia.com/recursively-merge-dictionaries-in-python/

Parameters

- a (dict) The first dictionary
- **b** (*dict*) The second dictionary
- **combine_lists** (*bool*) Controls whether lists should be combined (extended) or overwritten. Default is *True* which combines them.

Returns The merged dictionaries.

```
static keys_to_lower (source_dict)
```

Converts the keys of a dictionary to lowercase.

Parameters source_dict – The dictionary you want to convert.

Returns A dictionary with lowercase keys.

```
static list_of_lists (incoming_string)
```

Converts an incoming string or list into a list of lists.

```
static load_config_yaml (config=None, yaml_file=None, new_config_dict=None)
```

Merges a new config dictionary into an existing one.

This method does what we call a "deep merge" which means it merges together subdictionaries instead of overwriting them. See the documentation for *meth:dict_merge* for a description of how this works.

If the config dictionary you're merging in also contains links to additional config files, it will also merge those in.

At this point this method loads YAML files, but it would be simple to load them from JSON, XML, INI, or existing python dictionaires.

Parameters

- **config** The optional current version of the config dictionary that you're building up. If you don't pass a dictionary, this method will create one.
- yaml_file A YAML file containing the settings to deep merge into the config dictionary. This method will try to find a file with that name and open it to read in the settings. It will first try to open it as a file directly (including any path that's there). If that doesn't work, it will try to open the file using the last path that worked. (This path is stored in config['Config_path'].)
- new_config_dict A dictionary of settings to merge into the config dictionary.

Note that you only need to specify a yaml_file or new_config_dictionary, not both.

Returns: Python dictionary which is your source with all the new config options merged in.

```
static process_config (config_spec, source, target=None)
```

```
static string_to_list (string)
```

Converts a comma-separated and/or space-separated string into a Python list.

Parameters string – The string you'd like to convert.

Returns A python list object containing whatever was between commas and/or spaces in the string.

static string_to_lowercase_list (string)

Converts a comma-separated and/or space-separated string into a Python list where each item in the list has been converted to lowercase.

Parameters string – The string you'd like to convert.

Returns A python list object containing whatever was between commas and/or spaces in the string, with each item converted to lowercase.

static validate_config_item (spec, item='item not in config!@#')

mpf.system.devices module

Contains the parent classes Device and DeviceCollection

Bases: object

Generic parent class of for every hardware device in a pinball machine.

static create_devices (collection, config, machine)

```
classmethod get_config_info()
```

```
class mpf.system.devices.DeviceCollection (machine, collection, config_section)
```

Bases: mpf.system.config.CaseInsensitiveDict (page 73)

A collection of Devices.

One instance of this class will be created for each different type of hardware device (such as coils, lights, switches, ball devices, etc.)

```
is valid(name)
```

Checks to see if the name passed is a valid device.

Parameters name – The string of the device name you want to check.

Returns True or False, depending on whether the name is a valid device or not.

items_not_tagged(tag)

Returns of list of device objects which do not have a certain tag.

Parameters tag – A string of the tag name which specifies what devices are returned. All devices will be returned except those with this tag.

Returns A list of device objects. If no devices are found with that tag, it will return an empty list.

items_tagged(tag)

Returns of list of device objects which have a certain tag.

Parameters tag – A string of the tag name which specifies what devices are returned.

Returns A list of device objects. If no devices are found with that tag, it will return an empty list.

number (number)

Returns a device object based on its number.

mpf.system.events module

Contains the base classes for the EventManager and QueuedEvents

add_handler (event, handler, priority=1, **kwargs)

Registers an event handler to respond to an event.

If you add a handlers for an event for which it has already been registered, the new one will overwrite the old one. This is useful for changing priorities of existing handlers. Also it's good to know that you can safely add a handler over and over.

Parameters

- **event** String name of the event you're adding a handler for. Since events are text strings, they don't have to be pre-defined. Note that all event strings will be converted to lowercase.
- handler The method that will be called when the event is fired.
- **priority** An arbitrary integer value that defines what order the handlers will be called in. The default is 1, so if you have a handler that you want to be called first, add it here with a priority of 2. (Or 3 or 10 or 100000.) The numbers don't matter. They're called from highest to lowest. (i.e. priority 100 is called before priority 1.)
- **kwargs Any any additional keyword/argument pairs entered here will be attached to
 the handler and called whenever that handler is called. Note these are in addition to kwargs
 that could be passed as part of the event post. If there's a conflict, the event-level ones will
 win.

Returns A GUID reference to the handler which you can use to later remove the handler via remove_handler_by_key.

For example: handler_list.append(events.add_handler('ev', self.test))

Then later to remove all the handlers that a module added, you could: for handler in handler_list: events.remove_handler(handler)

add_monitor(monitor)

Adds a new event monitor.

Parameters monitor – Reference to the callback function that will be called on every event posting.

Event monitors are similar to event handlers except they're called on every single event. In other words, they're like handlers you register for every event instead of a single event.

The monitor you register will be called on each event posting with the following paramters:

- •event String name of the evnet
- •ev_type String of the type of event
- •callback Reference to the event callback (if it has one)
- •kwargs Dict of kwargs that will be passed to the handlers.

does event exist(event name)

Checks to see if any handlers are registered for the event name that is passed.

Parameters event_name – The string name of the event you want to check. This string will be converted to lowercase.

Returns True or False

get_current_event()

Returns a tuple with information about the current event that's in progress.

Returned result is a 4-element tuple:

[0] event name (str) [1] event type (str) [2] post-event callback (meth) [3] kwargs (dict)

If no event is in progress, these are all None.

```
post (event, callback=None, **kwargs)
```

Posts an event which causes all the registered handlers to be called.

Events are processed serially (e.g. one at a time), so if the event system is in the process of handling another event, this event is added to a queue and processed after the current event is done.

You can control the order the handlers will be called by optionally specifying a priority when the handlers were registed. (Higher priority values will be processed first.)

Parameters

- event A string name of the event you're posting. Note that you can post whatever event you want. You don't have to set up anything ahead of time, and if no handlers are registered for the event you post, so be it. Note that this event name will be converted to lowercase.
- callback An optional method which will be called when the final handler is done processing this event. Default is None.
- **kwargs One or more options keyword/value pairs that will be passed to each handler.
 (Just make sure your handlers are expecting them. You can add **kwargs to your handler methods if certain ones don't need them.)

```
post_boolean (event, callback=None, **kwargs)
```

Posts an boolean event which causes all the registered handlers to be called one-by-one. Boolean events differ from regular events in that if any handler returns False, the remaining handlers will not be called.

Events are processed serially (e.g. one at a time), so if the event system is in the process of handling another event, this event is added to a queue and processed after the current event is done.

You can control the order the handlers will be called by optionally specifying a priority when the handlers were registed. (Higher priority values will be processed first.)

- **event** A string name of the event you're posting. Note that you can post whatever event you want. You don't have to set up anything ahead of time, and if no handlers are registered for the event you post, so be it. Note that this event name will be converted to lowercase.
- callback An optional method which will be called when the final handler is done processing this event. Default is None. If any handler returns False and cancels this boolean event, the callback will still be called, but a new kwarg ev_result=False will be passed to it.
- **kwargs One or more options keyword/value pairs that will be passed to each handler. (Just make sure your handlers are expecting them. You can add **kwargs to your handler methods if certain ones don't need them.)

```
post_queue (event, callback, **kwargs)
```

Posts a queue event which causes all the registered handlers to be called.

Queue events differ from standard events in that individual handlers are given the option to register a "wait", and the callback will not be called until any handler(s) that registered a wait will have to release that wait. Once all the handlers release their waits, the callback is called.

Events are processed serially (e.g. one at a time), so if the event system is in the process of handling another event, this event is added to a queue and processed after the current event is done.

You can control the order the handlers will be called by optionally specifying a priority when the handlers were registed. (Higher priority values will be processed first.)

Parameters

- event A string name of the event you're posting. Note that you can post whatever event you want. You don't have to set up anything ahead of time, and if no handlers are registered for the event you post, so be it. Note that this event name will be converted to lowercase.
- callback The method which will be called when the final handler is done processing this event and any handlers that registered waits have cleared their waits.
- **kwargs One or more options keyword/value pairs that will be passed to each handler.
 (Just make sure your handlers are expecting them. You can add **kwargs to your handler methods if certain ones don't need them.)

```
post_relay (event, callback=None, **kwargs)
```

Posts a relay event which causes all the registered handlers to be called. A dictionary can be passed from handler-to-handler and modified as needed.

Parameters

- **event** A string name of the event you're posting. Note that you can post whatever event you want. You don't have to set up anything ahead of time, and if no handlers are registered for the event you post, so be it. Note that this event name will be converted to lowercase.
- callback The method which will be called when the final handler is done processing this
 event. Default is None.
- **kwargs One or more options keyword/value pairs that will be passed to each handler.
 (Just make sure your handlers are expecting them. You can add **kwargs to your handler methods if certain ones don't need them.)

Events are processed serially (e.g. one at a time), so if the event system is in the process of handling another event, this event is added to a queue and processed after the current event is done.

You can control the order the handlers will be called by optionally specifying a priority when the handlers were registed. (Higher priority values will be processed first.)

Relay events differ from standard events in that the resulting kwargs from one handler are passed to the next handler. (In other words, stanard events mean that all the handlers get the same initial kwargs, whereas relay events "relay" the resulting kwargs from one handler to the next.)

```
process_event_player (config, mode=None, priority=0)
```

```
remove_handler (method)
```

Removes an event handler from all events a method is registered to handle.

Parameters method – The method whose handlers you want to remove.

```
remove_handler_by_event (event, handler)
```

Removes the handler you pass from the event you pass.

- event The name of the event you want to remove the handler from. This string will be converted to lowercase.
- handler The handler method you want to remove.

Note that keyword arguments for the handler are not taken into consideration. In other words, this method only removes the registered handler / event combination, regardless of whether the keyword arguments match or not.

```
remove handler by key(key)
```

Removes a registered event handler by key.

Parameters key – The key of the handler you want to remove

```
remove_handlers_by_keys (key_list)
```

Removes multiple event handlers based on a passed list of keys

Parameters key_list - A list of keys of the handlers you want to remove

```
remove_monitor (monitor)
```

Removes / deregisters an event monitor.

Parameters monitor – The function you want to deregister.

This method can safely be called even if this monitor is not registered.

```
replace_handler (event, handler, priority=1, **kwargs)
```

Checks to see if a handler (optionally with kwargs) is registered for an event and replaces it if so.

Parameters

- **event** The event you want to check to see if this handler is registered for. This string will be converted to lowercase.
- handler The method of the handler you want to check.
- **priority** Optional priority of the new handler that will be registered.
- **kwargs The kwargs you want to check and the kwatgs that will be registered with the new handler.

If you don't pass kwargs, this method will just look for the handler and event combination. If you do pass kwargs, it will make sure they match before replacing the existing entry.

If this method doesn't find a match, it will still add the new handler.

```
unload_event_player_events (event_keys)
```

```
class mpf.system.events.QueuedEvent (callback, **kwargs)
    Bases: object
```

The base class for an event queue which is created each time a queue event is called.

See the documentation at http://missionpinball.com/docs/system-components/events/ for a description of how queue events work.

```
clear()
is_empty()
kill()
wait()
```

mpf.system.light_controller module

Manages the light shows in a pinball machine.

```
class mpf.system.light_controller.LightController(machine)
    Bases: object
```

Manages all the light shows in a pinball machine.

'light shows' are coordinated light, flasher, coil, and event effects. The LightController handles priorities, restores, running and stopping Shows, etc. There should be only one per machine.

Parameters machine – Parent machine object.

```
add_light_player_show (event, settings)
```

Creates a light show from a script.

Parameters

- script Python dictionary in MPF light script format
- **lights** String or iterable of multiples strings of the matrix lights that will be included in this show.
- leds String or iterable of multiples strings of the LEDs that will be included in this show.
- **light_tags** String or iterable of multiples strings of tags of matrix lights that specify which lights will be in this show.
- **led_tags** String or iterable of multiples strings of tags of LEDs that specify which lights will be in this show.
- key Object (typically string) that will be used to stop the show created by this list later.

current_time = None

The light controller uses a common system time for the entire show system so that every "current_time" of a single update cycle is the same everywhere. This ensures that multiple shows, scripts, and commands start in-sync regardless of any processing lag.

```
static hexstring_to_int (inputstring, maxvalue=255)
```

Takes a string input of hex numbers and an integer.

Parameters

- **input_string** A string of incoming hex colors, like ffff00.
- maxvalue Integer of the max value you'd like to return. Default is 255. (This is the real value of why this method exists.)

Returns Integer representation of the hex string.

```
static hexstring_to_list (input_string, output_length=3)
```

Takes a string input of hex numbers and returns a list of integers.

This always groups the hex string in twos, so an input of ffff00 will be returned as [255, 255, 0]

- **input_string** A string of incoming hex colors, like ffff00.
- **output_length** Integer value of the number of items you'd like in your returned list. Default is 3. This method will ignore extra characters if the input_string is too long, and it will pad with zeros if the input string is too short.

Returns List of integers, like [255, 255, 0]

load shows(path)

Automatically loads all the light shows in a path.

Light shows are added to the dictionary self.shows with they key set to the value of the file name.

For example, the light show 'sweep.yaml' will be loaded as self.shows['sweep']

This method will also loop through sub-directories, allowing the game programmer to organize the light show files into folders as needed.

Parameters path – A string of the relative path to the folder, based from the root from where the mpf.py file is running.

```
play_show (show, priority=0, **kwargs)
```

Plays a light show.

Parameters

- **show** Either the string name of a registered show or a direct reference to the show object you want to play.
- **priority** The priority this show will play at.
- **kwargs Contains the parameters and settings to control the playing of the show. See Show.play() for options and details.

```
process_light_player (config, mode=None, priority=0)
process_light_scripts (config, mode=None, priority=0)
```

queue = None

A list of dicts which contains things that need to be serviced in the future, including: (ot all are always used)

- •lightname
- priority
- •blend
- •fadeend
- •dest_color
- •color
- playlist
- •action time

restore_lower_lights (show=None, priority=0)

Restores the lights and LEDs from lower priority shows under this show.

This is only useful if this show is stopped, because otherwise this show will just immediately override these restored settings.

Parameters

- show The show which will set the priority of the lights you want to restore.
- priority An iteger value of the lights you want to restore.

In both cases it will only restore lights below the priority you pass, skipping ones that are at the same value.

```
run_registered_script (script_name, **kwargs)
```

run_script (script, lights=None, leds=None, repeat=True, callback=None, key=None, **kwargs)
Runs a light script.

Parameters

- script A list of dictionaries of script commands. (See below)
- lights A light name or list of lights this script will be applied to.
- leds An LED name or a list of LEDs this script will be applied to.
- repeat (bool) Whether the script repeats (loops).
- callback A method that will be called when this script stops.
- **key** A key that can be used to later stop the light show this script creates. Typically a unique string. If it's not passed, it will either be the first light name or the first LED name.
- **kwargs Since this method just builds a Light Show, you can use any other Light Show attribute here as well, such as tocks_per_sec, blend, repeat, num_repeats, etc.

Returns Show (page 85) object. Since running a script just sets up and runs a regular Show, run_script returns the Show object. In most cases you won't need this, but it's nice if you want to know exactly which Show was created by this script so you can stop it later. (See the examples below for usage.)

Scripts are similar to Shows, except they only apply to single lights and you can "attach" any script to any light. Scripts are used anytime you want an light to have more than one action. A simple example would be a flash an light. You would make a script that turned it on (with your color), then off, repeating forever.

Scripts could be more complex, like cycling through multiple colors, blinking out secret messages in Morse code, etc.

Interally we actually just take a script and dynamically convert it into a Show (that just happens to only be for a single light), so we can have all the other Show-like features, including playback speed, repeats, blends, callbacks, etc.

The script is a list of dictionaries, with each list item being a sequential instruction, and the dictionary defining what you want to do at that step. Dictionary items for each step are:

color: The hex color for the light time: How long (in ms) you want the light to be at that color fade: True/False. Whether you want that light to fade to the color

(using the time above), or whether you want it to switch to that color instantly.

Example usage:

Here's how you would use the script to flash an RGB light between red and off:

```
\label{eq:self.flash_red} $$ self.flash_red.append({"color": 'ff0000', 'tocks': 1}) $$ self.flash_red.append({"color": '000000', 'tocks': 1}) $$ self.machine.show_controller.run_script(script=self.flash_red, $$ $$
```

```
lights='light1', priority=4, blend=True)
```

Once the "flash_red" script is defined as self.flash_red, you can use it anytime for any light or LED. You can also define lights as a list, like this:

```
self.machine.show_controller.run_script(script=self.flash_red, lights=['light1', 'light2'], priority=4, blend=True)
```

Most likely you would define your scripts once when the game loads and then call them as needed.

You can also make more complex scripts. For example, here's a script which smoothly cycles an RGB light through all colors of the rainbow:

```
self.rainbow = [] self.rainbow.append({'color': 'ff0000', 'tocks': 1, 'fade': True}) self.rainbow.append({'color': 'ff7700', 'tocks': 1, 'fade': True}) self.rainbow.append({'color': 'ffcc00', 'tocks': 1, 'fade': True}) self.rainbow.append({'color': '000ff00', 'tocks': 1, 'fade': True}) self.rainbow.append({'color': '0000ff', 'tocks': 1, 'fade': True}) self.rainbow.append({'color': 'ff00ff', 'tocks': 1, 'fade': True})
```

If you have single color lights, your *color* entries in your script would only contain a single hex value for the intensity of that light. For example, a script to flash a single-color light on-and-off (which you can apply to any light):

```
self.flash = [] self.flash.append({"color": "ff", "tocks": 1}) self.flash.append({"color": "00",
"tocks": 1})
```

If you'd like to save a reference to the Show (page 85) that's created by this script, call it like this:

running_show_keys = None

Dict of active light shows that were created from scripts. This is useful for stopping shows later. Keys are based on the 'key' parameter specified when a script was run, values are references to the show object.

```
stop_script (key, **kwargs)
```

Stops and removes the light show that was created by a light script.

Parameters

- **key** The key that was specified in run_script().
- **kwargs Not used, included in case this method is called via an event handler that might contain other random parameters.

```
stop_show(show=None, key=None, **kwargs)
stop_shows_by_key(key)
stop_shows_by_keys(keys)
sync_ms_next_tick(sync_ms)
```

Figures out the next tick show should start based on the passed sync_ms value.

Parameters sync_ms – Integer of the sync period in ms.

Returns Int of a tick number

```
unload_light_player_shows(removal_tuple)
```

```
class mpf.system.light_controller.Playlist (machine)
    Bases: object
```

A list of Show (page 85) objects which are then played sequentially.

Playlists are useful for things like attract mode where you play one show for a few seconds, then another, etc.

Parameters machine – The main MachineController object

Each step in a playlist can contain more than one Show (page 85). This is useful if you have a lot of little shows for different areas of the playfield that you want run at the same time. For example, you might have one show that only controls a group of rollover lane lights, and another which blinks the lights in the center of the playfield. You can run them at the by putting them in the same step in your playlist. (Note you don't need to use a playlist if you simply want to run two Shows at the same time. In that case you could just call Show.play() (page 86) twice to play both shows.

For each "step" in the playlist, you can specify the number of seconds it runs those shows before moving on, or you can specify that one of the shows in that step plays a certain number of times and then the playlist moves to the next step from there.

You create a show by creating an instance Playlist (page 83). Then you add Shows to it via add_show() (page 84). Finally, you specify the settings for each step (like how it knows when to move on) via :meth: step_settings.

When you start a playlist (via start () (page 84), you can specify settings like what priority the show runs at, whether it repeats, etc.)

Example usage from a game mode: (This example assumes we have self.show1, self.show2, and self.show3 already loaded.)

Setup the playlist:

```
self.my_playlist = lights.Playlist(self.machine)
self.my_playlist.add_show(step_num=1, show=self.show1, tocks_per_sec=10)
self.my_playlist.add_show(step_num=2, show=self.show2, tocks_per_sec=5)
self.my_playlist.add_show(step_num=3, show=self.show3, tocks_per_sec=32)
self.my_playlist.step_settings(step=1, time=5)
self.my_playlist.step_settings(step=2, time=5)
self.my_playlist.step_settings(step=3, time=5)
```

Run the playlist:

```
self.my_playlist.start(priority=100, repeat=True)
```

Stop the playlist:

```
self.my_playlist.stop()
```

add_show (step_num, show, num_repeats=0, tocks_per_sec=32, blend=False, repeat=True)
Adds a Show to this playlist. You have to add at least one show before you start playing the playlist.

- **step_num** Interger of which step number you're adding this show to. You have to specify this since it's possible to add multiple shows to the same step (in cases where you want them both to play at the same time during that step). If you want the same show to play in multiple steps, then add it multiple times (once to each step). The show plays starting with the lowest number step and then moving on. Ideally they'd be 1, 2, 3... but it doesn't matter. If you have step numbers of 1, 2, 5... then the player will figure it out.
- **show** The Show object that you're adding to this step.
- num_repeats Integer of how many times you want this show to repeat within this step. Note this does not affect when the playlist advances to the next step. (That is controlled via step_settings() (page 85).) Rather, this is just how many loops this show plays. A value of 0 means it repeats indefinitely. (Well, until the playlist advances to the next step.) Note that you also have to have repeat=True for it to repeat here.
- tocks_per_sec Integer of how fast you want this show to play. See Show.play() (page 86) for details.
- **blend** Boolean of whether you want this show to blend with lower priority shows below it. See Show.play() (page 86) for details.
- **repeat** Boolean which causes the show to keep repeating until the playlist moves on to the next step.

```
start (priority=0, repeat=True, repeat count=0, reset=True)
```

Starts playing a playlist. You can only use this after you've added at least one show via add_show() (page 84) and configured the settings for each step via step settings() (page 85).

Args

priority: Integer of what priority you want the Show (page 85) shows in this playlist to play at. These shows will play "on top" of lower priority stuff, but "under" higher priority things.

repeat: Controls whether this playlist to repeats when it's finished. repeat_count: How many times you want this playlist to

repeat before it stops itself. (Must be used with *repeat=True* above.) A value of 0 here means that this playlist repeats forever until you manually stop it. (This is ideal for attract mode.)

reset: Boolean which controls whether you want this playlist to start at the beginning (True) or you want it to pick up where it left off (False). You can also use *reset* to restart a playlist that's currently running.

```
step settings(step, time=0, trigger show=None, hold=False)
```

Used to configure the settings for a step in a Playlist (page 83). This configuration is required for each step. The main thing you use this for is to specify how the playlist knows to move on to the next step.

Args:

step: Integer for which step number you're configuring time: Integer of the time in seconds that you want this step to run

before moving on to the next one.

trigger_show: If you want to move to the next step after one of the Shows in this step is done playing, pass that show's object here. This is required because if there are multiple Shows in this step of the playlist which all end at different times, we wouldn't know which one to watch in order to know when to move on.

Note that you can have repeats with a trigger show, but in that case you also need to have the num_repeats specified. Otherwise if you have your trigger show repeating forever then the playlist will never move on. (In that case use the *time* parameter to move on based on time.)

```
stop (reset=True, hold=None)
```

Stops a playlist. Pretty simple.

Parameters

- **reset** If *True*, it resets the playlist tracking counter back to the beginning. You can use *False* here if you want to stop and then restart a playlist to pick up where it left off.
- hold Boolean which specifies whether this playlist should should hold the lights and LEDs in their current states. Default is None which means it inherits whatever the shows or playlist settings were, but you can force it True or False if you want here.

Parameters tocks_per_sec – The new tocks_per_second play rate.

If you want to change the playback speed by a percentage, you can access the current tocks_per_second rate via Show's tocks_per_second variable. So if you want to double the playback speed of your show, you could do something like:

self.your_show.change_speed(self.your_show.tocks_per_second*2)

Note that you can't just update the show's tocks_per_second directly because we also need to update self.ticks_per_tock.

load show from disk()

Plays a Show. There are many parameters you can use here which affect how the show is played. This includes things like the playback speed, priority, whether this show blends with others, etc. These are all set when the show plays. (For example, you could have a Show file which lights a bunch of lights sequentially in a circle pattern, but you can have that circle "spin" as fast as you want depending on how you play the show.)

- **repeat** Boolean of whether the show repeats when it's done.
- **priority** Integer value of the relative priority of this show. If there's ever a situation where multiple shows want to control the same item, the one with the higher priority will win. ("Higher" means a bigger number, so a show with priority 2 will override a priority 1.)
- **blend** Boolean which controls whether this show "blends" with lower priority shows and scripts. For example, if this show turns a light off, but a lower priority show has that light set to blue, then the light will "show through" as blue while it's off here. If you don't want that behavior, set blend to be False. Then off here will be off for sure (unless there's a higher priority show or command that turns the light on). Note that not all item types blend. (You can't blend a coil or event, for example.)
- **hold** Boolean which controls whether the lights or LEDs remain in their final show state when the show ends. Default is None which means hold will be False if the show has more than one step, and True if there is only one step.
- tocks_per_sec Integer of how fast your show runs ("Playback speed," in other words.) Your Show files specify action times in terms of 'tocks', like "make this light red for 3 tocks, then off for 4 tocks, then a different light on for 6 tocks. When you play a show, you specify how many tocks per second you want it to play. Default is 30, but you might even want tocks_per_sec of only 1 or 2 if your show doesn't need to move than fast. Note this does not affect fade rates. So you can have tocks_per_sec of 1 but still have lights fade on and off at whatever rate you want. Also the term "tocks" was chosen so as not to confuse it with "ticks" which is used by the machine run loop.
- start_location Integer of which position in the show file the show should start in. Usually this is 0 but it's nice to start part way through. Also used for restarting shows that you paused. A negative value will count backwards from the end (-1 is the last position, -2 is second to last, etc.).
- callback A callback function that is invoked when the show is stopped.
- num_repeats Integer of how many times you want this show to repeat before stopping. A value of 0 means that it repeats indefinitely. Note this only works if you also have repeat=True.
- sync_ms Number of ms of the show sync cycle. A value of zero means this show will also start playing immediately. See the full MPF documentation for details on how this

works.

- reset Boolean which controls whether this show will reset to its first position once it ends. Default is True.
- **kwargs Not used, but included in case this method is used as an event handler which might include additional kwargs.

resync()

Causes this show to do a one-time update to resync all the LEDs and lights in the show with where they should be now. This is used when a higher priority show stops so lower priority shows can put all the lights back to how they want them.

```
stop (reset=True, hold=None)
```

Stops the Light Show.

Note you can also use this method to clear a stopped show's held lights and LEDs by passing hold=False.

Parameters

- reset Boolean which controls whether the show will reset its current position back to zero. Default is True.
- hold Boolean which controls whether the show will hold its current lights and LEDs in whatever state they are now, including their priorities. Default is None which will just use whatever the show setting was when you played it, but you can force it to hold or not with True or False here.

mpf.system.logic blocks module

MPF plugin which implements Logic Blocks

```
class mpf.system.logic_blocks.Accrual (machine, name, player, config)
    Bases: mpf.system.logic_blocks.LogicBlock (page 88)
```

A type of LogicBlock which tracks many different events (steps) towards a goal, with the steps being able to happen in any order.

```
enable (**kwargs)
```

Enables this accrual. Automatically called when one of the 'enable_events' is posted. Can also manually be called.

```
hit (step, **kwargs)
```

Increases the hit progress towards completion. Automatically called when one of the *count_events* is posted. Can also manually be called.

Parameters step – Integer of the step number (0 indexed) that was just hit.

```
reset (**kwargs)
```

Resets the hit progress towards completion

```
class mpf.system.logic_blocks.Counter(machine, name, player, config)
    Bases: mpf.system.logic_blocks.LogicBlock (page 88)
```

A type of LogicBlock that tracks multiple hits of a single event.

This counter can be configured to track hits towards a specific end-goal (like number of tilt hits to tilt), or it can be an open-ended count (like total number of ramp shots).

It can also be configured to count up or to count down, and can have a configurable counting interval.

```
enable(**kwargs)
```

Enables this counter. Automatically called when one of the 'enable_event's is posted. Can also manually be called.

hit (**kwargs)

Increases the hit progress towards completion. Automatically called when one of the 'count_events's is posted. Can also manually be called.

reset (**kwargs)

Resets the hit progress towards completion

stop_ignoring_hits(**kwargs)

Causes the Counter to stop ignoring subsequent hits that occur within the 'multiple_hit_window'. Automatically called when the window time expires. Can safely be manually called.

class mpf.system.logic_blocks.LogicBlock(machine, name, player, config)

Bases: object

Parent class for each of the logic block classes.

complete()

Marks this logic block as complete. Posts the 'events_when_complete' events and optionally restarts this logic block or disables it, depending on this block's configuration settings.

disable(**kwargs)

Disables this logic block. Automatically called when one of the disable_event events is posted. Can also manually be called.

enable (**kwargs)

Enables this logic block. Automatically called when one of the enable_event events is posted. Can also manually be called.

reset (**kwargs)

Resets the progress towards completion of this logic block. Automatically called when one of the reset_event events is called. Can also be manually called.

restart (**kwargs)

Restarts this logic block by calling reset() and enable() Automatically called when one of the restart_event events is called. Can also be manually called.

unload()

class mpf.system.logic_blocks.LogicBlocks(machine)

Bases: object

LogicBlock Manager.

class mpf.system.logic blocks.Sequence (machine, name, player, config)

Bases: mpf.system.logic_blocks.LogicBlock (page 88)

A type of LogicBlock which tracks many different events (steps) towards a goal, with the steps having to happen in order.

```
enable (step=0, **kwargs)
```

Enables this Sequence. Automatically called when one of the 'enable_events' is posted. Can also manually be called.

Parameters step – Step number this logic block will be at when it's enabled. Default is 0.

Note the step numbers are zero-based.

```
hit (**kwargs)
```

Increases the hit progress towards completion. Automatically called when one of the *count_events* is posted. Can also manually be called.

```
reset (**kwargs)
```

Resets the sequence back to the first step.

mpf.system.machine module

The main machine object for the Mission Pinball Framework.

```
class mpf.system.machine.MachineController(options)
```

Bases: object

Base class for the Machine Controller object.

The machine controller is the main entity of the entire framework. It's the main part that's in charge and makes things happen.

Parameters options – Dictionary of options the machine controller uses to configure itself.

options

A dictionary of options built from the command line options used to launch mpf.py.

confid

A dictionary of machine's configuration settings, merged from various sources.

physical_hw

Boolean as to whether there is physical pinball controller hardware attached.

done

Boolean. Set to True and MPF exits.

machineflow index

What machineflow position the machine is currently in.

machine_path

The root path of this machine_files folder

```
display
```

plugins

scriptlets

tilted

platform

events

add_platform(name)

Makes an additional hardware platform interface available to MPF.

Parameters name – String name of the platform to add. Must match the name of a platform file in the mpf/platforms folder (without the .py extension).

```
flow_advance (position=None, **kwargs)
```

Advances the machine to the next machine mode as specified in the machineflow. Typically this just advances between Attract mode and Game mode.

```
log_loop_rate()
```

log system info()

Dumps information about the Python installation to the log.

Information includes Python version, Python executable, platform, and system architecture.

power_off()

Attempts to perform a power down of the pinball machine and ends MPF.

This method is not yet implemented.

quit()

Performs a graceful exit of MPF.

register_monitor (monitor_class, monitor)

Registers a monitor.

Parameters

- monitor_class String name of the monitor class for this monitor that's being registered.
- **monitor** String name of the monitor.

MPF uses monitors to allow components to monitor certain internal elements of MPF.

For example, a player variable monitor could be setup to be notified of any changes to a player variable, or a switch monitor could be used to allow a plugin to be notified of any changes to any switches.

The MachineController's list of registered monitors doesn't actually do anything. Rather it's a dictionary of sets which the monitors themselves can reference when they need to do something. We just needed a central registry of monitors.

reset()

Resets the machine.

This method is safe to call. It essentially sets up everything from scratch without reloading the config files and assets from disk. This method is called after a game ends and before attract mode begins.

Note: This method is not yet implemented.

run()

Starts the main machine run loop.

set_default_platform(name)

Sets the default platform which is used if a device class-specific or device-specific platform is not specified. The default platform also controls whether a platform timer or MPF's timer is used.

Parameters name – String name of the platform to set to default.

string_to_class(class_string)

Converts a string like mpf.system.events.EventManager into a python class.

Parameters class_string (*str*) – The input string

Returns A reference to the python class object

This function came from here: http://stackoverflow.com/questions/452969/ does-python-have-an-equivalent-to-java-class-forname

timer_tick()

Called to "tick" MPF at a rate specified by the machine Hz setting.

This method is called by the MPF run loop or the platform run loop, depending on the platform. (Some platforms drive the loop, and others let MPF drive.)

mpf.system.machine_mode module

```
class mpf.system.machine_mode.MachineMode (machine, name)
     Bases: object
```

A machine mode represents as special modes, the idea is there's only one at a time.

You can specify an order so that when one ends, the next one starts.

Examples

```
*Attract *Game *Match *Highscore Entry *Service
```

The idea is the machine modes will control the buttons since they do different things in different modes. ("Buttons" versus "Switches" in this case. Buttons are things that players can control, like coin switches, control panel buttons, flippers, start, plunge, etc.)

```
start()
```

Starts this machine mode.

stop()

Stops this machine mode.

tick(

Most likely you'll just copy this entire method to your mode subclass. No need for super().

mpf.system.modes module

Contains the ModeController, Mode, and ModeTimers parent classes

```
class mpf.system.modes.Mode (machine, config, name, path)
    Bases: object
```

Parent class for in-game mode code.

active

```
add mode event handler(event, handler, priority=1, **kwargs)
```

Registers an event handler which is automatically removed when this mode stops.

This method is similar to the Event Manager's add_handler() method, except this method automatically unregisters the handlers when the mode ends.

- **event** String name of the event you're adding a handler for. Since events are text strings, they don't have to be pre-defined.
- handler The method that will be called when the event is fired.
- **priority** An arbitrary integer value that defines what order the handlers will be called in. The default is 1, so if you have a handler that you want to be called first, add it here with a priority of 2. (Or 3 or 10 or 100000.) The numbers don't matter. They're called from highest to lowest. (i.e. priority 100 is called before priority 1.)
- **kwargs Any any additional keyword/argument pairs entered here will be attached to the handler and called whenever that handler is called. Note these are in addition to kwargs that could be passed as part of the event post. If there's a conflict, the event-level ones will win.

Returns A GUID reference to the handler which you can use to later remove the handler via remove_handler_by_key. Though you don't need to remove the handler since the whole point of this method is they're automatically removed when the mode stops.

Note that if you do add a handler via this method and then remove it manually, that's ok too.

configure_mode_settings(config)

Processes this mode's configuration settings from a config dictionary.

mode init()

User-overrideable method which will be called when this mode initializes as part of the MPF boot process.

mode start()

User-overrideable method which will be called whenever this mode starts (i.e. whenever it becomes active).

mode_stop()

User-overrideable method which will be called whenever this mode stops (i.e. whenever it becomes inactive).

player = None

Reference to the current player object.

```
start (priority=None, callback=None, **kwargs)
```

Starts this mode.

Parameters

- **priority** Integer value of what you want this mode to run at. If you don't specify one, it will use the "Mode: priority" setting from this mode's configuration file.
- **kwargs Catch-all since this mode might start from events with who-knows-what keyword arguments.

Warning: You can safely call this method, but do not override it in your mode code. If you want to write your own mode code by subclassing Mode, put whatever code you want to run when this mode starts in the mode_start method which will be called automatically.

```
stop (callback=None, **kwargs)
```

Stops this mode.

Parameters **kwargs – Catch-all since this mode might start from events with who-knows-what keyword arguments.

Warning: You can safely call this method, but do not override it in your mode code. If you want to write your own mode code by subclassing Mode, put whatever code you want to run when this mode stops in the mode stop method which will be called automatically.

```
class mpf.system.modes.ModeController(machine)
```

Bases: object

Parent class for the Mode Controller. There is one instance of this in MPF and it's responsible for loading, unloading, and managing all game modes.

dump()

Dumps the current status of the running modes to the log file.

```
register_load_method(load_method, config_section_name=None, **kwargs)
```

Used by system components, plugins, etc. to register themselves with the Mode Controller for anything they need a mode to do when it's registered.

Parameters

• load method – The method that will be called when this mode code loads.

- **config_section_name** An optional string for the section of the configuration file that will be passed to the load method when it's called.
- **kwargs Any additional keyword arguments specified will be passed to the load_method.

Note that these methods will be called once, when the mode code is first initialized during the MPF boot process.

register_start_method (start_method, config_section_name=None, **kwargs)

Used by system components, plugins, etc. to register themselves with the Mode Controller for anything that they a mode to do when it starts.

Parameters

- **start_method** The method that will be called when this mode code loads.
- **config_section_name** An optional string for the section of the configuration file that will be passed to the start_method when it's called.
- **kwargs Any additional keyword arguments specified will be passed to the start method.

Note that these methods will be called every single time this mode is started.

```
\textbf{class} \; \texttt{mpf.system.modes.ModeTimer} \; (\textit{machine}, \textit{mode}, \textit{name}, \textit{config})
```

Bases: object

Parent class for a mode timer.

Parameters

- machine The main MPF MachineController object.
- mode The parent mode object that this timer belongs to.
- name The string name of this timer.
- config A Python dictionary which contains the configuration settings for this timer.

```
add_time (timer_value, **kwargs)
```

Adds ticks to this timer.

Parameters

- Args -
- timer_value The number of ticks you want to add to this timer's current value.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

```
change_tick_interval (change=0.0, **kwargs)
```

Changes the interval for each "tick" of this timer.

Parameters

- **change** Float or int of the change you want to make to this timer's tick rate. Note this value is added to the current tick interval. To set an absolute value, use the set tick interval() method. To shorten the tick rate, use a negative value.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

kill()

Stops this timer and also removes all the control events.

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

pause (timer value=0, **kwargs)

Pauses the timer and posts the 'timer_<name>_paused' event

Parameters

- **timer_value** How many seconds you want to pause the timer for. Note that this pause time is real-world seconds and does not take into consideration this timer's tick interval.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

reset (**kwargs)

Resets this timer based to the starting value that's already been configured. Does not start or stop the timer.

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

restart (**kwargs)

Restarts the timer by resetting it and then starting it. Essentially this is just a reset() then a start()

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

set_current_time (timer_value, **kwargs)

Sets the current amount of time of this timer. This value is expressed in "ticks" since the interval per tick can be something other than 1 second).

Parameters

- timer_value Integer of the current value you want this timer to be.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

set_tick_interval (timer_value, **kwargs)

Sets the number of seconds between ticks for this timer. This is an absolute setting. To apply a change to the current value, use the change_tick_interval() method.

Parameters

- **timer_value** The new number of seconds between each tick of this timer. This value should always be positive.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

start (**kwargs)

Starts this timer based on the starting value that's already been configured. Use set_current_time() if you want to set the starting time value.

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

```
stop (**kwargs)
```

Stops the timer and posts the 'timer_<name>_stopped' event.

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

```
subtract_time (timer_value, **kwargs)
```

Subracts ticks from this timer.

Parameters

- timer_value The numebr of ticks you want to subtract from this timer's current value.
- **kwargs Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

timer_complete()

Automatically called when this timer completes. Posts the 'timer_<name>_complete' event. Can be manually called to mark this timer as complete.

Parameters **kwargs – Not used in this method. Only exists since this method is often registered as an event handler which may contain additional keyword arguments.

```
class mpf.system.modes.RemoteMethod
```

Bases: tuple

RemotedMethod is used by other modules that want to register a method to be called on mode_start or mode_stop.

```
__getnewargs__()
```

Return self as a plain tuple. Used by copy and pickle.

__getstate__()

Exclude the OrderedDict from pickling

__repr__()

Return a nicely formatted representation string

config_section

Alias for field number 1

kwargs

Alias for field number 2

method

Alias for field number 0

mpf.system.platform module

Contains the parent classes Platform

```
{\bf class} \; {\tt mpf.system.platform.Platform} \, ({\it machine})
```

Bases: object

Parent class for the a hardware platform interface.

Parameters machine - The main MachineController instance.

This is the class that each hardware controller (such as P-ROC or FAST) will subclass to talk to their hardware.

```
clear_hw_rule(sw_name)
```

Subclass this method in a platform module to clear a hardware switch rule for this switch.

Clearing a hardware rule means actions on this switch will no longer affect coils.

Another way to think of this is that it 'disables' a hardware rule. This is what you'd use to disable flippers and autofire_coils during tilt, game over, etc.

configure dmd()

Subclass this method in a platform module to configure the DMD.

This method should return a reference to the DMD's platform interface object which will be called to access the hardware.

configure_driver (config, device_type='coil')

Subclass this method in a platform module to configure a driver.

This method should return a reference to the driver's platform interface object which will be called to access the hardware.

configure_gi (config)

Subclass this method in a platform module to configure a GI string.

This method should return a reference to the GI string's platform interface object which will be called to access the hardware.

configure_led(config)

Subclass this method in a platform module to configure an LED.

This method should return a reference to the LED's platform interface object which will be called to access the hardware.

configure_matrixlight (config)

Subclass this method in a platform module to configure a matrix light.

This method should return a reference to the matrix lights's platform interface object which will be called to access the hardware.

configure_switch(config)

Subclass this method in a platform module to configure a switch.

This method should return a reference to the switch's platform interface object which will be called to access the hardware.

get_switch_state(switch)

Subclass this method in a platform module to get the hardware state of a switch.

Parameters switch – A class Switch object.

Return a value of 1 if the switch is active, and 0 if the switch is inactive. This method should not compensate for NO or NC status, rather, it should return the raw hardware state of the switch.

run_loop()

Subclass this method in a platform module if the platform will control the run loop rather than MPF controlling it.

If you want to use this method and let your platform control the machine's run loop, set $self.features['hw_timer'] = True$.

If your platform controls the loop, it should call *self.machine.timer_tick()* periodically based on the *self.machine.HZ* rate.

Also the loop should continue running until *self.machine.done* is True. For example, it could run in *while not self.machine.done*: loop.

Your loop can call *self.machine.switch_controller.process_switch()* if any switch events come in "off cycle", but the timer_tick should be called consistently.

This loop can safely block. If the call to the hardware does not block, there should be a small pause in the loop (e.g. *time.sleep(.001)* to prevent 100% CPU utilization.)

Parameters

• **sw_name** – String name of the switch.

- **sw_activity** String description of the switch activity this rule will be set for, either 'active' or 'inactive'.
- coil_name String name of the coil.
- coil action ms Total time in ms the coil should activate for.
- pulse_ms How long in ms the coil should activate for. Default is 0.
- **pwn_on** The 'on' portion, in ms of a pwm-based patter. Default is 0.
- pwm_off The 'off' portion, in ms, of a pwm-based patter. Default is 0.
- **delay** The delay, in ms, the coil should wait before firing. Default is 0.
- recycle_time How long the coil must be inactive, in ms, before it can be fired again via this rule. Default is 0.
- **debounced** Boolean which specifies whether this coil should activate on a debounced or non-debounced switch change state. Default is False (non-debounced).
- **drive_name** Boolean which controls whether the coil should activate immediately when this rule is applied if the switch currently in in the state set in this rule.

Note that this method provides several convenience processing to convert the incoming parameters into a format that is more widely-used by hardware controls. It's intended that platform interfaces subclass write hw rule() instead of this method, though this method may be subclassed if you wish.

tick()

Subclass this method in a platform module to perform periodic updates to the platform hardware, e.g. reading switches, sending driver or light updates, etc.

If you want to use this method and let MPF control the machine's run loop, set *self.features['hw_timer']* = *False*.

This method is only used when MPF controls the game loop. Each platform interface either needs to implement this method or the *run_loop* method.

This method will be called every 1ms.

timer initialize()

Run this before the machine loop starts. I want to do it here so we don't need to check for initialization on each machine loop. (Or is this premature optimization?)

```
write_hw_rule(sw, sw_activity, coil_action_ms, coil, pulse_ms, pwm_on, pwm_off, delay, recy-
cle time, debounced, drive now)
```

Subclass this method in a platform interface to write a hardware switch rule to the controller.

Game programmers will typically use *set_hw_rule* instead of this method because *set_hw_rule* takes switch NC and NO settings into account, so it's a bit more convenient.

mpf.system.scoring module

MPF plugin for a score controller which handles all scoring and bonus tracking.

```
class mpf.system.scoring.ScoreController(machine)
    Bases: object
```

```
add (points, force=False)
```

Adds to the current player's score.

Use this method instead of changing the value of the player attribute directly because this method will post the scoring events that other modules use for effects and stuff.

Parameters points – Integer of points to add to the current player's score. Note this value can also be negative to subtract points from their score.

```
process_config (config, mode=None, priority=0)
```

```
register_score_event (event_name, points, priority=0, block=False)
```

Used to register a score event which adds to a player's score when a certain event is posted.

Parameters

- event name The string name of the event that should cause a score change to take place.
- **points** The integer number of points that should be added or subtracted to the current player's score when this event is posted.
- **priority** Integer priority which is used in conjunction with block.
- **block** Boolean which specifies whether this event should block lower priority events. If True, lower priority events will not score as long as this event is registered. If False then lower priority events will score as normal.

Returns: A "key" which can be used to later unregister this event via the "unregister_score_event" method.

```
unload_score_events(key_list)
```

Unloads and removes several score events at once.

Parameters key_list – A list of keys of the score events you want to remove.

```
unregister score event(score entry key)
```

Removes a score event.

Parameters score_entry_key – The key of the score event to remove. This is the key that's returned by the 'register_score_event()' method.

mpf.system.scriptlet module

Contains the parent class for Scriptlets.

```
class mpf.system.scriptlet.Scriptlet (machine, name)
    Bases: object
    on load()
```

Automatically called when this Scriptlet loads. It's the intention that the Scriptlet writer will overwrite this method in the Scriptlet.

mpf.system.shots module

MPF plugin for a shot controller which converts series of switch events to 'shots' in the game.

```
class mpf.system.shots.SequenceShot (machine, name, config, priority)
    Bases: mpf.system.shots.Shot (page 99)
    confirm_shot()
        Called when the shot is complete to confirm and reset it.
    disable()
```

Disables the shot. If it's disabled, the switch handlers aren't active and the shot event will not be posted.

enable()

Enables the shot. If it's not enabled, the switch handlers aren't active and the shot event will not be posted.

progress index = None

Tracks how far along through this sequence the current shot is.

reset()

Resets the progress without disabling the shot.

```
\textbf{class} \; \texttt{mpf.system.shots.Shot} \; (\textit{machine}, \textit{name}, \textit{config}, \textit{priority} \texttt{=} 0)
```

Bases: object

disable()

Disables this shot.

When a shot is disabled, it doesn't track switches or progress and doesn't post events when the shot is made.

enable()

Enables this shot.

Shots are enabled by default when they're created.

monitor_enabled = False

Class attribute which specifies whether any monitors have been registered to track shots.

shot_made()

Called when this shot was successfully made.

```
{\bf class} \; {\tt mpf.system.shots.ShotController} \; ({\it machine}) \\
```

Bases: object

```
process_config (config, mode=None, priority=0)
```

```
remove_shots (shot_list)
```

class mpf.system.shots.StandardShot (machine, name, config, priority)

```
Bases: mpf.system.shots.Shot (page 99)
```

disable()

Disables the shot.

enable()

Enables the shot.

mpf.system.switch_controller module

Contains the SwitchController class which is responsible for reading switch states and posting events to the framework.

Base class for the switch controller, which is responsible for receiving all switch activity in the machine and converting them into events.

More info: http://missionpinball.com/docs/system-components/switch-controller/

```
add_switch_handler(switch_name, callback, state=1, ms=0, return_info=False, call-
back_kwargs=None)
```

Register a handler to take action on a switch event.

- switch_name String name of the switch you're adding this handler for.
- callback The method you want called when this switch handler fires.

- **state** Integer of the state transition you want to callback to be triggered on. Default is 1 which means it's called when the switch goes from inactive to active, but you can also use 0 which means your callback will be called when the switch becomes inactive
- ms Integer. If you specify a 'ms' parameter, the handler won't be called until the witch is in that state for that many milliseconds (rounded up to the nearst machine timer tick).
- **return_info** If True, the switch controller will pass the parameters of the switch handler as arguments to the callback, including switch_name, state, and ms. If False (default), it just calls the callback with no parameters.
- callback_kwargs Additional kwargs that will be passed with the callback.

You can mix & match entries for the same switch here.

is_active (switch_name, ms=None)

Oueries whether a switch is active.

Returns True if the current switch is active. If optional arg ms is passed, will only return true if switch has been active for that many ms.

Note this method does consider whether a switch is NO or NC. So an NC switch will show as active if it is open, rather than closed.

is_inactive (switch_name, ms=None)

Queries whether a switch is inactive.

Returns True if the current switch is inactive. If optional arg *ms* is passed, will only return true if switch has been inactive for that many ms.

Note this method does consider whether a switch is NO or NC. So an NC switch will show as active if it is closed, rather than open.

is_state (switch_name, state, ms=0)

Queries whether a switch is in a given state and (optionally) whether it has been in that state for the specified number of ms.

Returns True if the switch_name has been in the state for the given number of ms. If ms is not specified, returns True if the switch is in the state regardless of how long it's been in that state.

log = <logging.Logger object at 0x10728ee90>

log_active_switches()

Writes out entries to the log file of all switches that are currently active.

This is used to set the "initial" switch states of standalone testing tools, like our log file playback utility, but it might be useful in other scenarios when weird things are happening.

This method dumps these events with logging level "INFO."

ms_since_change (switch_name)

Returns the number of ms that have elapsed since this switch last changed state.

process_switch (name=None, state=1, logical=False, num=None, obj=None, debounced=True) Processes a new switch state change.

- name The string name of the switch. This is optional if you specify the switch via the 'num' or 'obj' parameters.
- state Boolean or int of state of the switch you're processing, True/1 is active, False/0 is inactive.

- **logical** Boolean which specifies whether the 'state' argument represents the "physical" or "logical" state of the switch. If True, a 1 means this switch is active and a 0 means it's inactive, regardless of the NC/NO configuration of the switch. If False, then the state parameter passed will be inverted if the switch is configured to be an 'NC' type. Typically the hardware will send switch states in their raw (logical=False) states, but other interfaces like the keyboard and OSC will use logical=True.
- **num** The hardware number of the switch.
- **obj** The switch object.
- **debounced** Whether or not the update for the switch you're sending has been debounced or not. Default is True

Note that there are three different paramter options to specify the switch: 'name', 'num', and 'obj'. You only need to pass one of them.

This is the method that is called by the platform driver whenever a switch changes state. It's also used by the "other" modules that activate switches, including the keyboard and OSC interfaces.

State 0 means the switch changed from active to inactive, and 1 means it changed from inactive to active. (The hardware & platform code handles NC versus NO switches and translates them to 'active' versus 'inactive'.)

```
remove_switch_handler(switch_name, callback, state=1, ms=0)
```

Removes a registered switch handler.

Currently this only works if you specify everything exactly as you set it up. (Except for return_info, which doesn't matter if true or false, it will remove either / both.

```
secs_since_change (switch_name)
```

Returns the number of ms that have elapsed since this switch last changed state.

```
set_state (switch_name, state=1, reset_time=False)
```

Sets the state of a switch.

```
verify_switches()
```

Loops through all the switches and queries their hardware states via their platform interfaces and them compares that to the state that MPF thinks the switches are in.

Throws logging warnings if anything doesn't match.

This method is notification only. It doesn't fix anything.

mpf.system.target controller module

Contains the TargetController class.

```
class mpf.system.target_controller.TargetController (machine)
    Bases: object

apply_group_profiles (config, priority, mode, **kwargs)

apply_target_profiles (config, priority, mode, **kwargs)

profiles = None
    **target_profiles dict* - profile name* - dict of settings

settings dict:
    •loop: boolean
    •steps: list of tuples: name light_script lightshow
```

```
register_profile (name, profile)
     register_profiles (config, **kwargs)
     {\tt remove\_group\_profiles}\ (mode)
     remove target profiles (mode)
mpf.system.tasks module
class mpf.system.tasks.DelayManager
     Bases: object
     Parent class for a delay manager which can manage multiple delays.
     add (name, ms, callback, **kwargs)
           Adds a delay.
               Parameters
                    • name – String name of this delay. This name is arbitrary and only used to identify the
                      delay later if you want to remove or change it.
                    • ms – Int of the number of milliseconds you want this delay to be for. Note that the reso-
                      lution of this time is based on your machine's tick rate. The callback will be called on the
                      first machine tick after the delay time has expired. For example, if you have a machine
                     tick rate of 30Hz, that's 33.33ms per tick. So if you set a delay for 40ms, the actual delay
                      will be 66.66ms since that's the next tick time after the delay ends.
                    • callback – The method that is called when this delay ends.
                    • **kwargs – Any other (optional) kwarg pairs you pass will be passed along as kwargs to
                      the callback method.
     check (delay)
           Checks to see if a delay exists.
               Parameters delay – A string of the delay you're checking for.
           Returns: The delay object if it exists, or None if not.
     clear()
           Removes (clears) all the delays associated with this DelayManager.
     dead delay managers = set([])
     delay managers = set([])
     remove (name)
           Removes a delay. (i.e. prevents the callback from being fired and cancels the delay.)
               Parameters name – String name of the delay you want to remove. If there is no delay with this
                   name, that's ok. Nothing happens.
     reset (name, ms, callback, **kwargs)
           Resets a delay, first deleting the old one (if it exists) and then adding new delay with the new settings.
               Parameters as add() (same) -
     static timer_tick()
```

```
class mpf.system.tasks.Task (callback, args=None, name=None, sleep=0)
    Bases: object
```

A task/coroutine implementation.

Tasks are similar to timers except they can yield back to the main loop at any point, then be resumed later.

To wait from a Task, do yield <ms>, e.g. yield 200.

To exit from a Task, just return. This will raise a StopIteration exception which the scheduler will catch and remove the task from the run queue.

```
static Create (callback, args=(), sleep=0)
```

Creates a new task and insert it into the runnable set.

```
NewTasks = set([])
Tasks = set([])
restart()
    Restarts the task.
stop()
    Stops the task.
```

This causes it not to run any longer, by removing it from the task set and then deleting it.

```
static timer_tick()
```

Scans all tasks now and run those that are ready.

mpf.system.timing module

Contains Timing and Timer classes

```
class mpf.system.timing.Timer(callback, args=(), frequency=None)
    Bases: object
```

Periodic timer object.

A timer defines a callable plus a frequency (in sec) at which it should be called. The frequency can be set to None so that the timer is not enabled, but it still exists.

Parameters

- callback (method) The method you want called each time this timer is fired.
- args (tuple) Arguments you want to pass to the callback.
- **frequency** (int or float) How often, in seconds, you want this timer
- be called. (to) -

```
call()
```

```
class mpf.system.timing.Timing (machine)
    Bases: object
```

System timing object.

This object manages timing for the whole system. Only one of these objects should exist. By convention it is called 'timing'.

The timing keeps the current time in 'time' and a set of Timer objects.

HZ = None

Number of ticks per second.

```
add (timer)
```

static int_to_pwm(ratio, length)

Converts a decimal between 0 and 1 to a pwm mask of whatever length you want.

For example, an input ratio of .5 with a result length of 8 returns 10101010. And input ratio of .7 with a result length of 32 returns 11011011101101101101101101101101.

Another way to think about this is this method converts a decimal percentage into the corresponding pwm mask.

Parameters

- ratio (float) A value between 0 and 1 that you want to convert.
- length (int) How many digits you want in your result.

ms_per_tick = None

Float of how many milliseconds one tick takes.

static pwm_ms_to_byte_int (pwm_on, pwm_off)

Converts a pwm_on / pwm_off ms times to a single byte pwm mask.

```
remove (timer)
```

static secs (s)

secs_per_tick = None

Float of how many seconds one tick takes.

static string_to_ms (time_string)

Decodes a string of real-world time into an int of milliseconds. Example inputs:

200ms 2s None

If no "s" or "ms" is provided, this method assumes "milliseconds."

If time is 'None' or a string of 'None', this method returns 0.

Returns Integer. The examples listed above return 200, 2000 and 0, respectively

static string_to_secs (time_string)

Decodes a string of real-world time into an float of seconds.

See 'string_to_ms' for a description of the time string.

static string_to_ticks (time_string)

Converts a string of real-world time into a float of how many machine ticks correspond to that amount of time.

See 'string to ms' for a description of the time string.

tick = 0

Current tick number of the machine. Starts at 0 when MPF boots and counts up forever until MPF ends. Used instead of real-world time for all MPF time- related functions.

```
timer_tick()
```

1.6.2 Module contents

MODULE CONTENTS

```
mpf.platform.openpixel, 47
                                           mpf.platform.p3 roc, 49
mpf.devices, 23
                                           mpf.platform.p roc, 54
mpf.devices.autofire, 1
                                           mpf.platform.virtual, 59
mpf.devices.ball_device, 2
                                           mpf.plugins, 64
mpf.devices.diverter, 4
                                           mpf.plugins.auditor, 60
mpf.devices.driver,5
                                           mpf.plugins.ball_save,61
mpf.devices.drop_target,6
                                           mpf.plugins.ball_search, 61
mpf.devices.flasher,7
                                           mpf.plugins.info_lights,62
mpf.devices.flipper,8
                                           mpf.plugins.osc, 62
mpf.devices.gi,9
                                           mpf.plugins.socket_events,64
mpf.devices.led, 10
                                           mpf.plugins.switch_player,64
mpf.devices.matrix light, 11
                                           mpf.system, 104
mpf.devices.new device template, 12
                                           mpf.system.assets, 64
mpf.devices.playfield, 13
                                           mpf.system.ball_controller,67
mpf.devices.playfield transfer, 15
                                           mpf.system.bcp, 68
mpf.devices.score reel, 15
                                           mpf.system.config,73
mpf.devices.switch, 20
                                           mpf.system.devices, 75
mpf.devices.target, 21
                                           mpf.system.events, 76
mpf.game, 27
                                           mpf.system.light_controller,80
mpf.game.attract, 23
                                           mpf.system.logic blocks, 87
mpf.game.game, 24
                                           mpf.system.machine, 89
mpf.game.player, 26
                                           mpf.system.machine_mode, 91
mpf.media_controller,41
                                           mpf.system.modes, 91
mpf.media_controller.core, 40
                                           mpf.system.platform, 95
mpf.media_controller.core.keyboard, 28
                                           mpf.system.scoring, 97
mpf.media_controller.core.language, 29
                                           mpf.system.scriptlet,98
mpf.media_controller.core.modes, 30
{\tt mpf.media\_controller.core.show\_controllempf.system.shots}, 98
                                           mpf.system.switch_controller,99
       31
                                           mpf.system.target_controller, 101
mpf.media controller.core.slide, 33
mpf.media_controller.core.slide_builder, mpf.system.tasks, 102
                                           mpf.system.timing, 103
mpf.media controller.core.sound, 36
mpf.media controller.decorators, 40
                                           mpf, 105
mpf.media_controller.display_modules,
       40
mpf.media_controller.elements, 41
mpf.media_controller.transitions,41
mpf.media_controller.version, 41
mpf.platform, 60
mpf.platform.fadecandy,41
mpf.platform.fast,43
```

108 Python Module Index

Symbols	method), 31
gatneyergs () (mnf madis controller acre mades Remo	nadd_loaded_callback() (mpf.system.light_controller.Show
method), 31	method), 85
getnewargs() (mpf.system.modes.RemoteMethod	add_mode_event_handler() (mpf.system.modes.Mode
method), 95	method), 91
getstate() (mpf.media_controller.core.modes.RemoteN	
method), 31	method), 76
	add_pixel() (mpf.platform.openpixel.OpenPixelClient
getstate() (mpf.system.modes.RemoteMethod	method), 48
method), 95	add_platform() (mpf.system.machine.MachineController
repr() (mpi.media_controller.core.modes.RemoteMetr	method), 89
method), 31	add_ready_callback() (mpf.media_controller.core.slide.Slide
repr() (mpf.system.modes.RemoteMethod method),	method), 34
95	add_show() (mpf.system.light_controller.Playlist
A	method), 84
	add_show_player_show()
Accrual (class in mpf.system.logic_blocks), 87	(mpf.media_controller.core.show_controller.ShowController
activate() (mpf.devices.diverter.Diverter method), 4	method), 32
active (mpf.media_controller.core.modes.Mode at-	add_switch_handler() (mpf.system.switch_controller.SwitchController
tribute), 30	method), 99
active (mpf.media_controller.core.slide.Slide attribute),	add_time() (mpf.system.modes.ModeTimer method), 93
33	add_value() (mpf.devices.score_reel.ScoreReelGroup
active (mpf.system.modes.Mode attribute), 91	
$active_scorereel group (mpf. devices. score_reel. Score Reel Core Reel C$	ontroller method), 16 advance() (mpf.devices.score_reel.ScoreReel method), 15
attribute), 17	advance() (mpf.devices.score_feer.scoreReer method), 13 advance() (mpf.devices.target.Target method), 21
add() (mpf.system.scoring.ScoreController method), 97	advance() (mpf.devices.target.TargetGroup method), 22
add() (mpf.system.tasks.DelayManager method), 102	
add() (mpf.system.timing.Timing method), 104	aliases (mpf.platform.p.g.roc.PDBConfig attribute), 51
add_ball() (mpf.devices.playfield.Playfield method), 13	aliases (mpf.platform.p_roc.PDBConfig attribute), 56
add_balls_in_play() (mpf.game.game.Game method), 24	apply_group_profiles() (mpf.system.target_controller.TargetController
add_element() (mpf.media_controller.core.slide.Slide	method), 101
method), 34	apply_profile() (mpf.devices.target.Target method), 21
add_handler() (mpf.devices.gi.GI method), 10	apply_target_profiles() (mpf.system.target_controller.TargetController
add_handler() (mpf.devices.matrix_light.MatrixLight	method), 101
method), 11	are_balls_gathered() (mpf.system.ball_controller.BallController
add_handler() (mpf.system.events.EventManager	method), 67
method), 76	Asset (class in mpf.system.assets), 64
add_key_map() (mpf.media_controller.core.keyboard.Keyb	asset_class (in module mpf.media_controller.core.sound),
method), 28	40
add_light_player_show()	AssetLoader (class in mpf.system.assets), 65
(mpf.system.light_controller.LightController	AssetManager (class in mpf.system.assets), 65
method), 80	assumed_value_int (mpf.devices.score_reel.ScoreReelGroup
add_loaded_callback() (mpf.media_controller.core.show_c	ontroller.Show 18

$assumed_value_list (mpf.devices.score_reel.ScoreReelGround ScoreReelGround S$	
attribute), 18	bcp_receive_trigger() (mpf.system.bcp.BCP method), 69
Attract (class in mpf.game.attract), 23	bcp_reset() (mpf.system.bcp.BCP method), 69
audit() (mpf.plugins.auditor.Auditor method), 60	bcp_trigger() (mpf.system.bcp.BCP method), 69
audit_event() (mpf.plugins.auditor.Auditor method), 60	BCPClientSocket (class in mpf.system.bcp), 71
audit_player() (mpf.plugins.auditor.Auditor method), 61	blit_8bit_alpha() (mpf.media_controller.core.slide.Slide
audit_shot() (mpf.plugins.auditor.Auditor method), 61	method), 34
audit_switch() (mpf.plugins.auditor.Auditor method), 61	build_slide() (mpf.media_controller.core.slide_builder.SlideBuilder
Auditor (class in mpf.plugins.auditor), 60 AutofireCoil (class in mpf.devices.autofire), 1	method), 36
award_extra_ball() (mpf.game.game.Game method), 24	C
award_extra_ban() (inpr.game.game.dame method), 24	
В	call() (mpf.system.timing.Timer method), 103
	CaseInsensitiveDict (class in mpf.system.config), 73
ball_drain() (mpf.plugins.ball_save.BallSave method), 61	change_speed() (mpf.media_controller.core.show_controller.Show
ball_drained() (mpf.game.game.Game method), 24 ball_ended() (mpf.game.game.Game method), 24	method), 31 change_speed() (mpf.system.light_controller.Show
ball_ending() (mpf.game.game.Game method), 25	method), 85
ball_found() (mpf.devices.playfield.Playfield method), 13	change_tick_interval() (mpf.system.modes.ModeTimer
ball_lost() (mpf.devices.playfield.Playfield method), 13	method), 93
ball_search_begin() (mpf.devices.playfield.Playfield	Channel (class in mpf.media_controller.core.sound), 36
method), 13	check() (mpf.system.tasks.DelayManager method), 102
ball_search_disable() (mpf.devices.playfield.Playfield	check_config_file_version() (mpf.system.config.Config
method), 14	static method), 73
ball_search_end() (mpf.devices.playfield.Playfield	check_for_complete() (mpf.devices.target.TargetGroup
method), 14	method), 22
ball_search_failed() (mpf.devices.playfield.Playfield	check_hw_switches() (mpf.devices.score_reel.ScoreReel
method), 14	method), 16
ball_search_schedule() (mpf.devices.playfield.Playfield	chime() (mpf.devices.score_reel.ScoreReelGroup
method), 14	method), 18
ball_started() (mpf.game.game.Game method), 25	class_label (mpf.devices.autofire.AutofireCoil attribute),
ball_started() (mpf.plugins.info_lights.InfoLights	1
method), 62	class_label (mpf.devices.ball_device.BallDevice at-
ball_starting() (mpf.game.game.Game method), 25	tribute), 2
BallController (class in mpf.system.ball_controller), 67	class_label (mpf.devices.diverter.Diverter attribute), 4
BallDevice (class in mpf.devices.ball_device), 2	class_label (mpf.devices.driver.Driver attribute), 5
balls (mpf.devices.ball_device.BallDevice attribute), 2	class_label (mpf.devices.drop_target.DropTarget at-
balls (mpf.devices.playfield.Playfield attribute), 14	tribute), 7
balls (mpf.system.ball_controller.BallController at-	class_label (mpf.devices.drop_target.DropTargetBank at-
tribute), 67 balls_in_play (mpf.game.game.Game attribute), 25	tribute), 7 class_label (mpf.devices.flasher.Flasher attribute), 7
BallSave (class in mpf.plugins.ball_save), 61	class_label (mpf.devices.flipper.Flipper attribute), 8
BallSearch (class in mpf.plugins.ball_search), 61	class_label (mpf.devices.gi.GI attribute), 10
bank() (mpf.platform.p3_roc.PDBCoil method), 51	class_label (mpf.devices.led.LED attribute), 10
bank() (mpf.platform.p_roc.PDBCoil method), 56	class_label (mpf.devices.matrix_light.MatrixLight
BCP (class in mpf.system.bcp), 68	attribute), 12
bcp_game_start() (mpf.system.bcp.BCP method), 68	class_label (mpf.devices.new_device_template.YourNewDevice
bcp_mode_start() (mpf.system.bcp.BCP method), 68	attribute), 12
bcp_mode_stop() (mpf.system.bcp.BCP method), 68	class_label (mpf.devices.playfield_transfer.PlayfieldTransfer
bcp_player_added() (mpf.system.bcp.BCP method), 69	attribute), 15
bcp_receive_dmd_frame() (mpf.system.bcp.BCP	class_label (mpf.devices.score_reel.ScoreReel attribute),
method), 69	16
bcp_receive_error() (mpf.system.bcp.BCP method), 69	class_label (mpf.devices.score_reel.ScoreReelGroup at-
bcp_receive_get() (mpf.system.bcp.BCP method), 69	tribute), 18
bcp_receive_set() (mpf.system.bcp.BCP method), 69	class_label (mpf.devices.switch.Switch attribute), 20

class_label (mpf.devices.target.Target attribute), 21	color() (mpf.platform.p3_roc.PDBLED method), 52
class_label (mpf.devices.target.TargetGroup attribute), 22	color() (mpf.platform.p_roc.PDBLED method), 57
clear() (mpf.media_controller.core.slide.Slide method),	color() (mpf.platform.virtual.VirtualLED method), 60
35	compensate() (mpf.devices.led.LED method), 11
clear() (mpf.system.events.QueuedEvent method), 79	complete() (mpf.system.logic_blocks.LogicBlock
clear() (mpf.system.tasks.DelayManager method), 102	method), 88
clear_hw_rule() (mpf.platform.fast.HardwarePlatform	Config (class in mpf.system.config), 73
method), 44	config (mpf.system.machine.MachineController at-
clear_hw_rule() (mpf.platform.p3_roc.HardwarePlatform	tribute), 89
method), 49	config_section (mpf.devices.autofire.AutofireCoil at-
clear_hw_rule() (mpf.platform.p_roc.HardwarePlatform	tribute), 1
method), 54	config_section (mpf.devices.ball_device.BallDevice at-
clear_hw_rule() (mpf.platform.virtual.HardwarePlatform	tribute), 2
method), 59	config_section (mpf.devices.diverter.Diverter attribute), 4
clear_hw_rule() (mpf.system.platform.Platform method),	config_section (mpf.devices.driver.Driver attribute), 5
95	config_section (mpf.devices.drop_target.DropTarget at-
client_send_OSC_message() (mpf.plugins.osc.OSC	tribute), 7
method), 63	config_section (mpf.devices.drop_target.DropTargetBank
client_update_all() (mpf.plugins.osc.OSC method), 63	attribute), 7
client_update_all_switches() (mpf.plugins.osc.OSC	config_section (mpf.devices.flasher.Flasher attribute), 7
method), 63	config_section (mpf.devices.flipper.Flipper attribute), 8
client_update_light() (mpf.plugins.osc.OSC method), 63	config_section (mpf.devices.gi.GI attribute), 10
client_update_switch() (mpf.plugins.osc.OSC method),	config_section (mpf.devices.led.LED attribute), 11
63	config_section (mpf.devices.matrix_light.MatrixLight at-
collection (mpf.devices.autofire.AutofireCoil attribute), 1	tribute), 12
collection (mpf.devices.ball_device.BallDevice attribute), 2	config_section (mpf.devices.new_device_template.YourNewDevice attribute), 13
collection (mpf.devices.diverter.Diverter attribute), 4	config_section (mpf.devices.playfield_transfer.PlayfieldTransfer
collection (mpf.devices.driver.Driver attribute), 5	attribute), 15
collection (mpf.devices.drop_target.DropTarget at-	config_section (mpf.devices.score_reel.ScoreReel at-
tribute), 7	tribute), 16
$collection\ (mpf.devices.drop_target.DropTargetBank\ at-$	config_section (mpf.devices.score_reel.ScoreReelGroup
tribute), 7	attribute), 19
collection (mpf.devices.flasher.Flasher attribute), 7	config_section (mpf.devices.switch.Switch attribute), 20
collection (mpf.devices.flipper.Flipper attribute), 8	config_section (mpf.devices.target.Target attribute), 21
collection (mpf.devices.gi.GI attribute), 10	config_section (mpf.devices.target.TargetGroup at-
collection (mpf.devices.led.LED attribute), 10	tribute), 22
collection (mpf.devices.matrix_light.MatrixLight attribute), 12	config_section (mpf.media_controller.core.modes.RemoteMethod attribute), 31
$collection (mpf. devices. new_device_template. Your New Devices and the collection of the collecti$	vicenfig_section (mpf.system.modes.RemoteMethod at-
attribute), 12	tribute), 95
$collection (mpf. devices. play field_transfer. Play field Transfer and the collection (mpf. devices. play field_transfer. Play field Transfer and the collection (mpf. devices. play field_transfer. Play field$	configure() (mpf.devices.autofire.AutofireCoil method), 1
attribute), 15	configure() (mpf.devices.flipper.Flipper method), 8
collection (mpf.devices.score_reel.ScoreReel attribute), 16	configure_dmd() (mpf.platform.fast.HardwarePlatform method), 44
collection (mpf.devices.score_reel.ScoreReelGroup at-	configure_dmd() (mpf.platform.p3_roc.HardwarePlatform
tribute), 18	method), 49
collection (mpf.devices.switch.Switch attribute), 20	configure_dmd() (mpf.platform.p_roc.HardwarePlatform
collection (mpf.devices.target.Target attribute), 21	method), 54
collection (mpf.devices.target.TargetGroup attribute), 22	configure_dmd() (mpf.platform.virtual.HardwarePlatform
color() (mpf.devices.led.LED method), 10	method), 59
color() (mpf.platform.fast.FASTDirectLED method), 43	configure_dmd() (mpf.system.platform.Platform
color() (mpf.platform.openpixel.OpenPixelLED method),	method), 95
48	configure_driver() (mpf.platform.fast.HardwarePlatform
	S = V (1 1

```
method), 44
                                                                                        configure switch() (mpf.platform.p roc.HardwarePlatform
configure driver() (mpf.platform.p3 roc.HardwarePlatform
                                                                                                       method), 55
                                                                                        configure switch() (mpf.platform.virtual.HardwarePlatform
               method), 49
configure driver() (mpf.platform.p roc.HardwarePlatform
                                                                                                       method), 59
               method), 54
                                                                                        configure switch()
                                                                                                                                (mpf.system.platform.Platform
                                                                                                       method), 96
configure driver() (mpf.platform.virtual.HardwarePlatform
              method), 59
                                                                                        confirm shot()
                                                                                                                             (mpf.system.shots.SequenceShot
configure driver()
                                       (mpf.system.platform.Platform
                                                                                                       method), 98
               method), 95
                                                                                        connect() (mpf.platform.openpixel.OPCThread method),
configure_gi()
                             (mpf.platform.fast.HardwarePlatform
                                                                                                       47
               method), 44
                                                                                        count_balls()
                                                                                                                       (mpf.devices.ball_device.BallDevice
configure gi() (mpf.platform.p3 roc.HardwarePlatform
                                                                                                       method), 2
                                                                                        count balls() (mpf.devices.playfield.Playfield method),
               method), 50
configure_gi()
                          (mpf.platform.p_roc.HardwarePlatform
                                                                                                        14
               method), 54
                                                                                        Counter (class in mpf.system.logic_blocks), 87
configure_gi()
                        (mpf.platform.virtual.HardwarePlatform
                                                                                        Create() (mpf.system.tasks.Task static method), 103
              method), 59
                                                                                        create_channel() (mpf.media_controller.core.sound.Track
configure gi() (mpf.system.platform.Platform method),
                                                                                                       method), 39
                                                                                        create devices()
                                                                                                                      (mpf.system.devices.Device
                                                                                                                                                                      static
configure globals()
                                  (mpf.platform.p3 roc.PDBConfig
                                                                                                       method), 75
              method), 51
                                                                                        create_loader_thread() (mpf.system.assets.AssetManager
configure globals()
                                    (mpf.platform.p roc.PDBConfig
                                                                                                       method), 65
                                                                                        create_playfield_device()
              method), 56
                                                                                                       (mpf.system.ball controller.BallController
configure led()
                             (mpf.platform.fast.HardwarePlatform
                                                                                                       method), 67
              method), 44
configure led() (mpf.platform.openpixel.HardwarePlatform.create show from script()
              method), 47
                                                                                                       (mpf.system.light_controller.LightController
configure_led() (mpf.platform.p3_roc.HardwarePlatform
                                                                                                       method), 80
              method), 50
                                                                                        create_socket_threads() (mpf.system.bcp.BCPClientSocket
configure\_led() \quad (mpf.platform.p\_roc.HardwarePlatform
                                                                                                       method), 72
               method), 55
                                                                                        create_track() (mpf.media_controller.core.sound.SoundController
configure_led() (mpf.platform.virtual.HardwarePlatform
                                                                                                        method), 37
               method), 59
                                                                                        create_trigger_event() (mpf.system.bcp.BCP method), 69
configure_led() (mpf.system.platform.Platform method),
                                                                                        current_time (mpf.system.light_controller.LightController
                                                                                                       attribute), 80
configure matrixlight() (mpf.platform.fast.HardwarePlatform
              method), 44
configure_matrixlight() (mpf.platform.p3_roc.HardwarePlatformtivate() (mpf.devices.diverter.Diverter method), 4
               method), 50
                                                                                         dead delay managers (mpf.system.tasks.DelayManager
configure_matrixlight() (mpf.platform.p_roc.HardwarePlatform
                                                                                                       attribute), 102
              method), 55
                                                                                         decode() (mpf.platform.p3_roc.DriverAlias method), 49
configure\_matrixlight() \ (mpf.platform.virtual. Hardware Platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platform.platfo
               method), 59
                                                                                        decode_command_string() (in module mpf.system.bcp),
configure_matrixlight()
                                      (mpf.system.platform.Platform
               method), 96
                                                                                        decode pdb address() (in module mpf.platform.p3 roc),
configure_mode_settings()
              (mpf.media controller.core.modes.Mode
                                                                                         decode pdb address() (in module mpf.platform.p roc),
              method), 30
configure_mode_settings()
                                              (mpf.system.modes.Mode
                                                                                        decrease volume() (mpf.system.bcp.BCP method), 69
               method), 92
                                                                                        dedicated bank()
                                                                                                                              (mpf.platform.p3 roc.PDBLight
configure_switch() (mpf.platform.fast.HardwarePlatform
                                                                                                       method), 52
              method), 44
                                                                                        dedicated bank()
                                                                                                                               (mpf.platform.p roc.PDBLight
configure switch() (mpf.platform.p3 roc.HardwarePlatform
                                                                                                        method), 57
               method), 50
```

dedicated_output() (mpf.platform.p3_roc.PDBLight	70
method), 52	disconnect() (mpf.platform.openpixel.OPCThread
dedicated_output() (mpf.platform.p_roc.PDBLight	method), 47
method), 57	display (mpf.system.machine.MachineController at-
delay_managers (mpf.system.tasks.DelayManager	tribute), 89
attribute), 102	Diverter (class in mpf.devices.diverter), 4
DelayManager (class in mpf.system.tasks), 102	dmd (mpf.platform.p_roc.PROCDMD attribute), 58
depth (mpf.media_controller.core.slide.Slide attribute), 34	does_event_exist() (mpf.system.events.EventManager method), 76
Device (class in mpf.system.devices), 75	done (mpf.system.machine.MachineController attribute),
device_class_init() (mpf.devices.led.LED class method),	89
11	done() (mpf.platform.openpixel.OPCThread method), 47
$device_class_init() (mpf.devices.new_device_template. You$	=
class method), 13	DriverAlias (class in mpf.platform.p3_roc), 49
$device_class_init() (mpf.devices.score_reel.ScoreReelGrouples and the state of $	
class method), 19	DropTarget (class in mpf.devices.drop_target), 6
DeviceCollection (class in mpf.system.devices), 75	DropTargetBank (class in mpf.devices.drop_target), 7
dict_merge() (mpf.system.config.Config static method), 73	dump() (mpf.media_controller.core.modes.ModeController method), 30
disable() (mpf.devices.autofire.AutofireCoil method), 1	dump() (mpf.system.modes.ModeController method), 92
disable() (mpf.devices.diverter.Diverter method), 4	_
disable() (mpf.devices.driver.Driver method), 6	E
disable() (mpf.devices.flipper.Flipper method), 8	eject() (mpf.devices.ball_device.BallDevice method), 2
disable() (mpf.devices.gi.GI method), 10	eject() (mpf.devices.playfield.Playfield method), 14
disable() (mpf.devices.led.LED method), 11	eject_all() (mpf.devices.ball_device.BallDevice method),
disable() (mpf.devices.target.Target method), 21	2
disable() (mpf.devices.target.TargetGroup method), 22	eject_all() (mpf.devices.playfield.Playfield method), 14
disable() (mpf.platform.fast.FASTDirectLED method),	eject_failed() (mpf.devices.ball_device.BallDevice
43	method), 2
disable() (mpf.platform.fast.FASTDriver method), 44	$eject_in_progress_target (mpf.devices.ball_device.BallDevice$
disable() (mpf.platform.p3_roc.PDBLED method), 52	attribute), 3
disable() (mpf.platform.p3_roc.PROCDriver method), 53	eject_queue (mpf.devices.ball_device.BallDevice at-
disable() (mpf.platform.p_roc.PDBLED method), 57	tribute), 3
disable() (mpf.platform.p_roc.PROCDriver method), 58	elements (mpf.media_controller.core.slide.Slide at-
disable() (mpf.platform.virtual.VirtualDriver method), 59 disable() (mpf.platform.virtual.VirtualLED method), 60	tribute), 33
disable() (mpf.plugins.auditor.Auditor method), 61	enable() (mpf.devices.autofire.AutofireCoil method), 1
disable() (mpf.system.logic_blocks.LogicBlock method),	enable() (mpf.devices.diverter.Diverter method), 5
88	enable() (mpf.devices.driver.Driver method), 6
disable() (mpf.system.shots.SequenceShot method), 98	enable() (mpf.devices.flipper.Flipper method), 8
disable() (mpf.system.shots.Shot method), 99	enable() (mpf.devices.gi.GI method), 10
disable() (mpf.system.shots.StandardShot method), 99	enable() (mpf.devices.target.Target method), 21
disable_bcp_switch() (mpf.system.bcp.BCP method), 69	enable() (mpf.devices.target.TargetGroup method), 22 enable() (mpf.platform.fast.FASTDirectLED method), 43
disable_bcp_switches() (mpf.system.bcp.BCP method),	enable() (mpf.platform.fast.FASTDriver method), 44
70	enable() (mpf.platform.p3_roc.PDBLED method), 52
$disable_dithering() \ (mpf.platform.fadecandy.FadeCandyOF) \\$	Chente() (mpf.platform p3_roc_PROCDriver method) 53
method), 41	enable() (mpf.platform.p_roc.PDBLED method), 57
disable_held_coil() (mpf.devices.diverter.Diverter	enable() (mpf.platform.p_roc.PROCDriver method), 58
method), 4	enable() (mpf.platform.virtual.VirtualDriver method), 59
disable_hw_switch() (mpf.devices.diverter.Diverter	enable() (mpf.platform.virtual.VirtualLED method), 60
method), 5	enable() (mpf.plugins.auditor.Auditor method), 61
disable_interpolation() (mpf.platform.fadecandy.FadeCand	Profice I mpf, plugins, ball save. Ball Save method), 61
method), 41	enable() (mpf.system.logic_blocks.Accrual method), 87
	enable() (mpf system logic blocks Counter method), 87

enable() (mpf.system.logic_blocks.LogicBlock method), 88	future_pulse() (mpf.platform.p3_roc.PROCDriver method), 53
enable() (mpf.system.logic_blocks.Sequence method), 88 enable() (mpf.system.shots.SequenceShot method), 98	future_pulse() (mpf.platform.p_roc.PROCDriver method), 58
enable() (mpf.system.shots.Shot method), 99	future_pulse() (mpf.platform.virtual.VirtualDriver
enable() (mpf.system.shots.StandardShot method), 99	method), 59
enable_bcp_switch() (mpf.system.bcp.BCP method), 70	method), 39
enable_bcp_switches() (mpf.system.bcp.BCP method),	G
70	Game (class in mpf.game.game), 24
enable_dithering() (mpf.platform.fadecandy.FadeCandyOPC method), 42	game_ended() (mpf.game.game.Game method), 25 game_ended() (mpf.plugins.info_lights.InfoLights
enable_hw_switches() (mpf.devices.diverter.Diverter	method), 62
method), 5	game_ending() (mpf.game.game.Game method), 25
enable_interpolation() (mpf.platform.fadecandy.FadeCandy	Question (mp. game.game.game method), 25
method), 42	game_starting() (mpf.devices.score_reel.ScoreReelController
enable_no_hold() (mpf.devices.flipper.Flipper method), 9	method), 17
enable_partial_power() (mpf.devices.flipper.Flipper	game_starting() (mpf.plugins.info_lights.InfoLights
method), 9	method), 62
enable_volume_keys() (mpf.system.bcp.BCP method), 70	gather_balls() (mpf.system.ball_controller.BallController method), 68
enabled (mpf.plugins.auditor.Auditor attribute), 61	get_additional_ball_capacity()
encode_command_string() (in module mpf.system.bcp),	(mpf.devices.ball_device.BallDevice method),
73	3
end() (mpf.plugins.ball_search.BallSearch method), 62	get_additional_ball_capacity()
EventManager (class in mpf.system.events), 76	(mpf.devices.playfield.Playfield method),
events (mpf.system.machine.MachineController attribute), 89	get_bcp_messages() (mpf.system.bcp.BCP method), 70
expire_ms (mpf.media_controller.core.slide.Slide at-	get_config_info() (mpf.system.devices.Device class
tribute), 34	method), 75
_	get_current_event() (mpf.system.events.EventManager
F	method), 77
fade() (mpf.platform.fast.FASTDirectLED method), 43	get_from_socket() (mpf.system.bcp.BCPClientSocket
fade() (mpf.platform.p3_roc.PDBLED method), 52	method), 72
fade() (mpf.platform.p_roc.PDBLED method), 57	get_globals() (mpf.platform.p3_roc.PDBConfig method),
FadeCandyOPClient (class in mpf.platform.fadecandy),	51
41	$get_key_press_string() (mpf.media_controller.core.keyboard.Keyboard$
fadeout() (mpf.media_controller.core.sound.StreamTrack	method), 28
method), 38	$get_language() (mpf.media_controller.core.language. Language$
FASTDirectLED (class in mpf.platform.fast), 43	method), 29
FASTDMD (class in mpf.platform.fast), 43	get_physical_value_list()
FASTDriver (class in mpf.platform.fast), 44	(mpf.devices.score_reel.ScoreReelGroup
FASTGIString (class in mpf.platform.fast), 44	method), 19
FASTMatrixLight (class in mpf.platform.fast), 44	get_proc_number() (mpf.platform.p3_roc.PDBConfig
FASTSwitch (class in mpf.platform.fast), 44	method), 51
flag_confirm_eject_via_count	get_proc_number() (mpf.platform.p_roc.PDBConfig
(mpf.devices.ball_device.BallDevice attribute),	method), 56
3	get_sound() (mpf.media_controller.core.sound.Track
flash() (mpf.devices.flasher.Flasher method), 7	method), 39
Flasher (class in mpf.devices.flasher), 7	get_state() (mpf.devices.led.LED method), 11
Flipper (class in mpf.devices.flipper), 8	get_status() (mpf.devices.ball_device.BallDevice
flow_advance() (mpf.system.machine.MachineController method), 89	method), 3 get_subsurface() (mpf.media_controller.core.slide.Slide
found_new_OSC_client() (mpf.plugins.osc.OSC	method), 35
method), 63	memou), 55

get_switch_state() method), 96	(mpf.system.platform.Platform	is_active() (mpf.system. method), 100	switch_controller.SwitchController
get_switch_states() (mpf. method), 45	platform.fast.HardwarePlatform		devices.score_reel.ScoreReelGroup
	ntroller.core.language.Language		atform.p3_roc.PDBCoil method),
	_controller.core.sound.SoundCon	ntirollerrect_coil() (mpf.pl	atform.p_roc.PDBCoil method),
GI (class in mpf.devices.g	gi), 9	is_direct_lamp() method), 52	(mpf.platform.p3_roc.PDBLight
Н		is_direct_lamp()	$(mpf.platform.p_roc.PDBLight$
	in mpf.platform.fadecandy), 43	method), 57	. 0 15 1 1 70
HardwarePlatform (class			events.QueuedEvent method), 79
	in mpf.platform.openpixel), 47		all_device.BallDevice method), 3
	in mpf.platform.p3_roc), 49		m.switch_controller.SwitchController
	in mpf.platform.p_roc), 54	method), 100	1.1 6.1.6 2) 52
	in mpf.platform.virtual), 59		odule mpf.platform.p3_roc), 53
height (mpf.media_contraction) 33	roller.core.slide.Slide attribute),		odule mpf.platform.p_roc), 59 tform.p3_roc.PDBCoil method),
hex_to_rgb() (mp	f.platform.fast.FASTDirectLED	51	
method), 43	_		form.p_roc.PDBCoil method), 56
hexstring_to_int() (mpf.sy static method),	ystem.light_controller.LightContr 80	oileapdb_lamp() (mpf.pla 52	tform.p3_roc.PDBLight method),
hexstring_to_list() (mpf.c	levices.led.LED method), 11	is_pdb_lamp() (mpf.pla	ntform.p_roc.PDBLight method),
	ystem.light_controller.LightContr	roller 57	
static method),	80	is_playfield() (mj	of.devices.ball_device.BallDevice
hit() (mpf.devices.target.7		method), 3	
hit() (mpf.devices.target.7	-		witch_controller.SwitchController
	locks.Accrual method), 87	method), 100	
	locks.Counter method), 88	_	.system.devices.DeviceCollection
	locks.Sequence method), 88	method), 75	for the last Delica Calledian
hw_state (mpf.devices.sw		method), 75	f.system.devices.DeviceCollection
HZ (mpf.system.timing.T	iming attribute), 103		.system.devices.DeviceCollection
1		method), 75	system.devices.DeviceConcetion
	of.platform.fast.SerialCommunica	ntor	
method), 46 increase volume() (mpf.s	system.bcp.BCP method), 70	jump() (mpf.devices.targ	get.Target method), 21
indexes (mpf.platform.p3	_roc.PDBConfig attribute), 51	K	
	roc.PDBConfig attribute), 56		P
InfoLights (class in mpf.p		•	.media_controller.core.keyboard),
	ices.score_reel.ScoreReelGroup	28	of contain and Conference
method), 19	C. L. C	keys_to_lower() (mj method), 74	pf.system.config.Config static
initialize_drivers() (n method), 52	npf.platform.p3_roc.PDBConfig		s.QueuedEvent method), 79
, ,	mpf.platform.p_roc.PDBConfig		es.ModeTimer method), 93
method), 56		knockdown() (mp	of.devices.drop_target.DropTarget
int_to_hex_string() (mpf. method), 45	platform.fast.HardwarePlatform	method), 7 kwargs (mpf.media_con	troller.core.modes.RemoteMethod
	m.timing.Timing static method),	attribute), 31	
104		kwargs (mpf.system.mo	des.RemoteMethod attribute), 95
int_to_reel_list() (mpf.demethod), 19	vices.score_reel.ScoreReelGroup	L	
	per.Flipper class method), 9	Language (class in mpf	.media controller.core.language),

29	map_new_score_reel_group()
LED (class in mpf.devices.led), 10	(mpf.devices.score_reel.ScoreReelController
light() (mpf.devices.score_reel.ScoreReelGroup method),	method), 17
19	match() (mpf.plugins.info_lights.InfoLights method), 62
LightController (class in mpf.system.light_controller), 80	matches() (mpf.platform.p3_roc.DriverAlias method), 49
list_of_lists() (mpf.system.config.Config static method),	matches() (mpf.platform.p_roc.DriverAlias method), 54
74	MatrixLight (class in mpf.devices.matrix_light), 11
load() (mpf.system.assets.Asset method), 65	$method (mpf.media_controller.core.modes. Remote Method$
load_asset() (mpf.system.assets.AssetManager method),	attribute), 31
65	method (mpf.system.modes.RemoteMethod attribute), 95
load_assets() (mpf.system.assets.AssetManager method),	Mode (class in mpf.media_controller.core.modes), 30
66	Mode (class in mpf.system.modes), 91
load_config_yaml() (mpf.system.config.Config static	mode_init() (mpf.system.modes.Mode method), 92
method), 74	mode_start() (mpf.system.modes.Mode method), 92
load_from_disk() (mpf.plugins.auditor.Auditor method),	mode_stop() (mpf.system.modes.Mode method), 92
61	ModeController (class in
load_show_from_disk() (mpf.media_controller.core.show_o	<u> </u>
method), 31	ModeController (class in mpf.system.modes), 92
load_show_from_disk() (mpf.system.light_controller.Show	
method), 86	monitor_enabled (mpf.game.player.Player attribute), 27
$load_shows() \ (mpf.system.light_controller.LightController$	
method), 81	mpf (module), 105
locate_asset_file() (mpf.system.assets.AssetManager	mpf.devices (module), 23
method), 66	mpf.devices.autofire (module), 1
log (mpf.system.switch_controller.SwitchController at-	mpf.devices.ball_device (module), 2
tribute), 100	mpf.devices.diverter (module), 4
log_active_switches() (mpf.system.switch_controller.Switch	
method), 100	mpf.devices.drop_target (module), 6
log_loop_rate() (mpf.system.machine.MachineController	mpf.devices.flasher (module), 7
method), 89	mpf.devices.flipper (module), 8
log_system_info() (mpf.system.machine.MachineControlle	
method), 89	mpf.devices.led (module), 10
logical_to_physical() (mpf.devices.score_reel.ScoreReel	mpf.devices.matrix_light (module), 11
method), 16	mpf.devices.new_device_template (module), 12
LogicBlock (class in mpf.system.logic_blocks), 88	mpf.devices.playfield (module), 13
LogicBlocks (class in mpf.system.logic_blocks), 88	mpf.devices.playfield_transfer (module), 15
M	mpf.devices.score_reel (module), 15 mpf.devices.switch (module), 20
	•
machine (mpf.platform.p3_roc.HardwarePlatform at-	mpf.devices.target (module), 21
tribute), 49	mpf.game (module), 27 mpf.game.attract (module), 23
machine (mpf.platform.p_roc.HardwarePlatform at-	mpf.game.game (module), 24
tribute), 54	mpf.game.player (module), 24 mpf.game.player (module), 26
machine_path (mpf.system.machine.MachineController	mpf.media_controller (module), 41
attribute), 89	mpf.media_controller.core (module), 40
machine_type (mpf.platform.p3_roc.HardwarePlatform	mpf.media_controller.core.keyboard (module), 28
attribute), 49	mpf.media_controller.core.language (module), 29
machine_type (mpf.platform.p_roc.HardwarePlatform at-	mpf.media_controller.core.modes (module), 30
tribute), 54	mpf.media_controller.core.show_controller (module), 31
MachineController (class in mpf.system.machine), 89	
machineflow_index (mpf.system.machine.MachineControll	mpf.media_controller.core.slide_builder (module), 35
attribute), 89	mpf.media_controller.core.sound (module), 36
MachineMode (class in mpf.system.machine_mode), 91	mpf.media_controller.decorators (module), 40
make_sure_path_exists() (mpf.plugins.auditor.Auditor	mpf.media_controller.display_modules (module), 40
method), 61	mprimedia_controlleridisping_inodules (inodule), +0

	$num_balls_ejectable\ (mpf.devices.ball_device.BallDevice$
mpf.media_controller.transitions (module), 41	attribute), 3
mpf.media_controller.version (module), 41	num_balls_ejecting (mpf.devices.ball_device.BallDevice
mpf.platform (module), 60	attribute), 3
mpf.platform.fadecandy (module), 41	num_balls_in_transit (mpf.devices.ball_device.BallDevice
mpf.platform.fast (module), 43	attribute), 3
mpf.platform.openpixel (module), 47	$num_balls_known (mpf.system.ball_controller.BallController$
mpf.platform.p3_roc (module), 49	attribute), 68
mpf.platform.p_roc (module), 54	num_balls_requested (mpf.devices.ball_device.BallDevice
mpf.platform.virtual (module), 59	attribute), 3
mpf.plugins (module), 64	num_eject_attempts (mpf.devices.ball_device.BallDevice
mpf.plugins.auditor (module), 60	attribute), 3
mpf.plugins.ball_save (module), 61	num_jam_switch_count (mpf.devices.ball_device.BallDevice
mpf.plugins.ball_search (module), 61	attribute), 4
mpf.plugins.info_lights (module), 62	number() (mpf.system.devices.DeviceCollection
mpf.plugins.osc (module), 62	method), 76
mpf.plugins.socket_events (module), 64	0
mpf.plugins.switch_player (module), 64	
mpf.system (module), 104	off() (mpf.devices.led.LED method), 11
mpf.system.assets (module), 64	off() (mpf.devices.matrix_light.MatrixLight method), 12
mpf.system.ball_controller (module), 67	off() (mpf.platform.fast.FASTGIString method), 44
mpf.system.bcp (module), 68	off() (mpf.platform.fast.FASTMatrixLight method), 44
mpf.system.config (module), 73	off() (mpf.platform.p3_roc.PROCMatrixLight method),
mpf.system.devices (module), 75	53
mpf.system.events (module), 76	off() (mpf.platform.p_roc.PROCMatrixLight method), 58
mpf.system.light_controller (module), 80	off() (mpf.platform.virtual.VirtualGI method), 60
mpf.system.logic_blocks (module), 87	off() (mpf.platform.virtual.VirtualMatrixLight method),
mpf.system.machine (module), 89	60
mpf.system.machine_mode (module), 91	ok_to_confirm_ball_via_playfield_switch()
mpf.system.modes (module), 91	(mpf.devices.playfield.Playfield method),
mpf.system.platform (module), 95	14
mpf.system.scoring (module), 97	on() (mpf.devices.led.LED method), 11
mpf.system.scriptlet (module), 98	on() (mpf.devices.matrix_light.MatrixLight method), 12
mpf.system.shots (module), 98	on() (mpf.platform.fast.FASTGIString method), 44
mpf.system.switch_controller (module), 99	on() (mpf.platform.fast.FASTMatrixLight method), 44
mpf.system.target_controller (module), 101	on() (mpf.platform.p3_roc.PROCMatrixLight method),
mpf.system.tasks (module), 102	53
mpf.system.timing (module), 103	on() (mpf.platform.p_roc.PROCMatrixLight method), 58
ms_per_tick (mpf.system.timing.Timing attribute), 104	on() (mpf.platform.virtual.VirtualGI method), 60
ms_since_change() (mpf.system.switch_controller.SwitchC	
method), 100	60
N	on_load() (mpf.system.scriptlet.Scriptlet method), 98
	OPCThread (class in mpf.platform.openpixel), 47
name (mpf.media_controller.core.slide.Slide attribute),	OpenPixelClient (class in mpf.platform.openpixel), 47
33	OpenPixelLED (class in mpf.platform.openpixel), 48
NewTasks (mpf.system.tasks.Task attribute), 103	options (mpf.system.machine.MachineController at-
normalize_color() (mpf.platform.p3_roc.PDBLED	tribute), 89
method), 52	OSC (class in mpf.plugins.osc), 62
normalize_color() (mpf.platform.p_roc.PDBLED	output() (mpf.platform.p3_roc.PDBCoil method), 51
method), 57	output() (mpf.platform.p_roc.PDBCoil method), 56
normalize_hex_string() (mpf.platform.fast.HardwarePlatfor method), 45	P P
null_dmd_sender() (mpf.platform.fast.HardwarePlatform	
method), 45	palette (mpf.media_controller.core.slide.Slide attribute),

parse_matrix_num() (mpf.platform.p3_roc.PDBSwitch	22
method), 52	player_turn_start() (mpf.game.game.Game method), 25
parse_matrix_num() (mpf.platform.p_roc.PDBSwitch	Playfield (class in mpf.devices.playfield), 13
method), 57	playfield_switch_hit() (mpf.devices.playfield.Playfield
pause() (mpf.media_controller.core.sound.StreamTrack	method), 14
method), 38	PlayfieldTransfer (class in
pause() (mpf.system.modes.ModeTimer method), 94	mpf.devices.playfield_transfer), 15
PDBCoil (class in mpf.platform.p3_roc), 51	Playlist (class in mpf.system.light_controller), 83
PDBCoil (class in mpf.platform.p_roc), 56	plugin_class (in module mpf.plugins.auditor), 61
PDBConfig (class in mpf.platform.p3_roc), 51	plugin_class (in module mpf.plugins.ball_save), 61
PDBConfig (class in mpf.platform.p_roc), 56	plugin_class (in module mpf.plugins.ball_search), 62
PDBLED (class in mpf.platform.p3_roc), 52	plugin_class (in module mpf.plugins.info_lights), 62
PDBLED (class in mpf.platform.p_roc), 56	plugin_class (in module mpf.plugins.osc), 64
PDBLight (class in mpf.platform.p3_roc), 52	plugin_class (in module mpf.plugins.socket_events), 64
PDBLight (class in mpf.platform.p_roc), 57	plugin_class (in module mpf.plugins.switch_player), 64
PDBSwitch (class in mpf.platform.p3_roc), 52	plugins (mpf.system.machine.MachineController at-
PDBSwitch (class in mpf.platform.p_roc), 57	tribute), 89
pending_elements (mpf.media_controller.core.slide.Slide attribute), 35	pop_coil() (mpf.plugins.ball_search.BallSearch method), 62
persist (mpf.media_controller.core.slide.Slide attribute),	post() (mpf.system.events.EventManager method), 77
33	post_boolean() (mpf.system.events.EventManager
physical_hw (mpf.system.machine.MachineController at-	method), 77
tribute), 89	post_queue() (mpf.system.events.EventManager
Platform (class in mpf.system.platform), 95	method), 77
platform (mpf.system.machine.MachineController attribute), 89	post_relay() (mpf.system.events.EventManager method), 78
play() (mpf.media_controller.core.show_controller.Show method), 31	power_off() (mpf.system.machine.MachineController method), 90
play() (mpf.media_controller.core.sound.Channel method), 37	preload_check() (in module mpf.media_controller.core.keyboard), 28
play() (mpf.media_controller.core.sound.Sound method),	preload_check() (in module
37	mpf.media_controller.core.sound), 40
play() (mpf.media_controller.core.sound.StreamTrack method), 38	preprocess_settings() (mpf.media_controller.core.slide_builder.SlideBuilder method), 36
play() (mpf.media_controller.core.sound.Track method), 39	priority (mpf.media_controller.core.slide.Slide attribute), 33
play() (mpf.system.light_controller.Show method), 86	proc (mpf.platform.p3_roc.HardwarePlatform attribute),
play_show() (mpf.media_controller.core.show_controller.S	
method), 32	proc (mpf.platform.p3_roc.PDBConfig attribute), 52
	proc (mpf.platform.p_roc.HardwarePlatform attribute), 54
Player (class in mpf.game.player), 26	proc (mpf.platform.p_roc.PDBConfig attribute), 56
player (mpf.system.modes.Mode attribute), 92	proc_num() (mpf.platform.p3_roc.PDBSwitch method),
player_add_success() (mpf.game.game.Game method),	52
25	proc_num() (mpf.platform.p_roc.PDBSwitch method),
player_added() (mpf.plugins.info_lights.InfoLights	57
method), 62	PROCDMD (class in mpf.platform.p_roc), 57
player_eject_request() (mpf.devices.playfield.Playfield	PROCDriver (class in mpf.platform.p3_roc), 52
method), 14	PROCDriver (class in mpf.platform.p_roc), 58
player_rotate() (mpf.game.game.Game method), 25	process_assets_from_disk()
player_to_scorereel_map	(mpf.system.assets.AssetManager method), 66
(mpf.devices.score_reel.ScoreReelController	process_bcp_events() (mpf.system.bcp.BCP method), 70
attribute), 17	process_coil() (mpf.plugins.osc.OSC method), 63
player_turn_start() (mpf.devices.target.Target method),	process_config() (mpf.media_controller.core.slide_builder.SlideBuilder

method), 36 process_config() (mpf.plugins.osc.OSC method), 63 process_config() (mpf.plugins.socket_events.SocketClient	pwm() (mpf.platform.virtual.VirtualDriver method), 59 pwm_ms_to_byte_int() (mpf.system.timing.Timing static method), 104
method), 64	Q
process_config() (mpf.system.config.Config static	
method), 74 process_config() (mpf.system.scoring.ScoreController	query_fast_io_boards() (mpf.platform.fast.SerialCommunicator
process_config() (mpf.system.scoring.ScoreController method), 98	method), 47
process_config() (mpf.system.shots.ShotController	queue (mpf.devices.score_reel.ScoreReelController at-
method), 99	tribute), 17
process_event() (mpf.plugins.osc.OSC method), 63	queue (mpf.system.light_controller.LightController at- tribute), 81
process_event_player() (mpf.system.events.EventManager	queue_sound() (mpf.media_controller.core.sound.Track
method), 78	method), 39
process_flipper() (mpf.plugins.osc.OSC method), 63	OueuedEvent (class in mpf.system.events), 79
process_key_press() (mpf.media_controller.core.keyboard.l	Kayhoardnpf.system.machine.MachineController method),
method), 28	90
process_key_release() (mpf.media_controller.core.keyboard	l.Keyboard
method), 28	K
process_light() (mpf.plugins.osc.OSC method), 63	ready() (mpf.media_controller.core.slide.Slide method),
process_light_player() (mpf.system.light_controller.LightC	ontroller 35
method), 81	ready_callbacks (mpf.media_controller.core.slide.Slide
process_light_scripts() (mpf.system.light_controller.LightC	
method), 81	receive_dx() (mpf.platform.fast.HardwarePlatform
process_message() (mpf.plugins.osc.OSC method), 63	method), 45
process_received_message()	receive_goodbye() (mpf.system.bcp.BCPClientSocket
45	method), 72
process_shows_from_config()	receive_hello() (mpf.system.bcp.BCPClientSocket
(mpf.media_controller.core.show_controller.Show	method), 72 WController() (mpf plotform foot Hordword Plotform
method), 33	wheeling() (mpf.platform.fast.HardwarePlatform method), 45
process_switch() (mpf.plugins.osc.OSC method), 63	receive_local_closed() (mpf.platform.fast.HardwarePlatform
process_switch() (mpf.system.switch_controller.SwitchCor	itroller method), 45
method), 100	receive_local_open() (mpf.platform.fast.HardwarePlatform
PROCMatrixLight (class in mpf.platform.p3_roc), 53	method), 45
PROCMatrixLight (class in mpf.platform.p_roc), 58	receive_loop() (mpf.system.bcp.BCPClientSocket
PROCSwitch (class in mpf.platform.p3_roc), 53	method), 72
PROCSwitch (class in mpf.platform.p_roc), 58	receive_lx() (mpf.platform.fast.HardwarePlatform
profiles (mpf.system.target_controller.TargetController	method), 45
attribute), 101	receive_ni() (mpf.platform.fast.HardwarePlatform
progress_index (mpf.system.shots.SequenceShot at-	method), 45
tribute), 99	receive_nw_closed() (mpf.platform.fast.HardwarePlatform
pulse() (mpf.devices.driver.Driver method), 6 pulse() (mpf.platform.fast.FASTDriver method), 44	method), 45
pulse() (mpf.platform.p3_roc.PROCDriver method), 53	receive_nw_open() (mpf.platform.fast.HardwarePlatform
pulse() (mpf.platform.p_roc.PROCDriver method), 58	method), 45
pulse() (mpf.platform.virtual.VirtualDriver method), 59	receive_px() (mpf.platform.fast.HardwarePlatform
pulse_ms (mpf.devices.score_reel.ScoreReel attribute),	method), 45
16	receive_rx() (mpf.platform.fast.HardwarePlatform method), 45
pulsed_patter() (mpf.platform.virtual.VirtualDriver	receive_sa() (mpf.platform.fast.HardwarePlatform
method), 59	method), 45
pwm() (mpf.devices.driver.Driver method), 6	receive_sx() (mpf.platform.fast.HardwarePlatform
pwm() (mpf.platform.fast.FASTDriver method), 44	method), 45
pwm() (mpf.platform.p3_roc.PROCDriver method), 53	receive_wd() (mpf.platform.fast.HardwarePlatform
pwm() (mpf.platform.p_roc.PROCDriver method), 58	method) 45

```
(mpf.platform.fast.HardwarePlatform remove bcp connection()
                                                                                                                                            (mpf.system.bcp.BCP
receive wx()
              method), 45
                                                                                                      method), 71
                                                                                       remove element() (mpf.media controller.core.slide.Slide
                                (mpf.platform.virtual.VirtualDriver
reconfigure()
              method), 59
                                                                                                      method), 35
reel list to int() (mpf.devices.score reel.ScoreReelGroup remove group profiles()
              method), 19
                                                                                                      (mpf.system.target controller.TargetController
refresh() (mpf.media_controller.core.slide.Slide method).
                                                                                                       method), 102
                                                                                       remove handler() (mpf.devices.gi.GI method), 10
register_and_load_machine_assets()
                                                                                       remove handler() (mpf.devices.matrix light.MatrixLight
                                                                                                      method), 12
              (mpf.system.assets.AssetManager method), 66
register_asset()
                                  (mpf.system.assets.AssetManager
                                                                                       remove_handler()
                                                                                                                         (mpf.system.events.EventManager
              method), 66
                                                                                                      method), 78
                                  (mpf.system.assets.AssetManager
                                                                                       remove handler by event()
register_assets()
              method), 67
                                                                                                       (mpf.system.events.EventManager method), 78
register_data() (mpf.plugins.osc.OSC method), 63
                                                                                       remove_handler_by_key()
register_lights() (mpf.plugins.osc.OSC method), 63
                                                                                                       (mpf.system.events.EventManager method), 79
register_load_method() (mpf.media_controller.core.modes. Mende Controllers_by_keys()
              method), 30
                                                                                                      (mpf.system.events.EventManager method), 79
register load method() (mpf.system.modes.ModeControlleremove monitor()
                                                                                                                         (mpf.system.events.EventManager
              method), 92
                                                                                                      method), 79
register monitor() (mpf.system.machine.MachineControllerremove player controlled eject()
              method), 90
                                                                                                      (mpf.devices.playfield.Playfield
                                                                                                                                                               method),
register_mpfmc_trigger_events() (mpf.system.bcp.BCP
                                                                                                       15
              method), 70
                                                                                       remove profile() (mpf.devices.target.Target method), 22
register processor connection()
                                                                                                                            (mpf.devices.target.TargetGroup
                                                                                       remove profile()
              (mpf.platform.fast.HardwarePlatform method),
                                                                                                      method), 23
                                                                                       remove_shots()
                                                                                                                           (mpf.system.shots.ShotController
register_profile() (mpf.system.target_controller.TargetController
                                                                                                      method), 99
              method), 102
                                                                                       remove_switch_handler()
register_profiles() (mpf.system.target_controller.TargetController
                                                                                                      (mpf.system.switch controller.SwitchController
              method), 102
                                                                                                       method), 101
register_score_event() (mpf.system.scoring.ScoreControllerremove_target_profiles() (mpf.system.target_controller.TargetController
              method), 98
                                                                                                      method), 102
register\_sound\_event() \, (mpf.media\_controller.core.sound.Som the little register\_sound\_event() \, (mpf.media\_controller.core.sound.Som the little register\_sound\_event() \, (mpf.media\_controller.core.sound.Som the little register\_sound.Som the li
                                                                                                                         (mpf.system.events.EventManager
              method), 38
                                                                                                       method), 79
                                                                                                                      (mpf.devices.ball device.BallDevice
register sound events() (mpf.media controller.core.sound.ScoopadStobarb()er
              method), 38
                                                                                                       method), 4
register_start_method() (mpf.media_controller.core.modes.Mendesonthalter_add() (mpf.game.game.Game method),
              method), 30
register_start_method() (mpf.system.modes.ModeControllerrequest_to_start_game() (mpf.system.ball_controller.BallController
              method), 93
                                                                                                      method), 68
register switches() (mpf.plugins.osc.OSC method), 63
                                                                                       reset() (mpf.devices.drop target.DropTarget method), 7
register triggers() (mpf.system.bcp.BCP method), 71
                                                                                                              (mpf.devices.drop target.DropTargetBank
                                                                                       reset()
RemoteMethod
                                                (class
                                                                                 in
                                                                                                      method), 7
              mpf.media_controller.core.modes), 31
                                                                                       reset() (mpf.devices.target.Target method), 22
                                                                                       reset() (mpf.devices.target.TargetGroup method), 23
RemoteMethod (class in mpf.system.modes), 95
removal key (mpf.media controller.core.slide.Slide at-
                                                                                       reset() (mpf.system.logic blocks.Accrual method), 87
              tribute), 34
                                                                                       reset() (mpf.system.logic_blocks.Counter method), 88
remove() (mpf.media_controller.core.slide.Slide method),
                                                                                       reset() (mpf.system.logic_blocks.LogicBlock method),
                                                                                       reset() (mpf.system.logic_blocks.Sequence method), 89
remove() (mpf.system.tasks.DelayManager method), 102
remove() (mpf.system.timing.Timing method), 104
                                                                                       reset() (mpf.system.machine.MachineController method),
remove balls in play() (mpf.game.game.Game method),
                                                                                       reset() (mpf.system.modes.ModeTimer method), 94
```

reset() (mpf.system.shots.SequenceShot method), 99	ScoreReelGroup (class in mpf.devices.score_reel), 18
reset() (mpf.system.tasks.DelayManager method), 102	Scriptlet (class in mpf.system.scriptlet), 98
$reset_game_lights() (mpf.plugins.info_lights.InfoLights$	scriptlets (mpf.system.machine.MachineController
method), 62	attribute), 89
$reset_queue \ (mpf.devices.score_reel.ScoreReelController$	secs() (mpf.system.timing.Timing static method), 104
attribute), 17	secs_per_tick (mpf.system.timing.Timing attribute), 104
restart() (mpf.system.logic_blocks.LogicBlock method), 88	secs_since_change() (mpf.system.switch_controller.SwitchController method), 101
restart() (mpf.system.modes.ModeTimer method), 94	send() (mpf.platform.fast.SerialCommunicator method),
restart() (mpf.system.tasks.Task method), 103	47
restore() (mpf.devices.led.LED method), 11	send() (mpf.platform.openpixel.OpenPixelClient
restore() (mpf.devices.matrix_light.MatrixLight method),	method), 48
	send() (mpf.system.bcp.BCP method), 71
restore_lower_lights() (mpf.system.light_controller.LightC method), 81	
	send_goodbye() (mpf.system.bcp.BCPClientSocket method), 72
result_of_start_request() (mpf.game.attract.Attract method), 23	
	send_hello() (mpf.system.bcp.BCPClientSocket method),
resync() (mpf.system.light_controller.Show method), 87 rgb_to_hex() (mpf.platform.fast.FASTDirectLED	send_message() (mpf.plugins.socket_events.SocketClient
method), 43	method), 64
rotate() (mpf.devices.target.TargetGroup method), 23	send_switch() (mpf.media_controller.core.keyboard.Keyboard
rotate_left() (mpf.devices.target.TargetGroup method), 23	method), 28
rotate_player() (mpf.devices.score_reel.ScoreReelControlle	
method), 17	method), 72
rotate_right() (mpf.devices.target.TargetGroup method),	Sequence (class in mpf.system.logic_blocks), 88
23	SequenceShot (class in mpf.system.shots), 98
run() (mpf.platform.openpixel.OPCThread method), 47	SerialCommunicator (class in mpf.system.shots), 46
run() (mpf.system.assets.AssetLoader method), 65	set_balls_in_play() (mpf.game.game.Game method), 26
run() (mpf.system.machine.MachineController method),	set_current_time() (mpf.system.modes.ModeTimer
90	method), 94
run_loop() (mpf.system.platform.Platform method), 96	set_default_platform() (mpf.system.machine.MachineController
run_registered_script() (mpf.system.light_controller.Light()	
method), 81	set_destination_value() (mpf.devices.score_reel.ScoreReel
run_script() (mpf.system.light_controller.LightController	method), 17
method), 81	set_gamma() (mpf.platform.fadecandy.FadeCandyOPClient
running_show_keys (mpf.system.light_controller.LightCon	
attribute), 83	set_global_color_correction()
	(mpf.platform.fadecandy.FadeCandyOPClient
S	method), 42
save_to_disk() (mpf.plugins.auditor.Auditor method), 61	set_hw_rule() (mpf.system.platform.Platform method),
schedule() (mpf.platform.p3_roc.PROCDriver method),	96
53	set_language() (mpf.media_controller.core.language.Language
schedule() (mpf.platform.p_roc.PROCDriver method), 58	method), 29
schedule() (mpf.platform.virtual.VirtualDriver method),	set_linear_cutoff() (mpf.platform.fadecandy.FadeCandyOPClient
59	method), 42
schedule_deactivation() (mpf.devices.diverter.Diverter	set_linear_slope() (mpf.platform.fadecandy.FadeCandyOPClient
method), 5	method), 43
schedule_removal() (mpf.media_controller.core.slide.Slide	set_pixel_color() (mpf.platform.openpixel.OpenPixelClient
method), 35	method), 48
<pre>score_change() (mpf.devices.score_reel.ScoreReelControll</pre>	eset_rollover_reels() (mpf.devices.score_reel.ScoreReelGroup
method), 18	method), 19
ScoreController (class in mpf.system.scoring), 97	set_state() (mpf.system.switch_controller.SwitchController
ScoreReel (class in mpf.devices.score_reel), 15	method), 101
ScoreReelController (class in mnf devices score reel) 17	set tick interval() (mpf.system.modes.ModeTimer

method), 94	$source_bank() \ (mpf.platform.p_roc.PDBLight \ method),$
set_value() (mpf.devices.score_reel.ScoreReelGroup	57
method), 20	source_board() (mpf.platform.p3_roc.PDBLight
set_volume() (mpf.media_controller.core.sound.SoundCont method), 38	troller method), 52 source_board() (mpf.platform.p_roc.PDBLight method),
set_volume() (mpf.system.bcp.BCP method), 71	57
set_whitepoint() (mpf.platform.fadecandy.FadeCandyOPCl	
method), 43	method), 52
	source_output() (mpf.platform.p_roc.PDBLight method),
method), 64	57
<pre>setup_client_socket() (mpf.system.bcp.BCPClientSocket</pre>	split_matrix_addr_parts()
method), 72	(mpf.platform.p3_roc.PDBLight method),
setup_defaults() (mpf.system.assets.AssetManager	52
method), 67	split_matrix_addr_parts() (mpf.platform.p_roc.PDBLight
setup_midgame_restart() (mpf.game.game.Game	method), 57
method), 26	StandardShot (class in mpf.system.shots), 99
setup_OSC_client() (mpf.plugins.osc.OSC method), 63	start() (mpf.game.attract.Attract method), 24
setup_player_controlled_eject() (mof davises playfold Playfold prothed)	start() (mpf.game.game.Game method), 26
(mpf.devices.playfield.Playfield method),	start() (mpf.media_controller.core.modes.Mode method),
shoot_again() (mpf.game.game.Game method), 26	start() (mpf.plugins.ball_search.BallSearch method), 62
Shot (class in mpf.system.shots), 99	start() (mpf.plugins.osc.OSC method), 63
shot_made() (mpf.system.shots.Shot method), 99	start() (mpf.system.light_controller.Playlist method), 84
ShotController (class in mpf.system.shots), 99	start() (mpf.system.machine_mode.MachineMode
Show (class in mpf.media_controller.core.show_controller).	
31	start() (mpf.system.modes.Mode method), 92
Show (class in mpf.system.light_controller), 85	start() (mpf.system.modes.ModeTimer method), 94
show() (mpf.media_controller.core.slide.Slide method),	start_button_pressed() (mpf.game.attract.Attract
35	method), 24
ShowController (class in	start_button_released() (mpf.game.attract.Attract
mpf.media_controller.core.show_controller),	method), 24
3-2	state (mpf.devices.switch.Switch attribute), 20
shutdown() (mpf.system.bcp.BCP method), 71	state() (mpf.platform.p3_roc.PROCDriver method), 53
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method),	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p7_roc.PDBLight method), 52	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p7_roc.PDBLight method), 52 sink_output() (mpf.platform.p7_roc.PDBLight method), 57	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p7_roc.PDBLight method), 52 sink_output() (mpf.platform.p7_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method),
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p3_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p3_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_builde	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 det)p() (mpf.media_controller.core.show_controller.Show
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_builder) 35	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 detapp() (mpf.media_controller.core.show_controller.Show method), 32
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.plugins.socket_events), 64	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 det)p() (mpf.media_controller.core.show_controller.Show
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_builder) 35	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 det()p() (mpf.media_controller.core.show_controller.Show method), 32 stop() (mpf.media_controller.core.sound.Sound method), 37
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.plugins.socket_events), 64 Sound (class in mpf.media_controller.core.sound), 37	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 det()p() (mpf.media_controller.core.show_controller.Show method), 32 stop() (mpf.media_controller.core.sound.Sound method), 37
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p-roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p-roc.PDBLight method), 52 sink_output() (mpf.platform.p-roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.media_controller.core.sound), 37 sound_is_done() (mpf.media_controller.core.sound.Channemethod), 37 SoundController (class in	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.virtual.VirtualDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 detapp() (mpf.media_controller.core.show_controller.Show method), 32 stop() (mpf.media_controller.core.sound.Sound method), 37 elstop() (mpf.media_controller.core.sound.StreamTrack
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p3_roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p_roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide), 33 SlideBuilder (class in mpf.media_controller.core.slide_build 35 SocketClient (class in mpf.plugins.socket_events), 64 Sound (class in mpf.media_controller.core.sound), 37 sound_is_done() (mpf.media_controller.core.sound.Channe method), 37 SoundController (class in mpf.media_controller.core.sound), 37	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.p_roc.PROCDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 det)p() (mpf.media_controller.core.show_controller.Show method), 32 stop() (mpf.media_controller.core.sound.Sound method), 37 elstop() (mpf.media_controller.core.sound.StreamTrack method), 39 stop() (mpf.media_controller.core.sound.Track method), 40
shutdown() (mpf.system.bcp.BCP method), 71 sink_bank() (mpf.platform.p3_roc.PDBLight method), 52 sink_bank() (mpf.platform.p_roc.PDBLight method), 57 sink_board() (mpf.platform.p3_roc.PDBLight method), 52 sink_board() (mpf.platform.p-roc.PDBLight method), 57 sink_output() (mpf.platform.p3_roc.PDBLight method), 52 sink_output() (mpf.platform.p-roc.PDBLight method), 52 sink_output() (mpf.platform.p-roc.PDBLight method), 57 slam_tilt() (mpf.game.game.Game method), 26 Slide (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.media_controller.core.slide_build_35 SocketClient (class in mpf.media_controller.core.sound), 37 sound_is_done() (mpf.media_controller.core.sound.Channemethod), 37 SoundController (class in	state() (mpf.platform.p3_roc.PROCDriver method), 53 state() (mpf.platform.p_roc.PROCDriver method), 58 state() (mpf.platform.p_roc.PROCDriver method), 59 status_dump() (mpf.devices.ball_device.BallDevice method), 4 step_settings() (mpf.system.light_controller.Playlist method), 85 stop() (mpf.devices.ball_device.BallDevice method), 4 stop() (mpf.game.attract.Attract method), 24 stop() (mpf.game.game.Game method), 26 stop() (mpf.media_controller.core.modes.Mode method), 30 detop() (mpf.media_controller.core.show_controller.Show method), 32 stop() (mpf.media_controller.core.sound.Sound method), 37 elstop() (mpf.media_controller.core.sound.StreamTrack method), 39 stop() (mpf.media_controller.core.sound.Track method),

stop() (mpf.plugins.osc.OSC method), 63 stop() (mpf.system.bcp.BCPClientSocket method), 72	TargetController (class in mpf.system.target_controller),
stop() (mpf.system.light_controller.Playlist method), 72 stop() (mpf.system.light_controller.Playlist method), 85	TargetGroup (class in mpf.devices.target), 22
stop() (mpf.system.light_controller.Show method), 87	Task (class in mpf.system.tasks), 102
stop() (mpf.system.mghi_controller.snow inclined), 87 stop() (mpf.system.machine_mode.MachineMode	Tasks (mpf.system.tasks.Task attribute), 103
method), 91	text() (mpf.media_controller.core.language.Language
stop() (mpf.system.modes.Mode method), 92	method), 29
stop() (mpf.system.modes.ModeTimer method), 94	tick (mpf.system.timing.Timing attribute), 104
stop() (mpf.system.tasks.Task method), 103	tick() (mpf.devices.score_reel.ScoreReelGroup method),
stop_client() (mpf.plugins.socket_events.SocketClient	20
method), 64	tick() (mpf.platform.fast.FASTDMD method), 43
stop_ignoring_hits() (mpf.system.logic_blocks.Counter	tick() (mpf.platform.fast.HardwarePlatform method), 46
method), 88	tick() (mpf.platform.openpixel.OpenPixelClient method),
<pre>stop_script() (mpf.system.light_controller.LightController</pre>	48
method), 83	tick() (mpf.platform.p3_roc.HardwarePlatform method),
stop_show() (mpf.media_controller.core.show_controller.S	
method), 33	tick() (mpf.platform.p3_roc.PROCDriver method), 53
<pre>stop_show() (mpf.system.light_controller.LightController</pre>	tick() (mpf.platform.p_roc.HardwarePlatform method),
method), 83	55
stop_shows_by_key() (mpf.media_controller.core.show_continckl@n(SipsypController_roc.PROCDMD method), 58	
method), 33	tick() (mpf.platform.p_roc.PROCDriver method), 58
$stop_shows_by_key() (mpf.system.light_controller.LightCont$	ontick()e(mpf.platform.virtual.VirtualDriver method), 59
method), 83	tick() (mpf.plugins.ball_search.BallSearch method), 62
$stop_shows_by_keys() (mpf.system.light_controller.LightCon$	
method), 83	method), 91
StreamTrack (class in mpf.media_controller.core.sound), 38	tick() (mpf.system.platform.Platform method), 97 tilt() (mpf.game.game.Game method), 26
string_to_class() (mpf.system.machine.MachineController	
method), 90	tilted (mpf.system.machine.MachineController attribute),
string_to_list() (mpf.system.config.Config static method),	89
75	timed_pwm() (mpf.devices.driver.Driver method), 6
string_to_lowercase_list() (mpf.system.config.Config	timed_pwm() (mpf.platform.p3_roc.PROCDriver
static method), 75	method), 53
string_to_ms() (mpf.system.timing.Timing static	<pre>timed_pwm() (mpf.platform.p_roc.PROCDriver method),</pre>
method), 104	58
string_to_secs() (mpf.system.timing.Timing static	Timer (class in mpf.system.timing), 103
method), 104	timer_complete() (mpf.system.modes.ModeTimer
string_to_ticks() (mpf.system.timing.Timing static	method), 95
method), 104	timer_initialize() (mpf.system.platform.Platform
<pre>subtract_time() (mpf.system.modes.ModeTimer method),</pre>	method), 97
94	$timer_tick() \qquad (mpf.system.machine.MachineController$
surface (mpf.media_controller.core.slide.Slide attribute),	method), 90
33	timer_tick() (mpf.system.tasks.DelayManager static
sw_flip() (mpf.devices.flipper.Flipper method), 9	method), 102
sw_release() (mpf.devices.flipper.Flipper method), 9	timer_tick() (mpf.system.tasks.Task static method), 103
Switch (class in mpf.devices.switch), 20	timer_tick() (mpf.system.timing.Timing method), 104
SwitchController (class in mpf.system.switch_controller),	Timing (class in mpf.system.timing), 103
99	total_players (mpf.game.player.Player attribute), 27
SwitchPlayer (class in mpf.plugins.switch_player), 64	Track (class in mpf.media_controller.core.sound), 39
sync_ms_next_tick() (mpf.system.light_controller.LightContyphe(mpf.devices.switch.Switch attribute), 21	
method), 83	U
T	
	unlight() (mpf.devices.score_reel.ScoreReelGroup
Target (class in mpf.devices.target), 21	method), 20

```
unload() (mpf.system.assets.Asset method), 65
                                                                                                                                                                                                VirtualDriver (class in mpf.platform.virtual), 59
unload() (mpf.system.logic blocks.LogicBlock method),
                                                                                                                                                                                                VirtualGI (class in mpf.platform.virtual), 59
                                88
                                                                                                                                                                                                VirtualLED (class in mpf.platform.virtual), 60
unload assets()
                                                                           (mpf.system.assets.AssetManager
                                                                                                                                                                                                VirtualMatrixLight (class in mpf.platform.virtual), 60
                                method), 67
                                                                                                                                                                                                VirtualSwitch (class in mpf.platform.virtual), 60
unload event player events()
                                (mpf.system.events.EventManager method), 79
unload light player shows()
                                                                                                                                                                                                wait() (mpf.system.events.QueuedEvent method), 79
                                (mpf.system.light controller.LightController
                                                                                                                                                                                                width (mpf.media controller.core.slide.Slide attribute),
                                method), 83
unload_score_events() (mpf.system.scoring.ScoreControllerwrite firmware_options()
                                method), 98
                                                                                                                                                                                                                                (mpf.platform.fadecandy.FadeCandyOPClient
unload show player shows()
                                                                                                                                                                                                                                 method), 43
                               (mpf.media_controller.core.show_controller.ShowController.rule()
                                                                                                                                                                                                                                                                (mpf.platform.fast.HardwarePlatform
                                method), 33
                                                                                                                                                                                                                                 method), 46
unload\_slide\_events() \\ (mpf.media\_controller.core.slide\_builder_tSlide\_Puilder_t(mpf.platform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_roc.HardwarePlatform.p3\_ro
                                method), 36
                                                                                                                                                                                                                                method), 50
unpause() \, (mpf.media\_controller.core.sound.StreamTrack \\ write\_hw\_rule() \, \, (mpf.platform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatform.p\_roc.HardwarePlatf
                                method), 39
                                                                                                                                                                                                                                 method), 55
unregister\_score\_event() \ (mpf.system.scoring. ScoreControll \\ \textit{@rite\_hw\_rule()} \ (mpf.platform.virtual. HardwarePlatform. \\ \textit{wavePlatform} \ (mpf.system.scoring. ScoreControll) \\ \textit{wavePlatfo
                                method), 98
                                                                                                                                                                                                                                method), 59
unregister_sound_event()
                                                                                                                                                                                                write hw rule() (mpf.system.platform.Platform method),
                                (mpf.media_controller.core.sound.SoundController
                                method), 38
unregister sound events()
                                (mpf.media_controller.core.sound.SoundControlleyourNewDevice
                                                                                                                                                                                                                                                                                                           (class
                                                                                                                                                                                                                                                                                                                                                                                  in
                                method), 38
                                                                                                                                                                                                                                mpf.devices.new device template), 12
update() (mpf.media_controller.core.slide.Slide method),
update() (mpf.platform.fast.FASTDMD method), 43
update() (mpf.platform.p_roc.PROCDMD method), 58
update() (mpf.platform.virtual.VirtualDMD method), 59
update_audits() (mpf.plugins.osc.OSC method), 63
update_ball() (mpf.plugins.osc.OSC method), 63
update config() (mpf.plugins.osc.OSC method), 63
                                                               (mpf.platform.fast.HardwarePlatform
update leds()
                                method), 46
update_pixels() (mpf.platform.openpixel.OpenPixelClient
                                method), 48
update_player() (mpf.plugins.osc.OSC method), 63
update score() (mpf.plugins.osc.OSC method), 63
update state from switch()
                                (mpf.devices.drop target.DropTarget method),
V
validate() (mpf.devices.autofire.AutofireCoil method), 1
                                                    (mpf.devices.score reel.ScoreReelGroup
validate()
                                method), 20
validate_config_item() (mpf.system.config.Config_static
                                method), 75
verify switches() (mpf.system.switch controller.SwitchController
                                method), 101
VirtualDMD (class in mpf.platform.virtual), 59
```