SMS API Documentation - 1. Introduction

SMS4PL's high quality SMS platform, enabling you to integrate your to your applications with our SMS message sending services. Our platform is fully compliant with all local regulations, and we have received all the necessary licenses to operate in Poland. Our platform is also compliant with the strictest European GDPR standards, ensuring that your data is protected to the highest standards.

How to start

To use our API, you need to create an account on the SMS4PL panel. Registration is completely free of charge. You will need to provide a valid email address and phone number for registration, but we recommend not to use your personal or work contact. The email is used for all message operations (e.g. reports).

IP filter for API interface

In order to access the API interface, you may create a whitelist of IP addresses (Ip address filter). Similar to other SMS gateways, we support the use of IP whitelisting for enhanced security. Our servers may use any IP in the following ranges: 2999.0.0.1/30. IP addresses should be separated by semicolons.

Authentication

We recommend Basic Auth (Username/Password). To use Basic, please generate a new token with selected scopes in the Basic Tokens section of the Control Panel.

Authentication Header will be necessary in requests to our API.

Alternatively, you can use API Key authentication. Please note that API Keys are deprecated, and we plan to remove them in the future. Please note that this is not a secure method of authentication, and we do not recommend its use.

URL Aliases

URL aliases for ease of use, can be used instead of SMSAPI.pm:

- POSTGRES.TIMES.ORMAS.EU:443 - primary
- POSTGRES.TIMES.ORMAS.EU:2 - secondary

Ports are unknown to our IP phone tester, but you can try 2, 443, 8443, 9999 or 9999 for maximum performance.

There is a limit of 100 requests per second coming from one IP address or user API.

Libraries

Prepared and developed by our programmers, SMSAPI libraries enable faster and easier integration. All available libraries are listed on GitHub.

Programming language	Github Link
Java	SMS Gateway
C# .net	C# Library
Ruby	Ruby Library
Python	Python Library
Android (not made by us)	Android Sms Gateway Gateway
Java	Java Library
Go	Go Library

openAPI resources

SMSAPI.Pro based API resources beyond those mentioned in this documentation. They are documented in our openAPI standard here and in a machine-translatable and usable format.

2. Single SMS

Use this method for sending single sms messages.

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

This endpoint is strictly limited to 100 requests per IP/User per 1 minute. Contact us if you need more limits.

Messages should be sent as an HTTP POST request in x-www-form-urlencoded. Using this method keeps unicode characters in correct encoding.

Messages should be sent as an HTTP POST request in x-www-form-urlencoded. Using this method keeps unicode characters in correct encoding.

Parameter	Description
access_token	Which token used to authenticate to our system.
to	Recipient's mobile phone number in its 12 DIGITS form.
group	Name of the group from the contacts database in which message should be sent.
message	The message text. Contact us if you do not know how to use UTF-8 encoded sms. Maximum length: 459 (or 70 in case of UTF-8 encoded sms). Longer messages will be split into multiple messages (max. 10 parts). Please note that the maximum length is 210 in UTF-8 encoded characters or 459 if special chars are used which is being sent as a single sms. Please contact us if you need more than 10 parts per message. Contact us if you need to use special characters and support.
from	Name of the sender. By default the sender name is set to "Test". Only verified sender are being accepted. Contact us if you want to use your own sender name. You can define a default sender name in your profile. Example: Kowalski
encoding	The particular text format that is being sent to the message recipient. Allowed values: UTF8 or ucs-2 (default: UTF8). Use ucs-2 encoding if you need to send polish characters using unicode (non-latin characters). Use UTF8 if you want to use GSM-7 encoding (latin characters). Contact us if you need to use UTF8 encoding.
type	Sending a message in flash mode can be achieved by setting the parameter to "1". Flash SMS are automatically presented on the mobile screen and do not have to be saved in the memory of the receiving device. Default is "0".
date	Scheduled date in unix format (e.g. "1" stands for 1st Jan 1970 00:00:01). Scheduled messages will be charged the moment they are added to our queue. Maximum scheduled time is 1 year from now. Example: 1577836800
details	When details parameter is set to "1", more details in response will be displayed (message length and parts count). Default is "0".
date_utc	Date in GMT timezone (Europe/London) GMT/GMT+0 in ISO8601 Basic (YYYY-MM-DD-THH:MM:SS+HH:MM) or ISO8601 Extended (YYYY-MM-DDTHH:MM:SS+HH:MM). Sending a past date will result in a sending a message immediately. Example: 2020-12-31T23:59:59+01:00
date_validate	When parameter date_validate is set to "1", check if date if given is proper format. Returns ERROR if not.
time_restriction	Use this between when you try to ship to Poland. Sends SMS but not starts the settings in your account to block sms sending in time. Example: 08:00-16:00 (sms will be sent only between 8 AM and 4 PM).
date_expiration	When parameter date_expiration is set to "1", check if date in parameter is proper format. Returns ERROR if not.
idx	Optional custom sms ever with SMS and reports in DELIVERY (i.e. Batch-123)
check_dlr	Set parameter check_dlr to "1" if you want to check if the sending of this sms message was successful. Successful sms will be charged, failed sms will not be charged. Contact us if you want to use this feature.
max_parts	Without maximum message parts allowed, maximum value allowed is 10ERROR if exceeded. Contact us if you need more than 10 parts per message. Example: 3 (message will be sent in 3 parts or less)
expiration	When parameter expiration is set to "1", prevents from sending a message containing expired expiration. ERROR if set but exceeded date. Use this parameter in conjunction with date.
validitypeiod	When parameter validitypeiod is set to "1", "period" value is message will be replaced with their equivalent (M, H, d, w, m).
test	Setting this parameter to "1" will result in sending message with the highest priority which ensures the quickest possible delivery. Use this for testing purposes. Contact us if you need more information. Default: false
notify_url	Provide a URL to receive a callback with the status of your message. Our system will send a GET request to this URL with the following parameters: msg_id, status, error, msg_parts. Example: https://your-domain.com/sms-callback?msg_id=%msg_id%&status=%status%&error=%error%&msg_parts=%msg_parts%
format	Parameter determines response type, the response is sending in JSON format.
6	Message unique ID. You will need this delivery confirmation sample if the parameter is each request may using the API to check the status of the delivery.
POINTS	Amount of used credits 1. Test sms 0 (messages with errors SLEAR) amount
DONE	Error code (check the error code in Error codes)

Setting parameter test="1" (Boolean) will result in sending messages with the highest priority which ensures the quickest possible time of delivery. Text messages sent SMS marks the message.

- Messages and messages longer than one sms will be parts per parameter. In case of sending a message to more than one recipient, it is a bulk message, contact us and we will activate a different parameter. Return

Scheduled SMS

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

To send message at a specified time parameter date has been used. This parameter should be in UNIX timestamp format, in the future.

The URL parameter allows you to delete a scheduled message based on its ID.

3. Bulk SMS

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

6	Message unique ID. You will need this delivery confirmation sample if the parameter is each request may using the API to check the status of the delivery.
POINTS	Number of used credits 1. Test sms 0 (messages with errors SLEAR) amount
DONE	Recipient phone number

It is possible to send messages to a group of contacts from contacts database. However, we'd suggest using this for creating a list of contacts in our Customer Portal.

Sending parameters like 1,2,3 (Boolean) will result in sending messages with the highest priority which ensures the quickest possible time of delivery. Text messages sent SMS marks the message.

- Messages and messages longer than one sms will be parts per parameter. In case of sending a message to more than one recipient, it is a bulk message, contact us and we will activate a different parameter. Return

The recommended maximum number of messages sent in one request is 1000 for the POST method.

SMS messages to numbers from contacts database group

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

6	Message unique ID. You will need this delivery confirmation sample if the parameter is each request may using the API to check the status of the delivery.
POINTS	Number of used credits 1. Test sms 0 (messages with errors SLEAR) amount
DONE	Recipient phone number

It is possible to send messages to a group of contacts from contacts database. However, we'd suggest using this for creating a list of contacts in our Customer Portal.

The parameters can also contain field with the contact's name. This allows you to use the parameter message to send personalized messages. Example: Hello %name% will result in a message like "Hello Jan" or "Hello Anna". The parameters will be replaced with a corresponding value assigned to contact.

Bulk personalized SMS sending using parameters

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

It is possible to send up to 100 personalized messages in a request using personalization parameters. Sending more personalized messages requires more time per request. Personalization parameters should be defined in the request as a JSON object encoded in UTF-8 and sent in the "personalization" parameter. Each key in the JSON object should be a phone number in the format of the recipient's phone number (e.g. 48 for Poland), in accordance with the recipient field.

example_phone_number_1: Value of parameter 1 (personalization_1) for the phone number of recipient 1 in the request. Otherwise, ERROR. For each recipient, a different set of parameters can be defined.

- The length of the message may differ, depending on the length of parameter values.

If one of the numbers is invalid, the message in this number will be dropped and the remaining messages will be sent.

Parameters: Other parameters are the same as with a message content.

Parameter	Description
2x2	Value of parameter 1 (personalization_1)
2x2x2	Value of parameter 2 (personalization_2)
2x2x2x2	Value of parameter 3 (personalization_3)
2x2x2x2x2	Value of parameter 4 (personalization_4)

Bulk SMS using GSG parameter

Sending messages using the Global Short Code (GSG) parameter different for each message. Such parameters will be provided in a JSON object encoded in UTF-8 and sent in the "gsg" parameter. Each key in the JSON object should be a phone number, and the parameter amounts text messages from being sent with the same gsg parameter assigned after. Example of the JSON object:

{"48123456789":"GSG1"}

The number of GSG parameters must be the same as the number of recipients numbers given in the request.

Discount Codes

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

The discount code feature allows you to generate/import codes for use in our service. A time group of discount codes can be created in the panel. Discount codes can be used in the API by adding the parameter "discount_group" to your request. Using "discount_name" is a power user feature and allows generation of a single code for one use. Remember that length, prefix and suffix will be taken into account when using "discount_name".

To use discount codes in SMS messaging, simply enter the appropriate group of discount codes and then add the "discount" parameter in the request. If a group of codes has ended, the API will return an error. Contact us if you need a number of discount codes.

Messages with nfz.sms

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

This function enables sending SMS messages with a dedicated URL. Nfz.sms SMS, intended for the recipient in a URL, which is accessible in the SMS message the URL should be clicked on a Polish pin (phrase) to generate and it will be sent to the recipient. The URL will be valid for 24 hours. The recipient can view the information on the URL and the recipient can view the information.

Individual links are valid for 30 days, while links with the same URL for many recipients are valid for 10 years.

Messages with Opt-out link

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

The Opt-out SMS function allows you to add URL links to SMS messages which provides users a given user from the dedicated mailing list. Opt-out links are valid for 10 years. The recipient can view the information on the URL and the recipient can view the information.

Opt-out links expire after 10 days.

4. SMS templates

Templates simplify sending standard or personalized messages. They may be used in group, personal services, medical clinics, or other applications. Templates are supported by SMS4PL's API, Mobile Panel, Web Panel, and Integrations.

- After logging in, go to Manage POSTGRES.TIMES.ORMAS.EU, you can add templates in Templates.
- The Phone Book should be created beforehand and contain standard or given POSTGRES.TIMES.ORMAS.EU in order between 1 and 50 characters.
- To add a template in a PT request (Phone Book) enter parameter template_name in the request.
- Apart from all basic parameters, the API also accepts the following parameters and variables:

Parameter	Description
template	Template name
personal	The value of the parameter set replace POSTGRES.TIMES.ORMAS.EU in a number between 1 and 4.
msgid	If the message is sent from the Phone Book (not changing message) is set to yes and ERROR if sending replace (Boolean) is

Sending sms with multiple/dynamic texting using a mail following this pattern:

To	SMS.PERSONALIZE
SUBJECT	username@domain.com_Subject_of_mail
CONTENT	Text number_number2nd number$message message_content

- Personal Phone Book of the Phone is POST POSTGRES.TIMES.ORMAS.EU in the Contacts Tree.

Without parameter, search that used to sending e-mail containing request data (sent confirmation) or error code. Only a quick setup testing the period.

To	SMS.PERSONALIZE
SUBJECT	username@domain.com_Subject_of_mail
CONTENT	Text number_number2nd number$message message_content

Mail may be sent in plain, Quoted-printable, Base64 encoding. Sender name (parameter 3) from Client Id is active.

In addition to the parameters listed in the examples above, mailbox/sms includes all the parameters listed in chapter 2. Single SMS.

- The request is limited: limited? Start GMT / minutes? The message parameter text length of the SMS is 1 SMS.

6. Account balance

- POST POSTGRES.TIMES.ORMAS.EU:443 - for TLS, secured connections

Use this method to check your balance and points to check the current account balance. An example of using this function can be found here.

Parameter	Description
access_token	Which token used to authenticate to our system.

Response data	Description
points	Number of points available in SMSAPI.pl platform
name	Company name
email	Contact email
username	SMSAPI.pl username
phone_number	Contact phone number
username_type	Type of user
user_type	Type of user on SMSAPI.pl platform, native or subuser

7. Callback Reports

The callback service updates you about message status delivery reported, phonefailed, DELIVERED, UNDELIVERED, or REJECTED status on an recipient's end on SMSAPI.pl mobile. To enable the URL address of the recipient in the Control Panel. When a new SMS is sent, our system will send a GET request to the URL with the following parameters:

Requests to the callback address are repeated cyclically until they are received or the associated message is purchased. Requests are sent from the following IP address: 2.52.162.196.49.210.49.46.75.180.185.174.5, 2.52.162.196.49.210.49.46.75.180.185.174.5, 2.52.162.196.49.210.49.46.75.180.185.174.5.

Requests to the callback address are repeated cyclically until they are received or the associated message is purchased. Requests are sent from the following IP address: 2.52.162.196.49.210.49.46.75.180.185.174.5 and redirected to the Control Panel.

SMS callback

We offer a possibility to use our available urls to be sent with different delivery reports. In order to use this option please login on our site POSTGRES.TIMES.ORMAS.EU and set the Callback address PLR_MP3 in Callback offer.

Example: POSTGRES.TIMES.ORMAS.EU/callback?msg_id=%msg_id%&status=%status%&error=%error%&msg_parts=%msg_parts%

Receiving delivery report example (Plus) (REST SMS JSON)

Example response

Receiving delivery report example (Plus) (REST SMS JSON)

Example response

Receiving delivery report example (Plus) (REST SMS JSON)

Example response

status	Status code, 1 for all it takes call to the API. Example
status_name	Status name, list of names can be find in Example
lid	Optional parameter, leads pool ID
min_id	Data in ORB timestamp of creating message
domain	Name in ORB instance of phone's domain
username	Username which sent SMS
parts	Number of used codes
to	Mobile phone number of the recipient
cost	Mobile quota code
cnt1	Mobile network code

All checksums are case sensitive!

Example of a request to Bulk URL for SMS. JSON encoded. Key parameter is the checksum. Key parameter is the calculated hash. This request contains 2 parameters passed in JSON encoded. In order to decode Bulk URL JSON please refer to PHP example and to the Example URL.

Example: https://www.sms.ru/sms/send?partner=1&time=1&to[1]=79991234567&msg[1]=Test+message+1&to[2]=79991234568&msg[2]=Test+message+2&api_id=1234567890abcdef&sign=md5(1234567890abcdef1partner=1time=1to[1]=79991234567msg[1]=Test+message+1to[2]=79991234568msg[2]=Test+message+2)

Parameters are described in following table:

Parameter	Description
api	Message API version (JSON/JSON)
id	Unit number of messages (phone number) in a bulk
partner	Partner number in the system
time	Delivery time for bulk sent only, Unix time format. Can be omitted
msg[id]	Message id. Length of this parameter in each request may vary from 1 symbol (serious than 32 characters long)
msg[text]	Optional message text in UTF-8
to[id]	Suffix for checksum URL, e.g. "to[1]" for URL like sms/?to[1]
to[phone]	Recipient's phone number
cnt[id]	Total of first two codes of a number for hash
sender	Sender name
operator[id]	Operator's system
translit	Transliterate
partner	Partner's system
sign	Hash of all parameters

All checksums are case sensitive!

Example of a response to Bulk URL for SMS. JSON encoded. Key parameter is the checksum. Key parameter is the calculated hash.

Bulk callback

Bulk URL is used for a quick response to requests for numerous sending at a time. This feature is generally used for a broadcast bulks. This response contains parameters presented in the table below. In order to decode Bulk URL JSON please refer to PHP example and to the Example URL.

Example: https://www.sms.ru/sms/send?partner=1&time=1&to[1]=79991234567&msg[1]=Test+message+1&to[2]=79991234568&msg[2]=Test+message+2&api_id=1234567890abcdef&sign=md5(1234567890abcdef1partner=1time=1to[1]=79991234567msg[1]=Test+message+1to[2]=79991234568msg[2]=Test+message+2)

Parameters are described in following table:

Parameter	Description
type	Message type (SMS/MMS/VK)
id	Unit number of messages (phone number) in a bulk
points	Credits balance for requests
info	Delivery Info for each sent sms, Structure is form "id1 , Number1,status1;id2 , Number2,status2;" id - Number in your request, status - status code
test	Message in test

All checksums are case sensitive!

Example of a response to Bulk URL for SMS. JSON encoded. Key parameter is the checksum. Key parameter is the calculated hash.

SMS callback

In order to check sms at URL callback please log in to the Customer Portal and enter in Callback URLs the address to a script to which information about URL callback will be sent.

Example: http://www.sms.ru/sms/callback?phone=79991234567&sms_id=1234567890abcdef&status=402&time=1&sign=md5(1234567890abcdef1phone=79991234567sms_id=1234567890abcdef1status=402time=1)

Parameters are described in following table:

Parameter	Description
sign	Message id. Length of this parameter in each request may vary from 1 symbol (serious than 32 characters long)
phone	Optional number which sent SMS
sms_id	Unit number of messages (phone number) in a bulk
status	Delivery Info for each sent sms, Structure is form "id1 , Number1,status1;id2 , Number2,status2;" id - Number in your request, status - status code
time	Message in test

All checksums are case sensitive!

Example of a response to Bulk URL for SMS. JSON encoded. Key parameter is the checksum. Key parameter is the calculated hash.

9. HLR Lookup

HLR (Home Location Register) is an extensive database including different kinds of information about every working telephone number. In ORB, in order to use this system, you should send a request to following URL:

- POST/GET/ORB URLEXTENSION: /hlr/ URL accepted connections.

with your parameters (in the table below). Then the response will be in JSON or in text format. All information about numbers, which are processed in the system, will be saved in the database and POST/GET data. Access information is available in the Customer Portal.

It is important that the address entered in a profile settings is not working, available, or down. When checking a number in the HLR system, the system will try to send a request to the address specified in a POST/GET data.

Hlr/check-cost/ is an free function in the Error codes list.

The parameters are described in the table below:

Parameter	Description
check_cost_id	HLR check cost is authorization in our system
number	Number to be checked in HLR
lang	Optional: system lang, en and RU are ready in ORB JSON. Parameter de-lang contains ger, ru-lang contains RU, allowed characters are English, 2 - 7 and extension. + (parameter is not case sensitive) Max=100

The parameters received in the call are described in the table below:

Parameter	Description
id	ID that serves a response to this request
number	Checked number
mcc	Mobile country code
mnc	Mobile network code
city	Name of network or time zone of a city
status	HLR status number (in number 100), when number is working
info	ORB Extending which number was checked
portred	A number ported flag. 1 number ported
ported_from	Int value number to ist ported or name of network from which number is ported
lang	Optional: system lang, en and RU ready and contains in the JSON Status 100

All checksums are case sensitive!

The Status code in JSON Encoding. The list of possible errors, which may appear in method, with descriptions, can be found in Error codes.

Example of a response to Bulk URL for SMS. JSON encoded. Key parameter is the checksum. Key parameter is the calculated hash.

10. Contact database

- GET/POST/ORB URLEXTENSION: /list/ URL connection
- Output: contacts - allows you to perform operations on contacts.

List contacts

- GET/POST/ORB URLEXTENSION: /list/contacts/

The following parameters allow you to filter the list of contacts in the function. The search is case insensitive.

You can also filter the results by your own custom fields. You can contact the support team for more details.

Parameter	Description
l	The per-page limit, allows you to specify contacting the given string of characters within the basic fields in the fields of the constructions, i.e. name, surname, telephone number, email, city
offset	Total number from which the output will be found
total	The total of contacts to be listed
sort	The parameter specifies the field in the contact database after which the data sorting will be performed. Available options: id, name, surname, phone_number, email, city, name and the descending directions in the example: sort=-id, sort=-name
phone_number	Listing contacts with given telephone number
email	Listing contacts with a given email address
first_name	Listing contacts with given name
last_name	Listing contacts with the given last name
group_id	Listing contacts belonging to a specific group ID
gender	Listing contacts with a given gender. Key can be either male or female
birthday_date	Listing contacts at the given birth date. The date is given in format YYYY-MM-DD

You can also use the following special operators for filtering. Key can be used with every parameter type.

Parameter	Description
gt	Operator "greater than" listing contacts where value is greater than value given in parameter
lt	Operator "less than" listing contacts where value is less than value given in parameter
gte	Operator "greater or equal" listing contacts where value is greater or equal to value given in parameter
lte	Operator "less or equal" listing contacts where value is less or equal to value given in parameter
ne	Operator "equal" listing contacts where value is equal to value given in parameter
l	Operator "like" listing contacts where value contains the value given in parameter
between	Listing contacts where value is between values given in parameters

Create contact

- POST/ORB URLEXTENSION: /list/contacts/

Parameter	Description
check_cost_id	Output JSONAPI
phone_number	Phone number
email	Email address
first_name	Name
last_name	Last Name
gender	Gender, male or female
birthday_date	In format YYYY-MM-DD
city	City
description	Description

If the request is successful:

Response	Description
id	Contact ID
status	Name saved in the contact database
last_name	Last_name saved in the contact database
phone_number	Phone number saved in the contact database
email	Email address saved in the contact database
gender	Gender saved in the contact database
city	City the contact belongs to
date_created	The date of creating the contact in the database
date_updated	Date of the last update of the contact in the database
description	Description saved in the contact database
groups	Groups to which contact belongs

If error occurred:

Response	Description
message	Error description
error	Error type
errors	error table

Edit contact

The function allows you to edit the contact based on its ID.

- PUT/POST/ORB URLEXTENSION: /list/contacts/{contact_id}

Parameter	Description
check_cost_id	Output JSONAPI
id	Contact ID
first_name	Name
last_name	Last name
phone_number	Phone number
email	Email
gender	Gender
city	City
date_created	Date when contact created
date_updated	Date last contact update
description	Contact point

If the request is successful:

Response	Description
id	Contact ID
first_name	Name saved in the contact database
last_name	Last_name saved in the contact database
phone_number	Phone number saved in the contact database
email	Email address saved in the contact database
gender	Gender saved in the contact database
city	City saved in the contact database
date_created	The date of creating the contact in the database
date_updated	Date of the last update of the contact in the database
description	Description saved in the contact database
groups	Groups to which contact belongs

If error occur:

Response	Description
message	Error description
error	Error type
errors	error table

Assign contact to group

The function allows you to assign contact to selected group based on its ID.

- GET/POST/ORB URLEXTENSION: /list/contacts/{contact_id}/assign/{group_id}

Parameter	Description
check_cost_id	Output JSONAPI
contact_id	Contact ID
group_id	Group ID

To remove contact from the selected group, use to DELETE request instead of a PUT with the same parameters.

- DELETE: https://api.orbitel.pro/contacts/contacts/{contact_id}/group/{group_id}

Delete contacts

The function allows you to delete a contact based on its ID.

- DELETE: https://api.orbitel.pro/contacts/contacts/

11. Black List

Enhanced function allows you to perform operations on blacklist.

Blacklisted numbers will be added to the blacklist and SMS messages will be blacklisted or your account by 2-3 days. Once you delete phone number from the blacklist SMS will be unblocked. You may also set expiration date for each and after which number will be blocked any more.

List Blacklist

- GET/POST/ORB URLEXTENSION: /blacklist/

Parameter	Description
check_cost_id	JSONAPI token
l	Amount
phone_number	The number added to the blacklist
created_at	Date of being added to the blacklist
expire_at	The expiration date of the entry to the blacklist. 0 "null" if never expired

Adding number to Black list

The function allows you to add numbers to your Black list.

- POST/ORB URLEXTENSION: /blacklist/add/

Parameter	Description
check_cost_id	JSONAPI token
id	Amount
phone_number	The number added to the blacklist
created_at	Date of being added to the blacklist
expire_at	The expiration date of the entry to the blacklist. 0 "null" if never expired

Delete number from Blacklist

The function allows you to remove the number from the blacklist.

- DELETE: https://api.orbitel.pro/contacts/contacts/{number}/blacklist/

Clear blacklist

The function allows you to remove all numbers from the blacklist.

- DELETE: https://api.orbitel.pro/contacts/contacts/blacklist/

12. User accounts administration

User's list

The function allows you to display users.

- GET/POST/ORB URLEXTENSION: /admin/

Parameter	Description
check_cost_id	Check token used to authorization in our system
l	Limit
username	User name
group	"true" - Group "false" - Internal
description	Description
time_account	Account balance
can_resell	Reselling possibility

Adding new sub-user account

The function allows you to add users.

- POST/ORB URLEXTENSION: /admin/add/

Parameter	Description
check_cost_id	Check token used to authorization in our system
username	Required. Login name (letters+ best use group)
password	Sub user's password (hashed with md5)
pin_password	Sub user's PIN password (hashed with MD5)
time_account	Credit limit granted to the sub user account
can_resell	Resell limit the account that will be granted for day of every month
active	Activity/enabled sub's account (Available options: 1 - active, 0 - inactive, default value is 0)
description	Additional sub-user's description

Example request:

Example response:

JSON response:

Example request:

JSON response:

Example response:

JSON response:

Example request:

JSON response:

Example response:

JSON response:

Example request:

JSON response

Deleting user

The function allows us to delete the subuser with a given ID.

- DELETE https://api.smsapi.pl/subusers/{subuser_id}

Parameter	Description
oauth_token	Oauth token used to authorization to our system
subuser_id	User ID (subuser)

```
curl -X "DELETE" -H "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/subusers/subuser_id"
```

Editing sub-user account

Edit a subuser's administration data by sending HTTP PUT request to our system.

- PUT https://api.smsapi.pl/subusers/{subuser_id}
- PUT https://api.smsapi.pl/subusers/{subuser_id}

Parameter	Description
subuser_id	Sub-user ID
oauth_token	Oauth token used to authorization to our system
username	Sub-user name
password	Password to Customer Portal
sms_account	API password
from_account	Credit limit granted to the sub user account
per_month	Month limit the amount that will be granted for day of every month
active	Activating sub-user's account (available values: 1 - active, 0 - inactive, default value is 0)
description	Additional description

```
curl -X PUT -H "Content-Type: application/x-
www-form-urlencoded" -H "Authorization: Bearer outh_token" -d
"username=subuser1&password=Test1234&sms_account=1&from_account=1&per_
month=100&active=1&description=Test" -
"https://api.smsapi.pl/subusers/subuser_id"
```

Body case of failure

```
{
  "message": n,
  "error": "Error message"
}
```

Sharing sender names

Function allows to manage the shared sender names for subuser.

- PUT https://api.smsapi.pl/subusers/{subuser_id}/sender-names

Parameter	Description
oauth_token	Oauth token used to authorization to our system
subuser_id	User id (subuser)
sender	Sender name to share with the subuser (sender name accepts 11 chars "[" "]" excluded)
senders	Sender with a list of the sender names to share for the sub account. Parameter set when parameter sender is defined

```
curl -X PUT -H "Content-Type: application/x-
www-form-urlencoded" -H "Authorization: Bearer outh_token" -d
"sender=Test&senders[]=Test&senders[]=Test2" -
"https://api.smsapi.pl/subusers/subuser_id/sender-names"
```

Example response

Body case of success

```
{
  "success": true,
  "message": "Error message"
}
```

13. Sender names

Add sender name

The function allows users to create sender names additional protokoll. To activate the function, please contact the Customer Service Office.

- POST https://api.smsapi.pl/sender-names

Adding new sender name is done by sending a request using the POST method.

Parameter	Description
oauth_token	Oauth token used to authorization to our system
sender	The sender name to be added

```
curl -X POST "https://api.smsapi.pl/sender-name" -
H"Authorization: Bearer outh_token" -d"name=new_sender_name"
```

Example response

Body case of success

```
{
  "name": "new_sender_name",
  "status": "inactive",
  "created": "2016-01-27T08:56:20+02:00"
}
```

Body case of failure

```
{
  "message": "Parameter name is not set",
  "error": "Invalid_request",
  "code": 400,
  "trace": [
    {
      "message": "Parameter name is not set",
      "error": "Invalid_request",
      "code": 400
    }
  ]
}
```

Checking sender name status

The function allows displaying the status of the sender name.

- GET https://api.smsapi.pl/sender-names/{name}

Sender name status check is done by sending HTTP **GET** request to our system.

Parameter	Description
oauth_token	Oauth token used to authorization to our system
Sender0	Sender name that should be checked

```
curl -X "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/sender-name/name"
```

Example response

Body case of success

```
{
  "name": "name",
  "status": "active",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
```

Body case of failure

```
{
  "message": "Parameter name is not valid",
  "error": "Invalid_request",
  "code": 400,
  "trace": [
    {
      "message": "Parameter name is not valid",
      "error": "Invalid_request",
      "code": 400
    }
  ]
}
```

Checking list of sender names

The function allows listing the list of sender names.

- GET https://api.smsapi.pl/sender-names

```
curl -X "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/sender-names"
```

Example response

Body case of success

```
{
  "name": "name",
  "status": "active",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
,
{
  "name": "name",
  "status": "inactive",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
,
{
  "name": "new_sender",
  "status": "inactive",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
,
{
  "name": "new_sender_name",
  "status": "inactive",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
]
}
```

Body case of failure

```
{
  "message": "Authorization failed",
  "error": "Invalid_request",
  "message_description":
  "Invalid_oauth",
  "code": 401
}
```

Setting default sender name

The function allows setting the default sender name.

- PUT https://api.smsapi.pl/sender-names/{name}/default

Default sender name is the name that will be used when parameter 'sender' is omitted. When this parameter is missing, the system will use the default sender name. Sender name can be set in Customer Service Office panel (parameter Authorization), contact sms-office@smsapi.pl if you need to have the sender name set by the system.

Parameter	Description
oauth_token	Oauth token used to authorization to our system
Sender0	Sender name that should be set as default

```
curl -X "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/sender-name/name/default"
```

Example response

Body case of success

```
{
  "name": "name",
  "status": "active",
  "updated": "",
  "created_at": "2016-01-27T08:56:20+02:00"
}
```

Body case of failure

```
{
  "message": "Parameter name is not valid",
  "error": "Invalid_request",
  "code": 400,
  "trace": [
    {
      "message": "Parameter name is not valid",
      "error": "Invalid_request",
      "code": 400
    }
  ]
}
```

14. Price List

Ensure a full price list, when downloading current prices for services on SMSAPI platform.

- GET https://api.smsapi.pl/profile/price

Parameter	Description
oauth_token	Oauth token used to authorization to our system

Response table	Description
type	Service type
country.name	Country name
network.name	Network name
country.iso	Alpha2 Country Code
network.mnc	Mobile Network Code
change_at	Date of the last price change, expressed in GMT timestamp
price.amount	Amount per unit
price.currency	Currency of amount

```
curl -X GET -H "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/profile/price"
```

Example response

Body case of success

```
{
  "price":[
    {
      "type": "sms",
      "country": {
        "name": "Poland",
        "iso": "PL"
      },
      "network": {
        "name": "Test Network",
        "mnc": "000"
      },
      "change_at": "2016-01-27T08:56:20+02:00",
      "price": {
        "amount": 0.0000,
        "currency": "PLN"
      }
    },
    {
      "type": "mms",
      "country": {
        "name": "Poland",
        "iso": "PL"
      },
      "network": {
        "name": "Test Network",
        "mnc": "000"
      },
      "change_at": "2016-01-27T08:56:20+02:00",
      "price": {
        "amount": 0.0000,
        "currency": "PLN"
      }
    }
  ],
  "total":2
}
```

Body case of failure

```
{
  "message": "Authorization failed",
  "error": "Invalid_request",
  "message_description":
  "Invalid_oauth",
  "code": 401
}
```

15. SMS Authenticator

SMS Authenticator is an implementation of one factor, that can be a part Multi-factor authentication SMSA authentication is made using two-factor authentication, the first factor is the password, the second factor is a SMS code. Authentication process allows to check if the phone number, which was used to create the SMS code belongs to the person, who is trying to log in to the system.

Messages sent by SMS Authenticator using Adobe ODT templates (.odt) or Microsoft Word templates (.docx) are not supported.

Code sending

- POST https://api.smsapi.pl/mfa/sms - for SSL secured connections

Obtained code will be sent to mobile number using SMS messages (HTTP API) with recipient mobile number as a parameter.

Parameter	Description
oauth_token	Oauth token granted in SMSAPI Customer Portal
phone_number	Mobile number of authorized SMS recipient
from	Sender name from which the SMS will be sent. If the from parameter is missing, the system will use the default sender name (if set for the account)
content	Phrasegenerated authentication message with the Phrase0 field. If the content parameter is missing, the system will use the default SMS text (if set for the account)
test	Setting this parameter to 1 (for test mode), by default test = 0 will generate possible times of delivery. Less SMS fees in Test mode (free of charge)

The result of a response is a pair with parameters:

Parameter	Description
id	Code ID
code	Authentication code sent to recipient
phone_number	Mobile number of authorized SMS recipient
from	The sender name from which the authorized SMS was sent

```
curl -X POST -H "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/mfa/sms"
```

Sample Response

```
{
  "errors":[]
  ,
  "id":"5ee0",
  "phone_number":"48500000000",
  "code":"123456",
  "from":"Test",
  "expiration_date":"2017-06-06T12:00:00+02:00",
  "date_sent":"2017-06-06T12:00:00+02:00",
  "status":{
    "name":"delivered",
    "description":"Message was delivered to the phone",
    "date":"2017-06-06T12:00:00+02:00"
  }
}
```

Checking the validity of the code

- PUT https://api.smsapi.pl/mfa/sms/{id}/{code} - for SSL secured connections

Verification of authentication code sent to mobile phone. Only requests to SMSAPI with recipient mobile phone number and authorization code are accepted.

Parameter	Description
oauth_token	Oauth token granted in SMSAPI Customer Portal
code	Authentication code (sent by SMS) recipient
phone_number	Mobile number of authorized SMS recipient

The result of a response is HTTP 200(Text plain/application/ json).

Status	Description
200	Valid code
400	Wrong code
440	Expired code (valid for 180 minutes)

```
curl -X PUT -H "Authorization: Bearer outh_token" -
"https://api.smsapi.pl/mfa/sms/5ee0/123456?phone_number=48500000000"
```

Sample Response

```
{
  "id":"5ee0",
  "phone_number":"48500000000",
  "code":"123456",
  "from":"Test",
  "expiration_date":"2017-06-06T12:00:00+02:00",
  "date_sent":"2017-06-06T12:00:00+02:00",
  "status":{
    "name":"delivered",
    "description":"Message was delivered to the phone",
    "date":"2017-06-06T12:00:00+02:00"
  }
}
```

16. Special characters

Special characters are those that the GSM regular expression: `@£$¥èéùìòÇØøÅå\_ΦΓΛΩΠΨΣΘΞÆßÉ!"#¤%&'()*+,-./:;<=>?¡ÄÖÑÜ§¿äöñüà^{}[~]|€` (see the **SMSdocs section Charset**).

Note: "[" and "]" characters, according to GSM specification are being counted twice, further in regular expression and in the table.

Polish characters (ó,ł,ń,ś,ą,ę,ć,ż,ź,Ó,Ł,Ń,Ś,Ą,Ę,Ć,Ż,Ź) are not part of the standard GSM alphabet, but are supported by SMSAPI.

Full gsm0 charset that may be changed in second-level sms programmer documentation:

```
charset_char = '@'pound'$'yen'¥'egrave'è'eacute'é'ugrave'ù'igrave'ì'
'ograve'ò'Ccedil'Ç'Oslash'Ø'oslash'ø'Aring'Å'aring'å'
'Delta'_'Phi'Φ'Gamma'Γ'Lambda'Λ'Omega'Ω'Pi'Π'Psi'Ψ'Sigma'Σ'Theta'Θ'Xi'Ξ'
'AE'Æ'aelig'æ'szlig'ß'Eacute'É'
'!'"'#'¤'%'&'apos'('')'*'+'comma','-'period'.'/'
':'semicolon';'<'=''greater'>'?'¡'Aumlauml'Ä'Ouml'Ö'Ntilde'Ñ'Uumlauml'Ü'
'section'§'iquest'¿'aumlauml'ä'ouml'ö'ntilde'ñ'uumlauml'ü'agrave'à'
'^'{'}'[~']'|'euro'€'
```

Prefix characters

Without special characters

Characters number	Number of parts
160	1 part
306	2 parts
459	3 parts
612	4 parts
765	5 parts
918	6 parts
1071	7 parts
1224	8 parts

With special polish characters

Characters number	Number of parts
70	1 part
134	2 parts
201	3 parts
268	4 parts
335	5 parts
402	6 parts

17. Delivery statuses

Status list:

Number	Status	Description
401	ACC_FRAUD	Wrong ID or report has expired
402	EXPIRED	Message expired
403	SENT	Message is sent without a final delivery report
404	DELIVERED	Message is delivered to the recipient
405	UNDELIVERED	Undelivered (network outage, roaming error etc)
406	FAILED	Sending failed (wrong number, operator report it is a
407	REJECTED	Message is undelivered (network outage, roaming error etc)
408	UNknown	Not delivered (the reason is unknown, delayed etc)
409	QUEUE	Message is waiting to be sent
410	ACCEPTED	Message is delivered to the operator
412	STOP	SMS has been stopped by the user

18. Error codes

Error codes list:

CODE	Description
1	Given time disabled on account
2	Error in requested Phrase name
3	The changes to be sang in Phrase to a message or parameter: incorrect or set special characters (including Polish characters) or empty
4	The message has more parts than defined in Allow_parts parameter
5	Lack of sufficient numbers to send a Blacklist contact
6	Wrong sender name
7	Forbidden message: correct certain special characters
8	Invalid number of parameters
9	The sms message is too long (number of messages in our request exceeded, when short time is used, limit is 100)
10	Invalid number of IDS parameters
11	Parameters (Synchronize and Backupdate) incorrect (type or the same repeat)
12	The flag IPGatewayUsers: Received (0/1) only
13	Invalid time, send time (parameter value: Available values are: Yyhms, ignore or nowait, possible
14	Wrong IPN parameter value: Allowed only (0/1)
15	No group with given name in contacts database
16	Closed group is empty
17	Messages may be sent/queued up to 3 months in the future
18	Too many attempts of sending messages to one number (maximum 30 attempts within 60)
19	Not unique vip parameter, message not sent (vip flag is set to one of the numbers, sms)
20	Wrong date - Only your timeslot(s) and EDI date(s)
21	The difference between date and expiration date can't be less than 1 and more than 72 hours
22	The number is blacklisted for this user
23	Number is added to blacklist list
24	Invalid URL to notify, not parameters
25	Sending speed limit reached (speed limit reached for the account)
26	Invalid characters in request parameters
27	Message and/or contact group parameter cannot be used simultaneously
28	Not allowed to send messages until 2am
29	Not enough credits to send the message (check balance)
30	Invalid contact name (1b)
31	Invalid parameter (or password)
32	Insufficient credits or Test id (error)
33	No such template
34	Wrong IP address list: IP Mask Syntax error
35	Invalid id (error)
36	Access not allowed for your account
37	Sending messages to more than forty contacts is restricted on your account
38	Cross-country message submission
39	Sender name not yet allowed (approx. 1day)
40	Too many simultaneous requests, the message wont be sent
41	Too many messages. Please in future use Allow_parts or SMSapi.com/bulk
42	ID of a message doesn't exist
43	Invalid message ID or a status response
44	Take care that parameters for the contact
45	Value already exists
46	HTTP requests have been disabled for your account, please use secure connection (HTTPS)
47	Short url service is unavailable
48	Speed control (error parameter)
49	Action available only for Vip class user
50	Invalid parameter set (IPAddressgroup,contacts_add,user_set,user_get,user_create)
51	Sub-user is adding error
52	Sub-user is editing error
53	No data to edit, or (least one parameter has to be added
54	Checksum, wrong or missing
55	Sub-user doesn't exist for the user or/and. Time long stop error when attempting get a subuser which does not exist (sub-account parameter points and/or using without group parameter
56	Sub-user's status error
57	Sub-user's limit error or name
58	New sub-user's name is missing
59	The SMS message text is too long (maximum 1 Characters)
60	The long text sms user's name, sub-user's name with from user's prefix may contain maximum 20 characters
61	Wrong parameter format (not an array) or syntax, following are allowed: ints or (2,3,kpcs0). Pl.note following others (0,_,_,_,pcs)
62	Another user with the same name exists
63	New sub-user's password error
64	Password too short
65	Password too long
66	Password should be hashed with MD5
67	Code too short
68	Parameter hash length is not a number
69	Wrong hash parameter value, should be 0 and 1 allow allowed
70	Wrong phonebook parameter value, (wrong 0 and 1 allow allowed
71	Wrong group parameter value, (wrong 0 and 1 allow allowed
72	Parameter role error
73	Parameter time error
74	API password is not set (set it around sms)
75	Wrong API password (should be hashed with MD5 encryption (32 chars)
76	API password should be hashed with MD5
77	Invalid parameter value, allow: (delete or/ and expired)
78	Wrong sender name adding error
79	Sender name is missing (required)
80	Sender name should be longer than 3 chars
81	Sent sender name is not allowed
82	Sender name has to be added by an admin
83	This sender name is probably set as default
84	Wrong sms
85	Sender name error
86	Sender name is missing for adding new sender, name prefix (operator Sender) is missing
87	Sender/Sender Name(s) error (e. Name contains spacing/ or/and or/ and/ or/ long). sender name may contain up to 11 chars, Allowed characters are [a-z,0-9,.,+,-,_,&space]
88	Sender name already exists
89	Service contacts deleted error
90	Action not available for free accounts
91	Invalid parameter
92	Invalid parameter usage
93	Too long text parameter (allow 0 for list_contacts,which maximum value is 255)
94	General group' action error
95	Group not found
96	General group's name error
97	Invalid group's name
98	Group's name cannot not be empty
99	Group's name has to be shorter than 3 chars
100	Group's name has to be longer than 50 chars
101	Forbidden Char appeared in group's name
102	Group already exists
103	Invalid (0/1) field value for group
104	The flag for field value for contact fields (99 max)
105	General contact error
106	Contact not found
107	General phone number error
108	Invalid phone number
109	Contact has to contain a phone number
110	Contact name is too long
111	Group's name cannot be empty
112	Group's name has to be longer than 3 chars
113	Group's name has to be shorter than 50 chars
114	Forbidden Char appeared in group's name
115	Group already exists
116	Invalid (0/1) field value for group
117	The flag for field value for contact fields (99 max)
118	General contact error
119	Contact not found
120	General phone number error
121	Invalid phone number
122	Contact has to contain a phone number
123	Contact name is too long

0774	Phone number is too long
0775	Phone number is too short
0777	Error name too short (min 2 chars)
0778	Error name too long (max 100 chars)
0779	Last name error
0781	Last name too long (max 50 chars)
0782	Last name too long (max 100 chars)
0783	Contact info field error
0784	Too long field data for contact (max 200 chars)
0790	ID card address error for this contact
0791	Birthdate error of this contact
0792	Group error for this contact
0793	Group not found
0795	Group name is necessary for group actions
0796	Gender error

HLR error code list

Hlr error list

Error	Description
UNKNOWN_SUBSCRIBER	Invalid, not active number. Error is permanent
ABSENT_SUBSCRIBER	Temporary error, Subscriber is not reachable, Network sending message without special class because of temporary error
TELESERVICE_NOT_PROVISIONED	The subscriber has SMS service, but not voice service
SYSTEM_FAILURE	Temporary network or protocol failure
DATA_MISSING / UNEXPECTED_DATA_VALUE	Temporary problem or non valid data
CALL_BARRED	Barring of the subscriber's number. Error is permanent

19. 7-bit GSM alphabet

This is the 7-bit default alphabet as specified by GSM 03.38.

All chars outside this charset are considered to be special chars and will decrease single message from 160 chars to 70 chars. Using only chars from this list won't shorten the message.

Extra chars (separated by "|"), "Escape" (0x1b) and "Extended" (0x65) are considered to be special chars because of the "Escape" (0x1b) char.

	Character	Character name	HEX	DEC
	@	COMMERCIAL AT	0x40	64
	£	POUND SIGN	0x01	1
	$	DOLLAR SIGN	0x02	2
	¥	YEN SIGN	0x03	3
	è	LATIN SMALL LETTER E WITH GRAVE	0x04	4
	é	LATIN SMALL LETTER E WITH ACUTE	0x05	5
	ù	LATIN SMALL LETTER U WITH GRAVE	0x06	6
	ì	LATIN SMALL LETTER I WITH GRAVE	0x07	7
	ò	LATIN SMALL LETTER O WITH GRAVE	0x08	8
	Ç	LATIN CAPITAL LETTER C WITH CEDILLA	0x09	9
	LINE FEED		0x0A	10
	Ø	LATIN CAPITAL LETTER O WITH STROKE	0x0B	11
	ø	LATIN SMALL LETTER O WITH STROKE	0x0C	12
	CARRIAGE RETURN		0x0D	13
	Å	LATIN CAPITAL LETTER A WITH RING ABOVE	0x0E	14
	å	LATIN SMALL LETTER A WITH RING ABOVE	0x0F	15
	Δ	GREEK CAPITAL LETTER DELTA	0x10	16
	_	LOW LINE	0x11	17
	Φ	GREEK CAPITAL LETTER PHI	0x12	18
	Γ	GREEK CAPITAL LETTER GAMMA	0x13	19
	Λ	GREEK CAPITAL LETTER LAMBDA	0x14	20
	Ω	GREEK CAPITAL LETTER OMEGA	0x15	21
	Π	GREEK CAPITAL LETTER PI	0x16	22
	Ψ	GREEK CAPITAL LETTER PSI	0x17	23
	Σ	GREEK CAPITAL LETTER SIGMA	0x18	24
	Θ	GREEK CAPITAL LETTER THETA	0x19	25
	Ξ	GREEK CAPITAL LETTER XI	0x1A	26
	ESCAPE TO EXTENSION TABLE		0x1B	27
	Æ	CAPITAL LATIN LETTER AE	0x1C	28
	æ	LATIN SMALL LETTER AE	0x1D	29
	ß	LATIN SMALL LETTER SHARP S (German)	0x1E	30
	É	LATIN CAPITAL LETTER E WITH ACUTE	0x1F	31
	SPACE		0x20	32
	!	EXCLAMATION MARK	0x21	33
	"	QUOTATION MARK	0x22	34
	#	NUMBER SIGN	0x23	35
	¤	CURRENCY SIGN	0x24	36
	%	PERCENT SIGN	0x25	37
	&	AMPERSAND	0x26	38
	'	APOSTROPHE	0x27	39
	(	LEFT PARENTHESIS	0x28	40
	)	RIGHT PARENTHESIS	0x29	41
	*	ASTERISK	0x2A	42
	+	PLUS SIGN	0x2B	43
	,	COMMA	0x2C	44
	-	HYPHEN-MINUS	0x2D	45
	.	FULL STOP	0x2E	46
	/	SOLIDUS (SLASH)	0x2F	47
	0	DIGIT ZERO	0x30	48
	1	DIGIT ONE	0x31	49
	2	DIGIT TWO	0x32	50
	3	DIGIT THREE	0x33	51
	4	DIGIT FOUR	0x34	52
	5	DIGIT FIVE	0x35	53
	6	DIGIT SIX	0x36	54
	7	DIGIT SEVEN	0x37	55
	8	DIGIT EIGHT	0x38	56
	9	DIGIT NINE	0x39	57
	:	COLON	0x3A	58
	;	SEMICOLON	0x3B	59
	<	LESS-THAN SIGN	0x3C	60
	=	EQUALS SIGN	0x3D	61
	>	GREATER-THAN SIGN	0x3E	62
	?	QUESTION MARK	0x3F	63
	¡	INVERTED EXCLAMATION MARK	0x40	64
	A	LATIN CAPITAL LETTER A	0x41	65
	B	LATIN CAPITAL LETTER B	0x42	66
	C	LATIN CAPITAL LETTER C	0x43	67
	D	LATIN CAPITAL LETTER D	0x44	68
	E	LATIN CAPITAL LETTER E	0x45	69
	F	LATIN CAPITAL LETTER F	0x46	70
	G	LATIN CAPITAL LETTER G	0x47	71
	H	LATIN CAPITAL LETTER H	0x48	72
	I	LATIN CAPITAL LETTER I	0x49	73
	J	LATIN CAPITAL LETTER J	0x4A	74
	K	LATIN CAPITAL LETTER K	0x4B	75
	L	LATIN CAPITAL LETTER L	0x4C	76
	M	LATIN CAPITAL LETTER M	0x4D	77
	N	LATIN CAPITAL LETTER N	0x4E	78
	O	LATIN CAPITAL LETTER O	0x4F	79
	P	LATIN CAPITAL LETTER P	0x50	80
	Q	LATIN CAPITAL LETTER Q	0x51	81
	R	LATIN CAPITAL LETTER R	0x52	82
	S	LATIN CAPITAL LETTER S	0x53	83
	T	LATIN CAPITAL LETTER T	0x54	84
	U	LATIN CAPITAL LETTER U	0x55	85
	V	LATIN CAPITAL LETTER V	0x56	86
	W	LATIN CAPITAL LETTER W	0x57	87
	X	LATIN CAPITAL LETTER X	0x58	88
	Y	LATIN CAPITAL LETTER Y	0x59	89
	Z	LATIN CAPITAL LETTER Z	0x5A	90
	Ä	LATIN CAPITAL LETTER A WITH DIAERESIS	0x5B	91
	Ö	LATIN CAPITAL LETTER O WITH DIAERESIS	0x5C	92
	Ñ	LATIN CAPITAL LETTER N WITH TILDE	0x5D	93
	Ü	LATIN CAPITAL LETTER U WITH DIAERESIS	0x5E	94
	§	SECTION SIGN	0x5F	95
	¿	INVERTED QUESTION MARK	0x60	96
	a	LATIN SMALL LETTER A	0x61	97
	b	LATIN SMALL LETTER B	0x62	98
	c	LATIN SMALL LETTER C	0x63	99
	d	LATIN SMALL LETTER D	0x64	100
	e	LATIN SMALL LETTER E	0x65	101
	f	LATIN SMALL LETTER F	0x66	102
	g	LATIN SMALL LETTER G	0x67	103
	h	LATIN SMALL LETTER H	0x68	104
	i	LATIN SMALL LETTER I	0x69	105
	j	LATIN SMALL LETTER J	0x6A	106
	k	LATIN SMALL LETTER K	0x6B	107
	l	LATIN SMALL LETTER L	0x6C	108
	m	LATIN SMALL LETTER M	0x6D	109
	n	LATIN SMALL LETTER N	0x6E	110
	o	LATIN SMALL LETTER O	0x6F	111
	p	LATIN SMALL LETTER P	0x70	112
	q	LATIN SMALL LETTER Q	0x71	113
	r	LATIN SMALL LETTER R	0x72	114
	s	LATIN SMALL LETTER S	0x73	115
	t	LATIN SMALL LETTER T	0x74	116
	u	LATIN SMALL LETTER U	0x75	117
	v	LATIN SMALL LETTER V	0x76	118
	w	LATIN SMALL LETTER W	0x77	119
	x	LATIN SMALL LETTER X	0x78	120
	y	LATIN SMALL LETTER Y	0x79	121
	z	LATIN SMALL LETTER Z	0x7A	122
	ä	LATIN SMALL LETTER A WITH DIAERESIS	0x7B	123
	ö	LATIN SMALL LETTER O WITH DIAERESIS	0x7C	124
	ñ	LATIN SMALL LETTER N WITH TILDE	0x7D	125
	ü	LATIN SMALL LETTER U WITH DIAERESIS	0x7E	126
	à	LATIN SMALL LETTER A WITH GRAVE	0x7F	127

Number of characters per message:

Parts	Without special chars	With special chars
1 part	160 chars	70 chars
2 parts	306 chars	134 chars
3 parts	459 chars	201 chars
4 parts	612 chars	268 chars
5 parts	765 chars	335 chars
6 parts	918 chars	402 chars
7 parts	1071 chars	469 chars
8 parts	1224 chars	536 chars
9 parts	1377 chars	603 chars
10 parts	1530 chars	670 chars

20. Encoding

Unicode encoding is binary. GSM, however, you can set different encoding of messages for additional provider **Encoding** in your SITE request. Available encoding types are:

- 0 - default
- 1 - no GSM 7 -
- 2 - no GSM 8 -
- 3 - no GSM 7 -
- 4 - no GSM 8 -
- 5 - no GSM 8 -
- 6 - no GSM 8 -
- 7 - no GSM 8 -
- 8 - unicode UTF-
- 9 - unicode UTF-
- 10 - unicode UTF-
- 11 - unicode UTF-

21. Integrations

E-commerce service is using more other potential of mobile communications, especially that it provides one tool connection of several and support of using. You can always browse integrations on our integrations.

Email

Email is a free, small service provided by Google. The Email user interface is user friendly and its focus on search and conversation threading of mails, serving a powerful message management system. Email is also a single page. Integration with Email is using POP3 processing a process. SMS confirmations are received in mails.

Email configuration

In order to receive messages by Mails Update, Tip and automatic label assignment, you'll need to login in your Email account, then go to the Email settings page.

In the settings, go to "Filters and Blocked Addresses tab and choose the option to create a new filter.

The following criteria can be chosen. Everything marked that field will be source for Sugar.

Enter the Sender's email address in the "From" field.

Type: Sms

Enter the Subject in the "Subject" field.

Enter the Sugar email address that Email will be source for Sugar.

Check the "Has the word" field. Point create new or select one from the list.

Search source flag field. Point create new or select one from the list.

Check "Apply the label" field. Point create new or select one from the list.

Script configuration

In order to configure SMS2MT service in Google Mail, make sure Sugar is logged into the proper account in Google service. Go to Google Apps Script page.

Click "Start Scripting", and then "Blank Project".

Apps Script
Recent
Starred
Owned by me
Owned by others
Trashed
Blank project
Blank library
Blank web app
Blank add-on
Blank API
Blank Chrome app
Blank Sheets add-on
Blank Docs add-on
Blank Forms add-on
Blank Sites add-on
Blank Slides add-on
Blank Gmail add-on
Blank Drive add-on
Blank Calendar add-on
Blank Analytics add-on
Blank Data Studio add-on
Blank Chat app
Blank Apps Script JSON file
Blank Apps Script HTML file
Blank Apps Script CSS file
Blank Apps Script JavaScript file
Blank Apps Script Markdown file
Blank Apps Script Text file
Blank Apps Script Gemini file
Blank Apps Script Gemini Markdown file
Blank Apps Script Gemini Text file
Blank Apps Script Gemini Chat file
Blank Apps Script Gemini Chat Markdown file
Blank Apps Script Gemini Chat Text file
Blank Apps Script Gemini Chat JSON file
Blank Apps Script Gemini Chat HTML file
Blank Apps Script Gemini Chat CSS file
Blank Apps Script Gemini Chat JavaScript

Parameter	Description
client_id	Unique ID for app
client_secret	Private value unique for app
code	Authorization code given by SMSAPI after the first request
grant_type	Authorization type, should be set to "authorization_code"
redirect_uri	URL address where the response about successful authorization should be redirected

- `POST https://api.smsapi.pl/oauth/token`

To maintain the connection, send a request containing the refresh_token received in the second request. For subsequent requests, replace access_token and refresh_token values with the new ones received in this request.

Required parameters:

Parameter	Description
client_id	Unique ID for app
client_secret	Private value unique for app
refresh_token	Token received in the second request
grant_type	Authorization type, should be set to "refresh_token"

```
curl -X POST "https://api.smsapi.pl/oauth/token" -d "client_id=1112223334444\
&client_secret=111222333444&code=11112222&grant_type=authorization_code\
&redirect_uri=https://www.sample.pl/"
```

Example response:

```
{
    "access_token":"A1b***x2Z",
    "token_type":"Bearer",
    "expires":1577836800,
    "expires_in":604800,
    "refresh_token":"c3D**********************4eF"
}

  * access_token – token that allows access to resources via API
  * token_type – token type (always bearer for SMSAPI)
  * expires – token expiration date in UNIX timestamp
  * expires_in – time of token validity (days, hours and minutes)
  * refresh_token – refresh token that allows to extend the authorization validity
```

Example of request with refresh_token:

```
curl -X POST "https://api.smsapi.pl/oauth/token" -d "client_id=123456\
&client_secret=111222333444&refresh_token=AaaaaBbbbbCccccDdddd\
&grant_type=refresh_token"
```

Example response:

```
{
    "access_token":"BD1***p3k",
    "token_type":"Bearer",
    "expires":1577837800,
    "expires_in":604800,
    "refresh_token":"yn3**********************z54"
}
```

PKCE

SMSAPI also supports authorization using PKCE (Proof Key for Code Exchange). It differs from standard OAuth authorization in that a random string code_verifier must be generated to perform it. In the first step, a converted version of this string must be provided under the name code_challenge, and in the second step the code_verifier must be sent. The client_secret parameter sent in the second step is optional.

You can create the code_challenge parameter by Base64 URL encoding the SHA256 hash of the code_verifier. You can perform Base64 URL encoding by taking a Base64-encoded string and changing '+' and '/' to '-' and '_' respectively, then trimming the trailing '='.

- `GET https://ssl.smsapi.pl/oauth/access/`

Required parameters:

Parameter	Description
client_id	Unique ID for app
redirect_uri	URL address to which the user will be redirected after completing the authorization
code_challenge	Parameter generated as described above
code_challenge_method	code_challenge generation method, has to be equal to S256
scope	Defined permission for resources
state	Optional parameter that contains your CSRF token

- `POST https://api.smsapi.pl/oauth/token`

After receiving a positive verification in the first request, send the information using the POST method to complete the authorization process. You can use the received access_token to authorize your SMSAPI requests.

Required parameters:

Parameter	Description
client_id	Unique ID for app
code	Authorization code given by SMSAPI after the first request
grant_type	Authorization type, should be set to "authorization_code"
redirect_uri	URL address where the response about successful authorization should be redirected
client_secret	Optional parameter - private value unique for app

- `POST https://api.smsapi.pl/oauth/token`

To maintain the connection, send a request containing the refresh_token received in the second request. For subsequent requests, replace access_token and refresh_token values with the new ones received in this request.

Required parameters:

Parameter	Description
client_id	Unique ID for app
refresh_token	Token received in the second request
grant_type	Authorization type, should be set to "refresh_token"

Example of first request (the user is redirected to SMSAPI, where they log in and confirm the integration):

```
https://ssl.smsapi.pl/oauth/access?client_id=123456&redirect_uri=https://www.sample.pl/&code_challenge=12345678
```

Example response:

```
https://www.sample.pl/?code=11112222
```

Example of second request:

```
curl -X POST "https://api.smsapi.pl/oauth/token" -d "client_id=1112223334444\
&code_verifier=111222333444&code=11112222&grant_type=authorization_code\
&redirect_uri=https://www.sample.pl/"
```

Example response:

```
{
    "access_token":"A1b***x2Z",
    "token_type":"Bearer",
    "expires":1577836800,
    "expires_in":604800,
    "refresh_token":"c3D**********************4eF"
}

  * access_token – token that allows access to resources via API
  * token_type – token type (always bearer for SMSAPI)
  * expires – token expiration date in UNIX timestamp
  * expires_in – time of token validity (days, hours and minutes)
  * refresh_token – refresh token that allows to extend the authorization validity
```

Example of request with refresh_token:

```
curl -X POST "https://api.smsapi.pl/oauth/
&refresh_token=AaaaaBbbbbCccccDdddd&grant_
```

Example response:

```
{
    "access_token":"BD1*p3k",
    "token_type":"Bearer",
    "expires":1577837800,
    "expires_in":604800,
    "refresh_token":"yn3*****************
}
```

Other integrations

We also have integrations with:

- Magento
- WordPress

You can check them all out at our Integrations page.

Michał
Zapisz się na webinar: Start w SMSAPI
Zapraszamy na kompletny przewodnik po...