



Sunbeam Institute of Information Technology
Pune and Karad

Module - Embedded Operating System

Trainer - Devendra Dhande

Email – devendra.dhande@sunbeaminfo.com

chmod command

Human readable format : $rw-rw-r--$

Numeric format (Octal) : $\underline{110} \underline{110} \underline{100} = 664$

Permissions :

r - read

w - write

x - execute

levels :

u - user/owner

g - group

o - others

+ : add

- : remove

chmod \pm rwx filename

e.g. `chmod +x sample.txt`

- execute permission will be added to all levels

`chmod -r sample.txt`

- read permission will be removed from all levels

chmod u/g/o \pm r/w/x filename

e.g. `chmod u+x sample.txt`

- add execute permission to user

`chmod g-rw sample.txt`

- remove read & write permission of group

chmod mode filename

↑
numeric format

add execute to user & remove write of group


Existing mode : $rw-rw-r--$

$110 \ 110 \ 100$ (664)

$111 \ 100 \ 100$ (744)

New mode : $rw-x \ r-- \ r--$

e.g. `chmod 744 sample.txt`



demo

```
i_no = 922  
i_type = d  
i_nlink = 2
```


• 922
• • 848
~~one + 24 924~~
~~two + 24 924~~
~~three + 24 924~~

one.txt


```
i_no = 924  
i_type = f  
i_nlink = 123210
```

In one.txt two.txt
In one.txt three.txt

rm two.txt
rm three.txt
rm one.txt



demo



~~abc.tat gz4~~

 xyz.tat gz4

abc.txt

no = 924
nlink = 1 ~~2~~

```
rename  
    link ( abc.txt , xyz.txt)  
    unlink ( abc.txt)
```

`ln -s one.txt two.txt`

`ln -s /home/sunbeam/demo/one.txt
three.txt`

demo

```
i_no = 922  
i_type = d  
l_nlink = 2
```

```
.      922  
..     848  
one.txt 924  
two.txt 925  
three.txt 926
```

one.txt

```
i_no = 924  
i_type = f  
l_nlink = 1
```

```
==  
==  
==  
==
```

two.txt

```
i_no = 925  
i_type = f  
l_nlink = 1
```

one.txt

three.txt

```
i_no = 926  
i_type = f  
l_nlink = 1
```

/home/sunbeam/
demo/one.txt



Thank you!!!

Devendra Dhande

devendra.dhande@sunbeaminfo.com