MODULE 2

ENTITY RELATIONSHIP MODEL

CONTENT

- Basic concepts
- Design Issues
- Mapping Constraints
- Keys
- Entity-Relationship Diagram
- Weak Entity Sets
- Extended E-R features

BASIC CONCEPT OF ER-MODEL

Entity Set

- A *database* can be modeled as:
  - a collection of entities,
  - relationship among entities.
- An *entity* is an object that exists and is distinguishable from other objects.
  - Example: specific person, company, event, plant
- Entities have *attributes*
  - Example: people have *names* and *addresses*
- An *entity set* is a set of entities of the same type that share the same properties.
  - Example: set of all persons, companies, trees, holidays


Basic Concept of ER-Model(Contd.)

- Bus - Company owns busses and will hold information about them.
- Route - Buses travel on routes and will need described.
- Town - Buses pass through towns and need to know about them
- Driver - Company employs drivers, personnel will hold their data.
- Stage - Routes are made up of stages
- Garage - Garage houses buses, and need to know where they are.

Basic Concept of ER-Model(Contd.)

- An entity is represented by a set of attributes, that is descriptive properties possessed by all members of an entity set.
- **Attribute types:**
  - *Simple* and *composite* attributes.
  - *Single-valued* and *multi-valued* attributes
    - E.g. multivalued attribute: *phone-numbers*
  - *Derived* attributes
    - Can be computed from other attributes
    - E.g. *age*, given date of birth

COMPOSITE ATTRIBUTES



BASIC CONCEPT OF ER-MODEL(CONTD.)

Domains

- A domain definition specifies the kind of data represented by the attribute. More particularly, a domain is the set of all possible values that an attribute may validly contain. Domains are often confused with data types, but this is inaccurate.
- Data type is a physical concept while domain is a logical one. “Number” is a data type and “Age” is a domain. To give another example “StreetName” and “Surname” might both be represented as text fields, but they are obviously different kinds of text fields; they belong to different domains.

Basic Concept of ER-Model(Contd.)

Relationship

- A *relationship* is an association among several entities

  Example:

  Hayes — depositor — A-102

  customer entity — relationship set — account entity

- A *relationship set* is a mathematical relation among $n \geq 2$ entities, each taken from entity sets

  $$\{(e_1, e_2, \ldots e_n) \mid e_1 \in E_1, e_2 \in E_2, \ldots, e_n \in E_n\}$$

  where $(e_1, e_2, \ldots, e_n)$ is a relationship


  - Example:

    $$(\text{Hayes, A-102}) \in \text{depositor}$$

Basic Concept of ER-Model(Contd.)

Relationship Sets (Contd.)

- An *attribute* can also be property of a relationship set.
- For instance, the *depositor* relationship set between entity sets *customer* and *account* may have the attribute *access-date*



Design Issues

- **Use of entity sets vs. attributes**

Choice mainly depends on the structure of the enterprise being modeled, and on the semantics associated with the attribute in question.

- **Use of entity sets vs. relationship sets**

Possible guideline is to designate a relationship set to describe an action that occurs between entities


- **Binary versus *n*-ary relationship sets**

Although it is possible to replace any nonbinary (*n*-ary, for $n > 2$) relationship set by a number of distinct binary relationship sets, a *n*-ary relationship set shows more clearly that several entities participate in a single relationship.

Mapping Cardinalities

- Express the number of entities to which another entity can be associated via a relationship set.
- Most useful in describing binary relationship sets.
- For a binary relationship set the mapping cardinality must be one of the following types:
  - One to one
  - One to many
  - Many to one
  - Many to many

Mapping Cardinalities (contd.)



Many to one


Many to many

Note: Some elements in A and B may not be mapped to any elements in the other set

Cardinality Constraints


One-to-one relationship:

- A customer is associated with at most one loan via the relationship *borrower*
- A loan is associated with at most one customer via *borrower*




ONE-TO-MANY RELATIONSHIP

- In the one-to-many relationship a loan is associated with at most one customer via *borrower*, a customer is associated with several loans via borrower




Many-to-one relationships

- In a many-to-one relationship a loan is associated with several (including 0) customers via *borrower*, a customer is associated with at most one loan via *borrower*



Many-to-Many Relationship



- A customer is associated with several (possibly 0) loans via borrower
- A loan is associated with several (possibly 0) customers via borrower

Binary vs. non-binary relationships

- Some relationships that appear to be non-binary may be better represented using binary relationships
  - E.g. A ternary relationship *parents*, relating a child to his/her father and mother, is best replaced by two binary relationships, *father* and *mother*
    - Using two binary relationships allows partial information (e.g. only mother being know)
  - But there are some relationships that are naturally non-binary
    - E.g. *works-on*


KEYS

- A *super key* of an entity set is a set of one or more attributes whose values uniquely determine each entity.
- A *candidate key* of an entity set is a minimal super key
  - *Customer-id* is candidate key of *customer*
  - *account-number* is candidate key of *account*
- Although several candidate keys may exist, one of the candidate keys is selected to be the *primary key*.

Keys for Relationship Sets


- The combination of primary keys of the participating entity sets forms a super key of a relationship set.
  - (*customer-id, account-number*) is the super key of *depositor*
  - *NOTE: this means a pair of entity sets can have at most one relationship in a particular relationship set.*
    - E.g. if we wish to track all access-dates to each account by each customer, we cannot assume a relationship for each access. We can use a multivalued attribute though
- Must consider the mapping cardinality of the relationship set when deciding the what are the candidate keys
- Need to consider semantics of relationship set in selecting the *primary key* in case of more than one candidate key

E-R DIAGRAMS




- **Rectangles** represent entity sets.
- **Diamonds** represent relationship sets.
- **Lines** link attributes to entity sets and entity sets to relationship sets.
- **Ellipses** represent attributes
  - **Double ellipses** represent multivalued attributes.
  - **Dashed ellipses** denote derived attributes.
- **Underline** indicates primary key attributes

E-R DIAGRAM WITH COMPOSITE, MULTIVALUED, AND DERIVED ATTRIBUTES




Relationship Sets with Attributes




ROLES

- Entity sets of a relationship need not be distinct
- The labels “manager” and “worker” are called roles; they specify how employee entities interact via the works-for relationship set.
- Roles are indicated in E-R diagrams by labeling the lines that connect diamonds to rectangles.
- Role labels are optional, and are used to clarify semantics of the relationship




Participation of an Entity Set in a Relationship Set

- Total participation (indicated by double line): every entity in the entity set participates in at least one relationship in the relationship set
  - E.g. participation of *loan* in *borrower* is total
    - every loan must have a customer associated to it via borrower
- Partial participation: some entities may not participate in any relationship in the relationship set
  - E.g. participation of *customer* in *borrower* is partial



Alternative Notation for Cardinality Limits


- Cardinality limits can also express participation constraints



Cardinality Constraints on Ternary Relationship

- We allow at most one arrow out of a ternary (or greater degree) relationship to indicate a cardinality constraint
- E.g. an arrow from *works-on* to *job* indicates each employee works on at most one job at any branch.
- If there is more than one arrow, there are two ways of defining the meaning.
  - E.g a ternary relationship *R* between *A*, *B* and *C* with arrows to *B* and *C* could mean
  - 1. each *A* entity is associated with a unique entity from *B* and *C* or
  - 2. each pair of entities from (*A, B*) is associated with a unique *C* entity,and each pair (*A, C*) is associated with a unique *B*
  - Each alternative has been used in different formalisms
  - To avoid confusion we outlaw more than one arrow

E-R Diagram With a Ternary Relationship



Cardinality Constraints on Ternary Relationship


- We allow at most one arrow out of a ternary (or greater degree) relationship to indicate a cardinality constraint
- E.g. an arrow from *works-on* to *job* indicates each employee works on at most one job at any branch.
- If there is more than one arrow, there are two ways of defining the meaning.
  - E.g a ternary relationship *R* between *A*, *B* and *C* with arrows to *B* and *C* could mean
  - 1. each *A* entity is associated with a unique entity from *B* and *C* or
  - 2. each pair of entities from (*A*, *B*) is associated with a unique *C* entity, and each pair (*A*, *C*) is associated with a unique *B*
  - Each alternative has been used in different formalisms
  - To avoid confusion we outlaw more than one arrow

Weak Entity Sets

- An entity set that does not have a primary key is referred to as a *weak entity set*.
- The existence of a weak entity set depends on the existence of a *identifying entity set*
  - it must relate to the identifying entity set via a total, one-to-many relationship set from the identifying to the weak entity set
  - Identifying relationship depicted using a double diamond
- The *discriminator (or partial key)* of a weak entity set is the set of attributes that distinguishes among all the entities of a weak entity set.
- The primary key of a weak entity set is formed by the primary key of the strong entity set on which the weak entity set is existence dependent, plus the weak entity set's discriminator.

Weak Entity Sets (Contd.)

- We depict a weak entity set by double rectangles.
- We underline the discriminator of a weak entity set with a dashed line.
- *payment-number* – discriminator of the *payment* entity set
- Primary key for *payment* – (*loan-number, payment-number*)



Weak Entity Sets (Contd.)

- If *loan-number* were explicitly stored, *payment* could be made a strong entity, but then the relationship between *payment* and *loan* would be duplicated by an implicit relationship defined by the attribute *loan-number* common to *payment* and *loan*

- Note: the primary key of the strong entity set is not explicitly stored with the weak entity set, since it is implicit in the identifying relationship.

More Weak Entity Set Examples

- In a university, a *course* is a strong entity and a *course-offering* can be modeled as a weak entity
- The discriminator of *course-offering* would be *semester* (including year) and *section-number* (if there is more than one section)
- If we model *course-offering* as a strong entity we would model *course-number* as an attribute.

  Then the relationship with *course* would be implicit in the *course-number* attribute


EER-DIAGRAM

- Specialization
- Aggregation
- Generalization

SPECIALIZATION

- Top-down design process; we designate subgroupings within an entity set that are distinctive from other entities in the set.
- These subgroupings become lower-level entity sets that have attributes or participate in relationships that do not apply to the higher-level entity set.
- Depicted by a *triangle* component labeled ISA (E.g. *customer* “is a” *person*).
- Attribute inheritance – a lower-level entity set inherits all the attributes and relationship participation of the higher-level entity set to which it is linked.

Specialization Example



Generalization

- A bottom-up design process – combine a number of entity sets that share the same features into a higher-level entity set.
- Specialization and generalization are simple inversions of each other; they are represented in an E-R diagram in the same way.
- The terms specialization and generalization are used interchangeably.

Specialization and Generalization (contd.)

- Can have multiple specializations of an entity set based on different features.
- E.g. *permanent-employee* vs. *temporary-employee*, in addition to *officer* vs. *secretary* vs. *teller*
- Each particular employee would be
  - a member of one of *permanent-employee* or *temporary-employee*,
  - and also a member of one of *officer*, *secretary*, or *teller*
- The ISA relationship also referred to as **superclass - subclass** relationship

Design Constraints on a Specialization/Generalization


- Constraint on which entities can be members of a given lower-level entity set.
  - condition-defined
    - E.g. all customers over 65 years are members of *senior-citizen* entity set; *senior-citizen* ISA *person*.
  - user-defined
- Constraint on whether or not entities may belong to more than one lower-level entity set within a single generalization.
  - Disjoint
    - an entity can belong to only one lower-level entity set
    - Noted in E-R diagram by writing *disjoint* next to the ISA triangle
  - Overlapping
    - an entity can belong to more than one lower-level entity set

Design Constraints on a Specialization/Generalization (contd.)

- Completeness constraint -- specifies whether or not an entity in the higher-level entity set must belong to at least one of the lower-level entity sets within a generalization.
  - **total** : an entity must belong to one of the lower-level entity sets
  - **partial**: an entity need not belong to one of the lower-level entity sets

Aggregation


- Consider the ternary relationship *works-on*, which we saw earlier
- Suppose we want to record managers for tasks performed by an employee at a branch




Aggregation (contd.)

- Relationship sets *works-on* and *manages* represent overlapping information
  - Every *manages* relationship corresponds to a *works-on* relationship
  - However, some *works-on* relationships may not correspond to any *manages* relationships
    - So we can't discard the *works-on* relationship
- Eliminate this redundancy via *aggregation*
  - Treat relationship as an abstract entity
  - Allows relationships between relationships
  - Abstraction of relationship into new entity
- Without introducing redundancy, the following diagram represents:
  - An employee works on a particular job at a particular branch
  - An employee, branch, job combination may have an associated manager


E-R DIAGRAM WITH AGGREGATION




Summary of Symbols Used in E-R Notation




SUMMARY OF SYMBOLS (CONTD.)



Alternative E-R Notations



E-R DIAGRAM FOR A BANKING ENTERPRISE



END
OF
MODULE 2