Main Porcelain Commands

add Add file contents to the index

am Apply a series of patches from a mailbox

archive Create an archive of files from a named tree

backfill Download missing objects in a partial clone

bisect Use binary search to find the commit that introduced a bug

branch List, create, or delete branches

bundle Move objects and refs by archive

checkout Switch branches or restore working tree files

cherry-pick Apply the changes introduced by some existing commits

citool Graphical alternative to git-commit

clean Remove untracked files from the working tree

clone Clone a repository into a new directory

commit Record changes to the repository

describe Give an object a human readable name based on an available ref

:

See 'git help <command>' to read about a specific subcommand

Main Porcelain Commands

add Add file contents to the index

am Apply a series of patches from a mailbox

archive Create an archive of files from a named tree

backfill Download missing objects in a partial clone

bisect Use binary search to find the commit that introduced a bug

branch List, create, or delete branches

bundle Move objects and refs by archive

checkout Switch branches or restore working tree files

cherry-pick Apply the changes introduced by some existing commits

citool Graphical alternative to git-commit

clean Remove untracked files from the working tree

clone Clone a repository into a new directory

commit	Record changes to the repository
describe	Give an object a human readable name based on an available ref
diff	Show changes between commits, commit and working tree, etc
fetch	Download objects and refs from another repository
format-patch	Prepare patches for e-mail submission
gc	Cleanup unnecessary files and optimize the local repository
gitk	The Git repository browser
grep	Print lines matching a pattern
gui	A portable graphical interface to Git
init	Create an empty Git repository or reinitialize an existing one
log	Show commit logs
maintenance	Run tasks to optimize Git repository data
merge	Join two or more development histories together
mv	Move or rename a file, a directory, or a symlink
notes	Add or inspect object notes
pull	Fetch from and integrate with another repository or a local branch
push	Update remote refs along with associated objects
range-diff	Compare two commit ranges (e.g. two versions of a branch)
rebase	Reapply commits on top of another base tip
reset	Reset current HEAD to the specified state
restore	Restore working tree files
revert	Revert some existing commits
rm	Remove files from the working tree and from the index
scalar	A tool for managing large Git repositories
shortlog	Summarize 'git log' output
show	Show various types of objects
sparse-checkout	Reduce your working tree to a subset of tracked files
stash	Stash the changes in a dirty working directory away
status	Show the working tree status
submodule	Initialize, update or inspect submodules
survey	EXPERIMENTAL: Measure various repository dimensions of scale

switch	Switch branches
tag	Create, list, delete or verify tags
worktree	Manage multiple working trees

Ancillary Commands / Manipulators

config	Get and set repository or global options
fast-export	Git data exporter
fast-import	Backend for fast Git data importers
filter-branch	Rewrite branches
mergetool	Run merge conflict resolution tools to resolve merge conflicts
pack-refs	Pack heads and tags for efficient repository access
prune	Prune all unreachable objects from the object database
reflog	Manage reflog information
refs	Low-level access to refs
remote	Manage set of tracked repositories
repack	Pack unpacked objects in a repository
replace	Create, list, delete refs to replace objects

Ancillary Commands / Interrogators

annotate	Annotate file lines with commit information
blame	Show what revision and author last modified each line of a file
bugreport	Collect information for user to file a bug report
count-objects	Count unpacked number of objects and their disk consumption
diagnose	Generate a zip archive of diagnostic information
difftool	Show changes using common diff tools
fsck	Verifies the connectivity and validity of the objects in the database
gitweb	Git web interface (web frontend to Git repositories)
help	Display help information about Git
instaweb	Instantly browse your working repository in gitweb
merge-tree	Perform merge without touching index or working tree
rerere	Reuse recorded resolution of conflicted merges

show-branch	Show branches and their commits
verify-commit	Check the GPG signature of commits
verify-tag	Check the GPG signature of tags
version	Display version information about Git
whatchanged	Show logs with differences each commit introduces

Interacting with Others

archimport	Import a GNU Arch repository into Git
cvsexportcommit	Export a single commit to a CVS checkout
cvsimport	Salvage your data out of another SCM people love to hate
cvsserver	A CVS server emulator for Git
imap-send	Send a collection of patches from stdin to an IMAP folder
p4	Import from and submit to Perforce repositories
quiltimport	Applies a quilt patchset onto the current branch
request-pull	Generates a summary of pending changes
send-email	Send a collection of patches as emails
svn	Bidirectional operation between a Subversion repository and Git

Low-level Commands / Manipulators

apply	Apply a patch to files and/or to the index
checkout-index	Copy files from the index to the working tree
commit-graph	Write and verify Git commit-graph files
commit-tree	Create a new commit object
hash-object	Compute object ID and optionally create an object from a file
index-pack	Build pack index file for an existing packed archive
merge-file	Run a three-way file merge
merge-index	Run a merge for files needing merging
mktag	Creates a tag object with extra validation
mktree	Build a tree-object from ls-tree formatted text
multi-pack-index	Write and verify multi-pack-indexes
pack-objects	Create a packed archive of objects

prune-packed	Remove extra objects that are already in pack files
read-tree	Reads tree information into the index
replay	EXPERIMENTAL: Replay commits on a new base, works with bare repos too
symbolic-ref	Read, modify and delete symbolic refs
unpack-objects	Unpack objects from a packed archive
update-index	Register file contents in the working tree to the index
update-ref	Update the object name stored in a ref safely
write-tree	Create a tree object from the current index

Low-level Commands / Interrogators

cat-file	Provide contents or details of repository objects
cherry	Find commits yet to be applied to upstream
diff-files	Compares files in the working tree and the index
diff-index	Compare a tree to the working tree or index
diff-pairs	Compare the content and mode of provided blob pairs
diff-tree	Compares the content and mode of blobs found via two tree objects
for-each-ref	Output information on each ref
for-each-repo	Run a Git command on a list of repositories
get-tar-commit-id	Extract commit ID from an archive created using git-archive
last-modified	EXPERIMENTAL: Show when files were last modified
ls-files	Show information about files in the index and the working tree
ls-remote	List references in a remote repository
ls-tree	List the contents of a tree object
merge-base	Find as good common ancestors as possible for a merge
name-rev	Find symbolic names for given revs
pack-redundant	Find redundant pack files
repo	Retrieve information about the repository
rev-list	Lists commit objects in reverse chronological order
rev-parse	Pick out and massage parameters
show-index	Show packed archive index
show-ref	List references in a local repository

unpack-file	Creates a temporary file with a blob's contents
var	Show a Git logical variable
verify-pack	Validate packed Git archive files

Low-level Commands / Syncing Repositories

daemon	A really simple server for Git repositories
fetch-pack	Receive missing objects from another repository
http-backend	Server side implementation of Git over HTTP
send-pack	Push objects over Git protocol to another repository
update-server-info	Update auxiliary info file to help dumb servers

Low-level Commands / Internal Helpers

check-attr	Display gitattributes information
check-ignore	Debug gitignore / exclude files
check-mailmap	Show canonical names and email addresses of contacts
check-ref-format	Ensures that a reference name is well formed
column	Display data in columns
credential	Retrieve and store user credentials
credential-cache	Helper to temporarily store passwords in memory
credential-store	Helper to store credentials on disk
fmt-merge-msg	Produce a merge commit message
hook	Run git hooks
interpret-trailers	Add or parse structured information in commit messages
mailinfo	Extracts patch and authorship from a single e-mail message
mailsplit	Simple UNIX mbox splitter program
merge-one-file	The standard helper program to use with git-merge-index
patch-id	Compute unique ID for a patch
sh-i18n	Git's i18n setup code for shell scripts
sh-setup	Common Git shell script setup code
stripspace	Remove unnecessary whitespace

User-facing repository, command and file interfaces

- attributes Defining attributes per path
- cli Git command-line interface and conventions
- hooks Hooks used by Git
- ignore Specifies intentionally untracked files to ignore
- mailmap Map author/committer names and/or E-Mail addresses
- modules Defining submodule properties
- repository-layout Git Repository Layout
- revisions Specifying revisions and ranges for Git

Developer-facing file formats, protocols and other interfaces

- format-bundle The bundle file format
- format-chunk Chunk-based file formats
- format-commit-graph Git commit-graph format
- format-index Git index format
- format-pack Git pack format
- format-signature Git cryptographic signature formats
- protocol-capabilities Protocol v0 and v1 capabilities
- protocol-common Things common to various protocols
- protocol-http Git HTTP-based protocols
- protocol-pack How packs are transferred over-the-wire
- protocol-v2 Git Wire Protocol, Version 2

External commands

- askpass
- askyesno
- credential-helper-selector
- credential-manager
- lfs
- update-git-for-windows