# Vakil.app — Functional Requirements Specification

Oct 15, 2026 · @Harsh Vaghela

## 1. Purpose, scope and conventions

This FRS defines exactly what Vakil.app v1 does and looks like: design tokens, every UI component, every screen, every functional rule, the database and the API. It is the build contract for design (Figma) and development (Expo + NativeWind, Node.js, Supabase).

- **Single entity:** the Advocate is the only user and owner of every record. Every table has `advocate_id`; every API call is scoped to the signed-in advocate.
- **Data entry:** 100% manual in v1. No court data fetch.
- **Data access:** the app never calls Supabase directly. All reads and writes go through the Node.js REST API (`/api/v1`).
- **Priority:** P0 = v1.0 launch, P1 = v1.1, P2 = later.
- **IDs:** FR-<MODULE>-NN for requirements, SCR-NN for screens, CMP-NN for components.
- **Units:** dp for sizes, ms for durations, IST (Asia/Kolkata) for all dates, INR for money.

## 2. Color system

One blue drives the brand; a blue-tinted "Ink" neutral scale keeps dark mode rich instead of flat grey; five status hues carry meaning. Components use **semantic tokens only**, never raw hex, so both themes switch for free.

### 2.1 Primary: Blue

| Token | Hex | Use |
|---|---|---|
| blue-50 | #EEF4FF | Light: selected row tint |
| blue-100 | #DCE7FF | Light: chip / badge background |
| blue-200 | #BCD2FF | Light: focus ring |
| blue-300 | #8EB3FF | Dark: link text, icon on tint |

| Token | Hex | Use |
|---|---|---|
| blue-400 | #5B8CFF | Dark: pressed-hover, focus ring |
| **blue-500** | **#3366FF** | **Dark: primary brand** |
| **blue-600** | **#2350E6** | **Light: primary brand** / dark: pressed |
| blue-700 | #1C3FC0 | Light: pressed |
| blue-800 | #1B3699 | Gradient stop, dark tint |
| blue-900 | #1B3279 | Dark: primary-subtle border |
| blue-950 | #121F4A | Dark: primary-subtle background |

### 2.2 Neutral: Ink (blue-tinted)

| Token | Hex | Dark theme use | Light theme use |
|---|---|---|---|
| ink-0 | #FFFFFF | Text on primary | Surface, cards |
| ink-50 | #F6F8FC | Primary text | App background |
| ink-100 | #EDF1F8 | — | Secondary surface, input fill |
| ink-200 | #DCE3EF | — | Borders, dividers |
| ink-300 | #BCC7DA | Secondary text | Disabled border |
| ink-400 | #8C9AB3 | Tertiary text, placeholder | Placeholder |
| ink-500 | #64728C | Disabled text, icons idle | Tertiary text |
| ink-600 | #475570 | Strong border | Secondary text |
| ink-700 | #2E3A52 | Border, divider | — |
| ink-800 | #1C2538 | Elevated surface (sheet, input) | Primary text alt |
| ink-900 | #121A2B | Card surface | Primary text |
| ink-950 | #0A101D | App background | — |

### 2.3 Semantic tokens

| Token | Dark (default) | Light |
|---|---|---|
| `bg` | ink-950 #0A101D | ink-50 #F6F8FC |
| `surface` | ink-900 #121A2B | ink-0 #FFFFFF |
| `surface-2` (elevated, sheets, inputs) | ink-800 #1C2538 | ink-100 #EDF1F8 |
| `border` | ink-700 #2E3A52 | ink-200 #DCE3EF |
| `border-strong` | ink-600 #475570 | ink-300 #BCC7DA |
| `text` | ink-50 #F6F8FC | ink-900 #121A2B |
| `text-2` | ink-300 #BCC7DA | ink-600 #475570 |
| `text-3` | ink-400 #8C9AB3 | ink-500 #64728C |
| `text-disabled` | ink-500 #64728C | ink-300 #BCC7DA |
| `primary` | blue-500 #3366FF | blue-600 #2350E6 |
| `primary-pressed` | blue-600 #2350E6 | blue-700 #1C3FC0 |
| `primary-subtle` | blue-950 #121F4A | blue-50 #EEF4FF |
| `on-primary` | #FFFFFF | #FFFFFF |
| `focus-ring` | blue-400 #5B8CFF | blue-200 #BCD2FF |
| `overlay` (scrim) | #0A101D at 72% | #121A2B at 48% |

### 2.4 Status colors

| Status | Base | Dark: bg / text | Light: bg / text | Used for |
|---|---|---|---|---|
| Success | #22C55E | #0F2A1C / #4ADE80 | #E8F8EE / #15803D | Disposed in favour, payment received, saved |
| Warning | #F59E0B | #2E2209 / #FBBF24 | #FEF4E2 / #B45309 | Hearing today, fee due, unsaved draft |
| Error | #EF4444 | #2F1316 / #F87171 | #FDECEC / #B91C1C | Overdue next date, validation, delete |
| Info | #0EA5E9 | #0B2533 / #38BDF8 | #E6F6FD / #0369A1 | Tips, sync status |

| Status | Base | Dark: bg / text | Light: bg / text | Used for |
|---|---|---|---|---|
| Adjourned | #8B5CF6 | #221A3D / #A78BFA | #F1ECFE / #6D28D9 | Adjourned hearings |

### 2.5 Case status mapping

| Case status | Pill color | Icon (Tabler) |
|---|---|---|
| Active | Primary | `ti-briefcase` |
| Hearing today | Warning | `ti-gavel` |
| Adjourned | Adjourned | `ti-calendar-repeat` |
| Reserved for order | Info | `ti-hourglass` |
| Next date missing / overdue | Error | `ti-alert-triangle` |
| Disposed | Success | `ti-circle-check` |
| Closed / Archived | Neutral (ink-500) | `ti-archive` |

### 2.6 Gradients

| Name | Stops | Angle | Where |
|---|---|---|---|
| `grad-primary` | #3366FF to #6A4CFF | 135° | Primary FAB, gradient button, active progress |
| `grad-hero` | #1C3FC0 to #3366FF to #4FA3FF | 135° | Dashboard "Today" hero card, onboarding art |
| `grad-surface` (dark only) | #121A2B to #0A101D | 180° | Screen header backdrop |
| `grad-glow` | #3366FF at 35% to transparent | radial | Behind hero card and splash logo |
| `grad-success` | #16A34A to #22C55E | 135° | Disposed celebration, fee fully paid |
| `grad-shimmer` | surface to surface-2 to surface | 90°, animated | Skeleton loaders |

Rule: at most one gradient element per screen (plus skeletons). Text on gradients is always `#FFFFFF` and passes 4.5:1.

# 3. Typography, spacing, shape, icons and motion

### 3.1 Type scale: Plus Jakarta Sans

All numbers (dates, case numbers, amounts) use `fontVariant: ['tabular-nums']`. Line heights are fixed so lists align.

| Token | Size / line (dp) | Weight | Tracking | Use |
|---|---|---|---|---|
| `display` | 32 / 40 | 800 ExtraBold | -0.5 | Splash, onboarding headline |
| `h1` | 28 / 36 | 700 Bold | -0.4 | Large screen title (Home greeting) |
| `h2` | 24 / 32 | 700 Bold | -0.3 | Screen title, case title on detail |
| `h3` | 20 / 28 | 600 SemiBold | -0.2 | Section headers, sheet titles |
| `title` | 17 / 24 | 600 SemiBold | 0 | Card titles, list primary text |
| `body-lg` | 16 / 24 | 400 Regular | 0 | Note text, long content |
| `body` | 15 / 22 | 400 Regular | 0 | Default text, inputs |
| `body-sm` | 13 / 20 | 500 Medium | 0 | Card meta (court, date), helper text |
| `caption` | 12 / 16 | 500 Medium | 0.1 | Timestamps, badge text |
| `overline` | 11 / 16 | 700 Bold, UPPERCASE | 0.8 | Section labels ("TODAY", "UPCOMING") |
| `button` | 15 / 20 | 600 SemiBold | 0.1 | Buttons, tabs |
| `stat` | 28 / 32 | 800 ExtraBold, tabular | -0.5 | Dashboard stat numbers |

### 3.2 Spacing (4 dp grid)

| Token | 0 | 0.5 | 1 | 2 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| dp | 0 | 2 | 4 | 8 | 12 | 16 | 20 | 24 | 32 | 40 | 48 | 64 |

Screen gutter 20 · card padding 16 · gap between cards 12 · section gap 32 · bottom safe padding = inset + 16.

### 3.3 Radius

| Token | dp | Use |
|---|---|---|
| `rounded-sm` | 8 | Badges, small chips, checkbox |
| `rounded-md` | 12 | Buttons, inputs, list rows, icon buttons |
| `rounded-lg` | 16 | Cards |
| `rounded-xl` | 20 | Hero card, FAB (extended) |
| `rounded-2xl` | 28 | Bottom sheets (top corners), modals |
| `rounded-full` | 9999 | Avatars, pills, FAB, toggles |

### 3.4 Elevation

Dark mode shows depth with lighter surfaces plus a 1 dp `border`; shadows are nearly invisible on navy. Light mode uses soft blue-tinted shadows.

| Level | Dark | Light | Use |
|---|---|---|---|
| 0 | `bg` | `bg` | Screen |
| 1 | `surface` + border | `surface` + shadow 0 1 2 rgba(18,26,43,0.06) | Cards, list groups |
| 2 | `surface-2` + border | shadow 0 4 12 rgba(18,26,43,0.08) | Sticky headers, inputs focus |
| 3 | `surface-2` + glow 0 8 24 rgba(51,102,255,0.25) | shadow 0 8 24 rgba(35,80,230,0.18) | FAB, hero card |
| 4 | `surface-2` + scrim | shadow 0 -8 32 rgba(18,26,43,0.16) | Bottom sheets, dialogs |

### 3.5 Icons: Tabler

- Library: `@tabler/icons-react-native`. Sizes 16 (inline), 20 (inputs, chips), 24 (default, tab bar), 32 (empty-state badges).
- Stroke 1.75 at 24 dp; filled variant only for the active tab.
- Icon color = text token of its context; never status color unless conveying status.
- Key icons: home `ti-home`, cases `ti-briefcase`, calendar `ti-calendar`, clients `ti-users`, more `ti-dots`, add `ti-plus`, hearing `ti-gavel`, court `ti-building-bank`, document `ti-file-text`, note `ti-notes`, fee `ti-currency-rupee`, task `ti-checkbox`, search `ti-search`, filter `ti-adjustments-horizontal`, call `ti-phone`, WhatsApp `ti-brand-whatsapp`, bell `ti-bell`, settings `ti-settings`, theme `ti-moon` / `ti-sun`.

### 3.6 Motion

| Token | Value | Use |
|---|---|---|
| `fast` | 120 ms ease-out | Press states, toggles |
| `base` | 200 ms ease-out | Fades, color changes, tab switch |
| `slow` | 300 ms spring (damping 18, stiffness 180) | Bottom sheets, screen push |
| `press-scale` | 0.97 | Cards and buttons on press |
| Haptics | light on toggle / select, success on save, warning on delete | expo-haptics |

All motion is disabled or reduced to fades when the OS "Reduce Motion" setting is on.

## 4. UI component library

56 components in 8 groups. Every component supports dark and light, uses semantic tokens, has a pressed state at scale 0.97, a 2 dp `focus-ring` for keyboard / switch access, and an accessibility label. Universal states: **default, pressed, focused, disabled (40% opacity, no press), loading**, plus **error** for inputs.

### 4.1 Actions

| ID | Component | Variants | Sizes (height) | Style spec |
|---|---|---|---|---|
| CMP-01 | Button | Primary (solid `primary`), Gradient (`grad-primary`), Secondary (`primary-subtle` bg, `primary` text), Outline (1 dp `border-strong`), Ghost (text only), Destructive (Error solid), Destructive-ghost | sm 36, md 44, lg 52 | rounded-md, `button` type, icon 20 left/right gap 8, full-width option; loading = spinner replaces label, width locked |
| CMP-02 | Icon button | Filled, Tonal (`surface-2`), Ghost, Outline | sm 32, md 40, lg 48 (target always 48) | rounded-md or full; icon 20 / 24 |
| CMP-03 | FAB | Circular, Extended (icon + label), Speed-dial (expands to 3 actions) | 56 circular, 52 extended | `grad-primary`, elevation 3 glow, rounded-full / rounded-xl; hides on scroll down, shows on scroll up |
| CMP-04 | Link / text action | Default, Inline, With chevron | 20 line | `primary` text, underline on press |
| CMP-05 | Quick action tile | Icon + label tile (dashboard) | 88 x 88 | `surface` card, icon in 40 dp `primary-subtle` circle, `body-sm` label |
| CMP-06 | Swipe actions | Leading (status), Trailing (edit, delete) | row height | 72 dp action width, color = action meaning, haptic at threshold |

### 4.2 Inputs

| ID | Component | Variants | States / rules | Style spec |
|---|---|---|---|---|
| CMP-07 | Text field | Filled (default), Outline; with leading icon, trailing icon / clear, prefix (+91, ₹), suffix | default, focused (1.5 dp `primary` border + ring), filled, error (Error border + helper), disabled, read-only | height 52, rounded-md, `surface-2` fill, label above ( `body-sm` `text-2` ), helper / error below ( `caption` ), char counter optional |
| CMP-08 | Text area | Auto-grow 3 to 10 lines | same as field | min height 104 |
| CMP-09 | Search bar | Inline (in header), Expanded (full-screen search), With filter button | idle, focused, typing (clear), loading | height 44, rounded-full, `ti-search` leading, debounce 300 ms |
| CMP-10 | Select (picker) | Opens bottom sheet list; searchable when > 8 options; "Add new" row for courts / case types | closed, open, selected, error | looks like text field with `ti-chevron-down` |
| CMP-11 | Multi-select | Chips inside field; sheet with checkboxes | same | chips wrap to 2 lines then "+3" |
| CMP-12 | Date picker | Sheet with calendar grid; quick chips (Today, Tomorrow, +1 week, +2 weeks, +1 month) | no date, selected, past (warn for next hearing) | field shows `DD MMM YYYY, ddd` |
| CMP-13 | Time picker | Wheel; optional | — | 12-hour, 15-min steps |
| CMP-14 | Phone input | +91 prefix, 10-digit mask | valid, invalid | numeric keypad |
| CMP-15 | OTP input | 6 boxes, auto-advance, paste support, SMS autofill | empty, active, filled, error (shake), success | 48 x 56 boxes, rounded-md |

| ID | Component | Variants | States / rules | Style spec |
|---|---|---|---|---|
| CMP-16 | Amount input | ₹ prefix, Indian grouping (1,25,000) | — | tabular numbers |
| CMP-17 | Stepper form header | Step x of 4 + progress bar + step titles | current, done, upcoming | progress uses `grad-primary` |

### 4.3 Selection controls

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-18 | Toggle switch | On / off, with label row | 52 x 32 track, on = `primary`, thumb white, 120 ms |
| CMP-19 | Checkbox | Unchecked, checked, indeterminate | 22 dp, rounded-sm, `primary` fill + white `ti-check` |
| CMP-20 | Radio | Unselected, selected | 22 dp, 8 dp inner dot |
| CMP-21 | Segmented control | 2 to 4 segments (e.g. Petitioner / Respondent; Dark / Light / System) | height 40, `surface-2` track, selected = `surface` pill + shadow, sliding indicator |
| CMP-22 | Filter chip | Unselected, selected (with `ti-check`), with count | height 32, rounded-full, selected = `primary-subtle` bg + `primary` border |
| CMP-23 | Choice chip | Single-select row (case types, quick dates) | same as filter chip |
| CMP-24 | Input chip | Removable (`ti-x`), with avatar | height 28 |

### 4.4 Data display

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-25 | Status pill | One per case status (section 2.5); sizes sm 22 / md 26 | rounded-full, status subtle bg + status text, 6 dp dot or 14 dp icon, `caption` |

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-26 | Badge | Count (red, max "99+"), Dot, Text ("New") | 18 dp min, rounded-full |
| CMP-27 | Avatar | Initials (color hashed from name across 6 tints), Image, Icon; sizes 24, 32, 40, 56, 80 | rounded-full; advocate avatar has 2 dp `grad-primary` ring |
| CMP-28 | List row | 1-line, 2-line, 3-line; leading icon / avatar; trailing chevron / value / switch / badge | min height 56, padding 16, divider inset 56 |
| CMP-29 | Section header | Overline label + optional action ("See all") | `overline` `text-3`, margin-top 32 |
| CMP-30 | Key-value row | Label left, value right; copyable value ( `ti-copy` ) | used in case detail info |
| CMP-31 | Timeline | Vertical; node = dot colored by outcome; past / today / future | 2 dp `border` line, today node pulses once |
| CMP-32 | Calendar month grid | Day cells with up to 3 dots; today ring; selected fill | 44 dp cells, dots = hearing count |
| CMP-33 | Week strip | Horizontal 7-day scroller with counts | 56 x 72 day pills, selected = `grad-primary` |
| CMP-34 | Progress | Linear, Ring (fee paid %), Indeterminate | 6 dp track, rounded-full |
| CMP-35 | Divider | Full, Inset, With label ("or") | 1 dp `border` |
| CMP-36 | Info tag | Small icon + text meta (court, judge, date) | `body-sm` `text-2`, icon 16 |

### 4.5 Cards (domain)

| ID | Component | Content | Style spec |
|---|---|---|---|
| CMP-37 | Hero "Today" card | Greeting, date, count of hearings today, next court + time, CTA "View today" | `grad-hero`, rounded-xl, `grad-glow` behind, white text, subtle gavel illustration at 12% opacity |

| ID | Component | Content | Style spec |
|---|---|---|---|
| CMP-38 | Stat card | Icon, `stat` number, label, optional trend | `surface`, rounded-lg, 2 x 2 grid on dashboard, tap filters case list |
| CMP-39 | Case card | Title (Party A v. Party B), case no., court, status pill, next date, client avatar | `surface`, rounded-lg, 16 padding; overdue = 3 dp Error left accent |
| CMP-40 | Hearing card | Time / court room, case title, stage, last outcome, "Update" button | used in Today list and Calendar day |
| CMP-41 | Client card | Avatar, name, phone, case count, call / WhatsApp icons | — |
| CMP-42 | Document tile | File-type icon, name, size, date, overflow menu | grid 2-col or list |
| CMP-43 | Note card | Title, 3-line preview, updated time, pin icon | pinned notes get `primary-subtle` bg |
| CMP-44 | Fee summary card | Agreed, received, balance, ring progress | balance > 0 shows Warning tint |

### 4.6 Navigation

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-45 | Bottom tab bar | 5 tabs: Home, Cases, Calendar, Clients, More | height 64 + inset, `surface` with blur 20 and top border; active = filled icon + `primary` label + 4 dp pill indicator |
| CMP-46 | Top app bar | Large title (collapses on scroll), Compact (back + title + actions), Transparent over hero, Search mode | large 96, compact 56 |
| CMP-47 | Tabs | Underline (case detail sections), Pill (filters) | scrollable, 44 height, indicator slides 200 ms |

### 4.7 Feedback

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-48 | Toast / snackbar | Success, Error, Info, With action ("Undo") | bottom, above tab bar, `surface-2`, status icon, auto-dismiss 4 s (Undo 5 s) |
| CMP-49 | Inline banner | Info, Warning, Error, Offline (persistent) | full-width, status subtle bg, dismissible |
| CMP-50 | Empty state | Icon badge (32 icon in 72 circle, `grad-glow`), title, one line, primary CTA | centered, max width 280 |
| CMP-51 | Skeleton | Card, list row, text lines, avatar | `grad-shimmer` 1.2 s loop |

### 4.8 Overlays

| ID | Component | Variants | Style spec |
|---|---|---|---|
| CMP-52 | Bottom sheet | Auto-height, Snap 50% / 90%, Full-screen modal sheet; with handle, title, close | rounded-2xl top, `surface-2`, scrim `overlay`, drag to dismiss |
| CMP-53 | Dialog | Confirm, Destructive (type case no. to delete), Info | rounded-2xl, max width 340, two buttons stacked or side-by-side |
| CMP-54 | Action sheet | List of actions + Cancel | used for overflow menus |
| CMP-55 | Pull-to-refresh | Native spinner tinted `primary` | — |
| CMP-56 | Loading overlay | Blocking spinner for uploads / submit | rare; prefer inline loading |

## 5. Screen inventory

50 screens, sheets and dialogs. Navigation: 5 bottom tabs (Home, Cases, Calendar, Clients, More); create and edit flows open as full-screen modals; pickers and quick actions open as bottom sheets.

| ID | Screen | Type | Module | Key components | Priority |
|---|---|---|---|---|---|
| SCR-01 | Splash | Screen | Auth | Logo on `grad-glow` | P0 |
| SCR-02 | Welcome carousel (3 slides) | Screen | Onboarding | Illustration, dots, Gradient button | P0 |
| SCR-03 | Sign in (phone) | Screen | Auth | Phone input, Primary button, "Use email instead" link | P0 |
| SCR-04 | Sign in (email + password) | Screen | Auth | Text fields, Primary button | P0 |
| SCR-05 | OTP verification | Screen | Auth | OTP input, resend timer 30 s | P0 |
| SCR-06 | Profile setup | Screen | Onboarding | Avatar picker, name, enrolment no., practice areas multi-select | P0 |
| SCR-07 | Primary courts setup | Screen | Onboarding | Searchable multi-select, "Add court" | P0 |
| SCR-08 | Notification permission | Screen | Onboarding | Illustration, Allow / Later | P0 |
| SCR-09 | Home dashboard | Tab | Dashboard | Hero card, stat grid, week strip, today list, quick actions | P0 |
| SCR-10 | Today's hearings | Screen | Dashboard | Grouped by court, hearing cards, "Update" | P0 |
| SCR-11 | Cases list | Tab | Cases | Search, filter chips, sort, case cards, FAB | P0 |
| SCR-12 | Case filters | Sheet | Cases | Status, case type, court, date range, client | P0 |
| SCR-13 | Sort options | Sheet | Cases | Radio list (next date, recently added, A-Z) | P0 |
| SCR-14 | Add case, step 1: Basics | Modal | Cases | Stepper, case title, case no., year, case type, CNR (optional) | P0 |
| SCR-15 | Add case, step 2: Court | Modal | Cases | Court select, court room / hall no., judge, filing date | P0 |
| SCR-16 | Add case, step 3: Parties and client | Modal | Cases | Our side (segmented), client select / add, opposite party, opposite counsel | P0 |
| SCR-17 | Add case, step 4: Stage and next date | Modal | Cases | Stage select, next hearing date + quick chips, purpose, priority | P0 |
| SCR-18 | Add case: Review and save | Modal | Cases | Summary cards with edit links, Save, "Save and add another" | P0 |

| ID | Screen | Type | Module | Key components | Priority |
|---|---|---|---|---|---|
| SCR-19 | Case detail: Overview | Screen | Cases | Header with status pill, next-date card, key-value info, client card | P0 |
| SCR-20 | Case detail: Hearings | Tab | Hearings | Timeline, "Add hearing" | P0 |
| SCR-21 | Case detail: Documents | Tab | Documents | Document tiles, upload button | P1 |
| SCR-22 | Case detail: Notes | Tab | Notes | Note cards, add note | P1 |
| SCR-23 | Case detail: Fees | Tab | Fees | Fee summary card, payment list | P1 |
| SCR-24 | Case detail: Tasks | Tab | Tasks | Checklist rows, add task | P1 |
| SCR-25 | Edit case | Modal | Cases | Same fields as add, single scroll | P0 |
| SCR-26 | Change status | Sheet | Cases | Status radio list, disposal date + result if Disposed | P0 |
| SCR-27 | Case actions menu | Action sheet | Cases | Edit, Change status, Share summary, Archive, Delete | P0 |
| SCR-28 | Delete case confirm | Dialog | Cases | Destructive dialog, type case no. | P0 |
| SCR-29 | Update hearing outcome | Sheet (90%) | Hearings | Outcome chips, notes, next date + quick chips, next purpose | P0 |
| SCR-30 | Add / edit hearing | Sheet | Hearings | Date, time, purpose, court room | P0 |
| SCR-31 | Calendar: month | Tab | Calendar | Month grid with dots, selected-day list | P0 |
| SCR-32 | Calendar: day agenda | Screen | Calendar | Hearing cards for one day, grouped by court | P0 |
| SCR-33 | Clients list | Tab | Clients | Search, client cards, FAB | P0 |
| SCR-34 | Add / edit client | Modal | Clients | Name, phone, alt phone, email, address, notes | P0 |
| SCR-35 | Client detail | Screen | Clients | Contact actions, linked cases list | P0 |
| SCR-36 | Upload document | Sheet | Documents | Camera / Gallery / Files, name, category | P1 |

| ID | Screen | Type | Module | Key components | Priority |
|---|---|---|---|---|---|
| SCR-37 | Document viewer | Screen | Documents | PDF / image viewer, share, rename, delete | P1 |
| SCR-38 | Add / edit note | Modal | Notes | Title, body text area, pin toggle | P1 |
| SCR-39 | Add payment / set fee | Sheet | Fees | Amount input, date, mode (cash, UPI, bank, cheque), note | P1 |
| SCR-40 | Global search | Screen | Search | Search bar, recent searches, grouped results | P1 |
| SCR-41 | Notifications centre | Screen | Notifications | List rows grouped by day, mark all read | P0 |
| SCR-42 | More / Profile hub | Tab | Settings | Profile header, list rows to settings | P0 |
| SCR-43 | Edit profile | Modal | Settings | Same fields as setup | P0 |
| SCR-44 | Appearance | Screen | Settings | Segmented: Dark / Light / System, live preview card | P0 |
| SCR-45 | Notification settings | Screen | Settings | Toggles + time pickers for evening and morning reminders | P0 |
| SCR-46 | Manage courts and case types | Screen | Settings | Editable lists, add, rename, reorder | P0 |
| SCR-47 | Security (app lock) | Screen | Settings | Biometric toggle, PIN setup | P1 |
| SCR-48 | Help and about | Screen | Settings | FAQ, contact, version, privacy policy | P0 |
| SCR-49 | Logout / delete account | Dialog | Settings | Confirm dialogs | P0 |
| SCR-50 | System states | Overlay | Global | Offline banner, error state, empty states, force-update | P0 |

Every screen ships in dark (default) and light, with loading, empty, error and offline states defined in section 9.

# 6. Functional requirements

Each requirement is testable. "Must" = P0 unless the module is marked P1.

### 6.1 Authentication (FR-AUTH, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-AUTH-01 | Sign in with Indian mobile number + 6-digit OTP via `POST /auth/otp/send` and `/auth/otp/verify` | OTP sent within 10 s; resend enabled after 30 s; max 5 attempts per 15 min |
| FR-AUTH-02 | Email + password fallback | Password min 8 chars; "Forgot password" sends reset link |
| FR-AUTH-03 | Session persists; access token refreshed silently | User stays signed in for 30 days of inactivity; tokens stored in SecureStore |
| FR-AUTH-04 | New user routed to onboarding; returning user to Home | Decided by `advocates.onboarded_at` |
| FR-AUTH-05 | Logout clears tokens, cache and push token | After logout, back navigation cannot reach any data screen |

### 6.2 Onboarding (FR-ONB, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-ONB-01 | Collect full name (required), enrolment no. (optional), practice areas (multi), photo (optional) | Continue disabled until name is valid |
| FR-ONB-02 | Pick primary courts from a seed list or add custom | At least 1 court required; custom courts saved to `courts` |
| FR-ONB-03 | Ask for notification permission with explanation screen first | If denied, show banner in Settings with "Open settings" |

### 6.3 Dashboard (FR-DASH, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-DASH-01 | Hero card shows greeting by time of day, today's date, count of hearings today, first court | Zero hearings shows "No hearings today" variant with "Plan tomorrow" CTA |

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-DASH-02 | Stat grid: Active cases, Today, This week, Overdue (next date in past or missing) | Tapping a stat opens Cases list with that filter applied |
| FR-DASH-03 | Week strip (today + 6 days) with hearing count per day | Selecting a day shows its hearings below |
| FR-DASH-04 | Quick actions: Add case, Add client, Update hearing, Search | Each opens the correct modal / screen |
| FR-DASH-05 | Pull-to-refresh refetches `GET /dashboard` | Data under 60 s old is shown instantly from cache |

### 6.4 Cases (FR-CASE, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-CASE-01 | Add case through a 4-step form + review | Draft auto-saved locally on every step; leaving asks "Discard draft?" |
| FR-CASE-02 | Required fields: case title or parties, case type, court, our side, client | Inline validation on blur; step cannot advance with errors |
| FR-CASE-03 | Optional: case no., year, CNR (16 chars), court room, judge, filing date, opposite counsel, priority, description | CNR validated as 16 alphanumeric |
| FR-CASE-04 | Next hearing date + purpose can be set at creation | Creates the first `hearings` row; past date shows warning, allowed |
| FR-CASE-05 | Case title auto-composed as "Petitioner v. Respondent" if left blank | Editable later |
| FR-CASE-06 | "Save and add another" keeps court and case type | Success toast + haptic |
| FR-CASE-07 | List with infinite scroll (20 per page), default sort by next hearing date ascending | Overdue cases pinned on top with Error accent |

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-CASE-08 | Search by title, case no., CNR, party, client name, court | Results under 500 ms; highlights match |
| FR-CASE-09 | Filter by status, case type, court, client, next-date range; filters combine (AND) | Active filter count shown on filter button; "Clear all" |
| FR-CASE-10 | Sort by next date, recently added, recently updated, title A-Z | Choice persisted per device |
| FR-CASE-11 | Case detail shows header (title, case no., status), next-date card, info, client, tabs | Loads from cache first, then refreshes |
| FR-CASE-12 | Call / WhatsApp client and copy case no. / CNR from detail | WhatsApp opens `wa.me/91XXXXXXXXXX` |
| FR-CASE-13 | Change status: Active, Reserved for order, Disposed, Closed | Disposed requires disposal date + result (Allowed, Dismissed, Settled, Withdrawn, Other) |
| FR-CASE-14 | Archive hides case from default list; restorable from filter "Archived" | Soft flag `archived_at` |
| FR-CASE-15 | Delete requires typing the case no. (or "DELETE"); cascades hearings, notes, docs, fees, tasks | Soft delete 30 days, then purged |
| FR-CASE-16 | Share case summary as text | Native share sheet with title, court, next date, stage |

### 6.5 Hearings (FR-HEAR, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-HEAR-01 | Add a hearing: date (required), time, purpose / stage, court room | Updates `cases.next_hearing_at` if it is the earliest future hearing |
| FR-HEAR-02 | Update outcome from Today list, case detail or notification | Opens SCR-29 pre-filled with that hearing |

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-HEAR-03 | Outcome options: Adjourned, Heard, Arguments done, Evidence recorded, Order reserved, Disposed, Not reached, Other + free-text notes | One tap selects; notes optional |
| FR-HEAR-04 | Set next date in the same sheet with quick chips (+1 week, +2 weeks, +1 month, pick date) | Saving creates the next hearing and marks the current one complete in one API call |
| FR-HEAR-05 | If outcome = Disposed, prompt to change case status | Opens SCR-26 pre-selected |
| FR-HEAR-06 | Hearing timeline on case detail, newest on top, future hearings above a "Today" marker | Each node shows date, outcome pill, notes preview |
| FR-HEAR-07 | Hearing with date passed and no outcome is flagged "Needs update" | Shown on dashboard as a Warning banner with count |

### 6.6 Clients (FR-CLI, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-CLI-01 | Add client: name (required), phone (required, +91), alt phone, email, address, notes | Duplicate phone warns and offers to open existing |
| FR-CLI-02 | Client can be created inline from Add case step 3 | Returns to the form with the client selected |
| FR-CLI-03 | A case has one or more clients; a client has many cases | Many-to-many via `case_clients` |
| FR-CLI-04 | Client detail lists linked cases with status | Tap opens case detail |
| FR-CLI-05 | Call, WhatsApp, SMS actions | Uses device intents |
| FR-CLI-06 | Delete client only if no active cases linked | Otherwise dialog explains why |

### 6.7 Calendar (FR-CAL, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-CAL-01 | Month grid with up to 3 dots per day (more shows "+") | Fetches `GET /hearings?from&to` per visible month |
| FR-CAL-02 | Selecting a day lists its hearings grouped by court | Empty day shows "No hearings" |
| FR-CAL-03 | "Today" button jumps back; swipe between months | 200 ms transition |

### 6.8 Notifications (FR-NOTIF, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-NOTIF-01 | Evening digest at 8:00 PM IST the day before: "3 hearings tomorrow" with first court | Time configurable; sent only if count > 0 |
| FR-NOTIF-02 | Morning digest at 8:00 AM IST same day | Configurable; can be turned off |
| FR-NOTIF-03 | Evening "Needs update" nudge for today's hearings without outcome at 6:00 PM | Deep-links to Today's hearings |
| FR-NOTIF-04 | Tapping a notification deep-links to the right screen | Works from cold start |
| FR-NOTIF-05 | In-app notification centre stores the last 60 days | Unread badge on bell icon |

### 6.9 Settings (FR-SET, P0)

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-SET-01 | Edit profile | Saved via `PATCH /me` |
| FR-SET-02 | Theme: Dark (default), Light, System | Applies instantly without restart; stored locally and on profile |

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-SET-03 | Manage courts and case types (add, rename, reorder, hide) | Hidden items not shown in pickers but kept on existing cases |
| FR-SET-04 | Notification preferences | Saved to `advocates.notification_prefs` |
| FR-SET-05 | Delete account | Two-step confirm; all data purged within 30 days |

### 6.10 P1 modules

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-DOC-01 | Upload PDF, JPG, PNG, HEIC up to 20 MB per file from camera, gallery or files | Upload via signed URL from `POST /cases/:id/documents/upload-url`; progress shown |
| FR-DOC-02 | Categorize: Petition, Order, Evidence, Vakalatnama, Other | Filter chips on Documents tab |
| FR-DOC-03 | Preview in-app, rename, share, delete | Viewer supports pinch zoom |
| FR-DOC-04 | Images compressed to max 2000 px long edge before upload | Under 1.5 MB typical |
| FR-DOC-05 | Storage quota 1 GB per advocate (v1) | Usage bar in Settings |
| FR-NOTE-01 | Add note with title (optional) and body (required) | Auto-save every 2 s while typing |
| FR-NOTE-02 | Pin up to 3 notes per case | Pinned notes on top |
| FR-NOTE-03 | Edit, delete with Undo | 5 s Undo toast |
| FR-NOTE-04 | Notes searchable in global search | — |
| FR-FEE-01 | Set agreed fee per case | Amount in INR |

| ID | Requirement | Acceptance criteria |
|---|---|---|
| FR-FEE-02 | Record payments: amount, date, mode, note | Balance = agreed minus sum of payments |
| FR-FEE-03 | Fee summary card with ring progress | Fully paid uses `grad-success` |
| FR-FEE-04 | Dashboard stat "Fees pending" total | Optional card |
| FR-TASK-01 | Add task with title, due date, case link | Unlinked tasks allowed |
| FR-TASK-02 | Check off tasks; completed move to bottom | Haptic + strike-through |
| FR-TASK-03 | Overdue tasks shown in Error | — |
| FR-TASK-04 | Tasks due today included in morning digest | — |
| FR-SRCH-01 | Global search across cases, clients, notes with grouped results | Recent searches saved locally (10) |
| FR-SEC-01 | Biometric or 4-digit PIN app lock, lock after 1 min in background | Fallback to PIN |

# 7. Data model (Supabase Postgres)

Fifteen tables, all owned by one advocate. Every table has `id uuid pk default gen_random_uuid()`, `advocate_id uuid not null references advocates(id) on delete cascade`, `created_at`, `updated_at timestamptz default now()`, and `deleted_at` where soft delete applies. RLS policy on every table: `advocate_id = auth.uid()`.

| Table | Key columns | Notes |
|---|---|---|
| `advocates` | id (= auth.users.id), full_name, phone, email, enrolment_no, practice_areas text[], avatar_url, theme ('dark','light','system'), notification_prefs jsonb, onboarded_at | One row per user; the only entity |

| Table | Key columns | Notes |
|---|---|---|
| `courts` | name, short_name, city, district, state, sort_order, is_hidden | Seeded per advocate at onboarding |
| `case_types` | name (Civil Suit, Criminal Case, NI Act 138, Family, MACT, Writ, Appeal, Bail, Other), sort_order, is_hidden | Seeded, editable |
| `clients` | full_name, phone, alt_phone, email, address, notes | Unique (advocate_id, phone) |
| `cases` | title, case_number, case_year, cnr_number, case_type_id, court_id, court_room, judge_name, filing_date, our_side ('petitioner','respondent','complainant','accused','appellant','other'), petitioner_name, respondent_name, opposite_counsel, stage, status ('active','reserved','disposed','closed'), disposal_date, disposal_result, priority ('normal','high','urgent'), description, next_hearing_at, last_hearing_at, archived_at, deleted_at | `next_hearing_at` denormalized for fast lists; indexes on (advocate_id, next_hearing_at), (advocate_id, status), trigram index on title / parties for search |
| `case_clients` | case_id, client_id, role (e.g. 'primary') | Many-to-many |
| `hearings` | case_id, hearing_date date, hearing_time time, purpose, court_room, outcome ('adjourned','heard','arguments_done','evidence','reserved','disposed','not_reached','other'), outcome_notes, next_hearing_id, completed_at | Index (advocate_id, hearing_date) |
| `notes` | case_id, title, body, is_pinned, deleted_at | P1 |
| `documents` | case_id, file_name, category, mime_type, size_bytes, storage_path, deleted_at | P1; bucket `case-docs` private, path `{advocate_id}/{case_id}/{uuid}.{ext}` |
| `fees` | case_id, agreed_amount numeric(12,2) | One row per case, P1 |
| `payments` | case_id, amount numeric(12,2), paid_on date, mode ('cash','upi','bank','cheque'), note | P1 |
| `tasks` | case_id (nullable), title, due_date, completed_at | P1 |
| `notifications` | type, title, body, deep_link, read_at, sent_at | In-app centre, 60-day retention |
| `device_tokens` | expo_push_token, platform, last_seen_at | For reminders |

A DB trigger (or the API service) recalculates `cases.next_hearing_at` and `last_hearing_at` whenever a hearing is inserted, updated or deleted.

## 8. REST API specification

Base URL `https://api.vakil.app/api/v1`. JSON only. Every request except `/auth/*` carries `Authorization: Bearer <supabase_access_token>`; the API verifies it, sets `advocate_id`, and queries Supabase with the service key. Request bodies are validated with Zod; the same schemas are shared with the app.

### Conventions

- Pagination: `?limit=20&cursor=<opaque>` → `{ data: [...], nextCursor }`.
- Errors: `{ error: { code: "VALIDATION_ERROR", message, fields: { case_number: "Required" } } }` with HTTP 400 / 401 / 403 / 404 / 409 / 422 / 429 / 500.
- Dates: ISO 8601; `hearing_date` as `YYYY-MM-DD` in IST.
- Idempotency: create endpoints accept `Idempotency-Key` header so offline retries never duplicate.
- Rate limit: 120 req/min per advocate.

| Method | Endpoint | Purpose | FR |
|---|---|---|---|
| POST | /auth/otp/send | Send OTP to phone | FR-AUTH-01 |
| POST | /auth/otp/verify | Verify OTP, return session | FR-AUTH-01 |
| POST | /auth/email/sign-in | Email + password sign-in | FR-AUTH-02 |
| POST | /auth/refresh | Refresh access token | FR-AUTH-03 |
| POST | /auth/logout | Revoke session, remove device token | FR-AUTH-05 |
| GET | /me | Get advocate profile | FR-SET-01 |
| PATCH | /me | Update profile, theme, notification prefs | FR-ONB-01, FR-SET-01..04 |
| POST | /me/onboarding/complete | Mark onboarded, seed courts and case types | FR-ONB-02 |
| DELETE | /me | Delete account (soft, purge in 30 days) | FR-SET-05 |
| POST | /me/devices | Register Expo push token | FR-NOTIF-01 |
| GET | /dashboard | Hero, stats, week counts, today's hearings, needs-update count | FR-DASH-01..05 |

| Method | Endpoint | Purpose | FR |
|---|---|---|---|
| GET | /cases | List with `q, status, case_type_id, court_id, client_id, from, to, archived, sort, limit, cursor` | FR-CASE-07..10 |
| POST | /cases | Create case (+ optional first hearing, client links) | FR-CASE-01..06 |
| GET | /cases/:id | Case detail with clients, next hearing, counts | FR-CASE-11 |
| PATCH | /cases/:id | Edit case fields | FR-CASE-11 |
| PATCH | /cases/:id/status | Change status (+ disposal fields) | FR-CASE-13 |
| POST | /cases/:id/archive | Archive / unarchive ( `{ archived: bool }` ) | FR-CASE-14 |
| DELETE | /cases/:id | Soft delete with cascade | FR-CASE-15 |
| GET | /cases/:id/hearings | Hearing timeline | FR-HEAR-06 |
| POST | /cases/:id/hearings | Add hearing | FR-HEAR-01 |
| PATCH | /hearings/:id | Edit hearing | FR-HEAR-01 |
| POST | /hearings/:id/outcome | Record outcome + create next hearing (atomic) | FR-HEAR-02..05 |
| DELETE | /hearings/:id | Delete hearing | FR-HEAR-01 |
| GET | /hearings | Range query `from, to` for calendar and today | FR-CAL-01..02 |
| GET | /clients | List / search clients | FR-CLI-01 |
| POST | /clients | Create client | FR-CLI-01..02 |
| GET | /clients/:id | Client detail + linked cases | FR-CLI-04 |
| PATCH | /clients/:id | Edit client | FR-CLI-01 |

| Method | Endpoint | Purpose | FR |
|---|---|---|---|
| DELETE | /clients/:id | Delete (409 if active cases) | FR-CLI-06 |
| GET / POST / PATCH | /courts, /courts/:id | Manage courts | FR-SET-03 |
| GET / POST / PATCH | /case-types, /case-types/:id | Manage case types | FR-SET-03 |
| GET | /notifications | In-app notification list | FR-NOTIF-05 |
| POST | /notifications/read | Mark read (ids or all) | FR-NOTIF-05 |
| GET | /search | Global search `q` (cases, clients, notes) | FR-SRCH-01 (P1) |
| GET / POST | /cases/:id/notes | Notes list / create | FR-NOTE (P1) |
| PATCH / DELETE | /notes/:id | Edit / delete note | FR-NOTE (P1) |
| POST | /cases/:id/documents/upload-url | Get signed upload URL | FR-DOC-01 (P1) |
| POST | /cases/:id/documents | Confirm upload, save metadata | FR-DOC-01 (P1) |
| GET | /cases/:id/documents | List documents | FR-DOC-02 (P1) |
| GET | /documents/:id/url | Signed download URL (10 min) | FR-DOC-03 (P1) |
| PATCH / DELETE | /documents/:id | Rename / delete | FR-DOC-03 (P1) |
| GET / PUT | /cases/:id/fee | Get / set agreed fee + summary | FR-FEE-01, 03 (P1) |
| POST | /cases/:id/payments | Add payment | FR-FEE-02 (P1) |
| PATCH / DELETE | /payments/:id | Edit / delete payment | FR-FEE-02 (P1) |

| Method | Endpoint | Purpose | FR |
|---|---|---|---|
| GET / POST | /tasks | List ( `case_id, due, done` ) / create | FR-TASK (P1) |
| PATCH / DELETE | /tasks/:id | Toggle / edit / delete | FR-TASK (P1) |

### Example: record outcome

```
POST /api/v1/hearings/9f1c.../outcome
{
  "outcome": "adjourned",
  "outcome_notes": "Respondent sought time to file reply",
  "next_hearing": { "hearing_date": "2026-11-12", "purpose": "Reply by
respondent" }
}
→ 200 { "hearing": {...}, "next_hearing": {...}, "case": { "id": "...",
"next_hearing_at": "2026-11-12" } }
```

### Background jobs (Node, node-cron, IST)

| Job | Schedule | Action |
|---|---|---|
| evening-digest | every 15 min, sends to advocates whose evening time falls in the window | Push "N hearings tomorrow" |
| morning-digest | every 15 min, same windowing | Push "N hearings today" + due tasks |
| needs-update | 18:00 daily | Push for today's hearings without outcome |
| purge-deleted | 03:00 daily | Hard-delete rows soft-deleted more than 30 days ago |

# 9. Validation, states and system rules

## 9.1 Field validation

| Field | Rule | Error message |
|---|---|---|
| Full name | 2 to 80 chars, letters, spaces, `.` `'` | "Enter a name of at least 2 letters" |
| Phone | 10 digits starting 6 to 9 (+91 fixed) | "Enter a valid 10-digit mobile number" |
| Email | RFC 5322 basic | "Enter a valid email" |
| Case number | Up to 30 chars, letters, digits, `/` `-` `.` | "Use letters, numbers, / or -" |
| Case year | 1950 to current year + 1 | "Enter a year between 1950 and 2027" |
| CNR | Exactly 16 alphanumeric, uppercase | "CNR must be 16 characters" |
| Hearing date | Valid date; past allowed with warning | Warning: "This date is in the past" |
| Amount | 1 to 99,99,99,999, max 2 decimals | "Enter a valid amount" |
| Note body | 1 to 20,000 chars | "Note can't be empty" |
| File | PDF / JPG / PNG / HEIC, max 20 MB | "File is larger than 20 MB" |

### 9.2 Screen states

| State | Behaviour |
|---|---|
| Loading (first time) | Skeletons matching the final layout; never a blank spinner screen |
| Loading (refresh) | Cached data stays visible; pull-to-refresh spinner |
| Empty: Cases | Icon `ti-briefcase`, "No cases yet", "Add your first case" button |
| Empty: Today | Icon `ti-mood-smile`, "No hearings today", "View tomorrow" link |
| Empty: Clients | Icon `ti-users`, "No clients yet", "Add client" |
| Empty: Search | "No results for 'xyz'" + tips (search by case no., party, client) |

| State | Behaviour |
|---|---|
| Empty: Filtered list | "No cases match these filters" + "Clear filters" |
| Error (screen) | Icon `ti-cloud-off`, message, "Try again"; error code in small text |
| Error (action) | Error toast with retry; form keeps entered values |
| Offline | Persistent Info banner "You're offline. Changes will sync when you're back."; writes queued with a `ti-clock` marker on the item |
| Session expired | Silent refresh; if it fails, sign-in screen with "Session expired" banner, return to same screen after |
| Force update | Blocking sheet when API returns 426 |

### 9.3 Confirmation and undo rules

- Delete case / client / account: destructive dialog.
- Delete note, payment, task, document, hearing: immediate with 5 s Undo toast.
- Discard unsaved form: dialog "Discard changes?" with Keep editing / Discard.

### 9.4 Accessibility

- Text contrast at least 4.5:1, large text and icons at least 3:1, in both themes.
- All icon buttons have `accessibilityLabel`; status pills read as "Status: Adjourned".
- Supports font scaling to 130% without truncating primary actions.
- Color is never the only signal: status pills include text, overdue cards include an icon.

## 10. NativeWind starter config

Semantic tokens are CSS variables (NativeWind v4), so `bg-surface` or `text-primary` switch with the theme; dark is the default class on the root.

**global.css**

```
@tailwind base;
@tailwind components;
@tailwind utilities;

:root {
  --bg: 246 248 252;        --surface: 255 255 255;   --surface-2: 237 241
248;
  --border: 220 227 239;    --border-strong: 188 199 218;
  --text: 18 26 43;         --text-2: 71 85 112;      --text-3: 100 114 140;
  --primary: 35 80 230;     --primary-pressed: 28 63 192; --primary-subtle:
238 244 255;
}
.dark {
  --bg: 10 16 29;           --surface: 18 26 43;      --surface-2: 28 37 56;
  --border: 46 58 82;       --border-strong: 71 85 112;
  --text: 246 248 252;      --text-2: 188 199 218;    --text-3: 140 154 179;
  --primary: 51 102 255;    --primary-pressed: 35 80 230; --primary-subtle:
18 31 74;
}
```

### tailwind.config.js

```
const v = (name) => `rgb(var(--${name}) / <alpha-value>)`;

module.exports = {
  content: ['./app/**/*.{ts,tsx}', './components/**/*.{ts,tsx}'],
  presets: [require('nativewind/preset')],
  darkMode: 'class',
  theme: {
    extend: {
      colors: {
        bg: v('bg'), surface: v('surface'), 'surface-2': v('surface-2'),
        border: v('border'), 'border-strong': v('border-strong'),
        text: v('text'), 'text-2': v('text-2'), 'text-3': v('text-3'),
        primary: { DEFAULT: v('primary'), pressed: v('primary-pressed'),
subtle: v('primary-subtle') },
        blue: {
50:'#EEF4FF',100:'#DCE7FF',200:'#BCD2FF',300:'#8EB3FF',400:'#5B8CFF',500:'#33
66FF',600:'#2350E6',700:'#1C3FC0',800:'#1B3699',900:'#1B3279',950:'#121F4A'
},
        ink: {
0:'#FFFFFF',50:'#F6F8FC',100:'#EDF1F8',200:'#DCE3EF',300:'#BCC7DA',400:'#8C9A
B3',500:'#64728C',600:'#475570',700:'#2E3A52',800:'#1C2538',900:'#121A2B',950
```

```
:'#0A101D' },
        success: '#22C55E', warning: '#F59E0B', error: '#EF4444', info:
'#0EA5E9', adjourned: '#8B5CF6',
      },
      fontFamily: {
        sans: ['PlusJakartaSans_400Regular'],
        medium: ['PlusJakartaSans_500Medium'],
        semibold: ['PlusJakartaSans_600SemiBold'],
        bold: ['PlusJakartaSans_700Bold'],
        extrabold: ['PlusJakartaSans_800ExtraBold'],
      },
      fontSize: {
        display: [32, { lineHeight: '40px', letterSpacing: -0.5 }],
        h1: [28, { lineHeight: '36px', letterSpacing: -0.4 }],
        h2: [24, { lineHeight: '32px', letterSpacing: -0.3 }],
        h3: [20, { lineHeight: '28px', letterSpacing: -0.2 }],
        title: [17, { lineHeight: '24px' }],
        'body-lg': [16, { lineHeight: '24px' }],
        body: [15, { lineHeight: '22px' }],
        'body-sm': [13, { lineHeight: '20px' }],
        caption: [12, { lineHeight: '16px' }],
        overline: [11, { lineHeight: '16px', letterSpacing: 0.8 }],
      },
      borderRadius: { sm: 8, md: 12, lg: 16, xl: 20, '2xl': 28 },
    },
  },
};
```

Gradients use `expo-linear-gradient` with the stops in section 2.6, wrapped in a `<GradientSurface variant="primary|hero|success">` component.