

CS34110

Discrete Mathematics and Graph Theory

UNIT – I, Module – 2**Lecture 05: Predicate logic**

[Quantification with restricted domains; Bound, free variables; Logical equivalence; Negations; Predicates in practice; Laws for quantifiers]

Dr. Suddhasil De

Quantification: Restricted domain of discourse

- Quantification with **restricted** domain of discourse: notation specifying condition for quantified variable to be satisfied to restrict domain of discourse of quantifier.
- Property:: Restriction in domain of discourse to be included after quantifier.
- Property:: Restriction of universal quantification = universal quantification of conditional statement (i.e., implication statement).
- Property:: Restriction of existential quantification = existential quantification of conjunction of statements.

Discrete Mathematics

Dept. of CSE, NITP
2

Dr. Suddhasil De

Quantification: Restricted domain of discourse

- Quantification with restricted domain of discourse examples:
 - Example-1:: consider $P(x)$: " $x^2 > 0$ ", domain of discourse = \mathbb{R} , restriction: negative numbers of \mathbb{R} .
 $P(x) \equiv \text{True}$, for every $x \in \mathbb{R}$ and $x < 0$, as $x < 0$ fulfills $x^2 > 0$.
 That is, $\forall x < 0$ ($x^2 > 0$) to be TRUE in domain of discourse \mathbb{R} .
 In above sentence, condition $x < 0$ in universal quantification to express given restriction.
 Also, $(x < 0) \rightarrow (x^2 > 0)$, i.e., IF $(x < 0)$, THEN $(x^2 > 0)$.
 So, $\forall x < 0$ ($x^2 > 0$) $\equiv \forall x ((x < 0) \rightarrow (x^2 > 0))$.

Discrete Mathematics

Dept. of CSE, NITP
3

Dr. Suddhasil De

Quantification: Restricted domain of discourse

- Quantification with restricted domain of discourse examples:
 - Example-2: interpretation of $\forall x < 0 (x^2 > 0)$ in \mathbb{R} .
 $\forall x < 0 (x^2 > 0)$ stating "for every real number x with $x < 0$, $x^2 > 0$ ";
 i.e., "Square of negative real numbers are positive."
 As above statement TRUE, so given domain of discourse with restriction to become **model** of given predicate.
 - Example-3: interpretation of $\exists z > 0 (z^2 = 2)$ in \mathbb{R} .
 $\exists z > 0 (z^2 = 2)$ stating "there is a positive real number, which is square root of 2" \rightarrow TRUE, so given domain be **model** of predicate.
 Also, $\exists z > 0 (z^2 = 2) \equiv \exists z((z > 0) \wedge (z^2 = 2))$.

Discrete Mathematics

Dept. of CSE, NITP
4

Dr. Suddhasil De

Variable binding

- Variable **binding**: binding of all propositional variables in propositional function, by quantifying or setting to particular value to turn into proposition.
 - Property: Variable binding: by combination of universal quantifiers, existential quantifiers, and value assignments.
 - Property: **Bound variable**: when any form of quantification applied on variable of propositional function.
 - Property: **Free variable**: occurrence of variable — (i) not bound by quantifier, or (ii) set by value assignment, in propositional function.

Discrete Mathematics

Dept. of CSE, NITP
5

Dr. Suddhasil De

Variable binding

- Variable binding:
 - Property: Free variable \rightarrow if outside scope of all quantifiers in formula specifying it.
- Note: in common usage of variables in predicate logic, same letter allowed to represent variables bound by different quantifiers, but with non-overlapping scopes of quantification.

Discrete Mathematics

Dept. of CSE, NITP
6

Dr. Suddhasil De

Variable binding

- Variable binding examples:
 - Example-1:: consider $\exists x(x + y = 1)$.
Variable x **bound** by existential quantification $\exists x$.
Variable y **free**, as not bound by any quantifier or no value assigned.
 - Example-2:: consider $\exists x(P(x) \wedge Q(x)) \vee \forall xR(x)$, disjuncts of \exists & \forall .
Variable x **bound** in both disjuncts separately by $\exists x$ and $\forall x$.
Binding of x separated by **non-overlapping scope of quantification**, i.e., $\exists x$ binding in $P(x) \wedge Q(x)$, $\forall x$ binding in $R(x)$, no overlap between them.

Discrete Mathematics

Dept. of CSE, NITP

Dr. Suddhasil De

7

Logical equivalence in predicate logic

- Logical equivalence in predicate logic: given statements S and T (involving predicates and quantifiers) to be **logically equivalent** (notation: ' $S \equiv T$ '), if S and T having same truth values, irrespective of predicates substituted in S and T , and irrespective of domain of discourse used for variables in propositional functions of S and T .

Discrete Mathematics

Dept. of CSE, NITP

Dr. Suddhasil De

8

Logical equivalence in predicate logic

- Logical equivalence examples:
 - Example-1:: to show $\forall x(P(x) \wedge Q(x)) \equiv \forall xP(x) \wedge \forall xQ(x)$ in same domain of discourse — two-part proof.
(1) To show if $\forall x(P(x) \wedge Q(x))$ TRUE, **then** $\forall xP(x) \wedge \forall xQ(x)$ TRUE.
 $\forall x(P(x) \wedge Q(x)) \equiv \text{T}$ premise, in any domain of discourse \mathcal{D} .
 So, $P(a) \wedge Q(a) \equiv \text{T}$ for every $a \in \mathcal{D}$.
 So, $P(a) \equiv \text{T}$ and $Q(a) \equiv \text{T}$ for every $a \in \mathcal{D}$.
 So, $\forall xP(x) \equiv \text{T}$ and $\forall xQ(x) \equiv \text{T}$ in \mathcal{D} .
 So, $\forall xP(x) \wedge \forall xQ(x) \equiv \text{T}$ in \mathcal{D} .

(contd. to next slide)

Discrete Mathematics

Dept. of CSE, NITP

Dr. Suddhasil De

9

Logical equivalence in predicate logic

- Logical equivalence examples:
 - Example-1 contd.

(2) To show if $\forall x P(x) \wedge \forall x Q(x)$ TRUE, then $\forall x (P(x) \wedge Q(x))$ TRUE.

$$\forall x P(x) \wedge \forall x Q(x) \equiv \text{T} \quad \text{premise, in } \mathcal{D}.$$

So, $\forall x P(x) \equiv \text{T}$ and $\forall x Q(x) \equiv \text{T}$ in \mathcal{D} .

So, $P(a) \equiv \text{T}$ and $Q(a) \equiv \text{T}$ for every $a \in \mathcal{D}$.

So, $P(a) \wedge Q(a) \equiv \text{T}$ for every $a \in \mathcal{D}$.

So, $\forall x (P(x) \wedge Q(x)) \equiv \text{T}$ in \mathcal{D} .

In conclusion, $\forall x (P(x) \wedge Q(x)) \equiv \forall x P(x) \wedge \forall x Q(x)$.

Discrete Mathematics

Dept. of CSE, NITP
10

Dr. Suddhasil De

Negations of quantification

- Negation of universal quantification $\forall x P(x)$ in any domain of discourse: $\exists x \neg P(x)$ in same domain of discourse.
- Property: Negation of $\forall x_1 \forall x_2 \dots \forall x_n P(x_1, x_2, \dots, x_n)$ in any product set of n domains of discourse: $\exists x_1 \exists x_2 \dots \exists x_n \neg P(x_1, x_2, \dots, x_n)$ in same domains of discourse.
- Negation of existential quantification $\exists x P(x)$ in any domain of discourse: $\forall x \neg P(x)$ in same domain of discourse.
- Property: Negation of $\exists x_1 \exists x_2 \dots \exists x_n P(x_1, x_2, \dots, x_n)$ in any product set of n domains of discourse: $\forall x_1 \forall x_2 \dots \forall x_n \neg P(x_1, x_2, \dots, x_n)$ in same domains of discourse.

Discrete Mathematics

Dept. of CSE, NITP
11

Dr. Suddhasil De

Negations of quantification

- Negations of quantification:
 - Property: also known by De Morgan's laws for quantifiers.

De Morgan's Laws for Quantifiers			
Negation	Equivalent Statement	When Is Negation True?	When False?
$\neg \exists x P(x)$	$\forall x \neg P(x)$	For every x , $P(x)$ is false.	There is an x for which $P(x)$ is true.
$\neg \forall x P(x)$	$\exists x \neg P(x)$	There is an x for which $P(x)$ is false.	$P(x)$ is true for every x .

- Property: $\neg \forall x P(x) \equiv \exists x \neg P(x)$ in same domain of discourse;
- Property: $\neg \exists x P(x) \equiv \forall x \neg P(x)$ in same domain of discourse.

[Ref: Kenneth H. Rosen, Kamala Krithivasan, *Discrete Mathematics and its Applications*, Eighth edition, McGraw-Hill Education, 2021.]

Discrete Mathematics

Dept. of CSE, NITP
12

Dr. Suddhasil De

Negations of quantification

- Negations of quantification examples:
 - Example-1:: $\neg \forall x P(x) \equiv \exists x \neg P(x)$ in same domain of discourse.
 $\neg \forall x P(x) \equiv T$ iff $\forall x P(x) \equiv F$ in any domain of discourse \mathcal{D} .
 Also, $\forall x P(x) \equiv F$ iff $P(a) \equiv F$ for some $a \in \mathcal{D}$.
 Then, $P(a) \equiv F$ iff $\neg P(a) \equiv T$ for some $a \in \mathcal{D}$.
 Next, $\neg P(a) \equiv T$ iff $\exists x \neg P(x) \equiv T$ for some $a \in \mathcal{D}$.
 So, $\neg \forall x P(x) \equiv T$ iff $\exists x \neg P(x) \equiv T$ in \mathcal{D} .
 Thus, to conclude, $\neg \forall x P(x) \equiv \exists x \neg P(x)$.

Discrete Mathematics

Dept. of CSE, NITP
13

Dr. Suddhasil De

Negations of quantification

- Negations of quantification examples:
 - Example-2:: $\neg \exists x Q(x) \equiv \forall x \neg Q(x)$ in same domain of discourse.
 $\neg \exists x Q(x) \equiv T$ iff $\exists x Q(x) \equiv F$ in any domain of discourse \mathcal{D} .
 Also, $\exists x Q(x) \equiv F$ iff $Q(a) \equiv F$ for every $a \in \mathcal{D}$.
 Then, $Q(a) \equiv F$ iff $\neg Q(a) \equiv T$ for every $a \in \mathcal{D}$.
 Next, $\neg Q(a) \equiv T$ iff $\forall x \neg Q(x) \equiv T$ for every $a \in \mathcal{D}$.
 So, $\neg \exists x Q(x) \equiv T$ iff $\forall x \neg Q(x) \equiv T$ in \mathcal{D} .
 Thus, to conclude, $\neg \exists x Q(x) \equiv \forall x \neg Q(x)$.

Discrete Mathematics

Dept. of CSE, NITP
14

Dr. Suddhasil De

Negations of quantification

- Negations of quantification examples:
 - Example-3:: Negation of statement: "There is an honest politician".
 Let $H(x)$ denoting "x is honest".
 So, statement: "There is an honest politician", represented by $\exists x H(x)$, where domain of discourse = all politicians.
 Now, $\neg \exists x H(x) \equiv \forall x \neg H(x)$ expressing "Every politician is dishonest".
 - Example-4:: Negation of $\forall x (x^2 > x)$ in some domain of discourse.
 $\neg \forall x (x^2 > x) \equiv \exists x \neg (x^2 > x)$, and $\neg (x^2 > x)$ rewritten as $(x^2 \leq x)$.
 So, $\neg \forall x (x^2 > x) \equiv \exists x (x^2 \leq x)$.

Discrete Mathematics

Dept. of CSE, NITP
15

Dr. Suddhasil De

Negations of quantification

- Negations of quantification examples:
 - Example-5:: to show $\neg \forall x(P(x) \rightarrow Q(x)) \equiv \exists x(P(x) \wedge \neg Q(x))$ in same domain of discourse \mathcal{D} .

$$\neg \forall x(P(x) \rightarrow Q(x)) \equiv \exists x \neg(P(x) \rightarrow Q(x)) \quad \text{De Morgan's law in } \mathcal{D}$$
 Also, $\neg(P(x) \rightarrow Q(x)) \equiv P(x) \wedge \neg Q(x)$ Implication rule (I.12b)
 for every $x = a \in \mathcal{D}$, as each instantiation to result into proposition.
 Then, $\exists x \neg(P(x) \rightarrow Q(x)) \equiv \exists x(P(x) \wedge \neg Q(x))$ by substitution
 Thus, to conclude, $\neg \forall x(P(x) \rightarrow Q(x)) \equiv \exists x(P(x) \wedge \neg Q(x))$ in \mathcal{D} .

Discrete Mathematics

Dept. of CSE, NITP
16

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions using predicates and quantifiers (case – **single quantifier**):
- Example-1:: Given: "Every student in this class has learnt calculus."
 Rewriting, \mathcal{S} as, "For every student in this class, that student has learnt calculus."
 Introducing variable x in \mathcal{S} , "For every student x in this class, x has learnt calculus."
 Let $C(x)$ be " x has learnt calculus."
 So, \mathcal{S} represented by, $\forall x C(x)$, where domain of discourse = all students in class.

(contd. to next slide)

Discrete Mathematics

Dept. of CSE, NITP
17

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions (single quantifier):
- Example-1-alternate (with different domain of discourse)::
 Let, \mathcal{S}' be, "For every person x , if person x is a student in this class, then x has learnt calculus.", with all people as domain of discourse.
 Let $C(x)$ be, " x has learnt calculus.";
 $P(x)$ be, " x is a student in this class."
 So, \mathcal{S}' represented by, $\forall x(P(x) \rightarrow C(x))$, where domain of discourse = all people.

Discrete Mathematics

Dept. of CSE, NITP
18

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions (single quantifier):
 - Example-2:: Given: "Some student in this class has visited Himalayas."
Let, \mathfrak{U} , "There is a student x in this class having property that x has visited Himalayas.", with all students in class as domain of discourse.
Let, \mathfrak{U}' be, "There is a person x having properties that x is a student in this class and x has visited Himalayas.", with all people as domain of discourse.
Let $H(x)$ be, " x has visited Himalayas."; $P(x)$ be, " x is a student in this class."

(contd. to next slide)

Discrete Mathematics

Dept. of CSE, NITP
19

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions (single quantifier):
 - Example-2 contd.
So, \mathfrak{U} represented by, $\exists xH(x)$, where domain of discourse = all students in class.
And, \mathfrak{U}' represented by, $\exists x(P(x) \wedge H(x))$, where domain of discourse = all people.

Discrete Mathematics

Dept. of CSE, NITP
20

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions (double quantifier):
 - Example-1:: Given: "Every student in this class has learnt calculus."
Let, \mathfrak{I} be, "For every student x in this class, x has learnt calculus.", with all students in class as domain of discourse.
And, \mathfrak{I}' be, "For every person x , if person x is a student in this class, then x has learnt calculus.", with all people as domain of discourse.
Let $B(x, y)$ be, " x has learnt subject y ."
So, \mathfrak{I}' become, $\forall x(P(x) \rightarrow B(x, \text{calculus}))$, where domain of discourse = all people.
And, \mathfrak{I} , $\forall xB(x, \text{calculus})$, domain of discourse = all students in class.

Discrete Mathematics

Dept. of CSE, NITP
21

Dr. Suddhasil De

Predicate logic in practice

- English sentences into logical expressions (double quantifier):
- Example-2:: Given: "Every student in this class has visited either Himalayas or Nilgiris."
Let, \mathcal{U} be, "For every person x , if x is a student in this class, then x has the property that x has visited Himalayas or x has visited Nilgiris.", with all people as domain of discourse, and assuming inclusive OR.
Let $W(x, y)$ be, " x has visited location y ."
So, \mathcal{U} become, $\forall x(P(x) \rightarrow (W(x, \text{Himalayas}) \vee W(x, \text{Nilgiris})))$,
where domain of discourse = all people.

Predicate logic in practice

- English sentences into logical expressions (multiple quantifier):
- Example-1:: Given: "If a user is active, at least one network link will be available."
Let, \mathcal{U} be, "If a user u is active, network link ℓ will be in state available.", with 'all users', 'all network links', and 'all possible states for any network link' as domains of discourse.
Let, \mathcal{V} be, "There is a person u having property that if u is a user and if u is active, then network link ℓ will be in state available.", with 'all people', 'all network links', and 'all possible states for any network link' as domains of discourse.

(contd. to next slide)

Predicate logic in practice

- English sentences into logical expressions (multiple quantifier):
- Example-1 contd.
Let $A(u)$ be, " u is active."; $R(\ell, y)$ be, " ℓ is in state y ."; $P(u)$ be, " u is a user."
So, \mathcal{U} become, $\exists u A(u) \rightarrow \exists \ell S(\ell, \text{available})$, where domains of discourse = 'all users' (for u), 'all network links' (for ℓ).
And, \mathcal{V} become, $\exists u (P(u) \wedge A(u)) \rightarrow \exists \ell S(\ell, \text{available})$, where domains of discourse = 'all people' (for u), 'all network links' (for ℓ).

Laws for quantifiers (for same domains)

Distributive laws:	(Il.1a) $\forall x(P(x) \wedge Q(x)) \equiv \forall xP(x) \wedge \forall xQ(x)$	(Il.1b) $\exists x(P(x) \vee Q(x)) \equiv \exists xP(x) \vee \exists xQ(x)$
De Morgan's laws:	(Il.2a) $\neg \forall xP(x) \equiv \exists x\neg P(x)$	(Il.2b) $\neg \exists xP(x) \equiv \forall x\neg P(x)$
Null quantification laws:	(Il.3a) $P(x) \wedge \forall yQ(y) \equiv \forall y(P(x) \wedge Q(y))$ (Il.3b) $\forall yQ(y) \wedge P(x) \equiv \forall y(Q(y) \wedge P(x))$ both for nonempty domain of y	(Il.3c) $P(x) \wedge \exists yQ(y) \equiv \exists y(P(x) \wedge Q(y))$ (Il.3d) $\exists yQ(y) \wedge P(x) \equiv \exists y(Q(y) \wedge P(x))$
	(Il.4a) $P(x) \vee \forall yQ(y) \equiv \forall y(P(x) \vee Q(y))$ (Il.4b) $\forall yQ(y) \vee P(x) \equiv \forall y(Q(y) \vee P(x))$	(Il.4c) $P(x) \vee \exists yQ(y) \equiv \exists y(P(x) \vee Q(y))$ (Il.4d) $\exists yQ(y) \vee P(x) \equiv \exists y(Q(y) \vee P(x))$ both for nonempty domain of y

Discrete Mathematics

Dept. of CSE, NITP
25

Dr. Suddhasil De

Laws for quantifiers (for same domains)

Null quantification laws (contd.):	(Il.5a) $\forall y(P(x) \rightarrow Q(y)) \equiv P(x) \rightarrow \forall yQ(y)$	(Il.5b) $\exists y(P(x) \rightarrow Q(y)) \equiv P(x) \rightarrow \exists yQ(y)$, for nonempty domain of y
	(Il.6a) $\forall y(Q(y) \rightarrow P(x)) \equiv \exists yQ(y) \rightarrow P(x)$	(Il.6b) $\exists y(Q(y) \rightarrow P(x)) \equiv \forall yQ(y) \rightarrow P(x)$ for nonempty domain of y

Discrete Mathematics

Dept. of CSE, NITP
26

Dr. Suddhasil De

Summary

- Focus: Predicate logic (contd.).
- Quantification with restricted domain of discourse, with examples.
- Bound and free variables definitions, with examples.
- Logical equivalence of predicate definition, with examples.
- Negations of universal and existential quantifications definitions, with examples.
- Predicates with single quantifier, double quantifier and multiple quantifier examples.
- Laws for quantifiers (for same domains).

Discrete Mathematics

Dept. of CSE, NITP
27

Dr. Suddhasil De

References

1. [Ros21] Kenneth H. Rosen, Kamala Krithivasan, *Discrete Mathematics and its Applications*, Eighth edition, McGraw-Hill Education, 2021.

2. [Ross12] Kenneth A. Ross, Charles R. B. Wright, *Discrete Mathematics*, Fifth edition, Pearson Education, 2012.

3. [Mot15] Joe L. Mott, Abraham Kandel, Theodore P. Baker, *Discrete Mathematics for Computer Scientists and Mathematicians*, Second edition, Pearson Education, 2015.

4. [Lip07] Seymour Lipschutz, Marc L. Lipson, *Schaum's Outline of Theory and Problems of Discrete Mathematics*, Third edition, McGraw-Hill Education, 2007.

Further Reading

- Quantification with restricted domain:: [Ros21]:48.
- Bound and free variables:: [Ros21]:48-49.
- Logical equivalence of predicate:: [Ros21]:49.
- Negation of quantification:: [Ros21]:49-51.
- Predicates with single/double/multiple quantifiers:: [Ros21]:51-53.
- Laws for quantifiers (for same domains):: [Ros21]:49,51,59.

Lecture Exercises: Problem 1 [Ref: Gate 2020, Q.39, p.14]

Which one of the following predicate formulae is NOT logically valid?
Note that W is a predicate formula without any free occurrence of x .

(a) $\forall x(P(x) \vee W) \equiv \forall xP(x) \vee W$.

(b) $\exists x(P(x) \wedge W) \equiv \exists xP(x) \wedge W$.

(c) $\forall x(P(x) \rightarrow W) \equiv \forall xP(x) \rightarrow W$.

(d) $\exists x(P(x) \rightarrow W) \equiv \forall xP(x) \rightarrow W$.

Lecture Exercises: Problem 1 Ans

- Logical validity of given predicate formulae: in each formula, L.H.S. logically equivalent to R.H.S.
- (C) Given L.H.S.: ① $\forall x(P(x) \rightarrow W)$ premise
 - ② $\forall x(\neg P(x) \vee W)$ Implication rule (I.12a) on ①
 - ③ $\forall x(\neg P(x)) \vee W$ Null quantification of ② by (II.4b), as no free occurrence of x in W
 - ④ $\neg(\exists x P(x)) \vee W$ De Morgan's law (II.2b) on ③
 - ⑤ $\exists x P(x) \rightarrow W$ Implication rule (I.12a) on ④
 Given R.H.S.: $\forall x P(x) \rightarrow W$.
- So, L.H.S. **NOT logically equivalent** to R.H.S.
- Check for other options (A), (B), (D) similarly.

Discrete Mathematics

Dept. of CSE, NITP
31

Dr. Suddhasil De
